Exp.No.: 3 Map Reduce program to process a weather dataset

AIM:

To implement MapReduce program to process a weather dataset.

Procedure:

Step 1: Create Data File:

Create a file named "word_count_data.txt" and populate it with text data that you wish to analyse. Login with your hadoop user.

Download the dataset (weather data) Output: weather_data.txt hive-env.sh.template sample_weather.txt weather_data.txt × mapper.py hadoop-env.sh 2024-01-01 25.6 2024-01-02 26.1 2024-01-03 24.8 2024-01-04 22.7 2024-01-05 23.9 2024-02-01 28.5 2024-02-02 27.9 2024-02-03 26.7 2024-02-04 29.1 2024-03-01 31.2 2024-03-02 32.8 2024-03-03 30.4 2024-03-04 33.6 2024-04-01 34.5 2024-04-02 35.2 2024-04-03 33.9 2024-04-04 36.1 2024-05-01 40.0 2024-05-02 39.5 2024-05-03 41.2 2024-05-04 42.1 2024-06-01 43.6

Step 2: Mapper Logic - mapper.py:

Create a file named "mapper.py" to implement the logic for the mapper. The mapper will read input data from STDIN, split lines into words, and output each word with its count.

```
nano mapper.py
# Copy and paste the mapper.py code
```

```
#!/usr/bin/env python
import sys
# input comes from STDIN (standard input)
# the mapper will get daily max temperature and group it by month. so output will be
(month,dailymax_temperature)
for line in sys.stdin:
   # remove leading and trailing whitespace
   line = line.strip()
                      # split
the line into words
                      words =
line.split()
   #See the README hosted on the weather website which help us understand how each
position represents a column month = line[10:12] daily_max = line[38:45]
= daily_max.strip()
   # increase counters
                        for
word in words:
     # write the results to STDOUT (standard output);
     # what we output here will be go through the shuffle proess and then
     # be the input for the Reduce step, i.e. the input for reducer.py
     # tab-delimited; month and daily max temperature as output
print ('%s\t%s' % (month ,daily_max))
```

Step 3: Reducer Logic - reducer.py:

Create a file named "reducer.py" to implement the logic for the reducer. The reducer will aggregate the occurrences of each word and generate the final output.

```
nano reducer.py
# Copy and paste the reducer.py code
```

reducer.py

#!/usr/bin/env python

from operator import itemgetter import sys

#reducer will get the input from stdid which will be a collection of key, value(Key=month, value=daily max temperature)

#reducer logic: will get all the daily max temperature for a month and find max temperature for the month

#shuffle will ensure that key are sorted(month)

```
current month = None
current_max = 0 month =
None
# input comes from STDIN for
line in sys.stdin:
  # remove leading and trailing whitespace
                                             line
= line.strip()
  # parse the input we got from mapper.py
                                             month.
daily_max = line.split('\t', 1)
  # convert daily_max (currently a string) to float
                                                    try:
     daily_max = float(daily_max)
ValueError:
     # daily_max was not a number, so silently
     # ignore/discard this line
continue
  # this IF-switch only works because Hadoop shuffle process sorts map output
  # by key (here: month) before it is passed to the reducer
if current_month == month:
                                 if daily_max > current_max:
current_max = daily_max
                            else:
                                      if current_month:
       # write result to STDOUT
       print ('%s\t%s' % (current_month, current_max))
current_max = daily_max
     current\_month = month
# output of the last month if current_month == month:
print ('%s\t%s' % (current_month, current_max))
```

Step 4: Prepare Hadoop Environment:

Start the Hadoop daemons and create a directory in HDFS to store your data.

start-all.sh

Step 6: Make Python Files Executable:

Give executable permissions to your mapper.py and reducer.py files.

chmod 777 mapper.py reducer.py

Step 7: Run the program using Hadoop Streaming:

Download the latest hadoop-streaming jar file and place it in a location you can easily access.

Then run the program using Hadoop Streaming.

hadoop fs -mkdir -p /weatherdata

hadoop fs -copyFromLocal /home/sx/Downloads/dataset.txt /weatherdata

hdfs dfs -ls /weatherdata

hadoop jar /home/sx/hadoop-3.2.3/share/hadoop/tools/lib/hadoop-streaming-3.2.3.jar \

- -input /weatherdata/dataset.txt \
- -output /weatherdata/output \setminus
- -file "/home/sx/Downloads/mapper.py" \
- -mapper "python3 mapper.py" \
- -file "/home/sx/Downloads/reducer.py" \
- -reducer "python3 reducer.py"

hdfs dfs -text /weatherdata/output/* > /home/sx/Downloads/outputfile.txt

Step 8: Check Output:

Check the output of the program in the specified HDFS output directory. hdfs dfs -text

/weatherdata/output/* > /home/sx/Downloads/output/ /part-00000



After copy and paste the above output in your local file give the below command to remove the directory from hdfs: hadoop fs -rm -r /weatherdata/output

Result:

Thus, the program for weather dataset using Map Reduce has been executed successfully.

