


The new kid on the bloc



Felix Angelov @ Very Good Ventures

Very Good Ventures, Chicago





https://verygood.ventures

Agenda

- What's new in bloc v6.0.0
- Meet Cubit
- Cubit vs. Bloc
- Fluttersaurus (live coding)

What's New?

Initial State Changes

```
// OLD
class CounterBloc extends Bloc<CounterEvent, int> {
  <u>aoverride</u>
  int get initialState => 0;
// NEW
class CounterBloc extends Bloc<CounterEvent, int> {
  CounterBloc() : super(0);
```

Bloc Test Simplifications

```
// OLD
blocTest<CounterBloc, CounterEvent, int>(
  'emits [1] when increment is called',
 build: () async => CounterBloc(),
  act: (bloc) async => bloc.add(CounterEvent.increment),
  expect: const <int>[1],
// NEW
blocTest<CounterBloc, int>(
  'emits [1] when increment is called',
 build: () => CounterBloc(),
  act: (bloc) => bloc.add(CounterEvent.increment),
  expect: const <int>[1],
```

BlocDelegate -> BlocObserver

```
// OLD
class MyBlocDelegate extends BlocDelegate {
// NEW
class MyBlocObserver extends BlocObserver {
```

BlocObserver on Error accepts Cubit

```
// OLD
class MyBlocObserver extends BlocObserver {
 aoverride
 void onError(Bloc bloc, Object error, StackTrace stackTrace) {
    super.onError(bloc, error, stackTrace);
// NEW
class MyBlocObserver extends BlocObserver {
 aoverride
  void onError(Cubit cubit, Object error, StackTrace stackTrace) {
    super.onError(cubit, error, stackTrace);
```

BlocSupervisor Removed

```
void main() {
   // OLD
   BlocSupervisor.delegate = MyBlocDelegate();

   // NEW
   Bloc.observer = MyBlocObserver();
}
```

Tooling Improvements


```
nain.dart X
      lib > 🥎 main.dart > 😭 MyApp > 😚 build
            Run | Debug
            void main() => runApp(MyApp());
            class MyApp extends StatelessWidget {
              @override
              Widget build(BuildContext context) {
                return MaterialApp(
                 home: MyHome(),
       11
       12
                ); // MaterialApp
       13
       14
            class MyHome extends StatelessWidget {
       17
             @override
              Widget build(BuildContext context) {
               return Text('Home');
       20
UTF-8 LF Dart Flutter: 1.20.0 No Device Found 0 variables R
```

Complete migration guide

https://bloclibrary.dev/#/migration

Meet Cubit

Cubit = Bloc - Events



CounterCubit

```
import 'package:bloc/bloc.dart';

class CounterCubit extends Cubit<int> {
   CounterCubit() : super(0);

   void increment() => emit(state + 1);
}
```

Cubit vs. Bloc

Cubit

```
class CounterCubit extends Cubit<int> {
   CounterCubit() : super(0);

void increment() => emit(state + 1);
}
```

Bloc

```
enum CounterEvent { increment }


class CounterBloc extends Bloc<CounterEvent, int> {
   CounterCubit() : super(0);


   @override
   Stream<int> mapEventToState(CounterEvent event) async* {
     switch (event) {
        case CounterEvent.increment:
           yield state + 1;
           break;
     }
   }
}
```


Cubit vs. Bloc

	Cubit	Bloc
Simple		
Concise		
Traceable		
ReactiveX Operators		
Testable		
Scalable		
Tooling Support		

Fluttersaurus







https://github.com/felangel/fluttersaurus

Thanks! 🙏

Twitter @felangelov

Github @felangel