Neural Representations and Benign-Only Anomaly Detection for Unknown Attacks in In-Vehicle CAN Traffic Adda Surendra, Gera Vignan, and Vundadi Mani Kumar Abstract—An in-vehicle intrusion detector is often trained with a finite set of attack labels, whereas a deployed vehicle may encounter traffic patterns that were not represented during training. This study examines one practical response to that mismatch: train a multilayer perceptron (MLP) to classify known Controller Area Network (CAN) traffic classes, use its 64- dimensional hidden activations as a representation, and fit an Isolation Forest (IF) to benign training representations. The experiments use the public CAN-train-and-test v1.5 data and treat six attack families in an evaluation capture as unknown to the six-class MLP. At the primary operating point, defined by the 99th percentile of benign calibration scores, the detector obtains 30.68% precision, 19.00% recall, and a 23.47% F1-score, with a 1.04% false-positive rate. Its continuous scores yield ROC- AUC 0.9423 and PR-AUC 0.4299. The family-wise results are uneven: 65.27% of FUZZING records are detected, while no DOUBLE, INTERVAL, SPEED, or TRIPLE records cross the primary threshold. A 97.5th-percentile operating point produces 49.37% F1 and 62.53% recall, but it is retained as exploratory because the same unknown-test file had been examined during earlier threshold analysis. The comparison with an Isolation Forest fitted to the original features shows a distinction between ranking and thresholded decisions: the learned representation improves ROC-AUC and PR-AUC, but not F1 at the primary threshold. These results do not establish a new general-purpose detector or a complete reproduction of FedGAN-ID. They provide a reproducible account of one MLP–IF pipeline, its operating- point sensitivity, and the attack families it fails to identify. Index Terms—Automotive cybersecurity, Controller Area Net- work, in-vehicle network, intrusion detection, unknown attacks, anomaly detection, neural representation, Isolation Forest. I. INTRODUCTION A modern passenger vehicle is not a single computer. It is a collection of electronic control units (ECUs) that exchange short messages to coordinate functions such as engine management, braking, steering, body electronics, and driver assistance. The Controller Area Network (CAN) is one of the communication technologies used for this exchange. Its design favours timely, compact broadcast communication rather than the security properties normally associated with networks exposed to untrusted participants. In particular, a classical CAN frame does not by itself authenticate the ECU that transmitted it. An attacker who gains a route onto the The authors are with the Department of Computer Science and En- gineering (Data Science and Artificial Intelligence), Indian Institute of Information Technology Design and Manufacturing, Kancheepuram, India (e-mail: surendraadda@gmail.com; gvignankv@gmail.com; vundadimanikumar@gmail.com). This project was carried out under the guidance of Dr. Bhale Pradeepkumar Gajendra, Assistant Professor, Department of Computer Science and Engineering, IIITDM Kancheepuram. in-vehicle bus may therefore attempt to inject frames, replay observed messages, or impersonate the traffic of another component. The security implications of such access have been demonstrated in automotive security research and motivate monitoring at the network level [1]–[3]. An intrusion detection system (IDS) can complement pre- ventive con-

trols by observing bus activity and reporting be- haviour that departs from an expected profile. CAN IDS research has considered several kinds of evidence. Some methods examine message identifiers and payload bytes; oth- ers model frame frequency, inter-arrival time, message or- dering, or ECU-specific timing characteristics. These signals are related, but they are not interchangeable. A denial-of- service attack may create a pronounced rate change, whereas a masquerade or replay-like pattern may preserve a familiar identifier or approximate a legitimate transmission schedule. Timing-based methods can be useful when normal periodicity is stable, while content-oriented approaches can detect payload changes that a rate-only monitor would not see [2]–[4]. A common experimental assumption is that the attack classes available during training are also the classes that matter at evaluation time. That assumption is convenient for closed-set classification, but it does not describe the full operational problem. Attack variants change, and a vehicle manufacturer may not possess labelled examples of every malicious behaviour before deployment. An IDS intended to recognise previously unseen attacks must therefore do more than assign a test message to one of the labels learned during training. It needs a mechanism for identifying observations that are sufficiently unlike the benign operating region, while keeping false alarms at a usable level. This paper studies a small, testable pipeline for that setting. A supervised MLP is trained on six known classes. The penultimate hidden activation is then treated as a compact representation of each CAN record. An Isolation Forest is fitted only to the hidden representations of benign training records. A threshold is estimated from benign calibration records and subsequently applied to an evaluation file contain- ing benign traffic and six attack families excluded from MLP training. The design is deliberately narrower than the system that motivated the work. FedGAN-ID combines CAN-message graph construction, a GAN-based detector, federated learning, differential privacy, and energy-based unknown-attack detec- tion [5]. The present implementation does not include those graph, GAN, federated, or privacy mechanisms; it examines an MLP-representation/IF alternative on a public The central question is not whether the pipeline can be made to report a high aggregate score at any threshold. It is whether a representation trained for known-class discrimination retains useful structure for an anomaly detector, and whether this structure is useful across different unseen attack families. Four questions guide the experiments: 1) Does the MLP hidden representation provide a useful anomaly ranking when the IF is fitted using benign records only? 2) How do precision, recall, F1-score, and false-positive rate change between the initially selected 99th-percentile threshold and a more permissive exploratory threshold? 3) Do the six unknown attack families exhibit similar detection behaviour, or is the aggregate result dominated by a subset of them? 4) How does the representation-based detector compare with an IF fitted directly to the 13 input features and with the executed energy-based OOD experiments? The contributions are empirical rather than architectural. First, the manuscript documents the data preparation and unknown-attack protocol used in the project. Second, it reports the complete primary confusion matrix and per-family recalls, not accuracy alone. Third, it separates the preselected operat- ing point from

the exploratory threshold that was examined after test-set inspection. Fourth, it analyses why a strong ROC-AUC can coexist with a weak F1-score at a fixed threshold. Finally, it records negative results from the energy- based experiments and makes explicit which components of FedGAN-ID were not implemented. This narrower framing is important: the results should be judged as an evaluation of the implemented pipeline, not as a claim to reproduce or outperform a substantially different system. II. TECHNICAL BACKGROUND AND RELATED WORK A. CAN Communication and Its Security Context CAN was designed for communication among embedded controllers under constraints on message size, bus access, and latency. The arbitration mechanism prioritises messages by identifier, and frames are broadcast to nodes on the bus. These design choices support robust real-time communication, but the protocol's basic frame format does not provide crypto- graphic source authentication. Consequently, a receiving ECU generally cannot establish the sender's identity solely from the CAN identifier. A compromised node or an external interface that reaches the bus can potentially transmit a frame using an identifier associated with a legitimate signal. The Bosch CAN specification describes the protocol's communication format and bus access model; it should not be confused with a security mechanism that authenticates each sender [1]. The absence of native source authentication does not imply that every CAN message is equally easy to forge. Real vehicle traffic contains regularities: identifiers tend to be associated with particular message roles, payload fields often evolve within constrained ranges, and many messages are transmitted periodically. An IDS can learn a baseline from these regu- larities. The difficulty is that the same regularities can vary with vehicle state, driving conditions, diagnostic activity, and vehicle model. A detector that memorises a single capture can raise alarms on legitimate but unfamiliar operation. This makes the choice of data split and threshold policy as important as the classifier architecture. B. Families of CAN Intrusion Detectors A useful way to organise CAN IDS designs is by the evidence they analyse. Content-oriented systems examine the CAN identifier, payload length, or data bytes. Statistical sys- tems summarise the frequency or distribution of identifiers and payload values. Temporal systems monitor inter-arrival time or the periodicity of messages. Sequence-oriented systems model transitions across multiple frames. Physical-layer and ECU- fingerprinting approaches use characteristics such as clock behaviour or signal properties to associate messages with particular transmitters. These approaches address related but distinct questions: whether a frame looks unusual, whether its timing is unusual, and whether it came from an expected ECU. Surveys of AI-based in-vehicle IDSs discuss the range of learning strategies and the difficulty of comparing results across datasets and evaluation protocols [2], [6]. Muter and Asaj investigated entropy-based anomaly de- tection for in-vehicle networks, illustrating the use of traffic statistics as a baseline for abnormality [4]. Cho and Shin's clock-based IDS uses periodic message timing to fingerprint ECUs and detect deviations in clock behaviour [3]. Such work motivates the inclusion of timing features, but it also illustrates a limitation of record-wise models: when a detector processes each row independently, information encoded in longer mes- sage sequences or transmitter-specific clock

patterns may be only partially represented. C. Known-Attack Classification and Unknown-Attack Detec- tion A closed-set classifier estimates a label from a fixed class list. If the input belongs to a class absent from training, the classifier may still return one of its known labels with high confidence. This is not necessarily a software defect; it follows from the classification objective, which selects among the output classes rather than explicitly modelling every possible unknown class. Unknown-attack detection therefore requires an additional rule, score, or model that can indicate when an observation falls outside the learned benign region. Several strategies are possible. A one-class model can be trained on benign examples alone. A classifier can use confi- dence or energy scores as an indicator of out-of-distribution input. A generative model can approximate normal traffic and use a reconstruction or likelihood-related score. A hybrid detector can combine several types of evidence. FedGAN- ID is an example of a more elaborate design: its published description uses CAN-message graphs, a GAN-based detector, a second-level attack classifier, federated learning across vehicles, differential privacy, and energy-based OOD detection [5]. It evaluates its method on three real vehicles supported by XPeng. These system-level properties are not assumed in this work. Page 4 of 14 - AI PROJECT MANUSCRIPT, NOVEMBER 2026 3 D. Why Use a Neural Representation Before Isolation Forest? Isolation Forest isolates samples through random partition- ing. Anomalous observations are expected, on average, to require fewer splits to isolate than observations in dense regions. The original method does not require attack labels during fitting and is therefore a plausible choice when only benign examples are used to define the reference region [7]. However, Isolation Forest applied to raw features can be sensitive to mixed scales and to the geometry of the original feature space. A neural network trained for known-class classification transforms input features into a hidden space shaped by the classification objective. In principle, that space may bring together records that share known-class structure and separate records whose combinations of features differ. The assumption is not guaranteed to hold for unseen attacks. A representation optimised to discriminate six known labels may discard varia- tion that does not help distinguish those labels. It can also map an unseen attack close to a familiar benign or attack cluster. The MLP–IF combination is thus an empirical question: the representation may improve the ordering of benign and attack scores, but threshold performance and family coverage must be measured separately. E. Dataset Generalisation as an Evaluation Concern The can-train-and-test dataset was curated to support eval- uation across attack types and vehicles, and its associated publication discusses the limitations of available labelled auto- motive datasets [8]. The existence of multiple capture subsets is valuable because a randomly shuffled row-level split may place nearly identical traffic conditions on both sides of an evaluation. At the same time, a particular test capture does not automatically establish generalisation to all vehicle platforms or all driving conditions. The present study uses the named unknown-attack evaluation file and makes no claim that every aspect of cross-vehicle generalisation has been tested. III. STUDY DESIGN AND PROBLEM FORMULATION A. Threat Model The detector is intended to identify CAN records whose extracted attributes are

inconsistent with the learned benign region. The evaluation assumes that the attacker can cause one or more non-benign CAN records to appear in the observed stream, and that the monitoring component can access the identifier, payload length, payload bytes, and capture times- tamps required to derive the input features. The experiment does not model cryptographic key compromise, ECU firmware compromise, physical-layer signal manipulation, or an adver- sary that deliberately optimises messages against the detector. It also does not establish which ECU transmitted a suspicious frame. The output is a binary record-level anomaly flag, not an attribution or attack-family diagnosis. The threat model is intentionally limited to the capabilities represented by the dataset labels. The six evaluation families are treated as unknown because they are not among the six MLP training labels. This is an operational definition of unknown relative to the training protocol, not a claim that the attack techniques themselves are novel in the broader security literature. B. Notation and Learning Objective Let each captured record be represented by a feature vector xi ? R13 and a known training label yi ? {1, . . . , 6}. The six labels are BENIGN, DoS, FORCE NEUTRAL, FUZZING TARGETED, RPM, and STANDSTILL. The MLP learns a parameterised mapping g? : R13 -> R6 for this closed set. We denote the penultimate 64-dimensional activation by zi = f?(xi), zi ? R64 . (1) The IF is fitted to {zi : yi = BENIGN} only. It produces a scalar score s(z) whose sign is oriented in the implementation so that larger values indicate a more anomalous record. The decision rule is ^ a(x) = ? [s(f?(x)) > ?] , (2) where ^ a = 1 denotes an anomaly and ? is estimated from benign calibration scores. The evaluation target is binary: BENIGN records are nega- tive, and records from any of the six held-out attack families are positive. This aggregation is useful for measuring whether a previously unseen attack record is flagged, but it does not mean that all attacks are behaviourally equivalent. The per- family analysis is therefore reported alongside the aggregate confusion matrix. C. Research Questions and Interpretation Boundary The study is designed to answer the four research questions introduced above, under the following interpretation boundary. A higher ROC-AUC indicates that positive records tend to receive higher scores than negative records across score thresh- olds. It does not specify which threshold should be deployed. F1-score, precision, recall, and false-positive rate depend on the selected threshold and the mix of records in the evaluation set. The main result is consequently tied to a preselected calibration rule, and exploratory alternatives are kept separate. This distinction is especially relevant in an imbalanced test set, where a high proportion of benign records can make accuracy appear favourable even when a substantial fraction of attacks is missed. Precision–recall analysis is valuable in such settings because it makes the cost of false alerts and missed positives more visible [9]. IV. DATASET AND DATA PREPARATION A. Source Dataset and Capture Selection The experiments use CAN-train-and-test v1.5, an openly released dataset intended for developing and assessing auto- motive IDSs [8], [10]. The repository is maintained by the dataset authors and provides multiple train/test subsets. The dataset paper describes a curation strategy intended to test generalisation across attack types and vehicles; this project uses only one configured subset of that broader re-

source. The project uses the set 01 training data to construct the Page 5 of 14 - AI PROJECT MANUSCRIPT, NOVEMBER 2026 4 known-class training and calibration files, and the designated unknown-attack test capture for evaluation. In the local project workflow, the unknown evaluation file is referred to as test_ 03_known_vehicle_unknown_attack. The filename's distinction is retained: the experiment treats its attack families as unknown to the classifier; it does not label the evaluation as an unseen-vehicle test. Three processed files are used. The training file is used to fit the scaler and MLP, and its benign subset is used to fit the IF. The calibration file is used to estimate the anomaly- score threshold from benign records only. The unknown-test file is used to calculate the final metrics and family-wise recall. The labels from the unknown-test file are used for evaluation, not as model-fitting targets. However, the evaluation file was examined during earlier exploratory threshold analysis. For this reason, the 97.5th-percentile result is not presented as an independent confirmation. B. Record Counts and Class Composition Table I summarises the processed records. The training file contains 461,345 rows, of which 433,538 are benign and 27,807 are known attacks. The calibration file contains 492,435 rows; 463,134 of these are benign. It also contains known attack records, but the threshold calculation uses only its benign subset. The unknown-test file contains 882,269 rows, including 861,444 benign records and 20,825 records from the six attack families. The six known attack counts sum to 27,807 in the training file. In the unknown-test file, the attack count is 20,825, or approximately 2.36% of all processed records. This prevalence is a property of the prepared evaluation file, not an estimate of the frequency of attacks in normal vehicle operation. During preprocessing, benign records were subsampled at 10% per capture, subject to a maximum of 100,000 retained benign records per file, while attack records were retained. This changes the class mixture and therefore affects metrics such as precision and accuracy. The counts in the table should be retained when results are compared or reproduced. The calibration partition includes records from known attack classes, but only records whose label is BENIGN are passed to the threshold calculation in the embedding-IF script. The benign-only selection is relevant: using attack-labelled calibra- tion records to choose a threshold would change the evaluation protocol and would no longer represent a benign-reference calibration procedure. C. Feature Construction Each row is described by 13 numeric features. The CAN identifier and payload length provide frame-level information. The eight payload byte fields preserve the byte values as separate numeric inputs. Three timing features capture local temporal context: the inter-arrival time between the current record and its predecessor, the inter-arrival time since the previous message with the same identifier, and a rolling mean of inter-arrival time. Absolute timestamps are not passed to the MLP or the IF. Temporal features are calculated in capture order within the original capture file before the processed partitions are consumed by the model. Negative time differences are clipped to zero in preprocessing. This preserves the chronological ordering available in the capture, but it does not construct an explicit multi-frame sequence tensor. Once calculated, each row is treated as one 13-dimensional observation. Thus, the model can use local timing summaries

but cannot directly learn arbitrary long-range message dependencies. D. Feature Scaling and Label Mapping A standard scaler is fitted to the training feature matrix. The same fitted transformation is applied to calibration and test rows. No calibration or test feature values are used to estimate the scaler parameters. The MLP label mapping is restricted to the six known training classes. For binary unknown-attack evaluation, the ground-truth label is converted to zero for BENIGN and one for every non-BENIGN record. The six unknown labels are never added to the MLP output layer. E. Preprocessing Risks Preprocessing itself can affect apparent model performance. Subsampling benign records changes the empirical class prior. Calculating timing features within each original capture avoids using a timestamp from one capture as the predecessor of a record from another capture; however, the exact capture boundaries and ordering must be preserved to reproduce the features. Numeric treatment of CAN identifiers also imposes a geometry on the identifier values. The numerical distance between two IDs is not necessarily a meaningful semantic distance between their message functions. The current pipeline uses this numeric encoding because it is what the implemented model consumes; it does not claim that CAN identifiers are naturally continuous variables. V. PROPOSED EXPERIMENTAL PIPELINE A. Pipeline Overview Fig. 1 shows the stages actually implemented. Raw capture files are first converted into processed rows. The scaler and six-class MLP are fitted using the training partition. The penultimate activation is extracted for benign training rows, benign calibration rows, and all unknown-test rows. The IF is fitted to the benign training activations. Its anomaly scores on benign calibration activations determine the primary threshold. The decision rule is then applied to the unknown-test scores. The data flow contains two different learning objectives. The MLP is supervised: its purpose is to discriminate among the known labels. The IF is unsupervised with respect to attacks: it is fitted only to benign representations and does not use known-attack labels. The two objectives should not be conflated. In particular, the IF is not trained to classify DOUBLE, FUZZING, INTERVAL, SPEED, SYSTEMATIC, or TABLE I PROCESSED DATASET COMPOSITION USED IN THE EXPERIMENTS Partition Label/group Records Role in experiment Training BENIGN 433,538 MLP training and IF fitting Training DoS 9,139 MLP known class Training FORCE NEUTRAL 6,500 MLP known class Training FUZZING TARGETED 6,615 MLP known class Training RPM 3,338 MLP known class Training STAND-STILL 2,215 MLP known class Training Total 461,345 Calibration BENIGN 463,134 Threshold estimation Calibration Known attack records 29,301 Not used for threshold Calibration Total 492,435 Unknown test BENIGN 861,444 Negative evaluation class Unknown test DOUBLE 1,292 Unknown attack family Unknown test FUZZING 5,975 Unknown attack family Unknown test INTERVAL 4,418 Unknown attack family Unknown test SPEED 5,321 Unknown attack family Unknown test SYSTEMATIC 1,043 Unknown attack family Unknown test TRIPLE 2,776 Unknown attack family Unknown test Total 882,269 TABLE II INPUT FEATURES Feature Meaning in the processed row can_id Arbitration identifier represented numerically payload_length Number of data bytes in the frame byte_0–byte_7 Eight payload byte values; unused byte positions follow the

preprocessing convention delta_t_ms Time since the preceding record in capture order same_id_delta_t_ms Time since the previous occurrence of the same CAN identifier rolling_mean_delta_t_ms Rolling mean of the inter-arrival-time feature Fig. 1. Implemented MLP-representation and benign-only Isolation Forest pipeline. The MLP uses the six known labels; the IF fitting and primary threshold estimation use benign records only. B. Multilayer Perceptron The MLP receives the 13 standardised features. Its fully connected network has a first hidden layer with 128 units, a ReLU activation, and dropout of 0.2; a second hidden layer with 64 units, another ReLU activation and dropout of 0.2; and a six-unit linear output layer. The architecture can be written as h1 = Dropout0.2(ReLU(W1x + b1)), (3) h2 = Dropout0.2(ReLU(W2h1 + b2)), (4) l = W3h2 + b3, (5) where l ? R6 contains the class logits. During embedding extraction the network is placed in evaluation mode, so dropout is disabled, and the 64-dimensional activation immediately after the second ReLU is captured. In notation, this activation is z = f?(x). The training script uses cross-entropy loss with square- root inverse-frequency class weights. If nc is the number of training records for class c and N is the total number of training records, the unnormalised weight is proportional to ? N/(6nc); the weights are normalised to have mean one. This reduces the contribution imbalance caused by class sizes without applying the full inverse-frequency weighting. Optimisation uses Adam with learning rate 0.001, batch size 4096, and 25 epochs. The random seed is set to 42 for the Python numerical library and the PyTorch model. The MLP Page 7 of 14 - AI PROJECT MANUSCRIPT, NOVEMBER 2026 6 is run on CPU in the recorded experiment. The training log reported a final training accuracy of 99.86%. This figure is a training-set statistic. It does not measure unknown-attack detection performance and must not be presented as a held-out classification accuracy. The down- stream anomaly detector is evaluated separately using the unknown-test file. C. Extraction of the Hidden Representation The activation after the second ReLU is a 64-dimensional vector. The dropout layer follows this activation during MLP training, but embedding extraction is performed with the model in evaluation mode. Consequently, the IF receives the deterministic hidden activation from the trained model rather than the output logits. This choice makes the representation a learned feature map from the original 13-dimensional space to a 64-dimensional space. The representation has no explicit metric-learning loss or contrastive objective. Its geometry is induced by the six- class cross-entropy objective. This is a design choice, not an assumption that the embedding is optimal for unknown-attack detection. The later evaluation is necessary because the MLP was not trained with an explicit objective to separate every unseen attack from benign activity. D. Isolation Forest Fitting The IF is fitted to the hidden representations of the 433,538 benign training records. Its configuration uses 300 estimators, a maximum sample size of 2,048 per tree, automatic con- tamination handling, random state 42, and parallel execution. The detector is fitted without attack-labelled records. In scikit-learn's decision-function convention, lower values indicate greater abnormality; the project negates the returned decision function so that a higher stored score corresponds to a more anomalous observation. We denote this oriented score by

s(z). The maximum sample size is substantially smaller than the benign training set. This is consistent with the subsampling design of Isolation Forest, but it means that each tree is built from a subset of the training representations. The ensemble combines the resulting isolation behaviour across trees. The study does not tune the tree count or sample size through a nested validation procedure; the parameters are fixed at the values above. E. Calibration Rule and Operating Point Let SB cal be the anomaly scores obtained from benign calibration records. The primary threshold is the empirical 99th percentile: ?99 = Q0.99(SB cal) = 0.1633390. (6) A record is flagged when s(z) > ?99. The percentile is selected from a benign reference set, rather than from the distribution of unknown-test attack scores. The intended interpretation is an initial operating point that tolerates a small upper tail of benign calibration scores. The 99th percentile does not guarantee a 1% false-positive rate on a later capture: shifts in vehicle state, collection conditions, or the capture distribution can change the tail behaviour. A 97.5th-percentile threshold, ?97.5 = 0.0243811, is also reported. The numerical threshold is calculated from benign calibration scores. However, the decision to examine and emphasise this more permissive quantile followed earlier in- spection of unknown-test metrics. Therefore, the associated evaluation is exploratory. It is included to show threshold sen- sitivity and to preserve the experimental record, not to replace the primary result or to claim an unbiased improvement. F. Evaluation Measures For the binary task, true positives (TP) are attack records flagged by the detector; false positives (FP) are benign records flagged as anomalous; true negatives (TN) are benign records left unflagged; and false negatives (FN) are attack records left unflagged. The metrics are Precision = TP TP + FP , (7) Recall = TP TP + FN , (8) F1 = 2 Precision . Recall Precision + Recall , (9) FPR = FP FP + TN , (10) Accuracy = TP + TN TP + TN + FP + FN . (11) ROC-AUC and average precision (reported as PR-AUC in the project outputs) are calculated from continuous scores rather than binary predictions. This distinction matters because threshold changes alter precision, recall, F1, and FPR but do not alter the ranking of a fixed set of continuous scores. In an imbalanced evaluation, a large true-negative count can keep accuracy high even when many attacks are missed. Precision– recall measures are therefore reported with ROC-AUC and the confusion matrix [9]. VI. EXPERIMENTAL SETUP AND BASELINES A. Implementation Environment The implementation is written in Python and uses Py- Torch for the MLP, scikit-learn for feature standardisation and Isolation Forest, and pandas/NumPy for data handling. The recorded neural-network run used CPU execution, batch size 4096, 25 epochs, and learning rate 0.001. The IF used 300 trees and 2,048 samples per tree. A fixed random seed of 42 was specified in the principal scripts. The package list is supplied separately in requirements.txt in the project repository. The raw dataset is not redistributed with the research project. Reproduction requires obtaining the dataset from its maintainers, arranging the relevant capture files in the expected directory, and running the preprocessing script to regenerate the processed CSV files. Trained model checkpoints and local intermediate files are not part of the source package. Accordingly, the manuscript reports the outputs obtained in the project environment; it does not claim that a clean

machine can reproduce every numeric result without first obtaining the data and NOVEMBER 2026 7 B. Original-Feature Isolation Forest The first comparison model is an IF fitted directly to the original 13-dimensional feature vectors. It uses the benign training rows for fitting and benign calibration scores for the 99th-percentile threshold. The IF parameters are 300 estima- tors, maximum sample size 2,048, automatic contamination, and random state 42. This comparison helps answer whether the learned representation changes anomaly-score ranking rel- ative to the raw numeric inputs. It is not a comparison against the full set of state-of-the-art CAN IDS methods. C. Energy-Based OOD Experiments The project also executed a six-class MLP energy-score experiment. For logits l(x), the score follows E(x) = -T log 6 ? k=1 exp(lk(x)/T), (12) with temperature T = 1. The project evaluated a benign-calibration threshold policy and a maximum-training- malicious-energy adaptation inspired by the unknown-detection discussion in FedGAN-ID. Neither of these executed energy experiments flagged any unknown attack records at the reported operating points. This result is useful as a negative comparison, but it does not establish that energy-based OOD methods generally fail. It only describes these particular model outputs and threshold policies on this evaluation file. D. Comparison Protocol All methods in Table VI were evaluated on the same processed unknown-test file. The primary comparison uses the 99th percentile for the raw-feature IF and embedding IF. The 97.5th-percentile embedding result is separated with an asterisk because it is exploratory. The energy methods are included as executed project experiments. Direct comparison to FedGAN-ID is intentionally excluded: FedGAN-ID uses a different private vehicle dataset, different attack taxonomy, graph construction, GAN, federated aggregation and privacy mechanisms. Without a common benchmark and protocol, a numeric ranking between the two systems would be mislead- ing. VII. RESULTS A. Primary Result at the 99th Percentile At ?99 = 0.1633390, the embedding detector produces 3,956 true positives, 8,937 false positives, 852,507 true neg- atives, and 16,869 false negatives. These counts give 30.68% precision, 19.00% recall, and an F1-score of 23.47%. The false-positive rate is 1.04%, while accuracy is 97.08%. The accuracy value is not sufficient to describe the detector: the number of benign records is much larger than the number of attacks, and the detector misses more than four-fifths of the attack records at this operating point. The relatively high ROC-AUC and lower threshold-specific recall are not contradictory. ROC-AUC measures the ranking of positive and negative records across possible cut-offs. The TABLE III PRIMARY BINARY DETECTION RESULT AT THE 99TH-PERCENTILE THRESHOLD Measure Value Threshold 0.1633390 Accuracy 97.08% Precision 30.68% Recall 19.00% F1-score 23.47% False-positive rate 1.04% ROC-AUC 0.9423 PR-AUC / average precision 0.4299 TP / FP 3,956 / 8,937 TN / FN 852,507 / 16,869 TABLE IV UNKNOWN ATTACK-FAMILY RESULTS AT THE PRIMARY THRESHOLD Family Detected / total Recall DOUBLE 0 / 1,292 0.00% FUZZING 3,900 / 5,975 65.27% INTERVAL 0 / 4,418 0.00% SPEED 0 / 5,321 0.00% SYSTEMATIC 56 / 1,043 5.37% TRIPLE 0 / 2,776 0.00% 99th-percentile rule chooses one cut-off from benign calibra- tion data. If attack scores are often higher than benign scores but still fall below that

cut-off, the model can obtain a strong ranking measure while returning a low recall at the selected operating point. The converse operational issue is also visible: moving the cut-off lower identifies more attack records but increases the number of benign records raised as alerts. B. Per-Family Detection at the Primary Threshold The aggregate recall of 19.00% conceals large differences among attack families. FUZZING contributes 3,900 detected records out of 5,975, giving 65.27% recall. SYSTEMATIC contributes 56 detections out of 1,043, or 5.37%. No records from DOUBLE, INTERVAL, SPEED, or TRIPLE exceed the primary threshold. Table IV gives the counts and recalls. The zero-recall outcomes should not be interpreted as proof that the corresponding families are indistinguishable from benign traffic under every feature representation. They indicate that, with this feature set, this trained network, this IF configuration, and the primary threshold, none of the evaluated records in those four families crossed the decision boundary. The result identifies a concrete weakness in this configuration and motivates family-specific analysis rather than a broad claim that unseen CAN attacks are detected reliably. C. Threshold Sensitivity: Exploratory 97.5th Percentile The exploratory threshold is ?97.5 = 0.0243811. At this value the detector flags 13,022 attacks and 18,905 benign records, yielding 62.53% recall, 40.79% precision, 49.37% F1, and a 2.19% false-positive rate. Recall increases by 43.53 percentage points relative to the primary operating point; FPR increases by approximately MANUSCRIPT, NOVEMBER 2026 8 Fig. 2. Recall by unknown attack family at the primary 99th-percentile and exploratory 97.5th-percentile thresholds. TABLE V PRIMARY AND EXPLORATORY OPERATING POINTS Metric 99th (primary) 97.5th (exploratory) Threshold 0.1633390 0.0243811 Accuracy 97.08% 96.97% Precision 30.68% 40.79% Recall 19.00% 62.53% F1-score 23.47% 49.37% FPR 1.04% 2.19% ROC-AUC 0.9423 0.9423 PR-AUC 0.4299 0.4299 TP 3,956 13,022 FP 8,937 18,905 FN 16,869 7,803 TN 852,507 842,539 number of detected attack records rises by 9,066, while the number of false alerts rises by 9,968. This is a meaningful change in the alert burden, not a free increase in detector quality. The 97.5th-percentile result may be attractive where missed attacks are considered more costly than additional alerts, but that operational preference would need to be defined before examining the test labels. In this study, the unknown-test file was inspected during earlier threshold exploration. As a result, the selected 97.5th- percentile point is reported transparently as exploratory and should not be used as the headline validated performance figure. At this exploratory operating point, family-wise recall is 9.06% for DOUBLE, 80.52% for FUZZING, 96.42% for INTERVAL, 60.27% for SPEED, 34.32% for SYSTEMATIC, and 9.69% for TRIPLE. The gain is therefore not evenly distributed. INTERVAL and SPEED change from zero recall at the primary threshold to high or moderate recall at the exploratory threshold, while DOUBLE and TRIPLE remain difficult. Fig. 2 presents both sets of family-wise results. The ROC-AUC and PR-AUC values remain the same be- tween the two threshold rows because both are computed from the same continuous score vector on the same evaluation records. Threshold choice changes the binary predictions, not the score ranking. Reporting the same AUC values beside different F1 values is therefore expected; it is not a separate improvement

in ranking. Fig. 3. Confusion matrices for the primary and exploratory operating points. The exploratory panel is included to illustrate threshold sensitivity and is not an independent validation result. Fig. 4. Threshold-specific F1, recall, and FPR for the two Isolation Forest configurations. The 97.5th-percentile point is exploratory. D. Comparison with the Original-Feature Baseline The IF trained on the original 13 features obtains F1 28.94%, recall 24.47%, and FPR 1.08% at its 99th-percentile threshold. The embedding-based IF obtains F1 23.47%, recall 19.00%, and FPR 1.04%. Thus, by the selected threshold- specific metrics, the original-feature IF performs better on F1 and recall, while the embedding detector has a slightly lower FPR. The ranking measures show a different pattern. The original- feature IF has ROC-AUC 0.6303 and PR-AUC 0.2006, whereas the embedding IF has ROC-AUC 0.9423 and PR- AUC 0.4299. The embedding provides a much stronger or- dering of the evaluated benign and attack records according to these area measures. This does not make the embedding detector unambiguously superior. It means its score distribu- tion separates many positive and negative examples in ranking terms, but the selected 99th-percentile cut-off is conservative for this test distribution. A detector selection decision should take account of both ranking quality and the alert rate at the intended operating point. The energy-based experiments did not detect unknown records at the chosen operating points. Their near-zero FPR is not a useful result by itself because it is accompanied by zero recall. In practical intrusion detection, a detector that never raises an attack alert is not effective merely because it rarely alarms on benign traffic. This negative result is included because it influenced the model-selection process; it should not be generalised to all energy-based OOD methods. Page 10 of 14 - AI PROJECT MANUSCRIPT, NOVEMBER 2026 9 TABLE VI EXECUTED METHOD COMPARISONS ON THE SAME UNKNOWN-TEST FILE Method F1 Recall FPR ROC-AUC Raw-feature IF, 99th 28.94% 24.47% 1.08% 0.6303 Embedding IF, 99th 23.47% 19.00% 1.04% 0.9423 Embedding IF, 97.5th* 49.37% 62.53% 2.19% 0.9423 Energy OOD 0.00% 0.00% 0.001% 0.2325 Max-training-energy 0.00% 0.00% 0.0017% 0.2325 * Exploratory threshold: the evaluation file had been inspected during earlier threshold analysis. The energy rows describe only the two executed project configurations. Fig. 5. Median anomaly score by ground-truth group. Higher scores are more anomalous under the stored score convention. E. Anomaly-Score Distribution by Family The median anomaly score differs across the evaluated la- bels. The benign median is -0.131440. The medians for DOU- BLE and TRIPLE are -0.108853 and 0.006674, respectively, while FUZZING has a much higher median of 0.297320. INTERVAL and SPEED have medians of 0.044970 and 0.033780, and SYSTEMATIC has a median of -0.029677. These summaries are consistent with the observed recall pat- tern: FUZZING scores tend to lie further into the anomalous tail, whereas the score distributions for DOUBLE and TRIPLE overlap more strongly with the benign region. A median is only one point in a distribution. It does not describe the tails, spread, or proportion of records above a selected threshold. Therefore, the median plot is used as a descriptive diagnostic, not as a substitute for the family-wise confusion counts. In particular, a family may have a median below the threshold but still contain a high-scoring subset, and a median above

the threshold does not imply that every record is flagged. F. Timing and Payload Diagnostics The processed data also provide timing and payload sum- maries that help interpret the family-specific outcomes. The benign median inter-arrival time is 0.0138 ms, compared with 0.8030 ms for DOUBLE and 0.7639 ms for TRIPLE. Median payload length is 8 bytes for benign records, 7 for DOUBLE, and 5 for TRIPLE. FUZZING has a median inter-arrival time of 0.8988 ms and a very large median same-identifier inter- arrival time in the processed summary. INTERVAL shows a median inter-arrival time of 0.3589 ms and a same-identifier inter-arrival time of 0.3641 ms. SPEED records show median inter-arrival and same-identifier inter-arrival times of 0.8707 ms and 2.9240 ms, respectively. These are marginal summaries. They do not demonstrate that a specific timing feature caused a detection or miss. The MLP may combine all input dimensions nonlinearly, and the IF acts on the 64-dimensional representation rather than on an individual feature. A controlled ablation study would be needed to attribute the difference in family recall to timing, payload, or identifier information. No such ablation is claimed in this manuscript. VIII. DISCUSSION A. Ranking Performance and the Selected Threshold The embedding-based detector obtains ROC-AUC 0.9423 and PR-AUC 0.4299. At the primary threshold, however, recall is 19.00%. These values describe different properties of the detector. The AUC measures how the scores order benign and attack records over a range of cut-offs; recall measures the fraction of attacks detected at the single threshold used here. A strong ranking result therefore does not guarantee useful decisions at a particular operating point [9]. The exploratory 97.5th-percentile cut-off raises recall from 19.00% to 62.53%. The false-positive rate also rises, from 1.04% to 2.19%. On this test file, that change corresponds to 9,066 additional detected attacks and 9,968 additional false alarms. The 97.5th-percentile result is not an independent validation result: the test file had already been inspected during threshold exploration. A deployment threshold should instead be selected using a separate validation capture and a predeclared false-alarm budget, then held fixed for the final evaluation. B. Detection Differences Across Attack Families The primary threshold detects 65.27% of FUZZING records and 5.37% of SYSTEMATIC records. None of the evaluated DOUBLE, INTERVAL, SPEED, or TRIPLE records crosses this threshold. At the exploratory threshold, INTERVAL and SPEED recall increase substantially, while DOUBLE and TRIPLE remain below 10%. The score summaries show that the family distributions are not identical. For example, FUZZING has a higher median anomaly score than benign traffic, whereas the DOUBLE median is close to the benign median. This observation is consistent with the measured recall differences, but it does not identify the feature responsible for them. The MLP uses all 13 input features, and the IF operates on the resulting 64-dimensional representation. Feature ablations or sequence- level experiments would MANUSCRIPT, NOVEMBER 2026 10 payload, or identifier information explains the family-wise outcomes. C. Raw Features and Learned Representations The original-feature IF obtains an F1-score of 28.94% and recall of 24.47% at its 99th-percentile threshold. The embed- ding IF obtains 23.47% F1 and 19.00% recall. In contrast, the embedding IF has higher ROC-AUC (0.9423 versus 0.6303) and PR-AUC (0.4299 versus

0.2006). Thus, the embedding changes the score ordering, but this does not translate into better binary decisions at the selected threshold. The results do not support describing the embedding detec- tor as uniformly better. Its ranking metrics are higher, while the raw-feature baseline has better F1 and recall at the primary operating point. Which configuration is preferable depends on the intended operating requirement and the threshold policy. Both ranking metrics and threshold-specific measures should therefore be reported. D. Energy-Based OOD Experiments The two executed energy-score experiments did not flag any unknown attack records at their reported thresholds. This is the outcome for the particular MLP, score definition, calibration data, and thresholds tested here. It does not show that energy- based OOD detection is generally ineffective. One possible explanation is that the MLP assigns unknown records logits similar to those of known classes, resulting in energy scores that do not exceed the selected cut-off. The current experiments do not establish this explanation: they do not include a family-wise analysis of logit confidence or a controlled comparison of temperature and calibration choices. The implementation is also not the full FedGAN-ID system, which combines energy-based OOD detection with graph construction, GAN-based modelling, and federated learning [5]. No conclusion about the performance of that complete system can be drawn from these lo- cal experiments. E. Calibration Under Distribution Shift The 99th-percentile calibration rule is simple and repro- ducible: it fixes the threshold from the upper tail of benign calibration scores. Its weakness is that the calibration and test score distributions may differ. A new driving session, a different vehicle, changed bus load, maintenance activity, or a modified capture setup may shift the benign score distribution. A threshold that corresponds to one percent of benign calibra- tion scores can therefore produce a different false-positive rate elsewhere. This study observes a 1.04% FPR on the processed test file, which is close to but not guaranteed by the 99th- percentile calibration rule. An opera- tional calibration procedure should test stability over multiple benign sessions and vehicles. It should also include a method for handling drift. Updating a threshold automatically is not straightforward: if the data used for recalibration contain undetected attacks, the benign reference region may be contaminated. Future work should investigate drift detection and controlled recalibration with trusted benign intervals rather than treating a single calibration percentile as a universal constant. F. Implications for a Vehicle IDS The implemented pipeline can be understood as a research prototype for record-level anomaly scoring. It has not been evaluated on an automotive electronic control unit, a produc- tion gateway, or a hardware-in-the-loop setup. The reported training time and offline processing do not establish real- time inference feasibility. A deployment study would need to measure per-frame latency, throughput under bus load, memory consumption, model update cost, and the effect of logging and preprocessing on an embedded processor. It would also need to test whether timing features can be calculated with consistent semantics in the target gateway. A further distinction concerns alerts. The current output is binary and does not identify the originating ECU or ex- plain which byte or timing feature caused the score. For use by a vehicle-security engineer, an alert would ideally in- clude contextual

evidence: identifier, capture time, local score, threshold, surrounding frames, and a confidence or severity interpretation. That extension must be designed carefully so that explanation does not create false confidence or disclose sensitive vehicle information. IX. VALIDITY CONSIDERATIONS AND LIMITATIONS Several limitations determine how far the results can be generalised. A. Evaluation-Set Reuse The unknown-test file was examined during earlier ex- ploratory threshold analysis. Even though the threshold value is calculated from benign calibration scores, the decision to emphasise the 97.5th percentile followed inspection of test performance. This creates a model-selection concern: the exploratory result is no longer an untouched estimate of generalisation. The 99th-percentile operating point is retained as the primary result because it was the initially selected operating point. A new capture that has not been consulted during development is required for an independent estimate. B. Class Prevalence and Sampling Benign traffic was subsampled while attack records were retained. The unknown-test file has an attack prevalence of approximately 2.36%. Precision and accuracy depend on class prevalence, so they should not be transferred directly to a deployment environment with a different benign-to-attack ratio. Recall and FPR are also subject to dataset and capture shift. The sampling policy must be disclosed when using the reported precision and accuracy in a comparison. C. Limited Dataset and Capture Scope The experiments use one configured known-class train- ing/calibration workflow and one designated unknown-attack test file. They do not establish performance over all vehicles, software versions, road conditions, and bus configurations. The can-train-and-test paper was designed to support broader comparisons across attack types and vehicles, but this project has not run all of its subsets [8]. Consequently, no universal cross-vehicle claim is NOVEMBER 2026 11 D. Single Configuration and Randomness The reported model uses a fixed seed and one configured training run. There are no multi-seed means, standard devi- ations, confidence intervals, or statistical significance tests. The IF itself uses random partitioning. Although fixed random states make the recorded run more repeatable, they do not show how stable the performance is across different seeds. A stronger study would repeat the full pipeline using several seeds and report variation in both aggregate and family-wise metrics. E. Representation and Feature Limitations The MLP is trained for six-class classification, not for open- set representation learning. The hidden space may suppress variations that do not help separate the known classes. The 13-dimensional input contains only a small set of per-frame and local timing attributes. It does not include a learned graph of message transitions, a longer sequence window, physical- layer information, or explicit transmitter identity. Numeric CAN identifier encoding may also impose distances that do not reflect semantic relations among message IDs. F. No Complete FedGAN-ID Reproduction The work does not implement the GAN, federated aggre- gation, differential privacy, message-graph construction, MTF, READ, or the second-level classifier described in FedGAN- ID. It also does not evaluate privacy leakage, communication overhead, client heterogeneity, or attack detection latency on a real vehicle. The use of FedGAN-ID as motivation must not be interpreted as proof that the present project reproduces the article's architecture or val-

idates its reported results [5]. X. REPRODUCIBILITY AND REPORTING CHECKLIST To make a future rerun easier to audit, the following items should accompany the paper: (i) the exact repository commit used for the submitted manuscript; (ii) the dataset version and capture filenames; (iii) the preprocessing script and its sampling settings; (iv) the Python and library versions; (v) the MLP checkpoint and scaler or an instruction to regenerate them; (vi) the seed and training parameters; (vii) the exact calibration file and benign-row filtering rule; (viii) the IF configuration and threshold percentile; and (ix) the scripts that generate every reported table and figure. The raw dataset should be obtained from its maintainers rather than redis- tributed without checking its licence. A reproducibility package should distinguish source code from generated outputs. The scripts and configuration are necessary to reproduce the analysis, while the CSV result summaries and figures are convenient evidence of the par- ticular run. A clean installation test should start from the repository root, recreate the environment, run preprocessing, train the model, extract embeddings, fit the detector, and execute evaluation. A syntax check alone is not a runtime reproduction. The current manuscript therefore describes the implementation and its recorded outputs without claiming that a third party has independently rerun the complete workflow. XI. FUTURE WORK A first priority is to obtain an untouched evaluation capture. The threshold percentile, feature set, and model configuration should be frozen using training and validation data only. The final capture should be opened only after the complete decision rule is fixed. This would provide a cleaner estimate of whether the 99th-percentile operating point transfers to a new session and whether a more permissive threshold is justified by a predeclared alert budget. A second direction is to evaluate the effect of the input representation. Ablations could remove payload bytes, CAN identifier, or each timing feature group in turn. A temporal model could process a sequence of consecutive records rather than independent row vectors. A graph-based model could represent message transitions or co-occurrence patterns. These experiments would help test the hypothesis that DOUBLE and TRIPLE are difficult because their local feature distributions overlap with benign traffic. Such an explanation should only be accepted if the controlled experiments support it. Third, the threshold should be evaluated as an operational parameter. Instead of selecting a percentile after observing test results, the study could choose a target benign alert rate on a validation set, freeze the threshold, and report its performance across separate captures. Calibration stability should be measured by vehicle, session, and operating condition. The model should also be assessed using precision–recall curves, family- wise metrics, and confidence intervals across repeated training runs. Fourth, the energy-based baseline should be investigated with a controlled study of logit distributions and threshold policies. The present zero-recall outcome suggests that the current energy score is not separating the unknown attack examples at the tested threshold. It does not reveal whether the issue is the MLP, the score definition, the temperature, the calibration population, or the attack distribution. These factors should be varied one at a time on validation data before any claim is made. Finally, federated and privacy-preserving extensions could be explored if multiple vehicle datasets

become available. Such an extension would require a true multi-client setup, explicit local training and aggregation, a documented privacy mechanism and budget, and analysis of the effect of privacy noise on anomaly detection. Those are substantial additional experiments; they are not minor modifications to the current IF pipeline. XII. CONCLUSION The MLP–IF pipeline was evaluated on one designated unknown-attack capture from CAN-train-and-test v1.5. At the primary 99th-percentile threshold, it detected 3,956 of 20,825 attack records. This gives 19.00% recall, 30.68% precision, and 23.47% F1, with a 1.04% false-positive rate. The ROC- AUC was 0.9423 and the PR-AUC was 0.4299. Detection was concentrated in FUZZING (65.27% recall); no DOUBLE, INTERVAL, SPEED, or TRIPLE records crossed the NOVEMBER 2026 12 The comparison with the raw-feature IF produced a mixed result. The embedding detector ranked the evaluated records better according to ROC-AUC and PR-AUC, but the raw- feature detector achieved higher F1 and recall at the selected operating point. The exploratory 97.5th-percentile threshold increased recall to 62.53% and F1 to 49.37%, at a 2.19% false- positive rate. Because the unknown-test file was inspected during threshold exploration, this result should not be treated as an independent estimate of generalisation. The experiments describe this MLP–IF implementation only. They do not reproduce the GAN, federated aggregation, differential privacy, graph construction, or other components of FedGAN-ID. A stronger evaluation requires a new capture that has not been used during development, repeated training runs, and a threshold fixed using validation data before the final test. Until then, the reported measurements apply to the dataset split and configuration described in this paper. ACKNOWLEDGMENT The authors thank Dr. Bhale Pradeepkumar Gajendra for guidance during the research project. The authors are respon- sible for verifying the correctness of the experiments, interpret- ing the results, and ensuring that the final manuscript complies with the institution's research and authorship policies. REFERENCES [1] Robert Bosch GmbH, CAN Specification Version 2.0, Robert Bosch GmbH, 1991, technical specification. [2] S. Rajapaksha, H. Kalutarage, M. O. Al-Kadri, A. Petrovski, G. Madzudzo, and M. Cheah, "AI-based intrusion detection systems for in-vehicle networks: A survey," ACM Computing Surveys, vol. 55, no. 11, pp. 1–40, 2023. [3] K.-T. Cho and K. G. Shin, "Fingerprinting electronic control units for vehicle intrusion detection," in Proceedings of the 25th USENIX Security Symposium. USENIX Association, 2016, pp. 911–927. [Online]. Available: https://www.usenix.org/conference/usenixsecurity16/technical-sessions/presentation/cho [4] M. Muter and N. Asaj, "Entropy-based anomaly detection for in-vehicle networks," in 2011 IEEE Intelligent Vehicles Symposium, 2011, pp. 1110–1115. [5] M. Chen, B. Wu, H. Sun, and Z. Wang, "FedGAN-ID: Federated- learning-based intrusion detection for in-vehicle network using GANs," IEEE Internet of Things Journal, vol. 12, no. 17, pp. 36 155–36 167, Sep. 2025. [6] M. Althunayyan, A. Javed, and O. Rana, "A survey of learning- based intrusion detection systems for in-vehicle networks," Computer Networks, vol. 277, p. 112031, 2026. [7] F. T. Liu, K. M. Ting, and Z.-H. Zhou, "Isolation forest," in Proceedings of the 8th IEEE International Conference on Data Mining, 2008, pp. 413–422. [8] B. Lampe and W. Meng,

"can-train-and-test: A curated CAN dataset for automotive intrusion detection," Computers and Security, vol. 140, p. 103777, 2024. [9] J. Davis and M. Goadrich, "The relationship between precision-recall and ROC curves," in Proceedings of the 23rd International Conference on Machine Learning. ACM, 2006, pp. 233–240. [10] B. Lampe and W. Meng, "CAN-train-and-test-v1.5 dataset repository," https://bitbucket.org/brooke-lampe/can-train-and-test-v1.5/src/master/,