Command Prompt

```
Packet Tracer PC Command Line 1.0
PC>ping 192.168.1.3

Pinging 192.168.1.3 with 32 bytes of data:

Reply from 192.168.1.3: bytes=32 time=30ms TTL=128
Reply from 192.168.1.3: bytes=32 time=0ms TTL=128
Reply from 192.168.1.3: bytes=32 time=0ms TTL=128
Reply from 192.168.1.3: bytes=32 time=0ms TTL=128

Ping statistics for 192.168.1.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 30ms, Average = 9ms

PC>ping 192.168.2.2

Pinging 192.168.2.2 with 32 bytes of data:

Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.

Ping statistics for 192.168.2.2:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

Command Prompt

```
Packet Tracer PC Command Line 1.0
PC>ping 192.168.2.3

Pinging 192.168.2.3 with 32 bytes of data:

Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.
Reply from 192.168.1.1: Destination host unreachable.

Ping statistics for 192.168.2.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

Command Prompt

```
PC>ping 192.168.2.3

Pinging 192.168.2.3 with 32 bytes of data:

Reply from 192.168.2.3: bytes=32 time=21ms TTL=128
Reply from 192.168.2.3: bytes=32 time=1ms TTL=128
Reply from 192.168.2.3: bytes=32 time=3ms TTL=128
Reply from 192.168.2.3: bytes=32 time=1ms TTL=128

Ping statistics for 192.168.2.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 21ms, Average = 6ms
```

Exp: 09

Design a simple network topology and configure one router, two switches and four PCs using Cisco Packet Tracer

Aim:

To design and configure a simple network topology consisting of one router, two switches and four PCs using cisco packet tracer.

Procedure:

1. Open cisco packet tracer.
2. Add the following devices.
   - 1 Router (2911)
   - 2 switch (2960)
   - 4 PCs
3. Connect the device using copper straight through cables.
   - Router G0/0 → Switch 1 Fa0/1
   - Router G0/1 → Switch 2 Fa0/1
   - PC0 FastEthernet0 → Switch 1 Fa0/2.
   - PC1 FastEthernet0 → Switch 1 Fa0/3.
   - PC2 FastEthernet0 → Switch 2 Fa0/2
   - PC3 FastEthernet0 → Switch 2 Fa0/3
4. Configure Router G0/0 with IP address 192.168.1.1/24 & enable interface.

5. Configure Router Gol: with IP address 192.168.2.1/24.

6. Save the router configuration using copy running-config startup-config.

7. Configure the PCs with the following IP address and default gateways.

8. Open desktop → command prompt on PCs.

10. Verify the packets are successfully transmitted and recived without packet loss.

Result:

The network topology was successfully design and configured in cisco packets tracer. All four PCs communicated Successfully through the router, confirming proper network connectivity.