Implementation of Blocks World Program

PROGRAM :-

```
class BlocksWorld :
    def __init__(self, num_blocks):
        self.state = [[block] for block in range
                      (num_blocks)]
        self.num_blocks = num_blocks
    def display_state(self):
        for stack in self.state :
            print(f"Block(s) on stack : {stack}")
    def move(self, block, destination):
        destination_stack = self.find_block
    def find_block(self, block):
        for stack in self.state :
            if block in stack :
                return stack
        return None
    def main()
        blocks_world = BlocksWorld(3)
        print("Initial state :")
        blocks_world.display_state()
        goal = [[0,1],[2]]
        blocks_world.goal_state(goal)
    print("\n performing moves :")
    blocks_world.move(0,2)
    blocks_world.move(1,2)
    blocks_world.move(2,0)
if name__ == "__main__":
    main()
```

OUTPUT:-

Initial State

Block (s) on Stack: [0]

Block (s) on Stack: [1]

Block (s) on Stack: [2]

goal State Set:

Block (s) on Stack: [0,1]

Block (s) on Stack: [2]

Performing Moves:

Block (s) on Stack: [1]

Block (s) on Stack: [2,0]

Block (s) on Stack: []

Block (s) on Stack: [1]

Block (s) on Stack: [2,0]

Block (s) on Stack: []

Block (s) on Stack: [1,2]

Block (s) on Stack: [0]

Block (s) on Stack: []