

# Research on Brain-Signal-Based Communication for Non-Speaking Individuals

**TEAM MEMBERS:** Anchuri Harshith Sai, Chennaboina Janit Pradyun, Tejsai.ch, Kautilya Ramiseti, Rishi Kamishetty, Siddharth.M, Anshu Vanguru, Rithya Reddy

---

## Week 1: Understanding Communication Barriers and Existing Methods

During the first week of the research, the primary focus was on understanding the communication barriers faced by individuals who cannot speak or who experience severe speech impairments. Communication is a fundamental part of human interaction and plays a critical role in daily activities such as expressing needs, sharing ideas, asking questions, and building relationships. However, for individuals who cannot rely on spoken language, communication becomes significantly more difficult.

Many people around the world are unable to communicate through speech due to neurological, developmental, or physical conditions. Even though these individuals may fully understand language and possess normal cognitive abilities, they may lack the physical ability to produce speech sounds. This creates a major barrier between their thoughts and their ability to communicate those thoughts to others.

### Causes of Speech Impairment:

- **Neurological disorders:** Conditions affecting motor control, such as Cerebral Palsy.
- **Amyotrophic Lateral Sclerosis (ALS):** A progressive neurological disease that damages motor neurons.
- **Physical trauma:** Strokes or traumatic brain injuries that hinder speech production despite linguistic understanding.

### Alternative Communication Methods:

- **Gesture-based interaction:** Simplest form, though often lacking in complexity.
- **Sign Language:** Fully developed linguistic systems, but limited by the fact that many people outside the deaf community do not know it.
- **Assistive Technologies:** Communication boards, eye-tracking devices, and text-to-speech software. These often require physical interaction, which may not be possible for those with severe motor impairments.

### Research Papers Reviewed:

- **Research Paper 1 Title:** *The Neural Basis of Non-Verbal Communication: Enhanced Processing of “Give-Me” Gestures in Infants* **Link:** <https://www.frontiersin.org/journals/psychology/articles/10.3389/fpsyg.2015.00059/full>  
**Summary:** This research investigated how the brain responds to communicative gestures using EEG. The results suggest the brain has specialized mechanisms for interpreting non-verbal signals, highlighting the importance of alternative communication methods.
- **Research Paper 2 Title:** *A High-Performance Speech Neuroprosthesis* **Link:** <https://www.nature.com/articles/s41586-023-06377-x>  
**Summary:** This research introduced a brain-computer interface capable of translating neural signals from the speech motor cortex into text for individuals with paralysis. The system achieved speeds approaching natural conversation.

---

## Week 2: Brain Activity, Language Processing, and Brain-Computer Interfaces

During the second week of research, the focus shifted toward understanding how language and speech processes occur within the human brain. Language is a complex cognitive function that involves multiple regions of the brain working together:

- **Broca’s area:** Responsible for speech production and language planning.
- **Wernicke’s area:** Plays an important role in language comprehension and understanding meaning.

### Technologies for Measuring Brain Activity:

- **Electroencephalography (EEG):** Uses electrodes on the scalp to detect electrical signals generated by neurons. It is used to observe brain activity in real time, though it often contains "noise" and overlapping signals.

### Brain-Computer Interfaces (BCI):

A BCI is a technology that allows direct communication between the brain and external devices. Applications include controlling computer cursors or robotic limbs. A critical area of BCI research is **imagined speech** - where a person mentally thinks about a word without producing sound.

### Research Papers Reviewed:

- **Research Paper 3 Title:** *EEG-Transformer: Self-Attention from Transformer Architecture for Decoding EEG of Imagined Speech* **Link:** <https://arxiv.org/abs/2112.09239>  
**Summary:** This study applied transformer-based neural networks to analyze EEG signals during imagined speech. The results demonstrated that transformer models can successfully classify neural signals associated with imagined speech, suggesting AI can significantly improve BCI systems.

---

## Conclusions So Far

The research conducted during the first two weeks focused on understanding communication barriers experienced by non-speaking individuals and exploring how language and speech processes occur in the human brain.

Week 1 examined existing communication methods like gestures and sign language, while Week 2 focused on brain activity and BCIs. The research papers reviewed indicate that neural signals associated with speech and communication can potentially be interpreted using machine learning and signal processing. Studies on speech neuroprostheses and imagined speech decoding indicate it may be possible to translate neural activity into language.

The research direction moving forward is to explore how brain signals related to speech planning or imagined speech could be studied for communication purposes, contributing to the development of future assistive systems that allow individuals to express thoughts more effectively.

---

## Week 3: Primary Research – Interviews and Data Collection

During the third week of the research, the focus shifted from theoretical understanding to primary research through real-world data collection. The team conducted interviews with multiple participants, including patients with speech impairments, caregivers, and individuals with technical knowledge.

To ensure diverse and reliable data, different modes of data collection were used:

- Audio-based interviews
- Text-based chats
- Written responses from patients
- Structured interview transcripts

This mixed-method approach helped in capturing both detailed explanations and natural responses from participants.

### Participants Involved

The interviews included:

- Patients with speech impairments caused by neurological conditions
- Caregivers assisting such individuals

- Students with knowledge in AI and electronics

## Objective of Interviews

The main objective was to:

- Understand real-life communication challenges
- Evaluate the effectiveness of existing communication methods
- Gather opinions on brain-signal-based communication systems

## Key Observations from Interviews

### 1. Communication Challenges

Participants consistently reported that communication is slow and requires significant effort. Patients often rely on gestures, writing, or assistive tools, which limits their ability to express complex thoughts.

### 2. Emotional Impact

Many patients and caregivers highlighted frustration, stress, and emotional difficulty due to miscommunication and delays.

### 3. Limitations of Existing Solutions

Current tools such as communication boards and mobile applications were found to be:

- Time-consuming
- Difficult to use
- Not suitable for all users

### 4. Response to Proposed System

Most participants responded positively to the idea of a brain-signal-based communication system. They believed it could:

- Improve communication speed
- Reduce effort
- Increase independence

### 5. User Expectations

Participants emphasized the importance of:

- High accuracy
- Fast response time
- Ease of use
- Comfort (especially for wearable devices like EEG headsets)

---

## Week4 : Analysis and Insights from Primary Research

In the fourth week, the collected data from interviews, chats, and written responses was analyzed to identify patterns and derive meaningful insights.



## Data Analysis Approach

The responses were reviewed and grouped based on common themes such as:

- Communication difficulties
- Emotional impact
- Usability concerns
- Expectations from new technology

## Major Findings

### 1. Need for Faster Communication

All participants agreed that current communication methods are too slow and inefficient, especially in urgent situations.

### 2. Importance of Accuracy

Accuracy was identified as the most critical factor. Incorrect outputs could lead to confusion and misinterpretation.

### 3. User Comfort and Accessibility

Participants expressed the need for a system that is comfortable to wear and easy to operate, without requiring complex training.

### 4. Adaptability and Personalization

It was observed that communication patterns vary between individuals, highlighting the need for adaptive systems that can learn user-specific patterns.

### 5. Feasibility of Brain-Computer Interface Systems

Technical participants indicated that while challenges exist (such as signal noise and data variability), advancements in machine learning make such systems feasible.

### 6. Concerns and Limitations

Some concerns identified include:

- Cost of implementation
- Reliability of the system
- Data privacy and security

## Conclusion from Primary Research

The primary research strongly supports the need for an alternative communication system for non-speaking individuals. The findings validate the proposed idea of using brain signals for communication, while also highlighting key challenges that must be addressed.

The insights gained from interviews will guide the design and development of a system that is:

- Accurate
- Efficient
- User-friendly
- Adaptable to individual needs

---

## **Week-5: Check list and find for solutions:**

### **Main Problems Identified from Interviews**

#### **1. Slow Communication**

Problem:

Patients use gestures / eye movement / boards

Takes too much time to express basic needs

Interview Evidence:

“It’s quite slow.”

“Takes a lot of time to understand.”

Why solution:

Needed fast communication system

#### **2. Limited Expression**

Problem: Can only communicate basic needs

Cannot express: pain, emotions, detailed thoughts

Interview Evidence:

“Very limited when he wants to express something detailed.”

“Anything more complex becomes difficult.”

Why solution:

Needed brain-to-text + predictive system

### **3. Frequent Misunderstandings**

Problem:

Caregivers often misunderstand needs

Wrong assumptions happen

Interview Evidence:

“Sometimes we think she is asking one thing, but she means something else.”

Why solution:

Needed accurate decoding + emotion detection

### **4. Emotional Frustration / Stress**

Problem:

Patients feel:

frustrated

helpless

isolated

Interview Evidence: “He gets frustrated.”

“She withdraws from conversations.”

Why solution:

Needed emotion-aware communication support

### **5. Existing Assistive Tools Are Difficult**

Problem:

Current tools:communication boards confusing

apps slow

eye tracking tiring

Interview Evidence:

“Eye tracking is tiring.”

“App was difficult to use.”

“Communication board was confusing.”

Why solution:

Needed simple + low effort interface

## **6. Physical Limitations**

Problem:

Patients:

cannot move much

weak muscle control

speech loss progressing

Interview Evidence:

ALS patient cannot move much now

Why solution:

Needed non-invasive EEG headset

## **7. Need for High Accuracy**

Problem:

Wrong output can:

cause stress

create emergency risks

Interview Evidence:

“Accuracy is important.”

“Should work consistently.”

Why solution:

Needed:

AI learning

Personalization

Reliability

## **8. Reliability Concerns**

Problem:

Families worry:

What if the system fails?

What if signal errors happen?

Interview Evidence:

“Should work consistently without errors.”

Why solution:

Needed:

robust system

fallback methods

## **9. Cost / Accessibility Issues**

Problem:

Families need:

affordable solution

easy setup

Interview Evidence:

“Mainly cost.”

“Should not require too much setup.”

Why solution:

Needed:

practical home-use solution

### **Final Summary :**

#### **Problem Checklist:**

- ☐ Slow communication
- ☐ Limited expression
- ☐ Frequent misunderstandings
- ☐ Emotional frustration
- ☐ Existing tools difficult to use
- ☐ Physical movement limitations
- ☐ Need high accuracy
- ☐ Reliability concerns
- ☐ Cost / accessibility issues

“Our solutions were directly built to solve the real problems faced by patients and caregivers: slow communication, misunderstandings, emotional stress, and lack of reliable assistive tools.”

# 1. Hybrid Brain + Context AI Communicator

*(Smart prediction + brain signals = FAST communication)*

## Idea:


Instead of relying only on EEG → text (which is slow and noisy), combine:

-  Brain signals (intent)
-  Context (location, time, situation)
-  AI prediction


. System predicts what the user *wants to say before full decoding*

---

## How it works (Flow)





## EEG-based BCI












(a)



(b)

1. User thinks → EEG captures signal
2. AI detects **intent category** (food, pain, help, emotion)
3. System uses context:
  - Time (morning → breakfast)

- Location (home/hospital)
- 4. Predicts sentence:  
.. “I need water” / “I am uncomfortable”
- 5. User confirms via:
  - eye blink / slight signal

## this solves our interview problems

- ⚡ **Faster than current systems** (no full sentence decoding needed)
- 😞 Reduces frustration (auto-suggestions)
- 👤 Works even for low motor ability (ALS cases)

## Innovation

. Not just decoding thoughts — **predicting them intelligently**

## 2. Emotion + Intent Detection System

*(Understand feelings, not just words)*

### Idea:

our interviews showed:

“Frustration”, “stress”, “withdrawal”

So build a system that:

- Detects emotional state from brain signals
- Combines it with basic intent detection



## **Example:**

- EEG detects stress + urgency  
Output: "I am uncomfortable / something is wrong"
- EEG detects calm + food intent  
Output: "I want to eat"

## **Visualization:**

# Communication Device

|                                |                                                                                                      |                                                                                                  |                                                                                                    |                                                                                                    |                                                                                                   |                                                                                                 |                                                                                                   |                                                                                                     |
|--------------------------------|------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>BASIC EXPRESSIONS</b>       | <br>Yes             | <br>No          | <br>Thank you     | <br>Please        | <br>Hello       | <br>Goodbye  | <br>I love you | <br>I don't know |
| <b>FEELINGS &amp; EMOTIONS</b> | <br>I feel          | <br>Happy       | <br>Sad           | <br>Angry         | <br>Tired       | <br>Sick     | <br>Thirsty    | <br>Hungry       |
| <b>I NEED</b>                  | <br>I need          | <br>Sleep       | <br>Rest          | <br>Take a shower | <br>Get dressed | <br>Toilet   | <br>Medicine   | <br>Help         |
| <b>I WANT</b>                  | <br>I want          | <br>to          | <br>Drink         | <br>Eat           | <br>Play        | <br>Clean up | <br>Go out     | <br>Go home      |
|                                | <br>Be alone      | <br>More      | <br>Music       | <br>TV          | <br>Toys      | <br>Mom    | <br>Dad      | <br>Stop       |
|                                | <br>Male / Female | <br>Volume up | <br>Volume down | <br>REC         | <br>REC       | <br>REC    | <br>REC      | <br>REC        |





Entertech Affective Computing Cloud Structure















#### EEG Signal Analysis

Assessment of Brain Function  
via EEG Signal Decomposition  
and Deep/Machine Learning  
Techniques



#### Mental Health Status





## Why this is powerful

- Helps when user can't form full sentences
- Reduces misunderstandings (major issue in interviews)
- Works even with weak signals

## Innovation:

Communication becomes emotion-first, not word-first

## 3. Personal AI “Brain Translator” (Adaptive System)

*(Learns each user like a personal language model)*

### Idea:

Your research clearly says:


“Signals vary between individuals”

So instead of a generic model:

Build a personalized AI trained on one user

---


## How it works










## Anatomical




ADS  $\mu$ ES DBS iTBS TMS tRNS tACS tDCS tIDS

## Functional







**Code Loop:**  
Iterations on machine learning code

**Data Loop:**  
Developments on data

**Dev**


- 1 Define opportunity and desired outcomes
- 2 Design and prototype ML techniques
- 3 Model training, tuning, and selection

- a Identify and collect data from sources
- b Clean and label data
- c Explore, prepare, and split data

**Prod**

- 4 Testing, integration, and productionization
- 5 Deployment, system and prediction monitoring

- d Evaluate test data performance
- e Training vs. production data monitoring



1. Initial training phase:
  - User thinks words → system learns patterns
2. AI builds personal brain-language map
3. Over time:
  - Becomes faster
  - More accurate
  - Needs less effort

## Features

-  Self-learning system
-  Caregiver feedback loop
-  Converts to:
  - Text
  - Speech
  - App control

## Why it solves your problems

- ✓ High accuracy (top requirement from interviews)
- ✓ Personalized → reduces errors
- ✓ Works for ALS, stroke, elderly differently

## Innovation

.. Like ChatGPT for one person's brain

---

## Week 6: Hardware Research, Cost Estimation and Feasibility Planning

During the sixth week of the project, the team focused on identifying the hardware components required for developing the proposed brain-signal-based communication system. Since the project depends on capturing EEG brain signals and processing them using machine learning,

the team conducted research on various hardware devices and compared them based on cost, availability, ease of use, and compatibility.

The primary goal of this week was to understand the minimum hardware requirements needed for building a prototype and to estimate the overall budget before making any purchases.

## **Hardware Components Identified**

The following components were shortlisted for the project:

- EEG Headset / EEG Sensor – used for collecting brain signals from the user.
- ESP32 / Arduino Board – used for transferring sensor data and controlling communication between hardware and software.
- Bluetooth Module – used for wireless communication between the device and computer/mobile system.
- Laptop / Computer – used for running machine learning models and processing data.
- Electrodes / Conductive Gel – used for improving EEG signal quality.

## **Estimated Cost Analysis**

The approximate budget range identified was:

- EEG Headset: ₹4,000 to ₹15,000
- ESP32 / Arduino: ₹500 to ₹900
- Bluetooth Module: ₹300
- Electrodes / Accessories: ₹500

This gave an estimated total prototype cost between ₹6,000 and ₹17,000 depending on the EEG device selected.

## **Factors Considered During Research**

The team compared hardware based on:

- Cost affordability
- Availability in local and online markets
- Compatibility with Python and machine learning tools
- User comfort while wearing EEG devices
- Ease of setup and maintenance

## **Key Decision Taken**

The team decided not to purchase hardware immediately. Instead, it was concluded that the software model and machine learning pipeline should be prepared first so that the most suitable hardware can be selected later without unnecessary expenses.

## Week 6 Outcome

- Hardware options identified
- Budget estimation completed
- Feasibility of prototype confirmed
- Purchase plan postponed until coding phase

## Conclusion

Week 6 helped the team move closer to implementation by understanding the practical hardware requirements and cost feasibility of the project. This planning ensures better financial decisions and smoother prototype development in future weeks.

---

## Week 7: Machine Learning Model Selection and Development Planning

During the seventh week of the project, the team focused on selecting the most suitable machine learning model for classifying EEG brain signals and preparing the software development roadmap.

Since EEG signals are complex and contain patterns that change over time, different machine learning approaches were studied and compared.

### Models Researched

The following models were analyzed:

1. Convolutional Neural Network (CNN)  
Used for detecting hidden patterns in EEG signals and commonly applied in signal classification tasks.
2. CNN + LSTM  
A combination model where CNN extracts patterns and LSTM learns time-sequence relationships.
3. Random Forest  
A simpler machine learning model suitable for small datasets and basic classification tasks.

### Final Model Selected

After comparison, the team selected the **CNN model** as the starting model for implementation.

### Reason for Selecting CNN

- Effective for signal pattern recognition
- Easier to implement as first prototype
- Can later be upgraded to CNN + LSTM
- Suitable for EEG classification problems

## **Development Plan Prepared**

Although coding had not started during this week, the following roadmap was finalized:

### **Phase 1: Data Collection**

- Use public EEG datasets
- Study EEG signal formats
- Prepare labeled command classes

### **Phase 2: Preprocessing**

- Remove noise from EEG signals
- Normalize data
- Convert signals into model-ready format

### **Phase 3: Model Development**

- Build CNN architecture
- Train model using EEG data
- Predict simple commands such as:
  - Yes
  - No
  - Help
  - Water

### **Phase 4: Output System**

- Convert predicted command into text
- Future upgrade to speech output

## **Software Tools Finalized**

The team selected the following tools:

- Python
- TensorFlow / Keras
- NumPy
- Pandas
- Matplotlib

## Week 7 Outcome

- Machine learning model selected
- Software tools finalized
- Development workflow prepared
- Coding planned for next phase

## Conclusion

Week 7 focused on preparing the artificial intelligence side of the project. By selecting CNN and designing a structured implementation roadmap, the team is ready to begin practical coding and testing in the upcoming weeks.

## Week 8: Model Development Progress, Architecture Study and Partial Implementation

# “Design and Implementation of a Transformer LSTM Based EEG Brain–Computer Interface System”




Figure 1: Comprehensive technical workflow of the Transformer architecture, showing stacked Encoder/Decoder blocks and detailed breakdowns of Multi-Head and Scaled Dot-Product Attention mechanisms.

## Transformer Architecture – Theory

The Transformer is a deep learning architecture designed for sequence modeling tasks such as natural language processing, time-series analysis, and signal processing. Unlike traditional models like Recurrent Neural Networks (RNNs) or Convolutional Neural Networks (CNNs), Transformers rely entirely on attention mechanisms to model dependencies between elements in a sequence.

The architecture consists of two main components: the **Encoder** and the **Decoder**, each composed of multiple identical layers stacked together.

---

### Input Representation

The input sequence is first converted into numerical vectors using an **embedding layer**. Since Transformers do not inherently capture positional information, **positional encoding** is added to the embeddings to preserve the order of tokens in the sequence.

---

### Encoder

The encoder processes the input sequence and generates contextualized representations. Each encoder layer consists of:

1. **Multi-Head Self-Attention Mechanism**

This allows each token in the sequence to attend to all other tokens. It computes relationships using Query (Q), Key (K), and Value (V) vectors. The attention function is defined as:

$$\text{Attention}(Q, K, V) = \text{Softmax}((QK^T) / \sqrt{d_k}) V$$

Multiple attention heads are used in parallel to capture different types of relationships.

2. **Feed Forward Neural Network (FFN)**

A fully connected network applied independently to each position, introducing non-linearity and enhancing feature representation.

3. **Residual Connections and Layer Normalization**

Residual connections are added around each sub-layer, followed by layer normalization, to improve training stability and gradient flow.

---

## Decoder

The decoder generates the output sequence using both previously generated outputs and encoder outputs. Each decoder layer includes:

1. **Masked Multi-Head Self-Attention**

Ensures that predictions for a position depend only on earlier positions by masking future tokens.

2. **Multi-Head Cross-Attention**

Allows the decoder to attend to the encoder outputs, enabling alignment between input and output sequences.

3. **Feed Forward Network and Normalization**

Similar to the encoder, includes FFN and residual connections with layer normalization.

---

## Output Layer

The final output of the decoder is passed through a linear layer followed by a **Softmax function** to produce probability distributions over the target vocabulary. The token with the highest probability is selected as the output.

---




## Key Concepts

- **Attention Mechanism:** Captures dependencies between all tokens regardless of distance.
- **Multi-Head Attention:** Enables the model to learn multiple representations in parallel.
- **Parallelization:** Allows efficient training compared to sequential models like RNNs.
- **Scalability:** Performs well on large datasets and complex tasks.

## Conclusion

The Transformer architecture revolutionized sequence modeling by eliminating recurrence and relying entirely on attention mechanisms. Its ability to capture global dependencies, process data in parallel, and scale effectively has made it the foundation of modern models such as BERT, GPT, and Vision Transformers.



## Deep Neural Network for EEG State Recognition – Theory

This architecture represents a deep learning model designed to classify brain states from **multichannel electroencephalogram (EEG) signals**. EEG data consists of time-series signals recorded from multiple electrodes placed on the scalp, capturing neural activity over time.

## Input Representation

The input to the model is **multichannel EEG time-series data**, where each channel corresponds to a different electrode. These signals contain temporal patterns and frequency components that reflect different cognitive or physiological states.

## Convolutional Layers

The first stage of the model applies **convolutional layers followed by ReLU activation**. These layers act as feature extractors:

- Convolutions detect **local waveform patterns** such as oscillations and spikes in EEG signals.
  - Filters learn spatial and temporal features across channels.
  - The **ReLU (Rectified Linear Unit)** introduces non-linearity, enabling the model to capture complex patterns.
- 

### Pooling Layers

Pooling layers follow convolutional layers to:

- Reduce the dimensionality of feature maps
- Retain the most important information
- Improve computational efficiency
- Provide invariance to small variations in the signal

Common pooling methods include max pooling and average pooling.

---

### Deep Feature Extraction

By stacking multiple **convolution + pooling blocks**, the network progressively learns higher-level representations:

- Early layers capture simple signal patterns
  - Deeper layers capture more abstract and meaningful features related to brain activity
- 

### Flatten Layer

After feature extraction, the multi-dimensional feature maps are converted into a **one-dimensional vector** using a flattening operation. This prepares the data for classification.

---

### Fully Connected Layer

The flattened features are passed through one or more **fully connected (dense) layers**, which:

- Combine all extracted features

- Learn complex relationships between them
  - Map features to specific output classes
- 

### Output Layer (Softmax)

The final layer uses a **Softmax function** to produce a probability distribution over predefined EEG states, such as:

- Alert state
- Meditative state
- Motor imagery (left hand / right hand)
- Drowsy state

The class with the highest probability is selected as the predicted brain state.


---

### Key Concepts

- **Convolution:** Extracts local temporal and spatial features from EEG signals
  - **ReLU Activation:** Introduces non-linearity for better learning
  - **Pooling:** Reduces dimensionality and enhances robustness
  - **Hierarchical Learning:** Builds complex representations from simple patterns
  - **Softmax Classification:** Converts outputs into interpretable probabilities
- 

### Conclusion

This deep neural network effectively processes EEG signals by combining convolutional feature extraction with fully connected classification. It enables accurate recognition of brain states by learning both low-level signal patterns and high-level neural representations, making it suitable for applications such as brain-computer interfaces, cognitive monitoring, and medical diagnostics.



## EEG-CNN Architecture for Brain State Recognition – Theory

This architecture describes a Convolutional Neural Network (CNN) designed to classify brain states using multichannel EEG signals. It processes raw EEG time-series data through multiple stages, including data preparation, feature extraction, feature consolidation, and final prediction.

### Section 1: Input Data Preparation

The model takes **raw multichannel EEG signals** as input. Each channel represents electrical activity recorded from different electrodes on the scalp over time. These signals are segmented and structured into a multi-dimensional tensor, where one dimension represents time and another represents electrode channels.

### Section 2: Feature Learning Stage

This stage focuses on extracting meaningful patterns from EEG data using convolutional operations:

#### 1. Convolutional Layers with ReLU Activation

Convolutional filters are applied to the input data to detect **local temporal and spatial patterns**, such as oscillations and waveform structures. The ReLU activation function introduces non-linearity, enabling the model to learn complex signal representations.

#### 2. Pooling Layers

Pooling operations reduce the dimensionality of feature maps while preserving important features. This helps in minimizing computational complexity and provides robustness to small variations in the data.

By stacking multiple convolution and pooling layers, the network progressively learns hierarchical features, from low-level signal patterns to higher-level abstractions related to brain activity.

---

### Section 3: Feature Consolidation

#### 1. Flattening

The multi-dimensional feature maps obtained from the convolutional layers are transformed into a one-dimensional vector. This step prepares the extracted features for classification.

#### 2. Fully Connected Layers

The flattened feature vector is passed through dense layers, which integrate and interpret the learned features. These layers perform high-level reasoning and map features to specific output classes.

---

### Section 4: Prediction and Output

The final layer applies a **Softmax function** to produce a probability distribution over possible brain states, such as:

- Alert state
- Meditative state
- Motor imagery (left hand / right hand)
- Drowsy state

The class with the highest probability is selected as the predicted state.

---


### Key Concepts

- **Multichannel EEG Input:** Captures spatial and temporal brain activity
- **Convolutional Feature Extraction:** Identifies local patterns in signals
- **Pooling:** Reduces dimensionality and enhances important features
- **Hierarchical Learning:** Builds complex representations from simple patterns
- **Fully Connected Layers:** Perform classification based on extracted features
- **Softmax Output:** Provides probabilistic interpretation of predictions

---

### Conclusion

This EEG-CNN architecture effectively transforms raw brain signals into meaningful classifications by combining convolutional feature extraction with dense neural layers. It enables accurate recognition of cognitive and physiological states, making it highly suitable for applications such as brain-computer interfaces, neurofeedback systems, and medical diagnostics.



### Standard RNN and LSTM Cell Architecture – Theory

Recurrent Neural Networks (RNNs) are designed to process sequential data by maintaining a hidden state that captures information from previous time steps. They are widely used in tasks such as time-series prediction, speech recognition, and natural language processing.

#### Standard RNN Cell

A standard RNN processes input sequentially by updating its hidden state at each time step. The hidden state  $h_t$  is computed using the current input  $x_t$  and the previous hidden state  $h_{t-1}$ :

$$h_t = \tanh(W_h h_{t-1} + W_x x_t + b)$$

The output  $y_t$  is derived from the hidden state. The **tanh activation function** ensures non-linearity and keeps values within a bounded range.

#### Limitations of Standard RNN:

- Suffers from **vanishing and exploding gradient problems**
- Struggles to capture **long-term dependencies**

- Earlier information may be lost as sequences grow longer

---

## LSTM (Long Short-Term Memory) Cell

LSTM is an advanced type of RNN designed to overcome the limitations of standard RNNs by introducing a **memory cell** and gating mechanisms.

The key components of an LSTM cell include:

---

### 1. Cell State ( $C_t$ )

The cell state acts as a long-term memory that flows through the sequence with minimal modification, allowing the network to retain important information over time.

---

### 2. Forget Gate ( $f_t$ )

Determines which information from the previous cell state should be discarded:

$$f_t = \sigma(W_f[h_{t-1}, x_t] + b_f)$$

---

### 3. Input Gate ( $i_t$ ) and Candidate State ( $C_t$ )

Controls what new information is added to the cell state:

$$\begin{aligned} i_t &= \sigma(W_i[h_{t-1}, x_t] + b_i) \\ C_t &= \tanh(W_c[h_{t-1}, x_t] + b_c) \end{aligned}$$

---

### 4. Cell State Update

The new cell state is updated by combining old and new information:

$$C_t = f_t \cdot C_{t-1} + i_t \cdot C_t$$

---

### 5. Output Gate ( $o_t$ )

Determines what part of the cell state is output as the hidden state:

$$o_t = \sigma(W_o[h_{t-1}, x_t] + b_o)$$

$$h_t = o_t \cdot \tanh (C_t)$$

---

## Key Differences Between RNN and LSTM

- **Memory Handling:**  
RNN uses a single hidden state, while LSTM uses a separate cell state for long-term memory.
  - **Gating Mechanism:**  
LSTM introduces forget, input, and output gates to control information flow.
  - **Long-Term Dependencies:**  
LSTM can retain information over long sequences, whereas standard RNN struggles.
  - **Gradient Stability:**  
LSTM reduces vanishing gradient issues, making training more effective.
- 

## Conclusion

While standard RNNs are simple and effective for short sequences, they are limited in handling long-term dependencies. LSTMs address these limitations by introducing gated memory mechanisms, enabling them to learn and retain information over extended time steps. This makes LSTMs highly suitable for complex sequential data tasks such as language modeling, speech processing, and EEG signal analysis.

## Standard RNN vs LSTM – Conceptual and Physical Analogy Theory

This diagram presents an enhanced interpretation of Standard RNN and LSTM architectures using biological, fluid dynamics, and modular system analogies to illustrate how information flows through sequential models.

---

## Standard RNN Cell – Theory

A Standard RNN processes sequential data by maintaining a hidden state that evolves over time. At each time step, the hidden state  $h_t$  is computed using the current input  $x_t$  and the previous hidden state  $h_{t-1}$ , typically through a non-linear activation function such as tanh.

$$h_t = \tanh (W_h h_{t-1} + W_x x_t + b)$$

In the diagram, the RNN is represented as a **simple processing unit**, analogous to a basic biological neuron or a chamber where inputs combine and transform into outputs. The flow



of information is direct and continuous, but lacks mechanisms to regulate or preserve long-term dependencies.

### Key Characteristics:

- Single hidden state for memory
- Direct information flow
- Limited ability to retain long-term context
- Prone to vanishing and exploding gradients




Figure 2: Quantum/Fluidic Dynamics Field Simulation. Information flow is a complex energy fluid visualized with particle tracing and color mapping.




Figure 2: Quantum/Fluidic Dynamics Field Simulation. Information flow is a complex energy fluid, particle tracing, a color mapping




Figure 3: Modular Isometric Exploded-View & Data Trace. All typoes stones. All typoes are fixed and descriptions expanded.

## LSTM Cell – Theory

The LSTM extends the RNN by introducing a structured memory system called the **cell state**  $C_t$ , along with gating mechanisms that regulate information flow. These gates function like **control valves or biological regulators**, deciding what information to keep, update, or discard.

### Core Components of LSTM

#### 1. Cell State ( $C_t$ )

Represents long-term memory. It flows through the network with minimal modification, acting as a stable information pathway.

## 2. Forget Gate ( $f_t$ )

Determines which information from the previous cell state should be removed. Acts like a filtering mechanism or valve controlling memory retention.

---

## 3. Input Gate ( $i_t$ ) and Candidate State ( $C_t$ )

Controls how much new information is added to the cell state.

Functions like a mixing system where new signals are selectively integrated.

---

## 4. Cell State Update

Combines retained old information and selected new information:

$$C_t = f_t \cdot C_{t-1} + i_t \cdot C_t$$

---

## 5. Output Gate ( $o_t$ )

Regulates what portion of the cell state is exposed as the hidden state  $h_t$ . Acts like a controlled release mechanism.

---

## Conceptual Analogies in the Diagram

- **Biological System:**

The LSTM resembles a neuron with controlled ion channels and signaling pathways, where gates regulate signal transmission.

- **Fluid Dynamics:**

Information flow is visualized as fluid passing through valves and channels, with gates controlling pressure and direction.

- **Modular Engineering System:**

The architecture is depicted as interconnected modules with pipelines and regulators, emphasizing structured data flow and control.

---

## Key Differences

- **Memory Structure:**

RNN uses a single hidden state, while LSTM uses both hidden state and cell state.

- **Information Control:**

RNN has no gating mechanism, whereas LSTM uses multiple gates to regulate information flow.

- **Long-Term Dependency Handling:**

LSTM effectively preserves long-term information, unlike standard RNN.

- **Stability:**

LSTM mitigates vanishing gradient issues through controlled memory updates.

---

## Conclusion

The diagram highlights that while a Standard RNN operates as a simple sequential processor, the LSTM functions as a highly regulated system with memory control mechanisms. By introducing gates and a persistent cell state, LSTMs enable efficient learning of long-term dependencies, making them significantly more powerful for complex sequential data tasks such as language modeling, time-series prediction, and EEG signal analysis.



### EEG Signal Acquisition and Processing System – Theory

This system represents a complete pipeline for acquiring, processing, and analyzing brain signals using an Electroencephalography (EEG) device integrated with embedded hardware and signal processing units.

---

### EEG Headset (Signal Acquisition)

The EEG headset consists of multiple electrodes placed on the scalp to measure electrical activity generated by the brain. These electrodes capture **low-amplitude bioelectric signals** produced by neuronal activity.

- Each electrode records voltage fluctuations over time
  - Signals are analog and highly sensitive to noise
  - Multichannel acquisition enables spatial mapping of brain activity
- 

### Front-End Electronics (Amplification and Filtering)

The raw EEG signals are first passed through front-end circuitry:

- **Amplifiers** increase the signal strength while preserving waveform characteristics
  - **Analog filters** remove unwanted noise such as power-line interference and motion artifacts
  - Ensures signal quality before digitization
- 

### Analog-to-Digital Conversion (ADC)

The conditioned analog signals are converted into digital form using an ADC:

- Samples the signal at a specific frequency
  - Converts continuous signals into discrete numerical values
  - Enables further processing by digital systems
- 

### Embedded Processing Unit

A microcontroller or embedded processor receives the digitized EEG data and performs:

- Signal preprocessing (filtering, normalization)
- Feature extraction (frequency bands, temporal patterns)
- Data formatting and transmission

This stage may also include **real-time processing capabilities** for immediate feedback.

---

### Digital Signal Processing (DSP) Module

The DSP unit applies advanced algorithms to extract meaningful information:

- Time-domain and frequency-domain analysis
  - Detection of patterns such as alpha, beta, and theta waves
  - Noise reduction and artifact removal
- 

### Data Transmission and Interface

Processed data is transmitted to external systems via communication interfaces such as:

- USB or serial communication
- Wireless protocols (e.g., Bluetooth, Wi-Fi)

This enables integration with computers or other devices for visualization and analysis.

---

### Visualization and Output

The system displays EEG signals and processed results using:

- Oscilloscopes or monitoring screens
  - Graphical interfaces showing waveforms and features
  - Classification outputs for brain states or events
- 


### Key Concepts

- **Multichannel EEG Acquisition:** Captures spatial brain activity
  - **Signal Conditioning:** Improves signal quality through amplification and filtering
  - **Digitization:** Converts analog signals to digital data
  - **Embedded Processing:** Enables real-time analysis
  - **DSP Techniques:** Extract meaningful patterns from noisy signals
  - **System Integration:** Combines hardware and software for end-to-end functionality
- 

### Conclusion

This EEG system provides a complete framework for capturing and analyzing brain signals, from electrode-level acquisition to advanced digital processing and visualization. By integrating hardware components with signal processing techniques, it enables applications

such as brain-computer interfaces, cognitive monitoring, neurofeedback, and medical diagnostics.



## BCI (Brain-Computer Interface) System – Technical Architecture and Signal Flow

This system represents an end-to-end **Brain-Computer Interface (BCI)** pipeline that captures EEG signals, processes them using advanced models (Transformer + LSTM), and converts them into actionable outputs such as commands or audio.

### 1. EEG Sensor Array (Signal Acquisition)

The system begins with an **EEG sensor array**, which consists of electrodes placed on the scalp.

- Captures brain electrical activity as **analog signals**
- High-impedance sensors ensure accurate signal acquisition
- Produces multichannel time-series data

### 2. Front-End Module (Signal Conditioning)

The analog EEG signals are processed through the front-end hardware:

- **Instrumentation Amplifier**: Boosts weak EEG signals

- **Anti-aliasing Filter:** Removes high-frequency noise
- **ADC (Analog-to-Digital Converter):** Converts signals into digital form

— — Output: Clean digital EEG data

---

### 3. Communication Interface

The digitized data is transmitted to the processing unit via:

- **SPI / I2C protocols**
  - Ensures fast and reliable data transfer
- 

### 4. DSP Main Unit (Core Processing)

This is the brain of the system, typically using an **MCU or FPGA**. **Signal**

#### Processing Engine

- Removes artifacts (noise, motion interference)
  - Performs transformations like **FFT** for frequency analysis
- 

#### Transformer Block (Attention Mechanism)

- Learns relationships across EEG signals
  - Captures **spatial dependencies** between channels
  - Focuses on important patterns using attention
- 

#### LSTM Block (Temporal Modeling)

- Captures **time-based dependencies** in EEG signals
- Learns how brain patterns evolve over time

— — Together:

- Transformer = “What is important?”
  - LSTM = “How does it change over time?”
- 

### 5. Intent Decoding



The processed features are converted into meaningful outputs:

- **Intent Decoder:** Interprets brain activity
- **Command Generator:** Converts intent into control signals

— — Output: **Predicted Intent**

---

## 6. Data Output and Communication

The predicted intent is transmitted via:

- **Ethernet / Gigabit Data Port**
  - Enables integration with external systems
- 

## 7. Application Layer (User Interface)

A host system (PC/mobile) provides:

- **GUI:** Signal visualization and configuration
  - **Data Logger:** Stores EEG and predictions
  - **Control Panel:** User interaction
- 

## 8. Audio Output System

The system can generate real-world output:

- **Audio Amplifier (D-Class):** Amplifies signals
  - **Speaker:** Produces sound output
- 

## 9. Synthesized Intent-Based Signal

Final stage converts decoded intent into actions:

- Motor control commands
  - External device control
  - Feedback signals (audio/visual)
- 


## Key Concepts



- **End-to-End Pipeline:** From brain signals to actionable output
- **Hybrid AI Model:** Transformer (attention) + LSTM (temporal learning)
- **Real-Time Processing:** Enables immediate response
- **Multimodal Output:** Data, control signals, and audio

## Conclusion

This architecture integrates EEG hardware, embedded systems, and deep learning models to create a complete brain-computer interface. By combining signal processing with Transformer and LSTM models, the system can accurately decode user intent from brain activity and translate it into real-world actions.



## EEG-Based Brain-Computer Interface Using LSTM – System Overview

This architecture represents a complete pipeline for decoding brain signals into actionable outputs using EEG hardware, signal processing, and an LSTM-based deep learning model.

### 1. User Input (Brain Activity Generation)

The process begins with the user generating brain activity, such as imagining a movement (e.g., left or right hand). This mental activity produces electrical signals in the brain, which are captured as EEG signals.

---

## 2. EEG Hardware and Data

### Acquisition EEG Headset

- Consists of multiple electrodes placed on the scalp
- Captures **multichannel EEG signals**
- Records time-varying electrical activity

### Amplifier and ADC

- **Amplifier:** Strengthens weak EEG signals
- **ADC (Analog-to-Digital Converter):** Converts analog signals into digital form for processing

---

## 3. Signal Processing (Preprocessing Stage)

The raw EEG data is noisy and requires preprocessing:

- **Filtering:** Removes unwanted frequencies (bandpass, notch filters)
- **Artifact Removal:** Eliminates noise from eye movements (EOG), muscle activity (EMG), etc.

— — Output: Clean EEG signals ready for modeling

---

## 4. AI Model – LSTM (Temporal Learning)

The processed EEG signals are passed into an **LSTM (Long Short-Term Memory) network**, which learns temporal patterns in sequential data.

### LSTM Layers

- Input sequence  $X(t)$  is fed into stacked LSTM layers
- Each LSTM cell maintains:
  - **Hidden state  $h_t$ :** short-term memory
  - **Cell state  $C_t$ :** long-term memory
- Captures how brain signals evolve over time

---

### Fully Connected Layer

- Transforms learned features into a form suitable for classification
- 

### Softmax Activation

- Converts outputs into probabilities for each class
- Output: Predicted class (e.g., left-hand or right-hand movement)
- 

## 5. Brain Decoder Output

The system interprets the model output:

- Converts classification into **intent**
  - Example:
    - Class: Left-hand movement
    - Intent: Control command
- 

## 6. Real-Time Application

The decoded intent is used to control applications:

- Cursor movement
  - Assistive devices
  - Brain-computer interface applications
- 

## 7. Feedback and Model Update

- System output is compared with **ground truth**
  - Feedback is used for:
    - Model fine-tuning
    - Performance improvement over time
- 

### Key Concepts


- **Multichannel EEG Acquisition:** Captures brain activity
- **Signal Preprocessing:** Improves data quality

- **LSTM Network:** Learns temporal dependencies in EEG signals
- **Classification:** Maps brain signals to actions
- **Closed-Loop System:** Uses feedback for continuous improvement

---

## Conclusion

This architecture demonstrates an end-to-end EEG-based BCI system where brain signals are captured, cleaned, and processed using LSTM networks to decode user intent. The system enables real-time interaction between the brain and external devices, making it suitable for applications such as assistive technologies, neurorehabilitation, and human-computer interaction.



to retain information over longer sequences.




Figure 1. RNN architecture [4].

### Recurrent Neural Network (RNN) Architecture – Theory

A Recurrent Neural Network (RNN) is a type of neural network designed to process sequential data by maintaining a hidden state that captures information from previous time steps. This allows the model to learn temporal dependencies within a sequence.

---

#### Structure of the RNN

The RNN operates over a sequence of inputs  $x_1, x_2, x_3, \dots, x_n$ , where each input corresponds to a time step. At each step, the network produces a hidden state and an output.

---

#### Hidden State Computation

At time step  $t$ , the hidden state  $h_t$  is computed using:

- The current input  $x_t$
- The previous hidden state  $h_{t-1}$

$$h_t = f(W_h h_{t-1} + W_x x_t + b)$$

where  $f$  is typically a non-linear activation function such as tanh or ReLU. The initial hidden state  $h_0$  is usually initialized to zero or learned.

---

## Output Generation

At each time step, the hidden state produces an output  $y_t$ :

$$y_t = g(W_y h_t + b_y)$$

where  $g$  is often a Softmax or linear activation depending on the task.

---

## Sequential Information Flow

- The hidden state acts as **memory**, carrying information forward through time
  - Each state  $h_t$  depends on all previous inputs  $x_1, x_2, \dots, x_t$
  - This allows the model to capture patterns across the sequence
- 

## Key Characteristics

- **Shared Weights:** The same parameters are used at every time step
  - **Temporal Dependency Modeling:** Captures relationships across time
  - **Flexible Input Length:** Can process sequences of varying lengths
- 

## Types of RNN Usage

This diagram represents a **many-to-many RNN**, where:

- Multiple inputs  $\rightarrow$  Multiple outputs
  - Example applications:
    - Time-series prediction
    - Speech recognition
    - EEG signal classification
- 

## Limitation

Standard RNNs struggle with:

- **Vanishing and exploding gradients**
- Difficulty in learning long-term dependencies

This limitation led to advanced models like **LSTM** and **GRU**, which introduce memory gates.

---

## Conclusion

The RNN architecture processes sequential data by iteratively updating a hidden state that carries past information forward. This enables the model to learn temporal patterns, making it suitable for tasks involving time-dependent or ordered data.

The presented system demonstrates a comprehensive **EEG-based Brain–Computer Interface (BCI)** pipeline that integrates signal acquisition, preprocessing, and advanced deep learning models for accurate intent recognition. Beginning with multichannel EEG signal capture, the system ensures signal quality through amplification, filtering, and artifact removal, enabling reliable downstream processing.

Deep learning architectures such as **RNNs, LSTMs, and Transformers** play a crucial role in modeling the complex temporal and spatial patterns inherent in EEG data. While standard RNNs provide a foundation for sequential learning, LSTMs enhance performance by capturing long-term dependencies through gated memory mechanisms. Transformers further extend this capability by using attention mechanisms to identify the most relevant features across the entire signal.

By combining these approaches, the system achieves robust decoding of brain activity into meaningful outputs, such as motor intentions or control commands. The integration of hardware, signal processing, and hybrid AI models enables **real-time interaction** between the human brain and external devices.

Overall, this architecture highlights the potential of modern deep learning techniques in advancing BCI systems, making them more accurate, adaptive, and applicable to real-world domains such as assistive technologies, neurorehabilitation, and human–computer interaction.

---

During the eighth week of the project, the team started working on the implementation of the machine learning model for EEG signal classification. The main focus of this week was to begin the coding process and understand how the planned model can be developed practically.

Since the project involves EEG data and deep learning, initial efforts were made to set up the coding environment and study how to build the model step by step.

---

## Model Coding Progress

At this stage, approximately **40% of the model code is completed**.

---

## Work Done in This Week

- Basic understanding of EEG dataset structure
  - Python environment setup completed
  - Required libraries identified and installed
  - Initial code structure for the model created
  - Basic CNN model framework started
- 

## Current Status

- Model architecture is partially prepared
  - Coding has been started but not fully completed
  - Training and testing are yet to be done
- 

## Next Steps

- Complete remaining model layers
  - Train the model using dataset
  - Check accuracy and performance
  - Improve model based on results
- 

## Week 8 Outcome

- Coding phase initiated
  - Partial model development completed (~40%)
  - Clear direction for further implementation
- 

## Conclusion

Week 8 marked the beginning of the coding phase of the project. Although the implementation is still in progress, a basic structure of the model has been developed. The team will continue working on completing the model and testing it in the upcoming weeks.



# Week 9: Model Completion, System Integration and Poster Preparation

During the ninth week of the project, the team focused on completing the implementation of the EEG-based Brain Computer Interface system and integrating all major modules into a single working prototype.

The primary objective of this week was to finalize the machine learning pipeline, improve the user interface, and prepare project presentation materials.

---

## Machine Learning Model Completion

During this phase, the coding and implementation of the hybrid CNN + LSTM model were completed successfully.

### Work Completed

- EEG dataset loading completed
- Signal preprocessing implemented
- Bandpass filtering added for noise reduction
- CNN layers implemented for feature extraction
- LSTM layer integrated for temporal learning
- Dense output layers completed
- Softmax prediction layer implemented

The final model was capable of classifying EEG patterns into binary communication outputs.

---

## Dataset Processing and Training

The BCI Competition IV dataset was successfully integrated into the system.

### Tasks Completed

- EEG signal segmentation
- Multi-channel data handling
- Data normalization

- Label encoding
- Training and validation split

The model was trained using motor imagery EEG signals for classification.

---

## **Streamlit Interface Completion**

The Streamlit-based application interface was completed.

### **Features Added**

- EEG dataset upload option
- EEG signal visualization
- Frequency spectrum analysis
- Hybrid CNN + LSTM training module
- Real-time prediction interface
- Live decoding simulation

The interface allowed users to interact with the system in a simplified and understandable manner.

---

## **Poster Development**

The project poster design and content preparation were completed during this week.

### **Poster Sections Included**

- Problem statement
- User research insights
- Proposed solution
- Workflow architecture
- Hardware planning
- Machine learning pipeline
- Results and screenshots
- Future scope

Screenshots from the Streamlit application and EEG visualizations were also prepared for inclusion in the poster.

---

# Website Documentation Preparation

Initial online documentation structure was prepared.

## Planned Sections

- Project overview
  - Dataset explanation
  - Hardware details
  - AI model architecture
  - Results and testing
  - Future enhancements
- 

## Week 9 Outcome

- Full model code completed
  - Streamlit application completed
  - Hybrid CNN + LSTM integration completed
  - Poster preparation completed
  - Documentation structure prepared
- 

## Conclusion

Week 9 focused on consolidating all previous work into a complete functional prototype. The machine learning implementation, user interface, and presentation materials were finalized successfully.

---

# Week 10: Final Testing, Documentation and Project Finalization

During the tenth week of the project, the team focused on testing the completed Brain Computer Interface system, finalizing online documentation, and preparing the project for final submission and presentation.

The goal of this week was to ensure that all components of the project were organized, functional, and presentation-ready.

---

## Final System Testing

The completed Streamlit application was tested using the EEG dataset.

### Testing Areas

- EEG data upload functionality
- Signal visualization accuracy
- CNN + LSTM training process
- Real-time prediction module
- User interface responsiveness

The testing confirmed that the prototype workflow operated successfully from EEG input to prediction output.

---

## Model Evaluation

The model performance was evaluated using validation metrics.

### Metrics Observed

- Classification accuracy
- Prediction confidence
- Validation performance
- Confusion matrix analysis

The results demonstrated successful classification capability for motor imagery EEG signals.

---

## Documentation Completion

The final online documentation was completed.

### Documentation Included

- Introduction and objective
  - Problem statement
  - Interview findings
  - Hardware planning and cost estimation
  - Dataset explanation
  - Signal processing workflow
  - CNN + LSTM architecture
  - Streamlit interface screenshots
  - Results and future scope
- 

## **Final Poster Completion**

The A2 project poster was finalized according to the provided template.

### **Final Poster Included**

- Workflow diagrams
  - EEG signal screenshots
  - Model architecture
  - Project outcomes
  - QR code and project details
- 

## **Final Presentation Preparation**

Preparation for the final presentation and viva was completed.

### **Prepared Topics**

- Project explanation
  - EEG dataset overview
  - Hybrid AI model explanation
  - Workflow architecture
  - Real-time prediction demonstration
  - Future implementation possibilities
- 

## **Week 10 Outcome**

- Final testing completed
  - Documentation completed
  - Poster finalized
  - Presentation preparation completed
  - Complete prototype ready for submission
- 

## **Conclusion**

Week 10 marked the completion phase of the project. All major components including the machine learning system, interface, documentation, poster, and testing were finalized successfully, making the project ready for final evaluation and presentation.