Assignment 7: Sample Data Insertion

Sample records for all eight tables

Project Topic: Hotel Management System

1. Objective

This assignment inserts realistic sample data into every table. Insert parent records before child records so foreign key references are valid. Dates and names are illustrative sample data.

2. Insert Sample Records

```
INSERT INTO Guests VALUES
(1,'Asha','Rao','asha.rao@example.com','9876500001','Bengaluru','Aadhaar','ID1001'),
(2,'Rahul','Shah','rahul.shah@example.com','9876500002','Mysuru','Aadhaar','ID1002'),
(3,'Meera','Nair','meera.nair@example.com','9876500003','Chennai','Passport','P2003'),
(4,'Arjun','Das','arjun.das@example.com','9876500004','Hyderabad','Passport','P2004'),
(5,'Sara','Khan','sara.khan@example.com','9876500005','Pune','Aadhaar','ID1005');

INSERT INTO RoomTypes VALUES
(1,'Single',1800.00,1,'Compact room for one guest'),
(2,'Deluxe',3200.00,2,'Comfortable room with extra amenities'),
(3,'Suite',6500.00,4,'Large premium room');

INSERT INTO Rooms VALUES
(101,'101',1,1,'Available'),
(102,'102',1,2,'Occupied'),
(103,'201',2,2,'Available'),
(104,'202',2,3,'Occupied'),
(105,'301',3,1,'Under Maintenance');

INSERT INTO Staff VALUES
(1,'Nisha','Patel','Receptionist','9000000001','Morning'),
(2,'Kiran','Reddy','Manager','9000000002','Evening'),
(3,'Dev','Kumar','Receptionist','9000000003','Night');

INSERT INTO Reservations VALUES
(1001,1,102,1,'2026-10-10','2026-10-12',2,'Checked-Out',3200.00),
(1002,2,103,1,'2026-10-16','2026-10-18',2,'Checked-In',3200.00),
(1003,3,104,2,'2026-10-15','2026-10-18',3,'Checked-In',6500.00),
(1004,4,101,3,'2026-10-20','2026-10-21',1,'Confirmed',1800.00),
(1005,5,102,2,'2026-11-01','2026-11-03',2,'Confirmed',3200.00);

INSERT INTO Payments VALUES
(501,1001,6400.00,'2026-10-12','UPI','Paid'),
(502,1002,2000.00,'2026-10-16','Card','Paid'),
(503,1002,4400.00,'2026-10-16','UPI','Pending'),
(504,1003,13000.00,'2026-10-15','Card','Paid'),
(505,1004,1800.00,'2026-10-19','Cash','Pending');

INSERT INTO Services VALUES
(1,'Laundry',250.00),
(2,'Spa',1200.00),
(3,'Room Dining',500.00),
(4,'Airport Pickup',900.00);

INSERT INTO ServiceOrders VALUES
(701,1001,1,2,'2026-10-11'),
(702,1002,3,2,'2026-10-16'),
(703,1003,2,1,'2026-10-16'),
(704,1003,4,1,'2026-10-16'),
(705,1004,1,1,'2026-10-20');
```

3. Check the Inserted Data

```
SELECT COUNT(*) AS guest_count FROM Guests;\nSELECT COUNT(*) AS room_type_count FROM RoomTypes;\nSELECT COUNT(*) AS room_cou
```

4. Expected Row Counts

Table	Expected records
Guests	5
RoomTypes	3
Rooms	5
Staff	3
Reservations	5
Payments	5
Services	4
ServiceOrders	5

5. Relationship Check

```
SELECT r.reservation_id, g.first_name, g.last_name, rm.room_number\nFROM Reservations r\nJOIN Guests g ON r.guest_id = g.gue
```

Expected output should contain five reservations, each linked to an existing guest and room. The sample data uses valid IDs, unique room numbers and guest email addresses, and values that satisfy the constraints.

6. Conclusion

Sample records have been prepared for all eight tables. The insertion order follows the foreign key relationships, and the count and join queries can be used to verify that the data was inserted correctly.