

TelePreview: A User-Friendly Teleoperation System with Virtual Arm Assistance for Enhanced Effectiveness

Anonymous Authors




Fig. 1: **TelePreview** is a user-friendly teleoperation system enabling the real-time virtual preview before robot execution.

Abstract—Teleoperation provides an effective way to collect robot data, which is crucial for learning from demonstrations. In this field, teleoperation faces several key challenges: user-friendliness for new users, safety assurance, and transferability across different platforms. While collecting real robot dexterous manipulation data by teleoperation to train robots has shown impressive results on diverse tasks, due to the morphological differences between human and robot hands, it is not only hard for new users to understand the action mapping but also raises potential safety concerns during operation. To address these limitations, we introduce TelePreview. This teleoperation system offers real-time visual feedback on robot actions based on human user inputs, with a total hardware cost of less than \$1,000. TelePreview allows the user to see a virtual robot that represents the outcome of the user’s next movement. By enabling flexible switching between command visualization and actual execution, this system helps new users learn how to demonstrate quickly and safely. We demonstrate that it outperforms other teleoperation systems across five tasks, emphasize its ease of use, and highlight its straightforward deployment across diverse robotic platforms. We release our code and a deployment document on our website <https://telepreview.github.io>:

[//telepreview.github.io](https://telepreview.github.io).

Researchers have long recognized teleoperation as an essential component for gathering on-robot data used in learning from demonstrations [1]–[6]. An intuitive and user-friendly teleoperation system is crucial for collecting high-quality, diverse, and scalable data. However, effectively controlling robots with dexterous hands remains a significant challenge. The fundamental differences between human and robotic hands make the direct mapping of human movements to robotic actions exceptionally complex [7]–[9]. These inherent structural and functional disparities, combined with the precision required for fine-grained tasks, often result in inefficient and potentially compromised data collection processes.

Existing teleoperation systems face three significant challenges. First, new users often struggle to control the robot effectively due to the lack of intuitive feedback on how their commands translate to robot actions, especially during complex manipulation tasks. Second, without proper




Fig. 2: **Overview of our modular system architecture.** (1) Various input devices for capturing human motion. Only one device from each of the two input groups (wrist pose and hand gesture) is required during operation. The VR headset is shown at the intersection of the two groups, as it can capture both. (2) A processing pipeline performs joint mapping and collision-free retargeting. (3) The output commands are sent to diverse robot platforms for execution.

safeguards and real-time guidance, users may inadvertently issue unsafe commands that could damage the robot or its surroundings. Third, most current systems are tightly coupled with specific input devices or robot platforms, limiting their adaptability. These challenges significantly impact the quality and efficiency of data collection for robot learning.

To address these issues, we introduce **TelePreview**, a teleoperation system that delivers precise control while maintaining affordability through its sub-\$1,000 hardware setup, as shown in Fig. 2. At its core, TelePreview provides an interface that overlays a **virtual robotic arm** onto the real-world scene, enabling users to preview motions. Precisely, a foot pedal or other external signal IO allows for mode switching between *preview* (virtual-only) and *align* (physical action alignment) modes. In *preview* mode, users can verify and refine their intended actions with a virtual robot arm that is spatially aligned with the physical robot, ensuring that the final commands are safe and accurate once applied in the real world.

We present the significant contributions of TelePreview to advance teleoperation:

- **Interactive Visual Assistance:** We develop a visualization interface that enables users to preview intended actions before execution, enhancing teleoperation precision and accessibility for both new and experienced users during complex tasks.
- **Low-Cost System:** We introduce an economical yet high-performance teleoperation solution that integrates inertial motion capture technology and mocap gloves at a total hardware cost of under \$1,000, making it affordable for research.
- **Easy Adaptation to New Hardware:** Our framework achieves hardware-agnostic control by mapping diverse input devices to a unified SMPL-X body model, while adapting to various robot end-effectors with only minor hyper-parameter adjustments.

I. RELATED WORK

A. Teleoperation Frameworks for Dexterous Manipulation

Teleoperation provides an efficient method for demonstrating and recording intricate robotic tasks [10]–[12]. However, many existing teleoperation frameworks focus on low-degree-of-freedom (low-DoF) robotic grippers, using input modalities such as keyboards [13], joysticks [14], [15], or gamepads [16] to issue discrete commands. While effective for simple tasks, these interfaces are ill-suited for the fine-grained control of high-DoF dexterous hands. The primary challenge is the severe dimensionality mismatch between the low-DoF input device and the high-DoF manipulator. This mismatch forces users into non-intuitive control schemes, such as sequential joint selection or mode-switching, which significantly increases the operator’s cognitive load, slows down task execution, and makes fluid dexterous manipulation nearly impossible to achieve [17].

To overcome these limitations, researchers have explored various teleoperation systems for dexterous manipulation, each offering distinct benefits in accessibility, precision, and generalizability. These include VR headsets [1], [7], [18], motion capture systems [19]–[21], wearable gloves [6], [22]–[25], and exoskeletons [26], [27].

Among these categories, vision-based systems [1], [3], [7], [18] present a low-cost solution by using RGB cameras within VR headsets to detect and retarget hand poses via keypoint optimization. However, this approach faces significant practical challenges, including limited degrees of freedom (DoFs), constrained workspaces, and high computational demands. Furthermore, these systems are susceptible to perception failures from occlusions and finger overlap, while the keypoint-based retargeting can be too computationally expensive for real-time performance. While specialized hardware [2] can mitigate some of these issues, it substantially increases system costs, undermining the primary advantage of the vision-based approach.




Fig. 3: **Pipeline of Our Modules:** The system tracks user wrist and hand poses, maps them to robot joint configurations through joint-to-joint mapping and non-collision retargeting, and provides a visual preview before physical execution. We achieve precise alignment between virtual and physical robots through AprilTag calibration.

In contrast, exoskeleton systems [26], [27] provide highly accurate motion capture with low latency but tend to be tightly coupled to specific hardware platforms, which limits their generalizability across different robot embodiments.

In this work, we adopt a glove-based teleoperation framework that captures human hand motion at the joint level and maps it to a unified body model (e.g., SMPL-X) before retargeting it to the robot. This abstraction layer enables real-time, joint-level control of dexterous robotic hands while improving generalizability across different robot embodiments. Although glove-based teleoperation has previously been considered expensive, recent commercialization and the availability of low-cost, off-the-shelf data gloves have made this approach increasingly accessible.

B. Visual Feedback in Teleoperation Systems

Visual feedback plays a crucial role in teleoperation systems by providing users with spatial awareness and task-relevant information. Traditional approaches primarily rely on real-time camera feeds [28], [29], which can be limited by occlusions and restricted viewing angles. Moreover, the lack of preview capabilities for intended commands leaves users (especially new users) uncertain about the robot's response, which can increase error rates and user fatigue.

To address these limitations, researchers have explored enhanced visualization techniques [30]–[33] in AR-based teleoperation systems [34], [35], which aim to improve user understanding of spatial constraints and planned motions.

Prior work has effectively utilized Augmented Reality (AR) to enhance visual feedback in robotics. For instance, systems like [36] overlay projected future motions onto

the robot's workspace. However, the primary goal of such systems is typically to communicate the robot's autonomous intent to a human collaborator for improved safety and fluency in shared environments.

The key distinction in our work lies in the interaction paradigm. In contrast to systems designed to visualize autonomous robot behavior, our TelePreview is not for interpreting robot intent, but for empowering the human operator to visualize and refine their own commands in a virtual scene before execution. Our core contribution is a "preview-then-execute" closed-loop control model for direct teleoperation. This approach allows users to correct errors, test complex motions virtually, and ensure the intended action is safe and accurate before engaging the physical hardware.

II. SYSTEM OVERVIEW

Our system offers an integrated workflow for controlling robot movements with both precision and safety, leveraging low-cost hardware (under \$1,000) and diverse input devices. This workflow comprises two complementary modules:

- 1) **Teleoperation Module:** Includes a teleoperation pipeline for robust motion retargeting.
- 2) **Preview-Based Module:** Allows operators to check intended movements in a virtual setting before execution.

As illustrated in Fig. 3, the *teleoperation module* (Section IV) offers a safe and intuitive pipeline that proceeds in three stages:

- 1) Wrist pose estimation via IMU-based tracking (Section III-A),
- 2) Hand pose estimation using a motion capture glove (Section III-B),

- 3) Non-collision retargeting to ensure safe joint configurations (Section III-C).

Together, these components collectively enable an efficient mapping from human motion to robot commands. Moreover, by adopting SMPL-X (Section III-A.1) as a standardized representation of the human body, our pipeline can seamlessly integrate data from any input device conforming to this format.

Additionally, as illustrated in Fig. 3, the *preview-based module* (Section IV) then provides a safe and intuitive pipeline that proceeds in three stages:

- 1) The preview robot is aligned with the physical robot using AprilTag markers [37] (Section IV-B.1).
- 2) User commands are visualized on the aligned preview robot (Section IV-B.2).
- 3) Once the I/O state transitions, the final preview pose is captured and converted into an optimal trajectory for actual execution (Section IV-B.3).

This preview-then-execute scheme reduces errors and protects the robot and its surroundings by allowing users to visualize and refine their actions beforehand. Thus, it substantially improves efficiency and safety.

III. TELEOPERATION PIPELINE

A. Wrist Pose Estimation

Our system tracks the human operator's wrist motion to enable intuitive robot teleoperation. The input consists of raw IMU sensor data from sensors attached to the operator's arm, while the output is the 6-DoF wrist pose (position and orientation) in world coordinates. This wrist pose serves as the primary control signal for the robot's end-effector, allowing natural mapping between human arm movements and robot motion.

1) *SMPL-X Standard*: We adopt the SMPL-X standard [38] as our standard representation of the human body. The SMPL-X model represents a kinematic tree with standardized joint coordinate systems, where each joint's pose describes a rotation and translation relative to its parent frame. This hierarchical structure enables consistent pose representation across different motion capture devices and simplifies the integration with our TelePreview system.

2) *IMU-based Tracking System*: IMU-based motion capture offers robust tracking regardless of visual conditions and occlusions. Following the SMPL-X convention, we define the world frame system at the midpoint between the feet. All positions and orientations in this paper are expressed in this coordinate system unless otherwise specified. After obtaining the SMPL-X model, we compute the wrist position $\mathbf{p}_w \in \mathbb{R}^3$ and orientation $\mathbf{R}_w \in SO(3)$ relative to this world frame.

Based on the wrist parameters, we map the user's wrist pose to the end-effector pose through a transformation function $\mathcal{T}$. Specifically, we use the relative wrist position to control the end-effector position and the absolute wrist orientation to control the end-effector orientation:

$$\mathbf{p}_e(t) = \mathbf{p}_e(0) + (\mathbf{p}_w(t) - \mathbf{p}_w(0)), \quad \mathbf{R}_e(t) = \mathbf{R}_w(t), \quad (1)$$

where $\mathbf{p}_e(t)$ and $\mathbf{R}_e(t)$ represent the end-effector position and orientation at time t , and $\mathbf{p}_w(t)$ and $\mathbf{R}_w(t)$ represent the user's wrist position and orientation at time t .

B. Hand Pose Estimation

Mocap gloves offer direct joint angle measurements $\{q_i\}_{i=1}^{27}$ using flex sensors. Our joint-to-joint mapping approach provides a generalizable solution for retargeting high-dimensional human hand motion data to lower-dimensional robotic systems. This approach is particularly effective when the input space (e.g., the human hand with 27 DoF) has higher dimensionality than the target space (e.g., the robotic hand with 16 DoF), as it allows selective mapping of the most intuitive and task-relevant degrees of freedom. Through a manual selection of corresponding joints based on human intuition and task requirements, followed by range alignment between input and output spaces, we maintain natural and predictable motion correspondence.

We propose a direct joint-to-joint mapping function $\mathcal{M} : \mathbb{R}^{27} \rightarrow \mathbb{R}^{16}$ that transforms mocap glove readings to LEAP hand [39] joint configurations. Let $q_g \in \mathbb{R}^{27}$ denote the glove joint values and $q_r \in \mathbb{R}^{16}$ denote the robot joint values. For each robot joint i , we define a mapping:

$$q_r^i = f_i(q_g^{k_i}), \quad i \in 1, \dots, 16, \quad (2)$$


where k_i is the corresponding glove joint index for robot joint i which is manually picked, and f_i is a linear transformation:

$$f_i(x) = s_i(x - b_i)r_i. \quad (3)$$


Here, $s_i \in \mathbb{R}^+$ is a scaling factor that normalizes the joint ranges, $b_i \in \mathbb{R}$ is a bias term that aligns the neutral positions, and $r_i \in \{-1, 1\}$ is a direction indicator that ensures consistent joint rotations. This mapping guarantees:

$$\max q_g^{k_i} \Leftrightarrow \max q_r^i, \quad \min q_g^{k_i} \Leftrightarrow \min q_r^i, \quad (4)$$

Where q_g and q_r represent the joint angles of the glove and the Leap Hand, respectively, and max and min denote their upper and lower joint limits.



(a) Current Retargeting Method [3] Causes Collision.



(b) Our Self-collision Avoidance Retargeting.

Fig. 4: Comparison of Hand Configuration Retargeting Methods: (a) shows the direct mapping between human and robot hands leading to self-collision; (b) demonstrates our collision-aware retargeting approach that maintains safe configurations.

C. Non-Collision Retargeting Network

Direct mapping from human hand postures to robotic hands using existing retargeting approaches like [3] can result in self-collisions, as demonstrated in Fig. 4a. While traditional retargeting methods can achieve real-time performance for simpler end-effectors, they rely on optimization-based approaches that become computationally intensive for high-DoF configurations, highlighting the importance of collision-aware methods such as [33].

To address these challenges, we develop a learning-based framework with two key components:

- 1) A Self-Collision Prediction Network (CPN) that takes robot joint configurations $q \in \mathbb{R}^n$ as input and outputs a binary collision probability vector $p \in \mathbb{R}^m$ indicating collision likelihood for each link.
- 2) A Configuration Correction Network (CCN) that maps collision-prone joint configurations to their nearest collision-free counterparts. Specifically, it transforms an invalid robot configuration $q_{invalid} \in \mathbb{R}^n$ to a valid configuration $q_{valid} \in \mathbb{R}^n$ that minimizes both collision risk and deviation from the original pose.

As demonstrated in Fig. 4b, our method successfully transforms problematic configurations into stable, safe positions while maintaining efficient real-time performance (about 60Hz). The implementation detail can be found in the Appendix.

IV. PREVIEW PIPELINE

A. Why Preview System Assistance?

Traditional teleoperation approaches face significant challenges in data quality when collecting demonstrations for imitation learning. During complex manipulation tasks, users frequently make exploratory movements that contaminate the demonstration data with sub-optimal trajectories. These repeated probing actions to locate the socket edge and refine the approach angle before successful insertion introduced significant noise into the collected datasets. Such noise is particularly problematic for training imitation learning models, which benefit most from clean, purposeful demonstrations rather than trajectories cluttered with exploratory movements. Recent research has highlighted how errors or exploratory movements in teleoperation can decrease the generalization ability of the learned policies and negatively impact performance on unseen tasks. [40]–[44]

To address these limitations and provide a more efficient workflow, we propose incorporating a dedicated *preview* feature that allows users to refine their actions before physical execution. By separating exploration from the final command, our approach reduces sub-optimal motions that would otherwise degrade data quality.

B. Technical Implementation of Preview System

We designed our preview feature to integrate seamlessly with the teleoperation workflow. It requires three critical elements: (1) precise spatial calibration to maintain alignment between the virtual preview and the physical robot, (2)

realistic rendering to blend the preview with camera feeds, and (3) state management to handle transitions between preview and execution phases. The following subsections detail each of these technical components, highlighting how they collectively enable users to view and adjust planned motions before committing them to the physical robot.

1) *Spatial Alignment Using AprilTag*: To maintain a precise spatial alignment between the preview and the physical robot in the camera viewpoints, we implement a robust calibration system using AprilTags [37]. Our approach involves two sequential steps: (1) a hand-eye calibration that establishes the transformation between the robot’s base frame and the fixed camera frame, and (2) AprilTag pose detection that enables real-time tracking of the robot’s position and orientation relative to each camera view.




Fig. 5: **Our Transformation Relationship**: The number in the circle denotes the order of transformation acquisition.

As shown in Fig. 5, our calibration procedure involves multiple sequential transformations. We begin with hand-eye calibration of the fixed top-view camera, followed by AprilTag pose detection from this camera’s perspective. These steps allow us to compute the transformation from the AprilTag to the robot base frame. For the floating third-view camera, we detect the AprilTag pose and use it to determine its position relative to the robot base frame. This calibration ensures consistent visualization across dynamic or multi-view setups.

2) *Visual Preview Visualization*: Our system provides real-time visual feedback through a preview interface that overlays a virtual robot onto the real-world scene. For detailed technical information about our rendering pipeline and visualization methods, please refer to the Appendix.

3) *IO Control for Preview Visualization*: Our system uses a foot pedal as an intuitive control interface for state transitions. As shown in Fig. 6, when the IO is activated, the physical robot stops while the preview appears and responds to user commands for motion preview (Preview Mode). Upon IO deactivation, the preview disappears, and the system extracts its final configuration as the target pose to align, bypassing any exploratory movements made during the preview (Align Mode). The mplib motion planning library then processes this target to generate an optimal trajectory for execution. During this motion, the user does not need

to remain static—the robot executes the planned motion autonomously. Once the target pose is reached, the system enters a continuous teleoperation mode in which the robot follows the user’s live movements in real time until the next preview is initiated. This workflow ensures that users execute only refined, intentional movements, eliminating exploratory motions from demonstration data.




Fig. 6: State Transition of Preview Control

V. EXPERIMENTS

Our experiments aim to address the following questions:

Q1: How effective is TelePreview vs. Baselines?

Q2: How beneficial is TelePreview for new users?

Q3: How adaptable is TelePreview for new hardware?

A. Experiment Setup

TelePreview integrates several key components. We capture the user’s movements via an inertial motion capture suit and a pair of strain-gauge-based mocap gloves, providing high-fidelity joint angle data for both body posture and delicate hand movements. To visualize robot action before execution, we employ a RealSense RGB-D camera and render the preview on a standard 2D monitor. For the physical hardware, we use a UFactory xArm-6 robotic arm outfitted with a Leap hand [39], utilizing AprilTag [37] to align the initial poses of the preview and the real robot. The BOM list can be found in the Appendix.

Our study involved 20 participants in total, including 10 new users with no prior experience in robotic teleoperation and 10 experienced users. Participants attempted each task 10 times. Participants were given consistent task instructions and evaluated under a standardized protocol, including predefined success criteria. Task order was counterbalanced across participants to mitigate ordering effects.

B. Task Descriptions

We test TelePreview on five real-world tasks. These tasks [45] were carefully selected to cover a diverse range of manipulation skills, including grasping, rotation, alignment, and insertion, and are representative of common benchmarks used in teleoperation research:

- **Pick & Place:** Grasp an object and place it at precise locations.
- **Pour:** Tilt and rotate a cup to pour the beans into another container.
- **Hang:** Hang a spoon on a peg, requiring both fine positioning and subtle wrist rotations.
- **Box Rotation:** Rotate a box to change its orientation.
- **Cup Stacking:** Stack a cup onto another cup.

C. Evaluation Metrics

To provide a comprehensive evaluation, we measure both objective performance and subjective user experience through the following metrics:

- **Success Rate:** The proportion of trials where the operator completes the task under its defined constraints.
- **Execution Time:** The total duration from task initiation to successful completion for a given trial.
- **Subjective Workload:** To assess the cognitive and physical strain on the user, we administered the NASA-TLX questionnaire [46]. This evaluates workload across six subscales: *Mental Demand*, *Physical Demand*, *Temporal Demand*, *Performance*, *Effort*, and *Frustration*.
- **Practice Time:** The time required for a new user to practice with a control modality until they felt confident enough to begin formal trials.

D. Performance Comparison with Baselines (Q1)

To evaluate the performance of TelePreview, we selected three state-of-the-art vision-based teleoperation systems as baselines: **AnyTeleop** [3], **Open Teach** [1], and **Telekinesis** [33]. These systems were chosen as they represent the current standard for low-cost, accessible teleoperation frameworks that, like our own, do not depend on specialized motion capture hardware.

For our performance comparison, we cite the success rates reported in the original publications for each baseline. This approach was adopted after encountering frequent self-collision failures during local deployment of these vision-based methods. We believe citing the authors’ own optimized results provides the fairest comparison. A detailed discussion of our replication experiences is provided in the Appendix.

As summarized in Table I, TelePreview achieves higher success rates than all baselines. While Telekinesis, AnyTeleop, and Open Teach handle simpler, short-horizon tasks, they often struggle with complex manipulations requiring subtle wrist rotations and fine-grained positioning (e.g., the Hang task). TelePreview, by contrast, captures these nuances more effectively, reflecting stronger overall performance and versatility.

E. Effect of Preview for Users (Q2)

To investigate **Q2**—how the preview feature benefits non-expert users—we evaluate our method in two conditions: (1) with the preview enabled and (2) with the preview disabled. This section focuses on the new user group.

The same five tasks from Section V-B were attempted by new users, with each user repeating the tasks 10 times. In addition to objective performance metrics, we evaluated the subjective user experience by collecting workload ratings using the NASA Task Load Index (NASA-TLX) questionnaire and recording the practice time required for participants to gain confidence. Fig. 7 shows that the preview feature provides a superior user experience, significantly reducing both the perceived workload and the practice time needed to achieve proficiency.

Task	TelePreview (Ours)	Open Teach [1]	AnyTeleop [3]	Telekinesis [33]
Pick & Place	1.0	0.8	1.0	0.9
Hang	0.9	0	0	0
Pour	1.0	0.8	0.7	0.7
Box Rotation	1.0	0	0.6	0.6
Cup Stacking	1.0	0	0.7	0.3

TABLE I: Real Robot Teleoperation Success Rate Comparison.

Task	Success Rate			Average Success Execution Time (s)		
	w/o preview	w/ preview	Difference $\uparrow$	w/o preview	w/ preview	Difference $\downarrow$
Pick & Place	0.60 ± 0.05	1.00 ± 0.00	+0.40	23.56 ± 4.65	13.55 ± 3.17	-10.01
Hang	0.60 ± 0.05	1.00 ± 0.00	+0.40	29.30 ± 8.18	30.83 ± 3.65	+1.53
Pour	0.90 ± 0.03	0.80 ± 0.04	-0.10	43.20 ± 6.73	36.13 ± 5.86	-7.07
Box Rotation	0.60 ± 0.05	0.80 ± 0.04	+0.20	30.47 ± 14.08	19.12 ± 3.32	-11.35
Cup Stacking	0.50 ± 0.05	1.00 ± 0.00	+0.50	31.54 ± 6.04	18.91 ± 1.29	-12.63

TABLE II: Effect of Preview Assistance on New User Performance.




Fig. 7: Subjective Workload Assessment using NASA-TLX. For Performance, a lower score indicates better perceived performance.

As shown in Table II, enabling the preview boosts new user performance. Success rates increase across all tasks, with especially notable gains in challenging manipulations. Average execution times drop by up to 12.63 seconds (cup stacking), demonstrating not only improved accuracy but also greater efficiency. The standard deviations across trials are also reduced, suggesting more consistent user behavior.

By visualizing a virtual “preview” of the robot’s intended motion and confirming the final pose prior to executing physical movements, users eliminate the need for exploratory motions in the actual workspace. This design ensures that recorded trajectories contain only intentional, task-oriented actions. This results in higher-quality demonstrations that are free from unnecessary trial-and-error behaviors.

F. Deployment on Various Robots (Q3)

We evaluated the generalizability of TelePreview by deploying it on a Ufactory xArm with three distinct end-effectors: a 16-DoF anthropomorphic LEAP hand, a parallel-jaw gripper, and a vacuum gripper. As shown in Table III, the preview feature significantly reduced task completion time across all configurations. The most substantial improvement was observed with the high-DoF LEAP Hand, where execution time decreased by 10.0 seconds on average. In contrast, the gains for the simpler parallel-jaw and vacuum grippers

were more modest (-2.6s and -1.5s, respectively), highlighting TelePreview’s particular effectiveness for complex, fine-grained manipulation.

Importantly, adapting the system to each end-effector required only **minor parameter adjustments** (e.g., kinematic model, end-effector transform), while the core architecture remained unchanged. This result supports our claim that TelePreview is largely hardware-agnostic and can be integrated with diverse robot platforms with minimal effort.

End-Effector	w/o Preview	w/ Preview	Improvement
LeapHand (16-DoF)	23.6 ± 4.7	13.6 ± 3.2	-10.0
Parallel-jaw Gripper (1-DoF)	16.8 ± 1.7	14.2 ± 1.4	-2.6
Vacuum Gripper (binary)	15.2 ± 1.9	13.7 ± 1.3	-1.5

TABLE III: Average execution time (in seconds) for the Pick & Place task across different end-effectors.

VI. CONCLUSION

In this paper, we presented TelePreview, a low-cost teleoperation system featuring AR preview feedback designed for deployment across diverse robotic platforms. Our experiments demonstrate that TelePreview offers sufficient flexibility and safety to perform a variety of fine-grained tasks successfully. TelePreview provides immediate, robot-centric feedback that enables users to preview and refine their commands before physical execution.

While our results show promising advances in teleoperation interfaces, a key limitation is the visual ambiguity caused by occlusions between the preview robot and scene objects. This limitation stems from our use of alpha blending, which lacks depth-aware occlusion reasoning and cannot distinguish whether the virtual arm should occlude real objects or vice versa, resulting in artifacts even on passthrough-capable devices like the Meta Quest 3 without real-time depth estimation. To mitigate this ambiguity, our approach employs multi-view overlays (e.g., top-down and side views), allowing operators to compare perspectives and correctly infer spatial ordering.

Future work will leverage state-of-the-art monocular depth estimation, such as Depth Anything [47], from camera

feeds to enable robust spatial reasoning. To improve the preview's visual quality, we will investigate deep rendering optimizations like 3D Gaussian Splatting [48] and advanced multi-view fusion techniques [49], aiming to reduce user uncertainty during manipulation.

REFERENCES

- [1] A. Iyer, Z. Peng, and et al., "Open teach: A versatile teleoperation system for robotic manipulation," *arXiv preprint arXiv:2403.07870*, 2024.
- [2] Z. Fu, T. Z. Zhao, and et al., "Mobile aloha: Learning bimanual mobile manipulation with low-cost whole-body teleoperation," *arXiv preprint arXiv:2401.02117*, 2024.
- [3] Y. Qin, W. Yang, and et al., "Anyteleop: A general vision-based dexterous robot arm-hand teleoperation system," *arXiv preprint arXiv:2307.04577*, 2023.
- [4] K. Shaw, Y. Li, and et al., "Bimanual dexterity for complex tasks," *arXiv preprint arXiv:2411.13677*, 2024.
- [5] Y. Park and P. Agrawal, "Using apple vision pro to train and control robots," 2024.
- [6] C. Wang, H. Shi, and et al., "Dexcap: Scalable and portable mocap data collection system for dexterous manipulation," *arXiv preprint arXiv:2403.07788*, 2024.
- [7] X. Cheng, J. Li, and et al., "Open-television: Teleoperation with immersive active visual feedback," *arXiv preprint arXiv:2407.01512*, 2024.
- [8] F. Kennel-Maushart, R. Poranne, and et al., "Manipulability optimization for multi-arm teleoperation," in *ICRA 2021*. IEEE, 2021, pp. 3956–3962.
- [9] Y. Huang, D. Fan, and et al., "Human-like dexterous manipulation for anthropomorphic five-fingered hands: A review," *Biomimetic Intelligence and Robotics*, p. 100212, 2025.
- [10] K. Darvish, L. Penco, and et al., "Teleoperation of humanoid robots: A survey," *IEEE Transactions on Robotics*, vol. 39, no. 3, pp. 1706–1727, 2023.
- [11] S. Lichiardopol, "A survey on teleoperation," Technische Universiteit Eindhoven, Technical Report DCT-2007.155, 2007.
- [12] P. F. Hokayem and M. W. Spong, "Bilateral teleoperation: An historical survey," *Automatica*, vol. 42, no. 12, pp. 2035–2057, 2006.
- [13] K. D. Katyal, C. Y. Brown, and et al., "Approaches to robotic teleoperation in a disaster scenario: From supervised autonomy to direct control," in *IROS*. IEEE, 2014, pp. 1874–1881.
- [14] R. M. Aronson, T. Santini, T. C. Kübler, E. Kasneci, S. Srinivasa, and H. Admoni, "Eye-hand behavior in human-robot shared manipulation," in *Proceedings of the 2018 ACM/IEEE international conference on human-robot interaction*, 2018, pp. 4–13.
- [15] S. Scherzinger, A. Roennau, and R. Dillmann, "Learning human-inspired force strategies for robotic assembly," in *CASE 2023*. IEEE, 2023, pp. 1–8.
- [16] M. Micire, M. Desai, and et al., "Design and validation of two-handed multi-touch tabletop controllers for robot teleoperation," in *Proceedings of the 16th international conference on Intelligent user interfaces*, 2011, pp. 145–154.
- [17] S. An, Z. Meng, and et al., "Dexterous manipulation through imitation learning: A survey," *arXiv preprint arXiv:2504.03515*, 2025.
- [18] R. Ding, Y. Qin, and et al., "Bunny-visionpro: Real-time bimanual dexterous teleoperation for imitation learning," *arXiv preprint arXiv:2407.03162*, 2024.
- [19] M. Hirschmanner, C. Tsiourti, and et al., "Virtual reality teleoperation of a humanoid robot using markerless human upper body pose imitation," in *Humanoids 2019*, 2019, pp. 259–265.
- [20] C. Stanton, A. Bogdanovych, and et al., "Teleoperation of a humanoid robot using full-body motion capture, example movements, and machine learning," in *Proc. Australasian Conference on Robotics and Automation*, vol. 8, 2012, p. 51.
- [21] N. Miller, O. C. Jenkins, and et al., "Motion capture from inertial sensing for untethered humanoid teleoperation," in *Humanoids*, vol. 2. IEEE, 2004, pp. 547–565.
- [22] H. Liu, Z. Zhang, and et al., "High-fidelity grasping in virtual reality using a glove-based system," in *ICRA 2019*. IEEE, 2019, pp. 5180–5186.
- [23] M. Mosbach, K. Moraw, and et al., "Accelerating interactive human-like manipulation learning with gpu-based simulation and high-quality demonstrations," in *2022 IEEE-RAS 21st International Conference on Humanoid Robots (Humanoids)*. IEEE, 2022, pp. 435–441.
- [24] M. Schwarz, C. Lenz, and et al., "Nimbro avatar: Interactive immersive telepresence with force-feedback telemanipulation," in *IROS 2021*. IEEE, 2021, pp. 5312–5319.
- [25] F. P. Audonnet, J. Grizou, and et al., "Telesim: A modular and plug-and-play framework for robotic arm teleoperation using a digital twin," in *ICRA 2024*. IEEE, 2024, pp. 17 770–17 777.
- [26] S. Yang, M. Liu, and et al., "Ace: A cross-platform visual-exoskeletons system for low-cost dexterous teleoperation," *arXiv preprint arXiv:2408.11805*, 2024.
- [27] P. Wu, Y. Shentu, and et al., "Gello: A general, low-cost, and intuitive teleoperation framework for robot manipulators," 2023.
- [28] D. A. Lawrence, "Stability and transparency in bilateral teleoperation," *IEEE transactions on robotics and automation*, vol. 9, no. 5, pp. 624–637, 1993.
- [29] A. M. Ousaid, D. S. Haliyo, S. Régnier, and V. Hayward, "A stable and transparent microscale force feedback teleoperation system," *IEEE/ASME Transactions on Mechatronics*, vol. 20, no. 5, pp. 2593–2603, 2015.
- [30] Z. Zhao, P. Huang, and et al., "Augmented reality for enhancing tele-robotic system with force feedback," *Robotics and Autonomous Systems*, vol. 96, pp. 93–101, 2017.
- [31] D. Lee and Y. S. Park, "Implementation of augmented teleoperation system based on robot operating system (ros)," in *IROS 2018*. IEEE, 2018, pp. 5497–5502.
- [32] P. Milgram, A. Rastogi, and et al., "Telerobotic control using augmented reality," in *Proceedings 4th IEEE International Workshop on Robot and Human Communication*. IEEE, 1995, pp. 21–29.
- [33] A. Sivakumar, K. Shaw, and et al., "Robotic telekinesis: Learning a robotic hand imitator by watching humans on youtube," *arXiv preprint arXiv:2202.10448*, 2022.
- [34] J. Wang, C.-C. Chang, and et al., "Eve: Enabling anyone to train robots using augmented reality," in *UIST*, 2024, pp. 1–13.
- [35] J. Duan, Y. R. Wang, and et al., "Ar2-d2: Training a robot without a robot," *arXiv preprint arXiv:2306.13818*, 2023.
- [36] E. Rosen, D. Whitney, and et al., "Communicating robot arm motion intent through mixed reality head-mounted displays," in *Robotics research: The 18th international symposium ISRR*. Springer, 2019, pp. 301–316.
- [37] E. Olson, "Apriltag: A robust and flexible visual fiducial system," in *ICRA*. IEEE, 2011, pp. 3400–3407.
- [38] G. Pavlakos, V. Choutas, and et al., "Expressive body capture: 3d hands, face, and body from a single image," in *CVPR*, 2019, pp. 10 975–10 985.
- [39] K. Shaw, A. Agarwal, and et al., "Leap hand: Low-cost, efficient, and anthropomorphic hand for robot learning," *RSS*, 2023.
- [40] A. Mandlekar, D. Xu, and et al., "What matters in learning from offline human demonstrations for robot manipulation," *arXiv preprint arXiv:2108.03298*, 2021.
- [41] T. Zhang, Z. McCarthy, and et al., "Deep imitation learning for complex manipulation tasks from virtual reality teleoperation," in *ICRA 2018*. IEEE, 2018, pp. 5628–5635.
- [42] V. Tangkaratt, N. Charoenphakdee, and et al., "Robust imitation learning from noisy demonstrations," *arXiv preprint arXiv:2010.10181*, 2020.
- [43] M. Hussein and M. Begum, "Detecting incorrect visual demonstrations for improved policy learning," in *CoRL*. PMLR, 2023, pp. 1817–1827.
- [44] R. C. Zheng, K. Hu, and et al., "Extraneousness-aware imitation learning," in *ICRA 2023*. IEEE, 2023, pp. 2973–2979.
- [45] S. James, Z. Ma, and et al., "Rlbench: The robot learning benchmark & learning environment," *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 3019–3026, 2020.
- [46] J. M. Noyes and D. P. Bruneau, "A self-analysis of the nasa-tlx workload measure," *Ergonomics*, vol. 50, no. 4, pp. 514–519, 2007.
- [47] L. Yang, B. Kang, and et al., "Depth anything: Unleashing the power of large-scale unlabeled data," in *CVPR*, 2024, pp. 10 371–10 381.
- [48] B. Kerbl, G. Kopanas, and et al., "3d gaussian splatting for real-time radiance field rendering," *ACM Trans. Graph.*, vol. 42, no. 4, pp. 139–1, 2023.
- [49] Z. Li, T. Müller, and et al., "Neuralangelo: High-fidelity neural surface reconstruction," in *CVPR*, 2023, pp. 8456–8465.