Excavation Safety Hazards and OSHA Standards

Learn everything you need to know about excavation safety—OSHA trenching and excavation standards, hazards, safety measures, and more.

In this article

- **What is Excavation Safety?**
- What are the Hazards in Excavation?
- What are OSHA Excavation Standards?
- What are the Safety Measures for Excavation?
- Examples of Excavation Protection
- Excavation Safety Toolbox Talk Topics
- Streamline Excavation Risk Assessments with SafetyCulture

What is Excavation Safety?

Excavation safety is a standardized set of safety precautions for trenching and excavation to eliminate hazards and control risks in compliance with regulations. It is also referred to as Trenching and Excavation Safety, as often cited by the US Occupational Safety and Health Administration (OSHA).

What are the Hazards in Excavation?

Excavation work exposes workers to physical and atmospheric threats due to their unstable environment. Here are some of the common hazards associated with excavations:

- The collapse of the sides of the excavation
- Materials falling onto people
- Falls, either people or vehicles
- Nearby structures collapsing into the excavation
- Electrocution, explosion, blasts , gas leak, or flooding, caused by damage to underground services

Improve Safety in Construction and Excavation Operations

Raise the level of safety for all workers through real-time data, standardized procedures, and effective communication across multiple sites.

Explore Our Construction Safety Solution

What are OSHA Excavation Standards?

OSHA excavation standards are specifications of requirements for trenching and excavation, including protective systems. In US federal regulations, OSHA standards for excavations and backfilling are specifically found in Title 29 (Labor) Part 1926 (Safety and Health Regulations for Construction) Subpart P (Excavations), or 29 CFR 1926 subpart P. The excavation regulation also contains appendices for the following:

- Soil Classification
- Sloping and Benching
- Timber Shoring for Trenches
- Aluminum Hydraulic Shoring for Trenches
- Alternatives to Timber Shoring
- Selection of Protective Systems

What are the Safety Measures for Excavation?

The Bureau of Labor Statistics reported around a 70% decline in fatalities from trench collapses in 2022 due to strengthened measures against unprotected trenches. To protect workers from injuries and fatalities, preventive measures should be implemented when workers begin excavating.

According to OSHA, general safety measures to follow should cover the following:

- Establish protective systems like benching, sloping, shoring and shielding.
- Avoid collapsing by supporting the sides by either battering them or with sheets.
- Store materials from the excavation at a safe distance from the excavation. This will help reduce the risk of them falling onto people.
- Add barriers to excavation as a precaution to avoid people falling into the excavation.
- Keep vehicles completely out of the excavation area. However, if required, the use of barriers and stop-blocks should help mitigate that danger.

- Use cable, pipe, and service plans to ensure that underground service s are known so they can be marked on the ground or, ideally, the area avoided entirely.
- Around the areas where there are underground services, avoid mechanical equipment and instead use spades and/or shovels.
- Avoid picks and forks as they are more likely to pierce cables and pipes.
- Avoid flooding by ensuring that there is appropriate pumping equipment so that any water that seeps into the excavation can be easily pumped out to a safe area.

Workers should also keep in mind the following procedures to perform excavations safely:

- Inspect trenches daily before work begins. Don't go near an unprotected trench. Excavation safety software can help you ensure that your trenches are safe to work in by providing key safety measures and protocols to follow.
- Check weather conditions before work, be mindful of rain and storms.
- Keep heavy equipment away from trench edges.
- Be mindful of the location of utilities underground.
- Always wear proper protective equipment.
- Don't work beneath raised loads.
- Conduct atmosphere tests. If low oxygen and toxic gases were detected, workers must not enter the trench.
- Use a checklist to perform regular self-inspections and risk assessments.

Create your own excavation risk assessment checklist

Build from scratch or choose from our collection of free, ready-to-download, and customizable templates.

Browse excavation risk assessment checklists

Examples of Excavation Protection

OSHA requires employers to implement protective measures for the safety of employees, contractors, and subcontractors before they can work on and near excavations. Here are some examples of excavation protection:

- **Structural ramps** – whether for the exclusive use of employees or of equipment around excavations, structural ramps must be built according to the design of a competent person.
- **High-visibility vests** – employees who are not only working around excavations but are also exposed to public traffic must wear high-visibility vests or clothing with similar reflective material.
- **Warning signs** – mobile equipment operators who do not have easy visibility of the edge of excavations should be able to see warning signs such as barricades which will indicate proximity to excavations.
- **Testing** – the condition of the atmosphere in and around excavations must be tested to ensure that it is safe even before employees are allowed to work at the site.
- **Emergency equipment** – equipment such as stretchers, harness, etc. should be available in case of an emergency.

Excavation Safety Toolbox Talk Topics

Another way to help reinforce excavation safety is by conducting toolbox talks regularly. Listed below are sample ideas of relevant excavation safety topics you can talk about with your team:

- Safe Excavation Access and Egress
- Preventing Displacement of Ramps and Runways
- Safety Tips for Sloped and Benched Excavations
- Detecting Signs of Hazardous Atmosphere
- Precautions for Exposure to Vehicular Traffic
- Safety Measures for Exposure to Falling Loads
- Protection from Water Accumulation-related Hazards

- Accepted Engineering Practices for Specific Excavation Sites
- Application of Tabulated Data by Registered Professional Engineers
- Basics of Emergency Rescue Equipment

Streamline Excavation Risk Assessments with SafetyCulture

Why Use SafetyCulture?

SafetyCulture is a mobile-first operations platform adopted across industries such as manufacturing, mining, construction, retail, and hospitality. It's designed to equip leaders and working teams with the knowledge and tools to do their best work—to the safest and highest standard.

Efficiently manage and streamline health and safety processes across the organization, including incident management, safety audits and inspections, risk assessment, waste management, and more, using a comprehensive EHS software solution.

✓ Save time and reduce costs ✓ Stay on top of risks and incidents ✓ Boost productivity and efficiency ✓ Enhance communication and collaboration ✓ Discover improvement opportunities ✓ Make data-driven business decisions

Explore Our EHS Solution

FAQs About Excavation Safety

Who is responsible for excavation safety on site?

The person responsible for ensuring safety in excavation work is known as a competent person. This individual, designated by the employer, is authorized to take immediate corrective actions to eliminate excavation-related hazards that are dangerous to workers. Moreover, an excavation competent person should be able to do the following:

- Classify soil
- Clear sites safely
- Inspect protective systems

- Design structural ramps
- Monitor water removal or dewatering equipment
- Perform site inspections

What training is required for workers involved in excavation?

Workers involved in excavation must be trained to identify hazards like cave-ins, falls, and hazardous atmospheres and to use protective systems such as sloping, shoring, and shielding. They should also be informed about the following topics:

- Pre-planning
- Soil analysis
- Safe entry and exit
- Emergency response procedures
- Compliance with excavation safety regulations

With today's technology, you can easily deliver and track excavation safety training across multiple sites from wherever you are.

What is the 5 foot rule excavation?

The 5-foot rule in excavation is a safety practice that states that unless the pit is made entirely of stable rock, trenches 5 feet deep or greater require the use of a protective system. If, however, the excavation is under 5 feet, a competent person may decide whether a protective system is necessary or not.

What is the 5 4 3 2 1 rule excavation?

The 5 4 3 2 1 rule is a safety guideline for excavation work that helps prevent accidents and injuries. They are as follows:

- 5 feet deep trenches must have a protective system in place
- Trenches greater than 4 feet must have a ladder for exit and egress
- Ladders should extend at least 3 feet from the excavation for easy access and easy exit
- Place excavated materials 2 feet away from the edge of the excavation

- 1 competent person must be present at all times to monitor safety and eliminate hazards

What is the deadliest excavation hazard?

A cave-in is probably the deadliest excavation hazard, where walls can suddenly collapse without warning, workers do not have time to move out of the way, and cubic yards of dirt can fatally crush and suffocate. A 2024 investigative report revealed that over 250 workers have lost their lives due to trench cave-ins in the last 10 years.

What are the best practices for preventing cave-ins?

Trench cave-ins are a major hazard in excavation work, causing serious injuries and fatalities. Prevent them by:

- Using protective methods like sloping, shoring, and trench boxes
- Keeping soil and equipment away from edges
- Inspecting the premises regularly, ideally daily
- Training workers about safety measures
- Having emergency plans in place