Names: Emmanuel NIYOBUHUNGIRO
Tel; +250 785072512
Email: niyobuhungiroemmanuel17@gmail.com

Subject : NEBOSH ASSIGNMENT ON ELEMENT 4.
Date: October 2, 2025
Submitted to:
Kafela Global Concept Limited

Q1. Reactive vs. Active Monitoring (Definitions)

Reactive monitoring involves tracking incidents after they occur using data from accidents, near misses, cases of ill health, etc., to identify trends and problem areas. It is essentially lagging indicator monitoring of safety performance

In contrast, **Active monitoring** (proactive monitoring) is the ongoing, preventative checking of existing workplace conditions, practices, and systems before accidents happen. It includes planned inspections, audits, and sampling to identify and correct substandard conditions or compliance issues prior to any incident. Together, these approaches ensure that an organization learns from past events (reactive) and also actively checks that controls are working to prevent future incidents (active)

Q2. Purpose of Workplace Inspections

- Workplace inspections are a form of active monitoring aimed at preventing harm. Their primary purpose is to ensure that existing hazard controls are working effectively and remain suitable for current conditions, and to identify any potential hazards or deficiencies which is improving preparedness action.
- In essence, regular inspections help verify compliance with safety standards and highlight weaknesses or emerging risks in the workplace, allowing proactive improvements and prevention of accidents.
- This not only protects employees from injury but also monitors if safety measures (like guards, equipment, procedures) are functioning as intended and if any new hazards have arisen.

Q3. the Difference between of Safety Inspection and Safety Tour

A **safety inspection** is typically a routine, focused examination of specific workplace conditions or equipment, often conducted by a competent person (such as a supervisor) using a checklist. For example, a supervisor might perform a weekly inspection of a workshop, checking predefined items for safety compliance. Inspections usually have a narrow scope and are intended to spot and fix hazards in a particular area or process.

On the other hand, Safety tours are broader in scope and not limited to a checklist, the team observes any health and safety issues that come to light during the walk around It is a more general, high profile walk through of the workplace, usually carried out by a team that includes(senior managers,workers and possibly other staff to discuss their safety concerns with the purpose of keeping safety as culture .

In summary, **inspections** are routine, focused checks by staff (often using checklists), whereas **tours** are broader, management led visits intended to gauge overall safety performance and engage the workforce.

4.The Role of Senior Management in Workplace Inspections are follow:

- ✧ Primarily, they are responsible for establishing and ensuring effective inspection regimes within the organization.This means they must allocate resources and set expectations so that regular inspections and tours occur and are properly documented.
- ✧ Senior managers should also receive inspection reports from supervisors, review the findings, and oversee that appropriate corrective actions are taken in response.
- ✧ In addition, senior management is expected to participate visibly in some inspections for example, by joining safety tours on the shop floor. which is highly encouraged because it demonstrates their commitment to safety and helps promote a positive safety culture.

When employees see directors or senior leaders walking around discussing safety issues, it reinforces that safety is a top priority. In short, senior managers set the tone: they ensure the inspection program exists and functions effectively, and their leadership and participation in inspections can motivate the entire organization to take health and safety seriously.

Q5. Why Checklists Are Used in Inspections

Checklists are a common tool for workplace safety inspections because they help ensure consistency and attention on details.

An inspection checklist provides a structured list of items or conditions to examine, which guarantees a systematic and comprehensive approach so that no key safety element is overlooked. By following a checklist, different inspectors will cover the same critical points, leading to a more uniform standard of inspection each time.

Other benefits of using checklists include creating a written record of the inspection findings and actions, and saving time by clearly outlining what to look at. In short, checklists make inspections more efficient and repeatable, ensuring all important points are covered on every inspection.

Q6. Prime Purpose of an Accident Investigation

The main purpose of investigating an accident are:

a. To find the causes of the incident so that corrective actions can be taken to prevent it from happening again. Accident investigations are not about placing blame on individuals; rather, they aim to uncover both the immediate and underlying (root) causes of what went wrong by determining how and why an accident occurred.
b. Facilitate to know and implement measures such as improved training, new safety controls, procedure changes, or equipment fixes to avoid similar incidents in the future. In essence, an accident investigation's prime objective is preventive:

it provides the insight needed to improve health and safety performance and stop recurrences of that or related accidents.

Q7. Four Key Steps of the Accident Investigation Process

A thorough accident investigation generally involves four main steps:

1. **Gather Information:** Collect all possible facts about the event. This includes visiting the scene, taking photographs or measurements, collecting physical evidence, and obtaining witness statements by interview and reports. The goal is to known exactly what happened ,who was involved, what occurred, where, when.
2. **Analyze the Information:** Examine the facts to determine the immediate causes of the accident (the direct events or conditions that led to the incident) and the root/underlying cause**s**. Techniques like root cause analysis may be used here to trace back from what happened to why it happened.

3. **Identify Control Measures:** Based on the analysis, identify suitable corrective and preventive measures. These are the actions or controls needed to address the causes. This could include hierarchy of control.
4. **Plan and Implement Remedial Actions:**The plan should outline how each cause will be addressed and include a follow-up to verify that actions are completed and effective Develop an action plan to implement the recommended controls. This means assigning responsibilities and deadlines for each recommendation.

Q8. Staff Who Might Be Part of an Internal Accident Investigation Team

The categories of staff that could be useful members of an internal accident investigation team include

i. **Line Management:** The immediate line manager or supervisor of the area/department where the accident happened (or of the injured person). They know the routine work and people involved, and can provide operational insight
ii. **Senior Management Representative:** A member of senior management (e.g. a director or senior operations manager) to provide leadership, ensure resources for the investigation, and demonstrate the organization's commitment to finding the causes.
iii. **Health and Safety Officer/Advisor:** A safety practitioner or health and safety executive officer who is trained in investigation techniques and regulations. They contribute technical knowledge of safety management and help identify causes and compliance issues.
iv. **Worker Representative:** To bring workers' perspectives can help communicate with other employees.Their involvement also promotes transparency and trust in the investigation process.
v. **Technical Experts:** Depending on the accident, specialists such as an engineer, maintenance manager, or technical expert might be included. For example, if machinery was involved, an engineer can help examine equipment failures; or if a chemical incident, a process specialist might be needed.

vi. **First Aider or Witness (advisory):** Sometimes the first aider or an eye witness might be part of discussions or consulted due to their direct knowledge of the event.

Q9. The types of documentation to Consult During an Accident Investigation

A variety of **records and documents** should be reviewed as part of an accident investigation to build a complete picture of circumstances and causes. Relevant types of documentation include:

- **Inspection and Maintenance Records:** Logs showing equipment maintenance history, inspection reports, and any repair work done. These help determine if a mechanical failure or lack of maintenance contributed to the accident.
- **Risk Assessments:** The risk assessment documents for the task or area involved, to see if the hazards were identified and adequately controlled according to prior planning.
- **Safe Work Procedures or Permits-to-Work:** Any written safe operating procedures, method statements, or permits that were in place for the activity. This shows what should have been done and if procedures were followed.
- **Environmental or Health Monitoring Data:** Relevant measurements (like noise, air quality, or other environmental readings) if applicable to the incident, and any previous reports of unsafe conditions in the environment.
- **Medical Records (occupational health):** Medical or exposure records if the incident involves ill health or if the worker had any medical condition relevant to the accident (for instance, hearing tests if hearing protection or audible alarms were an issue).
- **Previous Incident Reports and Safety Analytics:** Any prior accident/incident reports or trend analysis related to similar events or the same department. This can reveal patterns or repeated issues.
- **Training Records and Personnel Files:** Records of training and qualifications for the people involved (to check if they were trained for the task and aware of the hazards). Also supervision records or disciplinary records if relevant (for example, past safety violations).
- **Safety Committee Minutes:** Minutes from health and safety committee meetings, to see if any concerns about the hazard or similar issues had been raised before by worker representatives.
- **Equipment Manuals and Technical Data:** The manufacturer's instructions or specifications for any equipment involved, which may indicate proper use and guarding requirements or maintenance schedules.

Q10. Two Categories of Immediate Causes of Accidents/Incidents are:

a. **Unsafe Acts:** These are human actions that deviate from safe procedures or practices. Unsafe acts include things like operating equipment improperly, failing to follow safety rules, not wearing required PPE, or any human error that immediately precipitates an incident. For example, a worker bypassing a machine guard or a driver speeding are unsafe acts.
b. **Unsafe Conditions:** These are hazardous physical or environmental conditions present in the workplace that directly cause or contribute to an accident. They include situations like defective or unguarded equipment, poor lighting, slippery

floors, exposed electrical wiring, etc. An unsafe condition might be the result of poor maintenance, design flaws, or environmental factors (e.g. ice on a walkway).

Often, an accident results from a combination of both an unsafe act and an unsafe condition. For instance, an incident could occur because a machine was unguarded (unsafe condition) and a worker reached into it (unsafe act). Identifying these immediate causes is the first step in investigating an accident, before drilling down to why those unsafe acts or conditions were present (the root causes).

Q11. Reversing Vehicle Accident Possible Immediate and Root Causes

Scenario: An employee was struck by a reversing vehicle in a loading bay. We need to list possible immediate causes and underlying root causes for this accident.

Immediate Causes: These are the direct factors that led to the collision essentially what went wrong at the moment of the incident:The vehicle had a mechanical failure, such as faulty brakes, resulting in loss of control.

The driver did not see the pedestrian while reversing the pedestrian was in the driver's blind spot or not visible in mirrors.The pedestrian was not conspicuous – e.g., the pedestrian was not wearing a high-visibility jacket, making them hard to spot.The driver's view was obstructed by loads or equipment on the vehicle or in the area (restricted visibility).

Human error or lapse by either the driver or the pedestrian (for example, the driver not paying full attention while reversing, or the pedestrian walking into the vehicle's path without awareness)

Root Causes: These are deeper systemic or organizational failings that allowed the immediate causes to occur. They answer *why* those situations arose:

Inadequate maintenance of the vehicle – for instance, poor maintenance procedures leading to faulty brakes or malfunctioning reversing alarms.Poor lighting or environmental conditions in the loading bay e.g., insufficient lighting or bad weather (fog, rain) making it hard for drivers to see pedestrians.

Lack of a high-visibility clothing policy or its enforcement the company may not require pedestrians in the loading bay to wear hi vis vests, or the rule existed but wasn't enforced, reducing pedestrian visibility

Inadequate traffic management and housekeeping ,perhaps there were no defined walkways or physical barriers separating pedestrians from vehicles, or the area was cluttered (so pedestrians and vehicles intermingle). Also, no mirrors or warning signs at blind corners would fall here.

No banksman (spotter) to assist with reversing:the absence of a designated person to guide reversing vehicles (lack of a signaling system) is a root cause that increases the risk of such collisions.

Insufficient training and awareness: the driver and/or pedestrian may not have been adequately trained in yard safety and reversing procedures. For example, the driver might not have been trained to check blind spots properly or the pedestrian was unaware of the vehicle movement rules.

Supervisory or procedural failures: perhaps there was no rule that work in the loading bay should stop during vehicle reversing, or supervision was lax in enforcing safe reversing protocols.

Each immediate cause can be traced to one or more of these root causes. For instance, if the driver didn't see the pedestrian, a root cause might be the lack of a banks man or poor mirror/camera equipment on the vehicle. Addressing the root causes (like improving maintenance, training, and site rules) is essential to prevent future incidents of this nature.

Q12. Who Is Responsible for Initially Reporting Accidents/Incidents

In most organizations, the responsibility for initially reporting an accident or safety-related incident lies with the person who was involved or witnesses it first. Typically, this means the injured employee should report the accident to their supervisor as soon as possible (assuming they are conscious and able to do so). If the injured person cannot report it (due to the severity of injury), then a colleague or witness who saw the incident should report it immediately.

. In some cases, the first aider who provided assistance or the immediate line manager of the area might be required to fill out the initial accident report form. Ultimately, line management should always be informed quickly, but the worker involved is usually expected to initiate the report (with coworkers helping if necessary).

Q13. Communication of Accident Investigation Results

After an accident investigation is concluded, it's important to **s**hare the findings and lessons learned with all relevant stakeholders. Typically, the results of accident investigations (the identified causes and recommended preventive measures) should be communicated to management, supervisors, and the workforce.

a) **Management:** Senior management and department managers need to know what went wrong and what actions are needed so they can allocate resources and drive the implementation of corrective actions. They often receive formal investigation reports and will take decisions on any policy or system changes.

b) **Supervisors:** Front-line supervisors should be informed because they are responsible for day-to-day safety and will likely be implementing many of the recommended changes. Understanding the causes helps them prevent similar incidents in their teams.

c) **Workers/Employees:** Perhaps most importantly, the workers(especially those who perform similar work) must be informed of what was found and what will be done about it. Communicating the findings "in context" to workers ensures they understand how the incident happened and what measures will prevent recurrence. This can be done via toolbox talks, safety briefings, or notices. Engaging workers with the lessons learned reinforces safety awareness and shows that reporting incidents leads to improvements.

Q14. Additional Information Relevant to a Personal Injury Claim (Guard Malfunction on Drill)

When pursuing a personal injury claim for an accident caused by a **guard malfunction on a drill**, the accident-specific documentation (e.g. the accident report and investigation findings) is critical. Beyond that, other information and evidence are:

Maintenance and Inspection Records for the Drill: Documentation showing the drill's maintenance history, any recent repairs, and routine inspection logs for the machine and its guards.

Equipment Manuals and Guard Specifications: The manufacturer's manual or specifications for the drill and its safety guards. This can establish what guarding was required. If the guard was modified or not in line with standard specifications, that could be important evidence.

Previous Incident or Complaint Records: Any prior reports of issues with the drill or its guarding (near-misses, minor incidents, or complaints). A history of guard problems or similar accidents would show the employer was or should have been aware of the hazard.

Risk Assessments and Safe Work Procedures: The risk assessment for the drilling task and any safe operating procedure documents. These should outline the hazards of the drill and the required control measures (including guards). If the risk assessment didn't address the guard failing, or if it did but controls weren't implemented (e.g. no checks of the guard), that information is pertinent. Safe work method statements might indicate if workers were expected to check the guard before use, etc.

Training Records of the Injured Employee (and Others): Proof of training on that drilling machine and general machinery safety. If the injured worker (or those supervising) were not adequately trained about the machine's guard or emergency stop, it could indicate employer negligence. Conversely, if training was provided, it might shift focus to why the guard still failed.

Photographs and Physical Evidence: Photographs of the drill and the guard taken immediately after the accident, and possibly the guard itself if it broke off. Visual evidence can document the state of the machine (e.g., the guard was missing a bolt or was broken) which is powerful in a legal claim.

Witness Statements: Statements from any co-workers who saw the accident or who can attest to the regular condition of that guard. For instance, a

colleague might state “that guard had been loose for days” – crucial evidence in a claim.

Company Policies and Repair Requests: Any company policy on machinery guarding, and any internal repair tickets or emails that show the guard issue had been reported prior to the accident. A documented request for fixing the guard that wasn’t acted upon would be strong evidence of employer fault.

Regulatory Standards Compliance: Information on whether the drill’s guarding met relevant safety standards (such as OSHA or HSE requirements, or standards like ISO/EN for machinery safety). A malfunctioning or insufficient guard might indicate non-compliance with these standards, supporting the claim..

Q15. Actions to Take Following a Serious Injury at Work are:

A **serious workplace injury** triggers a sequence of emergency and management actions. The response must address immediate care, scene security, notification, and investigation. Following a serious injury, the following actions should be taken.

Ensure Emergency Care and Safety: First, make the area safe to prevent further harm, this might involve shutting down equipment or stopping work in the vicinity (this step may need to happen concurrently with aiding the victim, to ensure no one else, including rescuers, is put at risk).

Immediately attend to the injured person:provide first aid and call for professional medical help. Ensuring the casualty gets appropriate medical treatment is the top priority.

Secure the Scene: Once the injured person is taken care of, isolate or cordon off the scene of the accident. This is to preserve evidence for the investigation nothing should be moved or altered unless necessary for safety. Only authorized personnel should access the area until the investigation is completed.

Notify Family and Authorities: Inform the victim’s next of kin about the incident as soon as possible, especially if the injury is severe. This should be done with sensitivity. In many jurisdictions, serious injuries must be reported to the occupational safety authority for legal compliance. Additionally, senior management and HR should be informed internally.

Provide Support: Arrange for any necessary counseling or support services for affected employees. A serious accident can be traumatic for co-workers or witnesses; offering support (employee assistance programs, counseling, or time off) can help them cope and demonstrates employer care.

Internal and External Communication: Inform safety representatives and the wider workforce about the incident in an appropriate manner. Serious injuries often serve as a lesson, without breaching confidentiality, the organization should let workers know that an incident happened and that it’s

being investigated, and later communicate what will be done to prevent it happening again. This might be via safety meetin.

Also,notify the company's insurance provider about the incident (especially important if there could be a compensation claim) Timely notification to. insurers is often required by insurance policies.

Follow-Up Remedial Actions: . This could involve repairing or upgrading equipment, revising work procedures, retraining staff, updating risk assessments, or other measures depending on what the investigation found. It's crucial to track that these actions are completed. Update any relevant documentation (like the safe operating procedures or maintenance schedules) to reflect changes.

Review and Monitor: After everything above, monitor the situation and review the effectiveness of the actions taken. This might involve a special audit or follow-up inspection. Also, conduct a review of the emergency response to see if any improvements can be made in how such incidents are handled. Senior management should review the entire incident and response in a formal management review or safety committee meeting. If necessary, revise company policies to address any larger issues revealed by the incident.

Q16. Definition of Health and Safety Auditing

A **health and safety audit** is a systematic, independent examination of an organization's health and safety management systems and practices. In other words, it is a structured process for collecting objective information about how effective and reliable the entire Health and Safety management system is, and then assessing that against set criteria. The audit will typically review policies, procedures, risk controls, and records, and include interviews and site observations, to verify that what is written in theory is actually working in practice.

Or *"*Health and safety auditing is the structured process of collecting independent information on the efficiency, effectiveness and reliability of the total health and safety management system and drawing up plans for any corrective action necessary.

17. Differences Between Health & Safety Audits and Workplace Inspections

Health and safety audits and **workplace inspections** are both tools for monitoring performance, but they differ significantly in scope, depth, and purpose. The key differences are outlined below:

Health & Safety Audit vs Workplace Inspection

Aspect	Audit (Health & Safety Audit)	Inspection (Workplace Inspection)
Scope and Aim	Evaluates the entire health & safety management system of the organization for effectiveness and compliance. Asks: "Is our H&S system	Examines physical conditions, equipment, and work practices in a specific area or activity. Checks use/effectiveness of control measures on the ground

	adequate and working properly overall?" → Strategic in nature.	→ Operational/Tactical.
Depth and Process	A deep, thorough process: reviews documentation (policies, procedures, records), interviews personnel at different levels, and observes practices across the organization. Systematically checks compliance with standards.	A focused, quick check: mainly direct observations (with a checklist). Minimal paperwork review. Interviews limited to workers/supervisors on-site.
Duration & Frequency	Lengthy and periodic: can take days/weeks, conducted infrequently (e.g., annually). Requires planning, resources, and sometimes external auditors.	Short and frequent: minutes/hours, carried out daily, weekly, or monthly. Requires only inspector's time and checklist, with little advance planning.
Output (Report)	Produces a comprehensive report on strengths/weaknesses of the H&S system. Highlights non-conformities, includes an action plan for systemic improvements.	Produces a short report or checklist noting hazards or non-compliances and listing corrective actions. Focus is on fixing specific, immediate issues.
Purpose and Impact	Strategic improvement: improves the overall H&S management system and ensures long-term compliance/effectiveness. Influences high-level policies/programs and future objectives. Often needed for certification/governance.	Operational control: prevents accidents by correcting unsafe conditions/behaviours immediately. Deals with the here-and-now. Main impact at shop-floor level (feeds into system review).

Q18. Purpose of Reviewing Health and Safety Performance

The purpose of such a review is to ensure that all the plans and arrangements for health and safety are actually effective and if they are not, to identify what needs to be improved. Essentially, a performance review asks: *"Have we achieved what we set out to do in our health and safety policy and objectives? Are our risk controls and programs successful?"*

Key aims of reviewing H&S performance include:

Verify Effectiveness: Confirm that the company's health and safety arrangements, standards, and systems are working as intended (e.g. training programs are yielding safe behaviors, inspections and maintenance are controlling risks, etc.).

Identify Shortcomings: Detect any deficiencies or failures in the health and safety management system.

Drive Continuous Improvement: Where performance is lacking, the review will lead to corrective actions or new initiatives. The idea is to continually

improve; by reviewing performance, organizations can update their strategies (perhaps setting new targets or changing procedures) to address any weaknesses.

Ensure Compliance: A formal performance review also checks compliance with legal requirements and internal standards. If laws or regulations have changed, the review ensures the organization adapts accordingly.

Inform Management Decisions: The outcome of performance reviews feeds into management discussions and decisions. It helps leadership allocate resources where they are most needed to improve safety (for instance, investing in new equipment if an old one is causing incidents, or arranging additional training if certain types of accidents indicate competency gaps).

In summary, the purpose of reviewing H&S performance is to take a strategic look at "how are we doing, and what can we do better" in terms of safety. This closes the loop of the Plan-Do-Check-Act cycle in safety management, by checking results and acting on them.

Q19. Participants in Occupational Health and Safety Management System Reviews

A review of the occupational health and safety management system (OHSMS) is often called a management review. It should involve the leadership of the organization as well as key stakeholders in the safety system. Specifically, those who should take part include:

Senior Management: Top executives and senior managers must lead and be actively involved in the review. Since they set H&S policy and objectives, they need to evaluate if the system is suitable and effectively implemented. Senior management's role is to ensure the OHSMS is achieving the organization's safety goals and remains aligned with business priorities. They also have authority to make decisions on changes and resources, so their presence is essential. (For example, a Plant Manager or Director would typically chair an annual H&S performance review meeting.)

Middle Management and Supervisors: Managers of departments or divisions and front-line supervisors should participate or at least provide input. They have hands-on knowledge of how the safety programs work in practice and can report on performance in their areas. Involving them ensures that the review considers operational realities and that those who must implement changes are on board.

Health and Safety Specialists: The organization's safety officer, HSE advisor, or occupational health specialists should be part of the review team or present their reports. These professionals bring expertise on regulatory compliance and technical aspects of the OHSMS. They usually compile the performance

data (accident statistics, audit findings, etc.) that are discussed in the review, and can advise on interpretation and next steps.

Worker Representatives: It is often beneficial to involve employee representatives;for instance, safety representatives or members of the health and safety committee,in the management review process Workers' input ensures their concerns are heard at a high level and adds credibility to the review. In some frameworks (like ISO 45001 or in unionized environments), involving workers in reviews is a requirement or best practice. Worker reps can convey the workforce's perspective on what is and isn't working in the H&S management system.

(Possibly) Other Stakeholders: Depending on the scope, the review might also solicit information from others like maintenance managers (for equipment safety issues), HR (for training and occupational health stats), or external experts if the system is audited externally. If the H&S committee meeting serves as part of the review, then its members (which cover various functions) are participants by default.

Q20. Frequency of OHS Management System Reviews

The optimal frequency for formal reviews of the occupational health and safety management system depends on the **nature of the organization – its risk level and the pace of change** in its operations. However, as a general guideline:

At least Annual at the Top Level: A comprehensive management review by senior management is commonly conducted once a year. An annual review is typical to ensure that the H&S policy, objectives, and overall performance are assessed and updated in line with any changes over the year. High-level reviews at board or executive level are often aligned with annual business planning cycles or required by standards like ISO 45001.

More Frequent Interim Reviews: Many organizations carry out quarterly or monthly reviews at lower levels. For example, at a divisional or departmental level, there might be quarterly H&S performance meetings to review local incidents, inspection results, and progress on safety action plans. At an operational site or team level, there could be even more frequent check-ins (like monthly safety meetings led by local management) to track shorter-term performance indicators.

Based on Risk and Change: If the workplace has higher risks or is undergoing significant changes, reviews should be more frequent. For instance, a construction project might have monthly project safety reviews due to the evolving hazards. Conversely, a low-risk static office might suffice with an annual review. The level of inherent risk (e.g., chemical manufacturing vs. a retail store) and rate of change (how often new processes, equipment, or personnel changes occur) are factors – a medium-risk, fairly stable workplace might adopt a routine like monthly local reviews, quarterly middle-management reviews, and annual corporate review,

Triggered Reviews: In addition to scheduled intervals, extraordinary reviews should take place after major incidents or significant changes. If there's a serious accident or a major legislative change, for example, management might convene a special review rather than waiting for the periodic cycle.

To illustrate a typical frequency model (for a moderate-risk organization):

Monthly: Local level (site or department) reviews by supervisors/managers to discuss recent accidents, inspection results, etc.

Quarterly: Division or business unit reviews by mid-level management, summarizing trends and ensuring actions from earlier meetings are progressing

Annually Organization-wide review by senior management (and possibly the Board), looking at the overall H&S performance, policy, and strategy.

In summary, formal top-level reviews at least once per year are expected, but supplemental reviews quarterly or more often can be appropriate to keep the pulse on safety performance. The goal is to have a cadence that is responsive to the organization's needs, ensuring issues are identified and corrected in a timely manner.

Q21. Documented Outputs from a Management Review (Evidence of Effectiveness)

After completing a health and safety management review, certain outputs should be **documented and kept as records**. These records both provide a summary of what was decided and serve as evidence that the review process is effective. Typical outputs from the management review that need to be documented include

Minutes of the Review Meeting: A written record of the discussions and decisions from the review. The minutes should capture who attended, the topics covered (e.g., review of objectives, audit results, incident trends), and any conclusions or agreements reached. Meeting minutes provide proof that a review took place and what was considered.

Revisions to H&S Policy or Objectives: If the review leads to changes in the organization's health and safety policy or updates to the H&S objectives, those changes should be documented. This could be an updated policy document or a set of new objectives/targets for the next period. Keeping these on record shows that the review resulted in concrete adjustments to the H&S strategic direction.

Action Plans with Responsibilities and Deadlines: Specific corrective actions or improvement actions decided in the review must be recorded, typically in an action plan or table For each action, document **what** needs to be done, **who** is responsible for it, and the **target date** for completion. For example, if the review noted a need for more training, an action might be "Develop and deliver manual handling training to warehouse staff –

Responsible: H&S Manager by March 31". This ensures accountability and enables follow-up.

Follow-up Review Date for Actions: It's useful to note when or how the completion of actions will be reviewed. For instance, an output might include a statement that progress on the actions will be checked in the next quarterly meeting, or a specific date to review a particularly critical action. Documenting the intended follow-up ensures that corrective measures aren't forgotten.

Areas of Emphasis for Future Audits/Inspections: The review might identify certain areas that need special attention moving forward. For example, if an increase in ergonomic injuries was noted, the management review might decide that **future internal audits should focus on ergonomics** or that inspections should pay extra attention to that issue. Documenting this means the next audit/inspection plans will incorporate these focus areas, evidencing a continuous improvement loop.

All these outputs should be **maintained as records**. They demonstrate that the management review was conducted and is driving improvements (which is often checked in external audits or by regulators). In frameworks like ISO 45001, maintaining documented information of management reviews is a requirement, as it proves top management's involvement and the effectiveness of the review process. For the organization, these documents are a road map for what to do after the review – they capture the commitments made and allow tracking of progress, thereby closing the loop in the "Check-Act" part of the management system

Reference:NEBOSH course material.

engineering-tracks.com

stockwellsafety.com

comcare.gov.au