2.

```
Router>en
Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip add 192.168.0.1 255.255.255.0
Router(config-if)#no shutdown


Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#ip dhcp excluded-address 192.168.0.1 192.168.0.5
Router(config)#ip dhcp pool companyname
Router(dhcp-config)#network 192.168.0.0 255.255.255.0
Router(dhcp-config)#default-router 192.168.0.1
Router(dhcp-config)#domain-name companyname
Router(dhcp-config)#dns-server 192.168.0.2
Router(dhcp-config)#exit
Router(config)#
```

3.

PC0 — □ ✕

Physical   Config   Desktop   Programming   Attributes

Web Browser   X

< | > | URL http://company.com   Go   Stop

Cisco Packet Tracer

Welcome to Cisco Packet Tracer. Opening doors to new opportunities. Mind Wide Open.

Quick Links:
A small page
Copyrights
Image page
Image

☐ Top

4.

```
C:\>ping 192.168.0.3

Pinging 192.168.0.3 with 32 bytes of data:

Reply from 192.168.0.3: bytes=32 time<1ms TTL=128
Reply from 192.168.0.3: bytes=32 time<1ms TTL=128
Reply from 192.168.0.3: bytes=32 time<1ms TTL=128
Reply from 192.168.0.3: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.0.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms
```