



Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up

Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa0/1
Switch(config-if)#sw ac vl 10
      ^
% Invalid input detected at '^' marker.

Switch(config-if)#sw ac vl 10
% Access VLAN does not exist. Creating vlan 10
Switch(config-if)#no sh
Switch(config-if)#int fa0/2
Switch(config-if)#sw ac vl 20
% Access VLAN does not exist. Creating vlan 20
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#int gi0/1
Switch(config-if)#sw mode trunk
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#int gi0/1
Switch(config-if)#sw mode trunk
Switch(config-if)#
Switch(config-if)#exit
Switch(config)#interface FastEthernet0/1
Switch(config-if)#
```

Copy Paste

Top

Root

Realtime Simulation

Type Color Time(sec) Periodic Num Edit







