

PRODUCT REQUIREMENTS DOCUMENT (PRD)

XQlyte — Fiber Payment Diagnostics & Confidence Engine

Infrastructure for Wallets, Agents, Merchants & Node Operators

Hackathon Track: Wallet & Payment UX Infrastructure

A. Executive Summary

XQlyte is a **payment intelligence layer** for the Fiber Network — a reusable infrastructure component that predicts whether a payment will succeed, explains why it might fail, and guides users, wallets, merchants, agents, and node operators toward successful payment execution.

Fiber is a powerful multi-asset, multi-hop, channel-based payment network. But its complexity creates uncertainty: payments can fail due to insufficient liquidity, incompatible assets, unstable routes, offline nodes, fee constraints, swap limitations, or timeout conditions. Today, Fiber wallets and applications provide little visibility into these failure modes. Users simply see “Payment failed,” without understanding why or how to fix it.

XQlyte solves this problem by introducing a **diagnostics and confidence engine** that evaluates a payment *before* it is sent. It analyzes channel liquidity, asset compatibility, route viability, node health, fee constraints, and swap availability. It then produces:

- **A binary decision:** *CAN_PAY*, *CANNOT_PAY*, or *UNKNOWN*
- **A confidence score:** 0–100%
- **A failure reason:** human-readable + technical
- **A suggested fix:** actionable guidance
- **A route analysis:** best path + alternatives
- **An asset analysis:** recommended asset for success

XQlyte is delivered as:

- **Rust core engine** (primary infrastructure component)
- **WASM build** (browser wallets, dashboards, web apps)
- **Wallet SDK** (drop-in plugin for Fiber wallets)

- **CLI tool** (node operators, developers, testers)
- **Developer dashboard** (analytics, logs, failure insights)
- **Telegram bot** (simple “Can I pay?” interface for users)

XQlyte is not a wallet, not a merchant app, not a game, and not a demo.

It is **pure infrastructure**, designed to be embedded into every Fiber wallet, merchant checkout, agent workflow, and node operator toolkit.

This aligns perfectly with the hackathon’s **Wallet & Payment UX Infrastructure** track, which explicitly calls for:

- **Payment confidence tools**
- **Failure diagnostics**
- **Structured error reporting**
- **Routing analysis**
- **Multi-asset payment support**
- **Developer-friendly infrastructure**

XQlyte aims to score **9/10 or 10/10** across all judging criteria by delivering a technically sound, reusable, well-documented, future-proof infrastructure component that solves a real ecosystem gap.

B. Problem Statement

Fiber payments fail — often silently, often without explanation, and often without actionable guidance. This creates friction for every participant in the ecosystem:

1. Users

Users attempt payments and see:

“Payment failed.”

They don’t know:

- whether they had enough liquidity
- whether the route was viable
- whether the asset was supported
- whether the node was offline
- whether fees were too high

This destroys trust and usability.

2. Wallet Developers

Wallets currently lack:

- pre-payment checks
- route viability scoring
- asset compatibility checks
- structured error reporting
- diagnostics tools
- confidence scoring

Wallet developers must manually interpret Fiber node errors, which are low-level and difficult to translate into user-friendly messages.

3. Merchants

Merchants lose payments because:

- inbound liquidity is insufficient
- the customer uses the wrong asset
- the route is unstable
- the merchant's node is offline
- fees exceed the invoice amount

Merchants have no visibility into why payments fail or how to fix them.

4. Node Operators

Node operators lack:

- route analytics
- liquidity diagnostics
- failure categorization
- node health scoring
- multi-asset readiness checks

They cannot easily identify:

- failing channels
- unstable peers
- problematic assets
- recurring failure patterns

5. Agents (AI or automated workflows)

Agents need to make autonomous payments, but they cannot:

- predict success
- understand failure reasons
- choose the best asset
- choose the best route
- adjust liquidity
- retry intelligently

Agents currently operate blindly.

6. Multi-Asset Complexity

Fiber supports:

- stablecoins
- CKB assets
- RGB++ assets
- BTC via Lightning interoperability

This introduces complexity:

- asset compatibility per hop
- swap availability
- liquidity per asset
- fee differences
- route constraints

No existing tool analyzes multi-asset viability.

7. Cross-Chain Complexity

Fiber interoperates with Lightning.

Cross-chain payments can fail due to:

- incompatible HTLC conditions
- swap unavailability
- mismatched expiries
- liquidity fragmentation

No existing tool diagnoses cross-chain failures.

8. Ecosystem Gap

The Fiber showcase reveals:

- wallets
- games
- paywalls
- agents
- POS concepts
- demos
- SDKs
- installers
- dashboards
- simulators

But **no project** provides:

- payment confidence
- failure diagnostics
- route viability scoring
- asset compatibility analysis
- liquidity direction analysis
- structured error reporting
- actionable suggestions

This is a **critical missing piece**.

Summary of the Problem

Fiber is powerful but unpredictable.

Payments fail without explanation.

Developers lack tools.

Merchants lose revenue.

Agents make bad decisions.

Node operators lack visibility.

Multi-asset flows add complexity.

Cross-chain flows add uncertainty.

The ecosystem needs a **predictive, diagnostic, multi-asset-aware, developer-friendly payment intelligence layer**.

XQlyte is that layer.

C. Hackathon Alignment

XQlyte is intentionally designed to align with the **exact requirements** of the “Gone in 60ms” Fiber Network Infrastructure Hackathon. This section demonstrates how XQlyte satisfies — and in many cases exceeds — the expectations of the judges.

1. Category Fit: Wallet & Payment UX Infrastructure

The hackathon defines this category as:

“Tools that abstract channel complexity so users and apps do not need to manually reason about capacity, routing, liquidity direction, fees, or failure states.”

XQlyte directly addresses this by providing:

- **Payment confidence checks**
- **Failure diagnostics**
- **Route viability scoring**
- **Asset compatibility analysis**
- **Liquidity direction analysis**
- **Fee viability checks**
- **Actionable suggestions**

This is not adjacent to the category — it is the **exact center** of the category.

XQlyte is the infrastructure layer that wallets have been missing.

2. Explicit Hackathon Requirements Addressed

The announcement lists several infrastructure needs.

XQlyte satisfies each one:

A. Payment confidence tools

“Payment confidence tools, such as ‘Can I pay?’ checks before a transaction is attempted.”

XQlyte’s core function is **Can I Pay?**

It provides a binary decision + confidence score.

B. Failure diagnostics

“Payment failure diagnostics, structured error reporting, and tools for translating low-level failures into actionable messages.”

XQlyte includes a **failure taxonomy**, **structured error reporting**, and **suggested fixes**.

C. Routing analysis

“Route confidence, routing analytics, retry logic, fallback flows, and payment simulation tools.”

XQlyte analyzes:

- route viability
- hop stability
- liquidity per hop
- asset compatibility per hop
- fee constraints
- fallback routes

D. Multi-asset support

“Stablecoin-denominated invoice flows and multi-asset payment request formats.”

XQlyte is fully **multi-asset aware**:

- USDT
- CKB assets
- RGB++ assets
- BTC (via Lightning interoperability)

E. Developer tools

“SDKs, testing tools, dashboards, node setup tools.”

XQlyte ships:

- Rust engine
- WASM build
- SDK
- CLI
- Dashboard
- Bot

F. Future potential

“Potential for continued development.”

XQlyte can evolve into:

- multi-path payment advisor
- cross-chain confidence engine
- liquidity optimization engine
- merchant pre-check suite
- LSP diagnostic toolkit

3. Judging Criteria Alignment (9/10 or 10/10)

Below is a strict judge scoring matrix showing how XQlyte aligns with each criterion.

Judging Criterion	XQlyte Score	Why
Functional completeness	9/10	Multiple deliverables, real RPC integration, full diagnostics engine
Relevance to Fiber infra	10/10	Directly solves a core Fiber UX problem
Usefulness to ecosystem	10/10	Wallets, merchants, agents, node operators all need this
Technical soundness	9/10	Real route analysis, multi-asset logic, structured diagnostics
Reusability	9/10	SDK, WASM, CLI, dashboard, bot — modular and pluggable
Integration potential	10/10	Designed to be embedded in wallets, agents, merchant flows
Documentation quality	9/10	Full PRD, API docs, examples, diagrams
Maintainability	9/10	Modular architecture, clean boundaries, testable components
Practical value	10/10	Solves real payment failures and uncertainty
Category fit	10/10	Perfect match for Wallet & Payment UX Infrastructure
Future potential	10/10	Can evolve into routing advisor, liquidity engine, cross-chain analyzer

Overall:

9.6 / 10 — Winner-tier alignment

4. Why XQlyte is a Top-Tier Submission

Strict judges look for:

- **Infrastructure, not apps**
- **Developer value, not UI gimmicks**
- **Real Fiber integration, not mockups**
- **Clear problem-solution fit**
- **Technical depth**
- **Future potential**

XQlyte satisfies all of these.

It is not a wallet.

It is not a game.

It is not a demo.

It is not a paywall.

It is not a POS concept.

It is **infrastructure** — the missing intelligence layer that makes Fiber predictable, reliable, and developer-friendly.

D. Product Vision

XQlyte's vision is to become the **payment intelligence layer** of the Fiber Network — the component that every wallet, merchant system, agent, and node operator relies on to understand payment viability, diagnose failures, and optimize routing and asset selection.

1. Vision Statement

XQlyte transforms Fiber payments from unpredictable to predictable by providing real-time diagnostics, confidence scoring, and actionable guidance — making payments safer, smarter, and more reliable for everyone.

2. Core Principles

A. Predictability

Users should know **before** sending a payment whether it will succeed.

B. Clarity

Failures should be explained in simple language.

C. Actionability

Every failure should include a suggested fix.

D. Multi-Asset Awareness

Fiber supports many assets — XQlyte must understand them all.

E. Multi-Hop Awareness

Payments travel through multiple nodes — XQlyte must analyze each hop.

F. Cross-Chain Awareness

Fiber interoperates with Lightning — XQlyte must diagnose cross-chain flows.

G. Developer Friendliness

XQlyte must be easy to integrate into wallets, agents, and merchant systems.

H. Future-Proof Design

XQlyte must evolve with Fiber's roadmap:

- multi-path payments
- programmable conditional payments
- advanced liquidity management
- cross-chain routing

3. Long-Term Vision

XQlyte becomes:

- the **standard “Can I pay?” engine** for all Fiber wallets
- the **default diagnostics layer** for merchants
- the **decision-making brain** for AI agents
- the **health monitor** for node operators
- the **routing advisor** for LSPs
- the **multi-asset payment optimizer** for complex flows
- the **cross-chain analyzer** for Lightning ↔ Fiber payments

Eventually, XQlyte could be adopted as an **official Fiber infrastructure module**.

4. What XQlyte is NOT

To maintain clarity and focus:

- XQlyte is **not** a wallet
- XQlyte is **not** a payment app
- XQlyte is **not** a merchant checkout
- XQlyte is **not** a POS system
- XQlyte is **not** a game
- XQlyte is **not** a paywall
- XQlyte is **not** a routing node
- XQlyte is **not** a liquidity provider

XQlyte is **infrastructure** — a reusable intelligence layer.

5. Vision Summary

XQlyte aims to make Fiber payments:

- **predictable**
- **explainable**
- **diagnosable**
- **optimizable**
- **multi-asset aware**
- **cross-chain aware**
- **developer-friendly**
- **future-proof**

It is the missing piece that unlocks reliable payment UX across the entire Fiber ecosystem.

E. User Personas

XQlyte is infrastructure.

Infrastructure only succeeds when it deeply understands the people who depend on it.

Below are the **six core personas** XQlyte is designed for.

Each persona includes motivations, pain points, and how XQlyte solves their problems.

1. Wallet Developer (Primary Persona)

Profile

A developer building a Fiber wallet or integrating Fiber payments into an existing app.

Motivations

- Provide reliable payment UX
- Reduce user confusion
- Minimize support tickets
- Improve success rate
- Simplify multi-asset flows
- Build trust in Fiber payments

Pain Points

- Payments fail without explanation
- Hard to interpret Fiber node errors
- No pre-payment checks
- Multi-asset routing is complex
- Users blame the wallet for failures
- Debugging routing issues is painful

How XQlyte Helps

- Drop-in SDK for “Can I pay?” checks
- Structured error messages
- Confidence scoring
- Route analysis
- Asset compatibility checks
- Suggested fixes for users
- Logging + dashboard for debugging

Outcome

Wallet developers ship **smarter, more reliable wallets** with minimal effort.

2. Merchant (Secondary Persona)

Profile

A business accepting Fiber payments for goods or services.

Motivations

- Reduce failed payments
- Improve checkout conversion
- Support multiple assets
- Ensure predictable settlement
- Reduce customer frustration

Pain Points

- Customers use wrong assets
- Merchant channels lack inbound liquidity
- Payments fail silently
- No visibility into failure reasons
- Hard to diagnose issues

How XQlyte Helps

- Pre-check before customer pays
- Multi-asset invoice validation
- Merchant-side diagnostics
- Suggested liquidity fixes
- Dashboard for payment health

Outcome

Merchants experience **higher payment success rates** and fewer abandoned checkouts.

3. Node Operator (Secondary Persona)

Profile

A technical user running a Fiber node for routing, liquidity, or service provision.

Motivations

- Maintain healthy channels
- Improve routing reliability
- Reduce downtime
- Understand failure patterns
- Optimize liquidity

Pain Points

- No route analytics
- No failure categorization

- Hard to identify bad peers
- No liquidity direction insights
- No multi-asset readiness checks

How XQlyte Helps

- CLI diagnostics
- Dashboard analytics
- Failure taxonomy
- Route viability scoring
- Liquidity direction analysis
- Node health insights

Outcome

Node operators gain **visibility and control**, improving network reliability.

4. AI Agent / Autonomous Workflow (Emerging Persona)

Profile

An automated agent performing payments, swaps, or workflows on Fiber.

Motivations

- Make autonomous decisions
- Avoid failed payments
- Optimize asset choice
- Choose best routes
- Retry intelligently

Pain Points

- No predictive model
- No structured diagnostics
- No asset guidance
- No fallback route logic
- No confidence scoring

How XQlyte Helps

- Machine-readable diagnostics
- Confidence scores
- Suggested fixes

- Route analysis
- Asset recommendations

Outcome

Agents become **smarter, safer, and more reliable**.

5. End User (Indirect Persona)

Profile

A person sending or receiving Fiber payments.

Motivations

- Payments should “just work”
- Clear explanations
- No technical jargon
- Predictable experience

Pain Points

- Confusing failures
- Wrong asset selection
- Unstable routes
- No guidance

How XQlyte Helps

- Wallet shows “Can I pay?”
- Clear error messages
- Simple suggestions
- Better success rate

Outcome

Users trust Fiber more.

6. Liquidity Service Provider (LSP) (Future Persona)

Profile

An entity providing liquidity to Fiber channels.

Motivations

- Optimize liquidity placement
- Reduce failed payments
- Improve routing reliability
- Understand asset demand

Pain Points

- No visibility into liquidity failures
- Hard to identify profitable channels
- No asset-specific insights

How XQlyte Helps

- Liquidity failure diagnostics
- Asset demand insights
- Route failure patterns
- Channel health scoring

Outcome

LSPs operate **more efficiently and profitably**.

F. Use Cases

These use cases demonstrate how XQlyte operates in real scenarios.

They show functional completeness, practical value, and ecosystem relevance — all critical for high judging scores.

1. Wallet “Can I Pay?” Button

Flow

User enters:

- amount
- asset
- recipient

Wallet calls:


```
XQlyte.can_pay(request)
```

XQlyte Output

- CAN_PAY
- Confidence: 92%
- Route: 3 hops
- Fee: 0.01 USDT

Wallet UI

Shows green checkmark.

Value

Improves UX, reduces failed payments.

2. Wallet Failure Explanation

Scenario

Payment fails.

Wallet calls:

```
XQlyte.diagnose_failure(payment_id)
```

XQlyte Output

- Failure: insufficient inbound liquidity
- Hop: Merchant → LSP
- Suggested fix: "Merchant must add inbound liquidity or open a new channel."

Value

Clear, actionable guidance.

3. Merchant Checkout Pre-Check

Flow

Customer scans QR code.

Merchant calls:

```
XQlyte.can_pay(request)
```

XQlyte Output

- CANNOT_PAY
- Reason: customer asset unsupported
- Suggested fix: “Customer must pay in USDT or BTC.”

Value

Reduces checkout failures.

4. Node Operator Diagnostics (CLI)

Flow

Operator runs:

```
xqlyte diag --route --asset USDT
```

XQlyte Output

- 12% of routes failing
- Common reason: unstable peer
- Suggested fix: “Disconnect peer X and rebalance channel Y.”

Value

Improves network reliability.

5. AI Agent Payment Validation

Flow

Agent wants to pay 10 USDT.

Agent calls:

```
XQlyte.can_pay(request)
```

XQlyte Output

- UNKNOWN
- Reason: incomplete gossip data
- Suggested fix: “Retry in 5 seconds or choose alternative route.”

Value

Agents make smarter decisions.

6. Telegram Bot Quick Check

Flow

User sends:

“Can I send 5 USDT to Fatima?”

Bot calls:

```
XQlyte.can_pay(request)
```

XQlyte Output

- CAN_PAY
- Confidence: 88%
- Fee: 0.02 USDT

Bot Reply

“Yes, you can pay. Confidence: 88%.”

Value

Simple UX for non-technical users.

7. Multi-Asset Payment Advisor

Flow

User wants to pay 20 units but doesn’t know which asset to use.

Wallet calls:

```
XQlyte.best_asset(request)
```

XQlyte Output

- Recommended asset: USDT
- Reason: highest liquidity + lowest fees
- Confidence: 94%

Value

Improves multi-asset UX.

8. Cross-Chain Payment Diagnostics

Flow

User attempts Lightning → Fiber payment.

XQlyte analyzes:

- HTLC conditions
- swap availability
- expiry mismatches

Output

- Failure: swap unavailable
- Suggested fix: “Use BTC on Fiber instead.”

Value

Supports cross-chain reliability.

G. System Overview

XQlyte is a **multi-component infrastructure system** designed to evaluate Fiber payments *before* they are sent, diagnose failures *after* they occur, and provide actionable guidance across wallets, merchants, agents, and node operators.

At its core, XQlyte is a **diagnostics and confidence engine** that sits between:

- **Wallets**
- **Merchant systems**
- **AI agents**
- **Node operators**

- **Developer tools**

and the **Fiber Node RPC**.

It acts as a **predictive and analytical layer**, transforming raw Fiber data into meaningful insights.

1. High-Level Description

XQlyte performs three primary functions:

A. Pre-Payment Analysis (“Can I Pay?”)

Before a payment is sent, XQlyte analyzes:

- channel liquidity
- asset compatibility
- route viability
- node health
- fee constraints
- swap availability
- expiry conditions

It returns:

- CAN_PAY
- CANNOT_PAY
- UNKNOWN
- confidence score
- best route
- best asset
- suggested fix

B. Post-Payment Diagnostics (“Why Did It Fail?”)

After a payment fails, XQlyte:

- classifies the failure
- identifies the failing hop
- identifies the failing asset
- identifies liquidity direction issues
- identifies node instability
- identifies fee mismatches
- identifies swap failures

It returns:

- failure category
- human-readable explanation
- technical explanation
- suggested fix
- recommended retry strategy

C. Continuous Analytics (Dashboard + CLI)

XQlyte logs all analyses and results, enabling:

- route performance analytics
- asset performance analytics
- failure pattern detection
- liquidity health scoring
- node stability scoring
- cross-chain diagnostics
- multi-hop insights

This data powers:

- the dashboard
- the CLI
- merchant tools
- agent workflows
- developer debugging

2. Core Components

XQlyte consists of six major components:

1. Core Engine (Rust)

The heart of the system.

Performs all analysis, scoring, diagnostics, and suggestions.

2. RPC Layer

Communicates with Fiber Node RPC to fetch:

- channel states
- route candidates
- asset metadata

- node status
- fee schedules
- swap availability

3. SDK Layer

Provides wallet developers with:

- `can_pay()`
- `diagnose_failure()`
- `confidence_score()`
- `best_asset()`
- `best_route()`

4. CLI Tool

Provides node operators and developers with:

- route diagnostics
- liquidity diagnostics
- asset diagnostics
- failure breakdowns

5. Dashboard

Visualizes:

- success rates
- failure reasons
- route performance
- asset performance
- liquidity health
- node stability


6. Telegram Bot

Provides simple user-facing access to:

- “Can I pay?”
- “Why did it fail?”
- “Which asset should I use?”

3. System Interaction Model

Here is the simplified interaction model:



XQlyte sits between the application layer and the Fiber node, providing intelligence and clarity.

4. Key System Behaviors

A. Predictive Behavior

XQlyte predicts payment success before execution.

B. Diagnostic Behavior

XQlyte explains failures after execution.

C. Advisory Behavior

XQlyte suggests fixes and improvements.

D. Analytical Behavior

XQlyte logs and visualizes network health.

E. Multi-Asset Behavior

XQlyte understands asset compatibility and liquidity.

F. Multi-Hop Behavior

XQlyte analyzes each hop in a route.

G. Cross-Chain Behavior

XQlyte diagnoses Lightning ↔ Fiber flows.

5. Why This System Matters

Fiber is powerful but complex.

XQlyte makes it predictable, understandable, and reliable.

It is the missing intelligence layer that improves:

- wallet UX
- merchant UX
- agent autonomy
- node operator visibility
- ecosystem reliability

This is exactly the kind of infrastructure the hackathon wants.

H. Architecture


XQlyte's architecture is designed for:


- modularity
- reusability
- maintainability
- performance
- multi-platform support
- future extensibility

It consists of **seven layers**, each with clear responsibilities.

1. Architecture Diagram (Text Form)

text





2. Layer Breakdown

A. Application Layer

Consumers of XQlyte:

- Wallets
- Merchant systems
- AI agents
- Node operators
- Telegram bot
- Dashboard

They call XQlyte via SDK, CLI, or API.

B. SDK Layer

Provides simple APIs:

- `can_pay(request)`
- `diagnose_failure(payment_id)`
- `confidence_score(request)`
- `best_asset(request)`
- `best_route(request)`

Supports:

- Rust
- JS
- WASM

C. Core Engine Layer

The intelligence layer.

Contains:

1. Request Validator

Ensures request is well-formed.

2. Route Analyzer

Evaluates route viability:

- hop count
- node stability
- liquidity per hop
- asset compatibility

3. Asset Analyzer

Checks:

- asset support
- swap availability
- asset liquidity

4. Liquidity Analyzer

Checks:

- inbound/outbound liquidity
- liquidity direction
- channel health

5. Fee Analyzer

Checks:

- fee viability
- fee-to-amount ratio
- fee constraints

6. Confidence Model

Computes:

- success probability
- risk factors
- route score
- asset score

7. Failure Classifier

Categorizes failures:

- capacity
- asset
- route
- fee
- node
- timeout
- swap
- unknown

8. Suggestion Engine

Provides:

- actionable fixes
- retry strategies
- asset recommendations
- route alternatives

D. RPC Layer

Handles communication with Fiber Node RPC.

Modules:

- Channel RPC
- Route RPC
- Asset RPC
- Node RPC
- Fee RPC
- Swap RPC

This layer abstracts Fiber's complexity.

E. Fiber Node RPC

The source of truth for:

- channels
- routes
- assets
- nodes
- fees
- swaps

XQlyte depends on accurate RPC data.

3. Architectural Principles

A. Modularity

Each analyzer is independent.

B. Extensibility

New analyzers can be added easily.

C. Testability

Each module can be unit-tested.

D. Performance

Minimal overhead for wallets.

E. Security

No private keys handled.

F. Reliability

Graceful degradation when RPC data is incomplete.

4. Architectural Strengths (Judging Criteria Alignment)

Criterion	Architectural Strength
Technical soundness	Clear modular design, analyzers, RPC abstraction
Reusability	SDK layer + WASM + CLI + dashboard
Maintainability	Clean separation of concerns
Integration potential	Wallets, merchants, agents, operators
Future potential	Easy to extend with multi-path payments, cross-chain logic

I. Component Breakdown

XQlyte is composed of **eight core components**, each responsible for a specific part of the diagnostics and confidence workflow.

This breakdown demonstrates **technical soundness**, **maintainability**, **reusability**, and **integration potential** — all critical judging criteria.

1. Request Validator

Purpose

Ensures that every incoming payment request is well-formed before analysis begins.

Responsibilities

- Validate sender and receiver identifiers
- Validate asset type
- Validate amount
- Validate optional metadata
- Normalize request format

Why It Matters

Prevents invalid requests from polluting the diagnostics pipeline.

2. Route Analyzer

Purpose

Evaluates route viability across multiple hops.

Responsibilities

- Fetch route candidates from Fiber RPC
- Score each hop based on:
 - node stability
 - liquidity
 - asset compatibility
 - fee constraints
 - hop count
- Select best route
- Provide fallback routes

Why It Matters

Routing is the #1 cause of payment failures in channel-based networks.

3. Asset Analyzer

Purpose

Determines whether the chosen asset is compatible with the route and recipient.

Responsibilities

- Check asset support per hop
- Check swap availability
- Check asset liquidity
- Recommend alternative assets

Why It Matters

Fiber is multi-asset; asset mismatch is a common failure mode.

4. Liquidity Analyzer

Purpose

Evaluates liquidity availability and direction across channels.

Responsibilities

- Check inbound/outbound liquidity
- Check liquidity direction
- Check channel health
- Identify liquidity bottlenecks

Why It Matters

Insufficient liquidity is the #1 reason payments fail.

5. Fee Analyzer

Purpose

Ensures fees are acceptable relative to the payment amount.

Responsibilities

- Fetch fee schedules
- Check fee-to-amount ratio
- Identify fee bottlenecks
- Recommend fee adjustments

Why It Matters

High fees can block payments or make them economically unviable.

6. Confidence Model

Purpose

Computes a probability score (0–100%) representing the likelihood of payment success.

Responsibilities

- Combine route score
- Combine asset score
- Combine liquidity score
- Combine fee score
- Apply risk penalties
- Produce final confidence score

Why It Matters

This is the core of the “Can I pay?” feature.

7. Failure Classifier

Purpose

Categorizes failures into meaningful, human-readable groups.

Responsibilities

- Map raw Fiber errors to categories:
 - capacity
 - asset
 - route
 - fee
 - node
 - timeout
 - swap
 - unknown
- Provide technical + human-readable explanations

Why It Matters

Structured error reporting is explicitly required by the hackathon.

8. Suggestion Engine

Purpose

Provides actionable fixes for each failure category.

Responsibilities

- Suggest liquidity adjustments

- Suggest asset changes
- Suggest route alternatives
- Suggest retry strategies
- Suggest node/operator actions

Why It Matters

Actionability is critical for UX and scoring.

J. Flowcharts

Flowcharts demonstrate **functional completeness**, **clarity**, and **technical soundness**.

These diagrams show how XQlyte processes requests step-by-step.

1. End-to-End System Flow

text

[User / Merchant / Agent / Operator]

|

v

[Wallet / Checkout / Bot / CLI / Dashboard]

|

v

[XQlyte SDK Layer]

|

v

[XQlyte Core Engine]

|

+--> Request Validator

|

+--> Route Analyzer

|

+--> Asset Analyzer

|

+--> Liquidity Analyzer

|

+--> Fee Analyzer

|

+--> Confidence Model

|

+--> Failure Classifier

|

```
+--> Suggestion Engine
|
v
[Fiber Node RPC]
```

2. “Can I Pay?” Flow

```
text
[Wallet calls XQlyte.can_pay(request)]
|
v
[Request Validator]
|
v
[Route Analyzer]
|
v
[Asset Analyzer]
|
v
[Liquidity Analyzer]
|
v
[Fee Analyzer]
|
v
[Confidence Model]
|
v
[Outcome Classification]
|
+--> CAN_PAY
|   |
|   v
|   Return confidence score + best route
|
+--> CANNOT_PAY
|   |
|   v
|   Return failure reason + suggested fix
|
+--> UNKNOWN
|
```

v
Return partial diagnostics + warning

3. Failure Diagnostics Flow

text
[Wallet calls XQlyte.diagnose_failure(payment_id)]
|
v
[Fetch payment metadata]
|
v
[Fetch RPC error logs]
|
v
[Failure Classifier]
|
v
[Suggestion Engine]
|
v
[Return diagnostics]
- failure category
- human-readable reason
- technical reason
- suggested fix
- retry strategy

4. CLI Diagnostics Flow

text
[Operator runs CLI command]
|
v
[XQlyte CLI parses arguments]
|
v
[XQlyte Engine performs analysis]
|
v
[CLI formats output]
|

v
[Operator sees structured diagnostics]

5. Dashboard Logging Flow

text
[XQlyte Engine logs analysis]
|
v
[Dashboard backend stores logs]
|
v
[Dashboard UI visualizes]
- success rate
- failure rate
- route performance
- asset performance
- liquidity health
- node stability

6. Telegram Bot Flow

text
[User sends message: "Can I send 5 USDT to Fatima?"]
|
v
[Bot parses message -> PaymentRequest]
|
v
[XQlyte.can_pay(request)]
|
v
[Bot formats response]
|
v
[User receives simple answer]

K. API Design

XQlyte exposes a clean, predictable, developer-friendly API that wallets, merchants, agents, and node operators can integrate with minimal effort. The API is designed to be:

- **simple** (easy to call)
- **predictable** (consistent outputs)
- **modular** (each function does one thing well)
- **multi-platform** (Rust, JS, WASM)
- **future-proof** (easy to extend)

This section defines the **public API surface** of XQlyte.

1. Core API Functions

These are the primary functions that wallets and agents will use.

1. `can_pay(request)`

Determines whether a payment is likely to succeed.

Input:

A `PaymentRequest` object containing:

- sender
- receiver
- amount
- asset
- optional metadata

Output:

A `PaymentConfidenceResult` containing:

- `status`: CAN_PAY | CANNOT_PAY | UNKNOWN
- `confidence_score`: 0–100
- `best_route`: route object
- `best_asset`: asset identifier
- `reason`: human-readable explanation
- `technical_reason`: detailed explanation
- `suggested_fix`: actionable guidance

2. `diagnose_failure(payment_id)`

Explains why a payment failed.

Input:

A `payment_id` referencing a failed payment.

Output:

A `FailureDiagnostics` object containing:

- `failure_category`
- `human_reason`
- `technical_reason`
- `failing_hop`
- `failing_asset`
- `suggested_fix`
- `retry_strategy`

3. `confidence_score(request)`

Returns only the confidence score without full diagnostics.

Output:

- `score`: 0–100
- `risk_factors`: list of penalties applied

4. `best_asset(request)`

Recommends the best asset for a payment.

Output:

- `asset`: recommended asset
- `confidence`: score
- `reason`: explanation

5. `best_route(request)`

Returns the best route for a payment.

Output:

- **route**: list of hops
- **score**: route viability score
- **reason**: explanation

6. **analyze_route(route)**

Analyzes a specific route.

Output:

- hop-by-hop analysis
- liquidity per hop
- asset compatibility
- fee constraints
- node stability

7. **analyze_asset(asset)**

Analyzes asset viability.

Output:

- liquidity
- swap availability
- route compatibility
- fee profile

8. **log_result(result)**

Logs analysis for dashboard and analytics.

2. Data Structures

PaymentRequest

```
json
{
  "sender": "string",
  "receiver": "string",
  "amount": "number",
  "asset": "string",
  "metadata": {}
}
```


PaymentConfidenceResult

```
json
{
  "status": "CAN_PAY | CANNOT_PAY | UNKNOWN",
  "confidence_score": "number",
  "best_route": {},
  "best_asset": "string",
  "reason": "string",
  "technical_reason": "string",
  "suggested_fix": "string"
}
```

FailureDiagnostics

```
json
{
  "failure_category": "string",
  "human_reason": "string",
  "technical_reason": "string",
  "failing_hop": {},
  "failing_asset": "string",
  "suggested_fix": "string",
  "retry_strategy": "string"
}
```

3. API Design Strengths (Judging Criteria Alignment)

Criterion	Strength
Reusability	Clean, modular API usable across wallets, merchants, agents
Integration potential	Simple function calls, predictable outputs
Technical soundness	Strong typing, clear data structures
Functional completeness	Covers pre-checks, diagnostics, scoring, suggestions
Maintainability	Each function has a single responsibility
Future potential	Easy to extend with multi-path, cross-chain logic

L. SDK Design

The SDK layer is how developers actually use XQlyte.

It must be:

- **easy to integrate**
- **consistent across languages**
- **lightweight**
- **well-documented**
- **safe**
- **fast**

XQlyte provides SDKs for:

- **Rust** (native wallets, agents)
- **JavaScript** (web wallets, dashboards)
- **WASM** (browser runtime)

1. Rust SDK

Purpose

For native wallets, agents, merchant systems, and node tools.

Design Principles

- idiomatic Rust
- strong typing
- zero-cost abstractions
- async support
- error-safe

Example Usage

```
rust
let request = PaymentRequest::new(
    "sender123",
    "receiver456",
    10.0,
    "USDT"
);

let result = xqlyte::can_pay(request);
```

```
println!("Status: {:?}", result.status);
println!("Confidence: {}", result.confidence_score);
println!("Reason: {}", result.reason);
```

2. JavaScript SDK

Purpose

For web wallets, dashboards, and browser-based tools.

Design Principles

- promise-based
- lightweight
- browser-friendly
- compatible with bundlers

Example Usage

```
javascript
import { canPay } from "xqlyte";
```

```
const result = await canPay({
  sender: "alice",
  receiver: "bob",
  amount: 5,
  asset: "USDT"
});
```

```
console.log(result.status);
console.log(result.confidence_score);
```

3. WASM SDK

Purpose

For browser wallets and web dashboards needing high performance.

Design Principles

- compiled from Rust
- minimal overhead
- fast execution
- secure sandboxing

Example Usage

```
javascript
const result = wasm.can_pay(request);
```

4. SDK Modules

A. Core Module

- request builder
- response parser
- error handler

B. Diagnostics Module

- failure classifier
- suggestion engine

C. Analytics Module

- route scoring
- asset scoring
- liquidity scoring

D. RPC Module

- Fiber RPC wrapper
- caching layer
- retry logic

5. SDK Strengths (Judging Criteria Alignment)

Criterion	Strength
Reusability	Multi-language SDKs, consistent API
Integration potential	Wallets can integrate in minutes

Technical soundness Rust core + WASM + JS bindings

Documentation quality Clear examples, typed interfaces

Maintainability Modular SDK structure

Practical value Developers get instant diagnostics tools

M. CLI Design

The XQlyte CLI is a critical component for **node operators**, **developers**, **LSPs**, and **advanced users**. It provides direct access to XQlyte's diagnostics and analytics without requiring a wallet or UI.

The CLI is designed to be:

- **simple**
- **powerful**
- **scriptable**
- **developer-friendly**
- **consistent**
- **modular**

It exposes the full capabilities of the XQlyte engine through terminal commands.

1. CLI Philosophy

The CLI must:

- provide **deep visibility** into Fiber routing, liquidity, and asset flows
- allow operators to **diagnose failures** quickly
- allow developers to **test payment scenarios**
- allow LSPs to **analyze liquidity health**
- allow merchants to **pre-check payment viability**

It is a **first-class interface**, not an afterthought.

2. CLI Command Structure

The CLI follows a simple pattern:

Code

xqlyte <command> [options]

Commands are grouped into functional categories.

3. Core Commands

1. **can-pay**

Checks whether a payment is likely to succeed.

Usage:

Code

```
xqlyte can-pay --to bob --from alice --amount 10 --asset USDT
```

Output:

- CAN_PAY / CANNOT_PAY / UNKNOWN
- confidence score
- best route
- best asset
- reason
- suggested fix

2. **diagnose**

Diagnoses a failed payment.

Usage:

Code

```
xqlyte diagnose --payment-id 0xabc123
```

Output:

- failure category
- human-readable reason
- technical reason
- failing hop
- suggested fix
- retry strategy

3. route

Analyzes route viability.

Usage:

Code

```
xqlyte route --to bob --asset USDT
```

Output:

- route candidates
- hop-by-hop analysis
- liquidity per hop
- node stability
- asset compatibility

4. asset

Analyzes asset viability.

Usage:

Code

```
xqlyte asset --asset USDT
```

Output:

- liquidity
- swap availability
- fee profile
- route compatibility

5. liquidity

Analyzes liquidity health.

Usage:

Code

```
xqlyte liquidity --channel 0x123
```

Output:

- inbound/outbound liquidity
- liquidity direction
- channel health
- bottlenecks

6. **node**

Analyzes node stability.

Usage:

Code

```
xqlyte node --id node123
```

Output:

- uptime
- routing reliability
- failure patterns
- asset support

7. **log**

Shows historical diagnostics.

Usage:

Code

```
xqlyte log --recent 20
```

Output:

- recent analyses
- success/failure
- reasons
- confidence scores

4. CLI Output Format

The CLI uses a structured, readable format:

Code

```
Status: CAN_PAY
```


Confidence: 92%
Best Route: alice -> nodeA -> nodeB -> bob
Reason: Sufficient liquidity and stable nodes.
Suggested Fix: None.

This ensures clarity and usability.

5. CLI Strengths (Judging Criteria Alignment)

Criterion	Strength
Functional completeness	Full diagnostics, route analysis, asset analysis
Usefulness	Node operators and devs get deep visibility
Integration potential	Scriptable for automation
Technical soundness	Uses core engine modules
Reusability	Works across all Fiber environments
Practical value	Essential for debugging and optimization

N. Dashboard Design

The XQlyte Dashboard is a **developer and operator analytics interface** that visualizes payment health, failure patterns, route performance, asset viability, and liquidity conditions.

It is designed to be:

- **clear**
- **informative**
- **actionable**
- **real-time**
- **multi-asset aware**
- **multi-hop aware**

This section defines the dashboard's structure, pages, and functionality.

1. Dashboard Philosophy

The dashboard must:

- reveal insights hidden in raw RPC data
- help operators identify problems quickly
- help merchants understand payment failures
- help developers debug routing issues
- help LSPs optimize liquidity

It is not a wallet dashboard — it is **infrastructure analytics**.

2. Dashboard Pages

1. Overview Page

Shows global health metrics:

- payment success rate
- payment failure rate
- average confidence score
- top failure categories
- top failing routes
- top failing assets
- node stability overview

This page gives a **quick snapshot** of network health.

2. Route Analytics Page

Shows:

- route success rate
- hop-by-hop performance
- unstable nodes
- liquidity bottlenecks
- fee bottlenecks
- asset compatibility issues

Operators can identify problematic routes instantly.

3. Asset Analytics Page

Shows:

- asset success rate
- asset liquidity
- swap availability
- fee profile

- asset-specific failure patterns

Merchants and wallets can choose the best assets.

4. Liquidity Health Page

Shows:

- inbound/outbound liquidity
- liquidity direction
- channel health
- liquidity bottlenecks
- recommended rebalancing actions

LSPs and operators can optimize liquidity placement.

5. Node Health Page

Shows:

- uptime
- routing reliability
- failure patterns
- asset support
- peer stability

Operators can identify unstable nodes.

6. Failure Explorer Page

Shows:

- failure categories
- failure reasons
- failing hops
- failing assets
- suggested fixes
- retry strategies

This page is essential for debugging.

7. Payment Explorer Page

Shows:

- individual payment analyses

- confidence scores
- route details
- asset details
- diagnostics
- logs

Developers can inspect specific payments.

3. Dashboard Components

A. Charts

- line charts
- bar charts
- pie charts
- heatmaps
- hop-by-hop diagrams

B. Tables

- sortable
- filterable
- searchable

C. Filters

- asset
- route
- node
- time range
- failure category

D. Drill-Down Panels

Click any item to see deeper insights.

4. Dashboard Strengths (Judging Criteria Alignment)

Criterion	Strength
Functional completeness	Full analytics suite

Usefulness	Operators, merchants, devs gain visibility
Integration potential	Works with logs from engine
Technical soundness	Real RPC data + structured logs
Reusability	Can be used by any Fiber node
Practical value	Helps diagnose and fix real problems
Future potential	Can evolve into LSP console

O. Telegram Bot Design

The XQlyte Telegram Bot is a lightweight, user-facing interface that exposes the core capabilities of the XQlyte engine in a simple conversational format. It is designed for:

- end users
- merchants
- support teams
- developers
- testers
- community members

The bot provides instant answers to questions like:

- “Can I pay?”
- “Why did my payment fail?”
- “Which asset should I use?”
- “What route is best?”

This makes XQlyte accessible to non-technical users and ideal for demos during the hackathon.

1. Bot Philosophy

The bot must be:

- **simple** — no jargon
- **fast** — instant responses
- **clear** — human-readable explanations
- **actionable** — suggestions included
- **multi-asset aware**
- **multi-hop aware**
- **cross-chain aware**

It is not a wallet — it is a **diagnostics assistant**.

2. Supported Commands

1. `/canpay`

Checks if a payment can succeed.

Example:

Code

```
/canpay sender=alice receiver=bob amount=10 asset=USDT
```

Bot Response:

Code

✓ Payment likely to succeed.

Confidence: 92%

Best route: alice → nodeA → nodeB → bob

Fee: 0.01 USDT

2. `/whyfail`

Explains why a payment failed.

Example:

Code

```
/whyfail payment_id=0xabc123
```

Bot Response:

Code

✗ Payment failed.

Reason: Insufficient inbound liquidity at hop 2.

Suggested fix: Receiver must add inbound liquidity.

3. `/bestasset`

Recommends the best asset for a payment.

Example:

Code

/bestasset receiver=bob amount=20

Bot Response:

Code

Recommended asset: USDT

Confidence: 94%

Reason: Highest liquidity and lowest fees.

4. /bestroute

Shows the best route.

Example:

Code

/bestroute receiver=bob asset=USDT

Bot Response:

Code

Best route:

alice → nodeA → nodeC → bob

Score: 88%

Reason: Stable nodes and sufficient liquidity.

5. /liquidity

Shows liquidity health.

Example:

Code

/liquidity channel=0x123

Bot Response:

Code

Inbound: 12 USDT
Outbound: 3 USDT
Status: Healthy

3. Bot Interaction Flow

text

[User sends command]

|

v

[Bot parses command]

|

v

[Bot builds PaymentRequest]

|

v

[XQlyte Engine processes request]

|

v

[Bot formats human-readable response]

|

v

[User receives clear, actionable answer]

4. Bot UX Principles

- No technical jargon
- Short sentences
- Clear icons (✓, ✗)
- Actionable suggestions
- Confidence scores
- Simple route diagrams

5. Bot Strengths (Judging Criteria Alignment)

Criterion	Strength
Functional completeness	Full diagnostics via chat

Usefulness	Helps users, merchants, devs
Integration potential	Uses core engine
Technical soundness	Real RPC-backed analysis
Practical value	Ideal for demos and support
Future potential	Can evolve into support bot

P. Confidence Model

The confidence model is the **mathematical and logical core** of XQlyte.

It computes a probability score (0–100%) representing the likelihood that a payment will succeed.

This model is essential for:

- wallets
- merchants
- agents
- node operators
- dashboards
- bots

It demonstrates **technical depth**, **functional completeness**, and **future potential** — three major judging criteria.

1. Confidence Model Philosophy

The model must be:

- **accurate**
- **predictive**
- **explainable**
- **multi-asset aware**
- **multi-hop aware**
- **cross-chain aware**
- **risk-sensitive**

It must not be a black box — it must provide **risk factors** and **penalties**.

2. Inputs to the Confidence Model

The model uses data from:

A. Route Analyzer

- hop count
- node stability
- route availability
- fallback routes

B. Asset Analyzer

- asset compatibility
- swap availability
- asset liquidity

C. Liquidity Analyzer

- inbound/outbound liquidity
- liquidity direction
- channel health

D. Fee Analyzer

- fee-to-amount ratio
- fee bottlenecks

E. Node RPC

- node uptime
- peer stability
- channel states

3. Scoring Formula (Simplified)

The confidence score is computed as:

$\text{Confidence} = \text{BaseScore} - \text{Penalties}$

Where:

BaseScore

Starts at **100**.

Penalties

Applied for:

- low liquidity
- unstable nodes
- high fees
- asset incompatibility
- swap unavailability
- long routes
- cross-chain risk
- incomplete RPC data

Each penalty reduces the score by 5–30 points depending on severity.

4. Detailed Scoring Breakdown

1. Route Score (0–30 points)

- fewer hops = higher score
- stable nodes = higher score
- fallback routes = higher score

2. Asset Score (0–20 points)

- compatible asset = high score
- swap required = medium score
- swap unavailable = zero score

3. Liquidity Score (0–30 points)

- sufficient liquidity = high score
- borderline liquidity = medium score
- insufficient liquidity = zero score

4. Fee Score (0–10 points)

- low fees = high score
- high fees = medium score
- fee bottleneck = zero score

5. Node Health Score (0–10 points)

- stable nodes = high score
- unstable nodes = medium score
- offline nodes = zero score

5. Confidence Thresholds

CAN_PAY

Confidence $\geq$ 70

CANNOT_PAY

Confidence $\leq$ 40

UNKNOWN

40<Confidence<70

6. Risk Factors Returned to Caller

The model returns:

- liquidity risk
- asset risk
- route risk
- fee risk
- node risk
- cross-chain risk
- RPC data risk

These help wallets and agents make informed decisions.

7. Example Confidence Calculation

Scenario

Alice wants to send 10 USDT to Bob.

Scores

- Route score: 25
- Asset score: 20
- Liquidity score: 30
- Fee score: 8

- Node score: 9

Total

25+20+30+8+9=92

Result

- CAN_PAY
- Confidence: 92%
- Suggested fix: None

8. Confidence Model Strengths (Judging Criteria Alignment)

Criterion	Strength
Technical soundness	Real scoring model, multi-factor analysis
Functional completeness	Predictive + diagnostic + advisory
Reusability	Works across wallets, merchants, agents
Integration potential	Simple API, deep logic
Practical value	Prevents failed payments
Future potential	Can evolve into multi-path scoring

Q. Failure Taxonomy

A failure taxonomy is essential for transforming raw Fiber errors into meaningful, actionable insights.

Fiber payments can fail for many reasons, and without a structured taxonomy, failures appear random, confusing, and impossible to fix.

XQlyte introduces a **clear, hierarchical failure taxonomy** that categorizes every failure into human-readable groups with actionable fixes.

This taxonomy is used by:

- wallets
- merchants
- node operators
- agents
- dashboards
- bots

It is one of the most important components of XQlyte.

1. Purpose of the Failure Taxonomy

The taxonomy must:

- simplify complex Fiber errors
- categorize failures consistently
- provide human-readable explanations
- provide technical explanations
- map each failure to a suggested fix
- support multi-asset and multi-hop flows
- support cross-chain flows
- support future Fiber features

It is the foundation of XQlyte's diagnostic capabilities.

2. Failure Categories

XQlyte defines **eight primary failure categories**.

Each category includes:

- definition
- symptoms
- causes
- detection method
- example RPC errors
- suggested fixes

1. Capacity Failure

Definition:

Insufficient liquidity in one or more channels along the route.

Symptoms:

- payment fails immediately
- route unavailable
- partial liquidity detected

Causes:

- sender lacks outbound liquidity
- receiver lacks inbound liquidity
- intermediate hop lacks liquidity

Detection:

- liquidity analyzer
- route analyzer

Suggested Fix:

- add liquidity
- rebalance channels
- reduce payment amount
- choose alternative asset

2. Asset Failure

Definition:

The chosen asset is not supported along the route or by the receiver.

Symptoms:

- asset mismatch
- swap unavailable
- asset unsupported

Causes:

- receiver does not accept asset
- hop does not support asset
- swap provider offline

Detection:

- asset analyzer
- swap RPC

Suggested Fix:

- use recommended asset
- enable swap provider
- choose multi-asset route

3. Route Failure

Definition:

No viable route exists between sender and receiver.

Symptoms:

- “route not found”
- unstable hops
- unreachable nodes

Causes:

- network fragmentation
- offline nodes
- insufficient gossip data

Detection:

- route analyzer
- node RPC

Suggested Fix:

- retry later
- choose alternative asset
- connect to more peers

4. Fee Failure

Definition:

Fees exceed acceptable thresholds or violate constraints.

Symptoms:

- fee bottleneck
- fee mismatch
- fee too high

Causes:

- high hop fees

- asset-specific fee spikes
- insufficient fee budget

Detection:

- fee analyzer

Suggested Fix:

- increase fee budget
- choose lower-fee asset
- choose shorter route

5. Node Failure

Definition:

One or more nodes along the route are unstable or offline.

Symptoms:

- intermittent failures
- route instability
- node unreachable

Causes:

- node downtime
- poor connectivity
- misconfigured node

Detection:

- node RPC
- route analyzer

Suggested Fix:

- avoid unstable nodes
- reconnect peers
- restart node

6. Timeout Failure

Definition:

HTLC or expiry conditions are violated.

Symptoms:

- payment stuck
- payment times out
- expiry mismatch

Causes:

- long routes
- slow nodes
- cross-chain expiry mismatch

Detection:

- route analyzer
- RPC logs

Suggested Fix:

- choose shorter route
- increase expiry window
- avoid cross-chain hops

7. Swap Failure

Definition:

Swap required but unavailable or incompatible.

Symptoms:

- swap provider offline
- swap unsupported
- swap liquidity insufficient

Causes:

- swap service down
- asset mismatch
- insufficient swap liquidity

Detection:

- asset analyzer
- swap RPC

Suggested Fix:

- use supported asset
- retry later
- enable alternative swap provider

8. Unknown Failure

Definition:

Failure cannot be classified due to incomplete data.

Symptoms:

- ambiguous errors
- partial RPC data
- inconsistent logs

Causes:

- gossip incomplete
- RPC timeout
- network instability

Detection:

- fallback classification

Suggested Fix:

- retry
- refresh gossip
- increase RPC timeout

3. Failure Taxonomy Strengths (Judging Criteria Alignment)

Criterion	Strength
Functional completeness	Covers all Fiber failure modes
Technical soundness	Maps raw RPC errors to structured categories
Usefulness	Helps wallets, merchants, agents, operators
Integration potential	Works across all XQlyte components

Reusability	Can be used by any Fiber application
Practical value	Reduces confusion and improves UX
Future potential	Supports new Fiber features

R. Data Requirements

XQlyte relies on accurate, real-time data from the Fiber network to perform diagnostics, scoring, and analysis.

This section defines the **data inputs**, **data sources**, **data formats**, and **data quality requirements**.

This demonstrates **technical soundness**, **functional completeness**, and **integration potential** — all critical judging criteria.

1. Data Inputs

XQlyte requires the following data:

A. Channel Data

- channel ID
- inbound liquidity
- outbound liquidity
- asset type
- channel capacity
- channel health
- channel age

B. Route Data

- route candidates
- hop list
- hop liquidity
- hop asset support
- hop fees
- hop stability

C. Asset Data

- asset type

- asset network
- asset liquidity
- swap availability
- fee profile

D. Node Data

- node ID
- uptime
- stability score
- peer list
- asset support
- routing reliability

E. Fee Data

- base fee
- proportional fee
- fee-to-amount ratio
- fee bottlenecks

F. Swap Data

- swap provider availability
- swap liquidity
- swap fees
- swap compatibility

G. Payment Metadata

- sender
- receiver
- amount
- asset
- timestamp
- payment ID

2. Data Sources

XQlyte retrieves data from:

A. Fiber Node RPC

Primary source for:

- channels
- routes
- nodes
- fees
- swaps

B. XQlyte Logs

Used for:

- historical analytics
- failure patterns
- route performance

C. Wallet Metadata

Used for:

- sender/receiver identity
- asset preferences

D. Merchant Metadata

Used for:

- invoice asset requirements
- merchant liquidity needs

3. Data Quality Requirements

XQlyte requires:

A. Freshness

Data must be recent (seconds old).

B. Completeness

Missing data triggers UNKNOWN classification.

C. Accuracy

Incorrect data leads to incorrect scoring.

D. Consistency

Data must match across RPC calls.

E. Reliability

RPC must respond consistently.

4. Data Formats

XQlyte expects:

JSON RPC Responses

For:

- channels
- routes
- nodes
- fees
- swaps

Structured Logs

For:

- diagnostics
- analytics
- dashboard

Typed SDK Objects

For:

- requests
- responses

5. Data Flow Diagram


text

[Fiber Node RPC]

|

v

[XQlyte RPC Layer]



6. Data Requirements Strengths (Judging Criteria Alignment)

Criterion	Strength
Technical soundness	Clear data sources and formats
Functional completeness	Covers all required data types
Integration potential	Works with Fiber RPC
Reusability	Any Fiber node can supply data
Maintainability	Modular data layer
Practical value	Accurate diagnostics require accurate data

S. Integration Points

XQlyte is designed as **infrastructure**, not an isolated tool.

Its value comes from how easily it integrates with the Fiber ecosystem.

This section defines all integration points across wallets, merchants, agents, node operators, and Fiber RPC.

It demonstrates **high integration potential**, which is one of the strongest scoring criteria.

1. Wallet Integration

Wallets are the primary consumers of XQlyte.

Integration Method

- Rust SDK (native wallets)
- JS/WASM SDK (browser wallets)

Wallet Features Powered by XQlyte

- “Can I pay?” button
- Pre-payment confidence scoring
- Asset recommendation
- Route recommendation
- Failure explanation
- Suggested fixes
- Retry strategies

Integration Flow

text

Wallet → XQlyte SDK → XQlyte Engine → Fiber RPC → XQlyte Engine → Wallet UI

Value

Wallets become smarter, more reliable, and easier to use.

2. Merchant Integration

Merchants need predictable payments.

Integration Method

- Merchant-side SDK
- Pre-check API
- Dashboard

Merchant Features Powered by XQlyte

- Invoice asset validation
- Pre-check payment viability
- Liquidity diagnostics
- Failure explanations
- Suggested liquidity fixes

Integration Flow

text

Merchant Checkout → XQlyte.can_pay() → Merchant UI

Value

Merchants reduce failed payments and abandoned checkouts.

3. Agent Integration

AI agents and automated workflows rely on XQlyte for decision-making.

Integration Method

- Rust SDK
- Machine-readable diagnostics

Agent Features Powered by XQlyte

- Autonomous payment validation
- Asset selection
- Route selection
- Retry logic
- Failure classification

Integration Flow

text

Agent → XQlyte.can_pay() → Agent Decision Engine

Value

Agents become safer, smarter, and more reliable.

4. Node Operator Integration

Node operators use XQlyte for diagnostics and analytics.

Integration Method

- CLI tool
- Dashboard

Operator Features Powered by XQlyte

- Route diagnostics
- Liquidity diagnostics
- Node stability analysis
- Failure pattern detection
- Asset performance analysis

Integration Flow

text

Operator → CLI/Dashboard → XQlyte Engine → RPC → Operator UI

Value

Operators gain visibility and control.

5. Fiber Node RPC Integration

XQlyte relies heavily on Fiber RPC.

RPC Endpoints Used

- channel RPC
- route RPC
- asset RPC
- node RPC
- fee RPC
- swap RPC

Integration Flow

text

XQlyte Engine → RPC Layer → Fiber Node RPC

Value

XQlyte becomes a real, RPC-backed infrastructure tool.

6. Dashboard Integration

The dashboard consumes logs from the engine.

Integration Method

- structured logs
- analytics backend

Dashboard Features Powered by XQlyte

- success/failure rates
- route performance
- asset performance
- liquidity health
- node stability

7. Telegram Bot Integration

The bot uses the SDK to expose diagnostics to users.

Integration Flow

text

Bot → XQlyte SDK → XQlyte Engine → Bot UI

Value

Non-technical users get instant clarity.

8. Integration Strengths (Judging Criteria Alignment)

Criterion	Strength
Integration potential	Works with wallets, merchants, agents, operators

Reusability	SDK + CLI + dashboard + bot
Technical soundness	Clean RPC abstraction
Functional completeness	Covers all ecosystem roles
Practical value	Reduces failures across the network
Future potential	Can integrate with multi-path and cross-chain tools

T. Technical Requirements

This section defines the technical foundation of XQlyte — languages, frameworks, architecture constraints, performance requirements, reliability expectations, and security considerations.

It demonstrates **technical soundness**, **maintainability**, and **future potential**, all major judging criteria.

1. Programming Languages

Rust (Primary Language)

Used for:

- core engine
- analyzers
- confidence model
- failure classifier
- suggestion engine
- RPC layer
- CLI tool

Reason:

Rust provides safety, performance, and reliability — ideal for infrastructure.

JavaScript / TypeScript

Used for:

- web SDK

- dashboard frontend
- bot integration

Reason:

Browser compatibility and developer accessibility.

WASM

Used for:

- browser wallets
- dashboard runtime

Reason:

High performance in web environments.

2. Frameworks & Libraries

Rust Ecosystem

- Tokio (async runtime)
- Serde (serialization)
- Reqwest (RPC calls)
- Clap (CLI parsing)

Web Ecosystem

- React or Svelte (dashboard UI)
- D3.js or Chart.js (visualizations)

3. Core Engine Requirements

A. Modularity

Each analyzer must be independent.

B. Extensibility

New analyzers (e.g., multi-path) must be easy to add.

C. Performance

Pre-check must complete in $< 50\text{ms}$.

D. Reliability

Engine must handle RPC failures gracefully.

E. Security

Engine must not handle private keys.

F. Determinism

Same inputs must produce same outputs.

4. RPC Layer Requirements

A. Retry Logic

Automatic retries for transient failures.

B. Caching

Short-lived caching for repeated queries.

C. Timeout Handling

Graceful fallback to UNKNOWN classification.

D. Error Normalization

Convert raw RPC errors into structured categories.

5. SDK Requirements

A. Consistent API

Same function names across Rust, JS, WASM.

B. Lightweight

Minimal overhead for wallets.

C. Typed Interfaces

Strong typing for safety.

D. Clear Errors

Human-readable + technical errors.

6. CLI Requirements

A. Scriptable

Must work in shell scripts.

B. Readable Output

Clear formatting.

C. Fast

Diagnostics must complete quickly.

7. Dashboard Requirements

A. Real-Time Updates

Refresh every few seconds.

B. Drill-Down

Click to inspect details.

C. Filters

Asset, route, node, time.

D. Charts

Visual clarity.

8. Logging Requirements

A. Structured Logs

JSON format.

B. Persistent Storage

SQLite or Postgres.

C. Queryable

Dashboard must query logs efficiently.

9. Security Requirements

A. No Private Keys

XQlyte never touches keys.

B. No Payment Execution

XQlyte only analyzes.

C. Safe RPC Usage

No dangerous RPC calls.

D. Sandboxed WASM

Browser runtime must be safe.

10. Technical Requirements Strengths (Judging Criteria Alignment)

Criterion	Strength
Technical soundness	Rust core + modular architecture
Maintainability	Clean separation of concerns
Reusability	SDK + CLI + dashboard
Integration potential	Works across all Fiber environments
Future potential	Supports multi-path, cross-chain, advanced liquidity

Practical value Reliable diagnostics require strong technical foundation

U. Non-Functional Requirements

Non-functional requirements (NFRs) define how XQlyte behaves under real-world conditions.

They ensure the system is **fast**, **reliable**, **secure**, **scalable**, and **maintainable** — qualities that judges look for when evaluating infrastructure projects.

XQlyte's NFRs are grouped into eight categories.

1. Performance Requirements

A. Low Latency

- Pre-payment checks must complete in **< 50ms** under normal network conditions.
- Diagnostics must complete in **< 100ms**.

B. Efficient RPC Usage

- RPC calls must be batched where possible.
- Short-lived caching must reduce redundant RPC calls.

C. WASM Performance

- Browser-based checks must run in **< 30ms**.

D. CLI Performance

- CLI commands must return results in **< 200ms**.

2. Reliability Requirements

A. Graceful Degradation

If RPC data is incomplete:

- XQlyte must return **UNKNOWN** instead of failing.

B. Retry Logic

Transient RPC failures must trigger:

- exponential backoff
- retry attempts
- fallback routes

C. Deterministic Output

Same inputs must always produce the same outputs.

D. High Availability

Dashboard backend must tolerate:

- temporary RPC outages
- partial data availability

3. Scalability Requirements

A. Horizontal Scaling

Dashboard backend must scale horizontally to support:

- thousands of logs
- hundreds of operators
- multiple nodes

B. Multi-Instance Support

Multiple XQlyte instances must run concurrently:

- wallet-side
- merchant-side
- operator-side
- bot-side

C. Multi-Asset Scaling

Support for additional assets must require:

- no architectural changes
- only configuration updates

4. Security Requirements

A. No Private Keys

XQlyte must **never** handle:

- private keys
- seed phrases
- signing operations

B. Safe RPC Usage

RPC calls must:

- avoid sensitive endpoints
- sanitize inputs
- validate outputs

C. WASM Sandboxing

Browser runtime must:

- isolate execution
- prevent unauthorized access

D. Log Sanitization

Logs must exclude:

- sensitive user data
- payment secrets

5. Maintainability Requirements

A. Modular Architecture

Each analyzer must be:

- independent
- testable
- replaceable

B. Clear Boundaries

Core engine must not depend on:

- dashboard

- CLI
- bot

C. Typed Interfaces

All SDKs must use:

- strong typing
- predictable schemas

D. Documentation

Must include:

- API docs
- SDK docs
- CLI docs
- dashboard docs
- architecture diagrams

6. Observability Requirements

A. Structured Logging

Logs must include:

- timestamp
- request metadata
- diagnostics
- confidence score
- failure category

B. Metrics

Dashboard must track:

- success rate
- failure rate
- route performance
- asset performance
- node stability

C. Alerts

Operators must be able to detect:

- unstable nodes
- failing routes
- liquidity bottlenecks

7. Compatibility Requirements

A. Fiber RPC Compatibility

XQlyte must support:

- current RPC endpoints
- future RPC extensions

B. Wallet Compatibility

Must work with:

- native wallets
- web wallets
- mobile wallets

C. Merchant Compatibility

Must integrate with:

- POS systems
- checkout flows
- invoice systems

8. Usability Requirements

A. Clear Error Messages

Diagnostics must be:

- human-readable
- actionable
- jargon-free

B. Simple SDK

Developers must integrate XQlyte in:

- < 10 lines of code

C. Intuitive Dashboard

Operators must understand:

- charts
- tables
- failure categories
- route diagrams

Non-Functional Requirements Strengths (Judging Criteria Alignment)

Criterion	Strength
Technical soundness	Strong performance, reliability, security
Maintainability	Modular architecture, typed interfaces
Reusability	Works across wallets, merchants, agents
Integration potential	Compatible with all Fiber environments
Practical value	Production-ready infrastructure
Future potential	Scalable, extensible, robust

V. Judging Criteria Scoring

This section explicitly maps XQlyte to the hackathon judging criteria and demonstrates how it achieves **9/10 or 10/10** across nearly all categories.

This is one of the most important sections for judges.

1. Functional Completeness — 9/10

XQlyte delivers:

- pre-payment checks
- diagnostics

- confidence scoring
- route analysis
- asset analysis
- liquidity analysis
- fee analysis
- suggestions
- SDK
- CLI
- dashboard
- bot

This is a **complete infrastructure suite**.

2. Relevance to Fiber Infrastructure — 10/10

The hackathon explicitly asks for:

- payment confidence tools
- failure diagnostics
- structured error reporting
- routing analysis
- multi-asset support

XQlyte delivers all of these.

3. Usefulness to Ecosystem — 10/10

XQlyte benefits:

- wallets
- merchants
- node operators
- agents
- LSPs
- developers
- end users

It solves real ecosystem problems.

4. Technical Soundness — 9/10

XQlyte uses:

- Rust core
- modular analyzers
- structured taxonomy
- confidence model
- RPC abstraction
- WASM runtime

This is a robust architecture.

5. Reusability — 9/10

XQlyte is reusable across:

- wallets
- merchants
- agents
- dashboards
- bots
- CLI tools

SDKs make integration trivial.

6. Integration Potential — 10/10

XQlyte integrates with:

- Fiber RPC
- wallets
- merchant systems
- bots
- agents
- dashboards

It is designed for ecosystem-wide adoption.

7. Documentation Quality — 9/10

XQlyte includes:

- full PRD
- API docs
- SDK docs
- CLI docs

- dashboard docs
- flowcharts
- architecture diagrams

This is judge-friendly documentation.

8. Maintainability — 9/10

XQlyte is:

- modular
- typed
- testable
- extensible

Future features can be added easily.

9. Practical Value — 10/10

XQlyte solves:

- failed payments
- unclear errors
- asset mismatch
- route instability
- liquidity bottlenecks

This is high-impact infrastructure.

10. Category Fit — 10/10

XQlyte is **exactly** what the Wallet & Payment UX Infrastructure track asks for.

11. Future Potential — 10/10

XQlyte can evolve into:

- multi-path payment advisor
- cross-chain confidence engine
- liquidity optimization engine
- LSP console
- merchant pre-check suite

This is long-term infrastructure.

Overall Score — 9.6 / 10

This is **winner-tier alignment**.

W. Competitive Analysis

XQlyte exists in a growing ecosystem of Fiber tools, wallets, dashboards, and infrastructure components.

To demonstrate strategic clarity and ecosystem fit, this section analyzes:

- what currently exists
- what is missing
- how XQlyte fills the gap
- why XQlyte is uniquely valuable
- why XQlyte is not duplicative
- why XQlyte is essential infrastructure

This is one of the most important sections for judges because it shows that XQlyte is not reinventing the wheel — it is building the missing wheel.

1. Overview of Existing Fiber Ecosystem

Based on the Fiber showcase, the ecosystem includes:

Wallets

- Fiber Wallet
- Lightning-compatible wallets
- Multi-asset wallets

Merchant Tools

- Paywalls
- POS concepts
- Payment demos

Developer Tools

- SDKs

- Node installers
- Simulators
- RPC wrappers

Dashboards

- Node dashboards
- Channel dashboards
- Network explorers

Agents

- AI agents
- automation scripts

Games & Apps

- micropayment games
- streaming payment apps

Infrastructure

- routing nodes
- liquidity providers
- swap providers

2. What the Ecosystem Does NOT Have

Despite the ecosystem's growth, **no existing project** provides:

A. Payment Confidence Engine

No tool answers:

“Will this payment succeed?”

B. Failure Diagnostics Layer

No tool explains:

“Why did this payment fail?”

C. Structured Error Reporting

No tool translates raw RPC errors into human-readable categories.

D. Route Viability Scoring

No tool scores routes based on:

- liquidity
- stability
- fees
- asset compatibility

E. Asset Compatibility Analysis

No tool checks whether an asset is supported across all hops.

F. Multi-Asset Payment Advisor

No tool recommends the best asset for a payment.

G. Liquidity Direction Analysis

No tool identifies inbound/outbound liquidity bottlenecks.

H. Cross-Chain Diagnostics

No tool explains Lightning ↔ Fiber failures.

I. Unified SDK for Diagnostics

No tool provides a drop-in SDK for wallets.

J. Developer Dashboard for Payment Health

No tool visualizes:

- failure patterns
- route performance
- asset performance
- node stability

K. Telegram Bot for Diagnostics

No tool exposes diagnostics to users via chat.

3. Why XQlyte is Unique

XQlyte is the **only** project that provides:

- predictive payment confidence
- structured diagnostics
- multi-asset analysis
- multi-hop analysis
- cross-chain analysis
- actionable suggestions
- SDK + CLI + dashboard + bot
- unified failure taxonomy
- confidence scoring model

This makes XQlyte **infrastructure**, not an app.

4. Competitive Positioning

XQlyte vs Wallets

Wallets execute payments.

XQlyte predicts and diagnoses payments.

XQlyte vs Dashboards

Dashboards show node/channel data.

XQlyte analyzes payment viability.

XQlyte vs Agents

Agents perform actions.

XQlyte guides agents with intelligence.

XQlyte vs RPC Tools

RPC tools expose raw data.

XQlyte transforms raw data into insights.

XQlyte vs Paywalls/POS

Paywalls accept payments.

XQlyte ensures payments succeed.

5. Why XQlyte is Essential Infrastructure

XQlyte solves the **biggest UX problem** in Fiber:

Payments fail without explanation.

This problem affects:

- wallets
- merchants
- agents
- node operators
- users

XQlyte is the missing intelligence layer that makes Fiber predictable, reliable, and developer-friendly.

6. Competitive Analysis Strengths (Judging Criteria Alignment)

Criterion	Strength
Relevance	Directly fills ecosystem gaps
Usefulness	Benefits all ecosystem roles
Technical soundness	Unique diagnostics + scoring model
Integration potential	Works with all Fiber tools
Future potential	Can evolve into routing advisor
Practical value	Reduces failed payments

X. Risks & Mitigations

Every serious infrastructure project must identify risks and propose mitigations.

This section demonstrates **technical maturity**, **realistic planning**, and **long-term viability** — all critical for judges.

XQlyte's risks fall into four categories:

- technical risks
- integration risks
- UX risks
- timeline risks

Each risk includes a mitigation strategy.

1. Technical Risks

Risk A: Incomplete RPC Data

Fiber RPC may occasionally return incomplete data.

Impact:

Confidence model may produce UNKNOWN results.

Mitigation:

- implement retry logic
- implement fallback RPC nodes
- degrade gracefully to UNKNOWN
- log incomplete data for debugging

Risk B: Rapid Ecosystem Changes

Fiber is evolving quickly.

Impact:

New features may require updates to analyzers.

Mitigation:

- modular architecture
- analyzers are plug-and-play
- versioned SDK releases
- compatibility layer

Risk C: Multi-Asset Complexity

New assets may introduce unexpected behavior.

Impact:

Asset analyzer may need updates.

Mitigation:

- asset registry
- dynamic asset configuration
- asset-specific scoring rules

Risk D: Cross-Chain Instability

Lightning ↔ Fiber swaps may fail unpredictably.

Impact:

Confidence scoring may be affected.

Mitigation:

- cross-chain risk penalty
- swap availability checks
- fallback asset suggestions

2. Integration Risks

Risk A: Wallet Adoption

Wallet developers may hesitate to integrate new infrastructure.

Impact:

Slower ecosystem adoption.

Mitigation:

- simple SDK
- clear documentation
- drop-in integration
- demo wallet plugin
- strong hackathon presentation

Risk B: Merchant Integration

Merchants may not understand diagnostics.

Impact:

Misuse or misunderstanding.

Mitigation:

- simple UI
- clear language
- actionable suggestions
- merchant-focused documentation

Risk C: Node Operator Complexity

Operators may find CLI commands overwhelming.

Impact:

Underutilization.

Mitigation:

- clear CLI help
- examples
- dashboard alternative

3. UX Risks

Risk A: Overwhelming Information

Too much detail may confuse users.

Impact:

Poor UX.

Mitigation:

- simple wallet messages
- detailed CLI/dashboard messages
- layered UX design

Risk B: Misinterpreting Confidence Scores

Users may misunderstand probabilities.

Impact:

Incorrect decisions.

Mitigation:

- clear thresholds
- simple labels (High, Medium, Low)
- warnings for UNKNOWN

4. Timeline Risks

Risk A: RPC Changes During Hackathon

RPC endpoints may change.

Impact:

Breakage.

Mitigation:

- abstraction layer
- rapid patching
- fallback RPC logic

Risk B: Dashboard Complexity

Dashboard may take longer than expected.

Impact:

Reduced functionality.

Mitigation:

- prioritize core pages
- use pre-built chart libraries
- focus on essential metrics

Risk C: WASM Integration Challenges

WASM may require debugging.

Impact:

Delays.

Mitigation:

- start WASM early
- use proven Rust → WASM toolchains

5. Risk Strengths (Judging Criteria Alignment)

Criterion	Strength
Technical soundness	Clear understanding of risks
Maintainability	Modular architecture reduces risk
Future potential	Mitigations support long-term growth
Practical value	Realistic risk planning
Integration potential	Addresses wallet/merchant/operator concerns

Y. Roadmap

XQlyte's roadmap is intentionally designed so that the **Hackathon MVP is already extremely powerful**, already solves the core Fiber UX problems, and already demonstrates the full value of the diagnostics + confidence engine.

- The MVP is not a “prototype.”

It is a **real, working infrastructure product**.

Everything after the MVP is simply expansion.

Phase 1 — Hackathon MVP

This MVP is fully functional, production-grade, and solves the core Fiber problems.

Core Deliverables (ALL completed for MVP)

1. Rust Core Engine (COMPLETE)

- Fully modular analyzers

- Deterministic confidence model
- Failure taxonomy
- Suggestion engine
- High-performance async runtime

2. RPC Layer (COMPLETE)

- Channel RPC
- Route RPC
- Asset RPC
- Node RPC
- Fee RPC
- Swap RPC
- Retry logic
- Caching layer

3. Core Analyzers (COMPLETE)

- **Route Analyzer** (multi-hop, stability, fallback routes)
- **Asset Analyzer** (multi-asset, swap-aware)
- **Liquidity Analyzer** (inbound/outbound, direction-aware)
- **Fee Analyzer** (fee-to-amount ratio, bottleneck detection)

4. Confidence Model (COMPLETE)

- 0–100 scoring
- multi-factor scoring
- risk penalties
- thresholds (CAN_PAY, CANNOT_PAY, UNKNOWN)

5. Failure Taxonomy (COMPLETE)

- 8 categories
- human-readable + technical reasons
- mapped to RPC errors

6. Suggestion Engine (COMPLETE)

- actionable fixes
- retry strategies
- asset recommendations
- route alternatives

7. SDKs (COMPLETE)

- Rust SDK
- JS/WASM SDK
- typed interfaces
- simple API (`can_pay`, `diagnose_failure`, etc.)

8. CLI Tool (COMPLETE)

- `can-pay`
- `diagnose`
- `route`
- `asset`
- `liquidity`
- `node`
- structured output

9. Telegram Bot (COMPLETE)

- `/canpay`
- `/whyfail`
- `/bestasset`
- `/bestroute`
- simple UX

10. Dashboard MVP (COMPLETE)

- Overview page
- Failure explorer
- Basic route analytics
- Basic asset analytics
- Basic liquidity analytics

MVP Goals (ALL achieved)

- Fully functional “Can I pay?” engine
- Fully functional diagnostics engine
- Fully functional confidence scoring
- Fully functional CLI
- Fully functional Telegram bot
- Fully functional dashboard (MVP)
- Fully functional SDKs
- Fully functional RPC integration
- This MVP is **not** a demo.

It is **real infrastructure**.

Hackathon Submission Package (COMPLETE)

- Full PRD (this document)
- Architecture diagrams
- Flowcharts
- API documentation
- SDK documentation
- CLI documentation
- Dashboard screenshots
- Demo video
- GitHub repository
- Installation instructions
- Example integrations (wallet plugin demo)

This is a **complete, polished submission**.

Phase 2 — Post-Hackathon Expansion

These are enhancements, not required for MVP.

Engine Enhancements

- multi-path route scoring
- dynamic asset scoring
- improved swap analysis
- cross-chain diagnostics

Dashboard Enhancements

- advanced route analytics
- liquidity direction heatmaps
- node stability scoring
- merchant pre-check module

SDK Enhancements

- mobile SDK
- TypeScript types

- improved error messages

Phase 3 — Ecosystem Adoption

This phase focuses on integration and partnerships.

Integrations

- wallet integrations
- merchant integrations
- agent integrations
- LSP integrations

Partnerships

- Fiber core team
- node operators
- wallet developers

Advanced Features

- liquidity optimization engine
- route recommendation engine
- asset routing advisor
- cross-chain routing advisor

Phase 4 — Long-Term Vision

XQlyte becomes official Fiber infrastructure.

XQlyte becomes:

- the default diagnostics layer for Fiber
- the standard “Can I pay?” engine
- the intelligence layer for agents
- the analytics layer for operators
- the advisor for merchants
- the optimizer for LSPs

Future Features

- multi-path payment advisor
- programmable payment conditions
- liquidity prediction models
- machine learning route scoring
-

Z. Demo Script

This is the script you will use during the hackathon demo.

It demonstrates **clarity**, **impact**, and **practical value** — all critical for judges.

1. Introduction (30 seconds)

“Hello judges, my name is Temitope, and this is **XQlyte** — the Fiber Payment Diagnostics & Confidence Engine.

XQlyte answers three critical questions:

1. *Can this payment succeed?*
2. *Why did it fail?*
3. *What should I change?*

It is infrastructure — not a wallet — designed for wallets, merchants, agents, and node operators.”

2. Problem Statement (20 seconds)

“Fiber payments fail silently.

Users see ‘Payment failed’ without explanation.

Wallets cannot predict success.

Merchants lose payments.

Agents operate blindly.

Node operators lack diagnostics.

XQlyte solves this.”

3. Live Demo — “Can I Pay?” (40 seconds)

Open CLI:

Code

```
xqlyte can-pay --from alice --to bob --amount 10 --asset USDT
```

Output:

Code

✓ CAN_PAY

Confidence: 92%

Best route: alice → nodeA → nodeB → bob

Fee: 0.01 USDT

Explain:

“This is the first payment confidence engine in the Fiber ecosystem.”

4. Live Demo — Failure Diagnostics (40 seconds)

Code

```
xqlyte diagnose --payment-id 0xabc123
```

Output:

Code

✗ CANNOT_PAY

Reason: Insufficient inbound liquidity at hop 2.

Suggested fix: Receiver must add inbound liquidity.

Explain:

“XQlyte translates raw RPC errors into human-readable explanations and actionable fixes.”

5. Live Demo — Telegram Bot (30 seconds)

User sends:

“Can I send 5 USDT to Fatima?”

Bot replies:

“✓ Yes, you can pay. Confidence: 88%.”

Explain:

“Non-technical users get instant clarity.”

6. Dashboard Demo (40 seconds)

Show:

- success rate
- failure categories
- route performance
- asset performance
- node stability

Explain:

“This is the first payment health dashboard for Fiber.”

7. Closing (20 seconds)

“XQlyte is the missing intelligence layer for Fiber.

It improves wallet UX, merchant UX, agent autonomy, and node operator visibility.

It is reusable, technically sound, and future-proof.

Thank you.”

AA. Resources

1. Core Fiber Docs

Fiber main docs hub:

- <https://www.fiber.world/docs>

What is Fiber Network?

- <https://www.fiber.world/docs/what-is-fiber-network>

How Fiber Network works (channels, routing, HTLCs):

- <https://www.fiber.world/docs/how-fiber-network-works>

Fiber Network Node (FNN) & running a node:

- <https://www.fiber.world/docs/fiber-network-node>

Payment channels & multi-hop routing details:

<https://www.fiber.world/docs/payment-channels>

- <https://www.fiber.world/docs/multi-hop-routing>

Assets & multi-asset payments (RGB++, stablecoins, etc.):

- <https://www.fiber.world/docs/assets>

2. Developer & Integration Resources

Developer overview / building on Fiber:

- <https://www.fiber.world/docs/developer-overview>

RPC & node interaction (for XQlyte's engine):

<https://www.fiber.world/docs/reference/rpc>

- <https://www.fiber.world/docs/reference>

Simulators & visual tools (for understanding channels & routing):

<https://www.fiber.world/docs/simulator>

- <https://www.fiber.world/docs/tools>

Examples & tutorials (good for grounding XQlyte flows):

<https://www.fiber.world/docs/tutorials>

- <https://www.fiber.world/docs/examples>

3. Hackathon & Ecosystem Context

Gone in 60ms: Fiber Network Infrastructure Hackathon announcement:

- <https://talk.nervos.org/t/gone-in-60ms-fiber-network-infrastructure-hackathon-announcement/10418>

Fiber showcase (to position XQlyte vs existing tools):

- <https://www.fiber.world/showcase>

