Bug Report

Nexo InOuty frontend: defects found while adding automated tests

24 October 2026 · branch `test/coverage`

97	11	43	43
bugs in total	High severity	Medium severity	Low severity

About this report

Every bug below was found while writing automated tests for the frontend (98.9% of lines covered). Each one is **proven by a test** that describes the correct behaviour and currently fails. The test is marked `it.fails` and named in the "Proven by" line. When a bug is fixed, its test starts passing and the test runner flags it, so the marker can be removed.

Severity. High: wrong pay, lost or overwritten data, or a security hole on a main workflow. **Medium**: wrong results in specific situations (time zones, slow connections, timing), misleading screens, or security issues with limited reach. **Low**: display, wording, accessibility or example-page problems.

Effect says what goes wrong for the business or the user. **What happens** is the observed behaviour in the test. Some bugs depend on how the backend behaves and are marked "needs backend confirmation".

Bugs by area

Area	High	Medium	Low	Total
Core library & API helpers	1	5	9	**15**
Face-recognition clock-in	2	7	3	**12**
Clock-in, history & employees	5	12	6	**23**
New planning	1	3	2	**6**
View planning & shifts	1	4	2	**7**
Reporting & payroll	1	8	6	**15**
Admin, sign-in & kiosk	–	1	5	**6**
UI kit, forms & help	–	3	10	**13**

All bugs at a glance

ID	Severity	Area	Bug
BUG-015	**High**	Core library & API helpers	Saving a worktime can overwrite another employee's record
BUG-101	**High**	Face-recognition clock-in	Last night's clock-out becomes today's clock-in on overnight shifts
BUG-102	**High**	Face-recognition clock-in	A clock-out after an overnight shift's end time is lost
BUG-206	**High**	Clock-in, history & employees	Leaving early on a shift that ends after midnight counts ~21 hours of overtime
BUG-209	**High**	Clock-in, history & employees	Clocking in on a second shift overwrites the first shift's record
BUG-217	**High**	Clock-in, history & employees	Adding a punch on the history page wipes the day's penalty, consumption and bonus
BUG-218	**High**	Clock-in, history & employees	The history page counts lateness and overtime from midnight
BUG-221	**High**	Clock-in, history & employees	Editing a punch shows its UTC time, and saving it moves the punch an hour
BUG-302	**High**	New planning	Saving while the next day is loading writes the previous day's planning onto it
BUG-406	**High**	View planning & shifts	Backups saved by the planning editor never appear in View Planning
BUG-503	**High**	Reporting & payroll	The employee page sends a zero or negative weekly advance
BUG-001	**Medium**	Core library & API helpers	Date ranges start a day early in time zones behind UTC
BUG-003	**Medium**	Core library & API helpers	Plans on the first day of a range are missed in time zones behind UTC
BUG-007	**Medium**	Core library & API helpers	The login token is sent to any host whose address starts like the API's
BUG-009	**Medium**	Core library & API helpers	A refused refresh token is sent a second time
BUG-012	**Medium**	Core library & API helpers	A delete answered with "204 No Content" is reported as a failure
BUG-103	**Medium**	Face-recognition clock-in	A punch at exactly 00:00 counts as "no punch"
BUG-104	**Medium**	Face-recognition clock-in	Shifts ending before 16:00 never get overtime
BUG-105	**Medium**	Face-recognition clock-in	No overtime after midnight for a shift ending at 00:00
BUG-106	**Medium**	Face-recognition clock-in	A failed load says "No shifts found" and hides the error
BUG-109	**Medium**	Face-recognition clock-in	The saved delay is not the delay shown on screen
BUG-110	**Medium**	Face-recognition clock-in	Marking someone with machine punches absent still saves their hours
BUG-111	**Medium**	Face-recognition clock-in	New machine punches never appear while the page is open
BUG-202	**Medium**	Clock-in, history & employees	After a failed save, the employees list shows the error instead of the employees
BUG-205	**Medium**	Clock-in, history & employees	A failed load says "No shifts found" instead of showing the error
BUG-207	**Medium**	Clock-in, history & employees	Arriving after midnight on a night shift isn't counted as late
BUG-208	**Medium**	Clock-in, history & employees	The delay saved to the server isn't the one the page shows
BUG-210	**Medium**	Clock-in, history & employees	"Reset" only clears the screen; the times come back on reload
BUG-211	**Medium**	Clock-in, history & employees	After changing the date, the new day's times are stored under the first day
BUG-212	**Medium**	Clock-in, history & employees	Changing the date while a change is being saved crashes the page

ID	Severity	Area	Bug
BUG-213	**Medium**	Clock-in, history & employees	The page opens on yesterday between midnight and 1 am
BUG-215	**Medium**	Clock-in, history & employees	A saved change still counts as "unsaved" after reload and hides the server's newer times
BUG-219	**Medium**	Clock-in, history & employees	Worked hours run from the first to the last punch, so breaks are paid
BUG-220	**Medium**	Clock-in, history & employees	Adding a punch between midnight and 1 am fails after saving it
BUG-222	**Medium**	Clock-in, history & employees	Punches between midnight and 1 am are grouped with the previous day
BUG-301	**Medium**	New planning	Typing a new main employee without picking him shows his name but keeps the old employee
BUG-305	**Medium**	New planning	An employee listed twice in an imported file is added twice to the same cell
BUG-306	**Medium**	New planning	PDF import puts employees of unlisted hours into the previous hour's shift
BUG-401	**Medium**	View planning & shifts	A slow answer for the previous day replaces the planning of the selected day
BUG-402	**Medium**	View planning & shifts	In time zones ahead of Algeria, a picked day shows the previous day's planning
BUG-403	**Medium**	View planning & shifts	Deleting a shift that is still in use never asks to force the delete
BUG-405	**Medium**	View planning & shifts	A slow Active list replaces the Archived list after switching tabs
BUG-501	**Medium**	Reporting & payroll	A slow answer for a previous range replaces the range chosen last
BUG-502	**Medium**	Reporting & payroll	When the planning can't be loaded, the payroll and weekly advances lists are empty
BUG-504	**Medium**	Reporting & payroll	A double click on "Give Advance" gives the advance twice
BUG-506	**Medium**	Reporting & payroll	Hours worked by an employee without a planning entry are left out of the payroll
BUG-507	**Medium**	Reporting & payroll	West of UTC, picked weeks start a day early or last 6 days
BUG-508	**Medium**	Reporting & payroll	Advances and bonuses are deleted with one click, without confirmation
BUG-513	**Medium**	Reporting & payroll	Typing a week start on the employee page scrambles the date
BUG-515	**Medium**	Reporting & payroll	The attendance page loads two different weeks on open, and the slower one wins
BUG-605	**Medium**	Admin, sign-in & kiosk	Sign-in can redirect to another site through `?next=`
BUG-701	**Medium**	UI kit, forms & help	The Modal's close button has no accessible name
BUG-702	**Medium**	UI kit, forms & help	The Modal isn't exposed as a dialog
BUG-708	**Medium**	UI kit, forms & help	"Close" in a modal form submits the form
BUG-002	**Low**	Core library & API helpers	A company setting of 0 is ignored
BUG-004	**Low**	Core library & API helpers	Date filters in the URL aren't validated
BUG-005	**Low**	Core library & API helpers	Negative durations are converted wrongly
BUG-006	**Low**	Core library & API helpers	Non-numeric values become NaN in worktime rows
BUG-008	**Low**	Core library & API helpers	A failed branding request is cached until the page is reloaded
BUG-010	**Low**	Core library & API helpers	Downloading a file whose name contains "%" fails
BUG-011	**Low**	Core library & API helpers	A manager or admin with no company can open the activity log
BUG-013	**Low**	Core library & API helpers	Worktime responses are printed to the browser console
BUG-014	**Low**	Core library & API helpers	Errors from `shifts.api.ts` and `worktime.api.ts` show raw server text

ID	Severity	Area	Bug
BUG-107	**Low**	Face-recognition clock-in	With no employees the table says "Loading attendance..." for ever
BUG-108	**Low**	Face-recognition clock-in	A failed save shows "✓ Saved" for employees with machine punches
BUG-112	**Low**	Face-recognition clock-in	Machine logs and saved payloads are printed to the browser console
BUG-201	**Low**	Clock-in, history & employees	The "Last Name" column sorts by first name
BUG-203	**Low**	Clock-in, history & employees	Deleting the last employee on the last page leaves an empty page
BUG-204	**Low**	Clock-in, history & employees	The employee form's fields have no accessible names
BUG-214	**Low**	Clock-in, history & employees	A backup who is also planned on the shift is listed twice
BUG-216	**Low**	Clock-in, history & employees	The machine status always comes from http://localhost:3001
BUG-223	**Low**	Clock-in, history & employees	A punch without an id shows an open time editor instead of its time
BUG-303	**Low**	New planning	Days are off by one when the browser is in a time zone ahead of Algiers
BUG-304	**Low**	New planning	A failed day in "Save to every / next weekday" shows the raw server reply
BUG-404	**Low**	View planning & shifts	A failed shift delete shows the raw technical error
BUG-407	**Low**	View planning & shifts	"Today" and the day arrows don't move the mini calendar, so the selected day can't be seen
BUG-505	**Low**	Reporting & payroll	A failed "Undo" on the employee page is silent
BUG-509	**Low**	Reporting & payroll	Total hours show floating-point noise
BUG-510	**Low**	Reporting & payroll	The month picker ignores the month being shown
BUG-511	**Low**	Reporting & payroll	The bonus totals row mixes filtered and unfiltered figures
BUG-512	**Low**	Reporting & payroll	The Overview shows a rise as a fall when the previous value was negative
BUG-514	**Low**	Reporting & payroll	The employee page shows "0" in the Absent column for days worked
BUG-601	**Low**	Admin, sign-in & kiosk	A cancelled password reset pre-fills the next user's new password
BUG-602	**Low**	Admin, sign-in & kiosk	Clicking "Next" right after the list loads jumps back to page 1
BUG-603	**Low**	Admin, sign-in & kiosk	A kiosk account is stuck on "Loading..." when the company has clock-in switched off
BUG-604	**Low**	Admin, sign-in & kiosk	The kiosk list's loading text isn't translated
BUG-606	**Low**	Admin, sign-in & kiosk	The profile page shows a made-up person and its Save does nothing
BUG-703	**Low**	UI kit, forms & help	MultiSelect's arrow button never opens the list
BUG-704	**Low**	UI kit, forms & help	Removing a MultiSelect chip opens the option list
BUG-705	**Low**	UI kit, forms & help	A disabled MultiSelect still lets you remove options
BUG-706	**Low**	UI kit, forms & help	Switch can't be used with the keyboard
BUG-707	**Low**	UI kit, forms & help	PhoneInput always starts on the US prefix
BUG-709	**Low**	UI kit, forms & help	"Okay, Got It" doesn't close the alert modals
BUG-710	**Low**	UI kit, forms & help	The language menu can't be closed with Escape
BUG-711	**Low**	UI kit, forms & help	The theme toggle buttons have no accessible name
BUG-712	**Low**	UI kit, forms & help	Tooltips can't be seen with the keyboard
BUG-713	**Low**	UI kit, forms & help	The header's "more" button on phones has no name or state

High severity · details

11 bugs, sorted by ID.

BUG-015 Saving a worktime can overwrite another employee's record — HIGH

Area	Core library & API helpers
Effect	**Clock-ins can overwrite another employee's worked hours. That employee's day is lost from payroll, and wages are paid on the wrong data.**
What happens	`existing[0]` is updated whatever it is. `src/lib/reporting.ts` says "The API ignores ?empId and returns every employee's rows". If `/worktime` also ignores `emp_id`/`work_date`, the first record in the database is overwritten by every clock-in.
Steps to reproduce	`upsertWorktime({ emp_id: 101, work_date: "2026-03-01" })` with no known id. The search `GET /worktime?emp_id=101&work_date=2026-03-01` returns a record for employee 202.
Expected	Only a record with the same `emp_id` and `work_date` is updated. Otherwise a new one is created.
Where	`src/components/tables/worktime.api.ts`, `upsertWorktime`
Type	Data-loss
Severity note	needs backend confirmation
Suggested fix	`existing.find(r => String(r.emp_id) === String(payload.emp_id) && r.work_date?.split("T")[0] === payload.work_date)`. Also check whether the backend applies these filters.
Proven by	`worktime.api.test.ts` › "never updates another employee's record"

BUG-101 Last night's clock-out becomes today's clock-in on overnight shifts — HIGH

Area	Face-recognition clock-in
Effect	**On night shifts, the wrong clock-in and clock-out times are paired and saved automatically, so employees are paid for the wrong hours.**
What happens	Clock-in 01:30, no clock-out, 14:30 worked, Pending. When any shift crosses midnight, every punch on the operation date counts, including the early-morning punches that close the previous night's shift. All IN/OUT pairs after it are shifted by one, so the hours, delay and overtime are wrong every day for overnight workers. These wrong values are also saved to the worktime automatically.
Steps to reproduce	Shift 16:00 → 02:00. Operation date 2026-03-10. Machine logs for employee 101: `2026-03-10T01:30` (clock-out of the 9 March shift), `2026-03-10T16:00`, `2026-03-11T01:45`.
Expected	Clock-in 16:00, clock-out 01:45, 09:45 worked, Present.
Where	`ClockInFaceRecognitionPage.tsx`, `isPunchInsideOperationalDay` (used by `getDeviceAttendanceForOperationalDate` and `deviceLogsToEntries`)
Type	Bug / Payroll
Suggested fix	On the operation date, skip punches before the latest overnight end (they belong to the previous operation day), just as punches after it are skipped on the next date.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "does not take last night's clock-out as today's clock-in"

BUG-102 A clock-out after an overnight shift's end time is lost — HIGH

Area	Face-recognition clock-in
Effect	**Anyone who leaves even a minute after a night shift ends gets no clock-out. Their overtime is never recorded and the next day's times are shifted.**
What happens	The 02:10 punch is dropped (no clock-out, 00:00 hours, Pending). Next-day punches are only kept up to the exact shift end, with no margin. Anyone leaving even one minute late never gets a clock-out, and that punch is then read as the first punch (clock-in) of the next operation day. Overtime after an overnight shift can never be recorded, although `calcOvertime` is written to handle it. For a shift ending at 00:00 the window is zero minutes, so every clock-out after midnight is lost.
Steps to reproduce	Shift 16:00 → 02:00. Punches `2026-03-10T16:00` and `2026-03-11T02:10`.
Expected	Clock-out 02:10, 10:10 worked, 00:10 overtime, Present.
Where	`ClockInFaceRecognitionPage.tsx`, `isPunchInsideOperationalDay` (`parsed.minutes <= overnightEnd`)
Type	Bug / Payroll
Suggested fix	Keep next-day punches up to the shift end plus a margin (e.g. until the earliest next shift start, or a fixed number of hours). Pair punches per shift, not per calendar window.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "keeps a clock-out made a few minutes after an overnight shift ends"

BUG-206 Leaving early on a shift that ends after midnight counts ~21 hours of overtime — HIGH

Area	Clock-in, history & employees
Effect	**Leaving early on a shift that ends after midnight is recorded as about 21 hours of overtime, a large overpayment.**
What happens	Overtime 21:00 (1260 minutes). Only a shift ending exactly at 00:00 is treated as overnight; for 02:00 the clock-out 23:00 is compared with 02:00 of the same day.
Steps to reproduce	Shift 18:00–02:00, clock-in 18:00, clock-out 23:00.
Expected	Overtime 00:00.
Where	`src/components/tables/ClockInPage.tsx`, `calcOvertime` (used for the table and for the saved `overtime_minutes`)
Type	Bug (payroll)
Suggested fix	Treat the shift as overnight when `end < start` and add 1440 to the end, and to a clock-out earlier than the start.
Proven by	`ClockInPage.test.tsx` › "gives no overtime for leaving early on a shift that ends after midnight"

BUG-209 Clocking in on a second shift overwrites the first shift's record — HIGH

Area	Clock-in, history & employees
Effect	**Employees working two shifts in one day lose their first shift's hours when they clock in for the second.**
What happens	The page keeps one entry per employee **and shift**, but the evening entry has no id yet, so `upsertWorktime` searches by `emp_id` + `work_date` only, finds `w1` and `PUT`s over it: `w1` becomes shift `s2`, clock-in 17:00. The morning hours are lost. This happens even when the backend filters correctly; with BUG-015 (backend ignoring the filters) any employee's record can be hit. So this page makes BUG-015 worse rather than working around it.
Steps to reproduce	Ali is planned on 08:00–16:00 and 17:00–23:00. His morning record `w1` (shift `s1`, 08:00–12:00) is saved. At 17:00 he clocks in on the evening tab.
Expected	A new record for shift `s2` (`POST /worktime`); `w1` is unchanged.
Where	`src/components/tables/ClockInPage.tsx`, `scheduleSave` → `upsertWorktime` (`worktime.api.ts`)
Type	Data-loss
Suggested fix	Include `shift_id` in the search (and check it on the result) when the caller works per shift, or pass the known id of the shift's record.
Proven by	`ClockInPage.test.tsx` › "keeps a separate record for each shift of the day"

BUG-217 Adding a punch on the history page wipes the day's penalty, consumption and bonus — HIGH

Area	Clock-in, history & employees
Effect	**Adding a missing punch silently erases the day's penalty, consumption and bonus, so pay goes up wrongly.**
What happens	Both are overwritten with 0 (and `bonus` too). `saveEditedPunch` explicitly keeps these fields from the existing worktime; `addPunch` always sends the form's values.
Steps to reproduce	The day's worktime has `penalty: 500, consomation: 300`. Add the clock-out punch with the form left at its defaults (0).
Expected	The penalty and consumption stay 500 and 300.
Where	`src/components/tables/ClockInPageHistory.tsx`, `addPunch` (`worktimePayload`)
Type	Data-loss (payroll)
Suggested fix	Read the existing worktime as `saveEditedPunch` does and only send the form's values when they were filled in (or add them to the existing ones).
Proven by	`ClockInPageHistory.test.tsx` › "keeps the day's penalty and consumption when a punch is added"

BUG-218 The history page counts lateness and overtime from midnight — HIGH

Area	Clock-in, history & employees
Effect	**On the history page, every edit saves huge lateness and overtime values (a clock-in at 08:10 saves 490 minutes late), which corrupts payroll.**
What happens	`late_minutes: "490"`. The page reads `start_time`/`end_time`, which don't exist, so both fall back to `"00:00"`: every clock-in is "late" by its time of day and every clock-out is overtime from midnight (editing 08:00→16:30 saves late 540 min, overtime 990 min, and the success toast says so).
Steps to reproduce	`GET /shifts` returns `{ _id: "s1", startTime: "08:00", endTime: "16:00" }` (the `ShiftRecord` shape in `calendar/types.ts`, also read by `ClockInPage`). The employee is planned on it. Add a clock-in at 08:10 on the history page.
Expected	`late_minutes: "10"`.
Where	`src/components/tables/ClockInPageHistory.tsx`, `addPunch` and `saveEditedPunch` (`shift.start_time` / `shift.end_time`)
Type	Bug (payroll)
Suggested fix	Read `shift.startTime ?? shift.start_time` and `shift.endTime ?? shift.end_time` (or reuse the mapping in `ClockInPage`).
Proven by	`ClockInPageHistory.test.tsx` › "measures the delay from the shift start sent by the API"

BUG-221 Editing a punch shows its UTC time, and saving it moves the punch an hour — HIGH

Area	Clock-in, history & employees
Effect	**Opening a punch and saving it without changes moves it one hour earlier, which changes the day's hours, delay and overtime.**
What happens	It opens on 07:00, the UTC time. Clicking ✓ without changing anything saves `new Date("2026-03-09T07:00:00")` local = 06:00Z, so the punch moves one hour earlier and the day's hours, delay and overtime are recalculated from the wrong time.
Steps to reproduce	A punch `2026-03-09T07:00:00.000Z`, shown as 08:00. Double-click it.
Expected	The editor opens on 08:00.
Where	`src/components/tables/ClockInPageHistory.tsx`, the `onDoubleClick` handlers (`rawLog.timestamp.substring(11, 16)`)
Type	Data-loss
Suggested fix	Pre-fill with `formatTime(rawLog.timestamp)` (the Algiers time the table shows), and build the new timestamp in the same time zone.
Proven by	`ClockInPageHistory.test.tsx` › "opens the editor on the time shown in the table"

BUG-302 Saving while the next day is loading writes the previous day's planning onto it — HIGH

Area	New planning
Effect	**Saving while the next day is loading copies the previous day's planning onto it and erases the real one, without anything on screen showing it.**
What happens	`currentDate` is already the 25th but `grid` still holds the 24th, so `POST /planning/bulk` sends Alice with `planDate: "2026-10-25"`, replacing the 25th's real planning. The grid of the 24th stays on screen while loading, so the user can't tell.
Steps to reproduce	Saturday 24 has Alice planned. Click "next day" and, before `GET /planning/import/2026-10-25` answers, click Save.
Expected	Nothing is saved for the 25th until its planning is loaded (or Save is disabled while `loadingGrid` is true).
Where	`src/hooks/useNewPlanning.ts`, `handleSavePlanning` (also `handleSaveToAllWeekdays` / `handleSaveToNextWeekdays`); `src/components/calendar/NewPlanning.tsx`, the Save buttons
Type	Data-loss
Suggested fix	Disable the three Save buttons while `loadingGrid` is true and return early in the save handlers when it is; better, clear the grid (or store the date the grid belongs to) when the date changes and save with that date.
Proven by	`useNewPlanning.save.test.tsx` › "does not save the previous day's employees onto a day that is still loading"

BUG-406 Backups saved by the planning editor never appear in View Planning — HIGH

Area	View planning & shifts
Effect	**Backups chosen in the planning editor never show in View Planning, so staff don't know who covers for whom.**
What happens	The cell shows only "Ali Ben". In table-only mode it says "Backup: No backup". The hook builds `cell.backups` correctly, but the component only shows `backupTitle`, which comes from the legacy `backupEmpId` field. `types.ts` says that field will be removed after the migration. Once it is, View Planning never shows a backup again.
Steps to reproduce	A planning entry with `backupEmpIds: [Sara Kaci]` and no `backupEmpId`. This is what `useNewPlanning` saves today (`backupEmpIds: getBackupIds(cell)`).
Expected	The cell shows "Ali Ben (Backup: Sara Kaci)".
Where	`src/components/calendar/ViewPlanning.tsx` (cells, table-only mode and the list modal all read `emp.backupTitle` only)
Type	Bug
Suggested fix	Render `emp.backups` (all of them, joined by ", ") and use `backupTitle` only when `backups` is empty.
Proven by	`ViewPlanning.test.tsx` › "shows the backups saved with the planning"

BUG-503 The employee page sends a zero or negative weekly advance — HIGH

Area	Reporting & payroll
Effect	**A negative 'advance' can be given, and it then increases the employee's net pay at month end. Zero advances are also recorded.**
What happens	`POST /advances { amount: -200 }`, toast "Advance given.", and the week shows "Advance given". At month end net = … − advances, so a −200 advance adds 200 DA to the take-home pay. A week without hours posts an advance of 0 and marks the week as given.
Steps to reproduce	Employee at 200 DA/h worked 8 h this week and consumed 2 000 DA. The offer is (1 600 − 2 000) × 0.5 = −200. Click "Give Advance" on their page.
Expected	Nothing is sent, or a message says there is nothing to advance. The list page's modal already refuses amounts ≤ 0.
Where	`src/hooks/useEmployeeReport.ts`, `giveAdvance`; button in `src/components/reporting/EmployeeDetailView.tsx` (`WeeklyAdvanceTab`)
Type	Bug (pay)
Suggested fix	Return (with a message) when `weekAdvanceOffer <= 0`, and disable the button in that case.
Proven by	`useEmployeeReport.test.ts` › "never sends an advance of zero or less"

Medium severity · details

43 bugs, sorted by ID.

BUG-001 Date ranges start a day early in time zones behind UTC — MEDIUM

Area	Core library & API helpers
Effect	**For companies west of UTC, reports and payroll periods cover the wrong days: one day too early, and the last day is missing.**
What happens	`["2026-02-28", "2026-03-01"]`. `new Date("YYYY-MM-DD")` is UTC midnight, but the loop reads local dates. This is the same kind of bug the file's own comment on `toLocalDateString` warns about. Correct in Algeria (UTC+1), but companies have a `utcOffset` setting.
Steps to reproduce	Time zone `America/New_York`, `generateDateRange("2026-03-01", "2026-03-02")`.
Expected	`["2026-03-01", "2026-03-02"]`
Where	`src/lib/reporting.ts`, `generateDateRange` (used by `fillMissingDates`)
Type	Bug
Severity note	only for companies west of UTC
Suggested fix	Parse with `new Date(y, m - 1, d)` or `new Date(`${start}T00:00:00`)`.
Proven by	`reporting.test.ts` › "starts on the requested day in a time zone behind UTC"

BUG-003 Plans on the first day of a range are missed in time zones behind UTC — MEDIUM

Area	Core library & API helpers
Effect	**For companies west of UTC, employees planned on the first day of a period are treated as not scheduled. They can be left off payroll lists.**
What happens	Not counted. The plan's UTC midnight is 19:00 on Feb 28 local time, which is outside the local range. Plans on the day after the range are counted instead.
Steps to reproduce	Time zone `America/New_York`, plan `planDate: "2026-03-01T00:00:00.000Z"`, range March.
Expected	Employee counted as scheduled.
Where	`src/lib/reporting.ts`, `fetchScheduledEmpIds`
Type	Bug
Severity note	only for companies west of UTC
Suggested fix	Compare date strings: `r.planDate.split("T")[0]` between `range.start` and `range.end`.
Proven by	`reporting.test.ts` › "counts a plan on the first day of the range in a time zone behind UTC"

BUG-007 The login token is sent to any host whose address starts like the API's — MEDIUM

Area	Core library & API helpers
Effect	**The login token can leak to a look-alike server. Whoever holds it can act as the signed-in user, for example to read payroll or change data.**
What happens	`url.startsWith(origin)` matches, so the bearer token and the acting company id are sent to the other host. The hard-coded `http(s)://localhost:3001` origins also get the token in production.
Steps to reproduce	API at `https://api.test`, then `fetch("https://api.test.evil.com/x")`.
Expected	No `Authorization` header.
Where	`src/lib/auth.ts`, `isApiUrl`
Type	Security
Suggested fix	Compare `new URL(url).origin === new URL(API_BASE_URL).origin`. Only allow the localhost origins in development.
Proven by	`auth.test.ts` › "does not send the token to a host that only starts with the API address"

BUG-009 A refused refresh token is sent a second time — MEDIUM

Area	Core library & API helpers
Effect	**If the backend detects refresh-token reuse, users can be signed out of all their devices at once, at random-looking moments.**
What happens	Two `/auth/refresh` calls with the same refresh token. With token rotation, reusing a refresh token often counts as theft and can end all of that user's sessions.
Steps to reproduce	The access token expires in under 30 s, so the early renewal runs and `/auth/refresh` answers 401. The request then goes out with the old token and gets `TOKEN_EXPIRED`.
Expected	One refresh call, then sign-in.
Where	`src/lib/auth.ts`, `installAuthFetch` and `refreshTokens`
Type	Bug / Security
Severity note	Low if the backend has no reuse detection
Suggested fix	If the early renewal returns `false`, sign out (or skip the second refresh).
Proven by	`auth.test.ts` › "tries the refresh token only once when it is refused"

BUG-012 A delete answered with "204 No Content" is reported as a failure — MEDIUM

Area	Core library & API helpers
Effect	**Deletes that actually worked are shown as failures. Users retry or report problems, and the screen no longer matches the database.**
What happens	`[worktime] 204 - Empty response from /worktime/w1` / `SyntaxError: Unexpected end of JSON input`. The record is deleted, but the UI shows an error.
Expected	The delete succeeds.
Where	`worktime.api.ts` `request()` (throws "Empty response"), `employee.api.ts` `request()` (`res.json()` on an empty body)
Type	Bug
Severity note	depends on the backend; it may return JSON today
Suggested fix	Use `fetchJson` from `src/lib/errors.ts`, which already handles empty bodies.
Proven by	`worktime.api.test.ts` and `employee.api.test.ts` › "treats an empty 204 delete as success"

BUG-103 A punch at exactly 00:00 counts as "no punch" — MEDIUM

Area	Face-recognition clock-in
Effect	**A real clock-out at exactly midnight is ignored. The day stays 'Pending' and the hours are not saved.**
What happens	"No punch", 00:00 hours, Pending, and no `clock_out` is saved. The time 00:00 is also the "not set" marker, so a real punch at 00:00–00:00:59 is lost. A first punch at 00:00 stops the machine save completely ("MACHINE SAVE SKIPPED - no clock-in").
Steps to reproduce	Shift 16:00 → 00:00. Punches `2026-03-10T16:00` and `2026-03-11T00:00`.
Expected	Clock-out 00:00, 08:00 worked, Present.
Where	`ClockInFaceRecognitionPage.tsx`, `"00:00"` used as the "empty" value in `deviceLogsToEntries`, `calcHoursFromPeriods`, `getStatus`, `entryToPayload`, the machine save
Type	Bug
Suggested fix	Use `null`/`""` for "not set" instead of `"00:00"`.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "counts a clock-out at midnight"

BUG-104 Shifts ending before 16:00 never get overtime — MEDIUM

Area	Face-recognition clock-in
Effect	**Morning shifts (ending before 16:00) never earn overtime, so employees are underpaid.**
What happens	00:00. Any shift ending before 16:00 is treated as an overnight shift, so its end becomes 24 h later and overtime is never positive. This affects all morning shifts.
Steps to reproduce	Shift 06:00 → 14:00. Punches 06:00 and 15:00.
Expected	Overtime 01:00 (on screen and in `overtime_minutes`).
Where	`ClockInFaceRecognitionPage.tsx`, `calcOvertime` (`if (endMinutes < toMinutes("16:00")) endMinutes += 1440`)
Type	Bug
Severity note	payroll
Suggested fix	Decide "overnight" from the shift itself (`end < start`), not from a fixed 16:00 cut-off. Pass the shift start to `calcOvertime`.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "gives overtime to someone leaving late from a morning shift"

BUG-105 No overtime after midnight for a shift ending at 00:00 — MEDIUM

Area	Face-recognition clock-in
Effect	**Staff on shifts ending at midnight are never paid overtime for time worked after midnight.**
What happens	00:00. The end becomes 1440, but the clock-out is only moved to the next day when the end is *greater* than 1440, so 00:30 counts as 30 minutes after the previous midnight. The function's comment says it handles "16:00 -> 00:00".
Steps to reproduce	Shift 16:00 → 00:00. Saved worktime with clock-in 16:00, clock-out 00:30.
Expected	Overtime 00:30.
Where	`ClockInFaceRecognitionPage.tsx`, `calcOvertime` (`actualOut < 12:00 && endMinutes > 1440`)
Type	Bug
Severity note	payroll
Suggested fix	Use `endMinutes >= 1440`, or better, the fix of BUG-104.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "gives overtime to someone leaving after a shift that ends at midnight"

BUG-106 A failed load says "No shifts found" and hides the error — MEDIUM

Area	Face-recognition clock-in
Effect	**When loading fails, managers are told to create shifts that already exist, and the real error stays hidden.**
What happens	"No shifts found. Add shifts in Shifts Management first." The error message is set but never shown. The manager is sent to create shifts that already exist.
Steps to reproduce	`GET /employees` answers 500 (or `/shifts` fails, or the network is down).
Expected	"Couldn't load today's data. …"
Where	`ClockInFaceRecognitionPage.tsx`, render (`if (!loading && !shifts.length) return …`), placed before the error banner
Type	Bug / UX
Suggested fix	Show `apiError` (with a retry) before the "no shifts" message, and only show "no shifts" when the shifts were loaded.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "explains when the day's data can't be loaded"

BUG-109 The saved delay is not the delay shown on screen — MEDIUM

Area	Face-recognition clock-in
Effect	**Employees are penalised for lateness they didn't have (the screen shows 5 minutes late, but 125 minutes are saved).**
What happens	Screen shows 00:05, `late_minutes: "125"` is saved. Payroll penalises the employee for 2 hours they were not expected to work. Overtime has the same problem with the task end time.
Steps to reproduce	Shift 08:00 → 17:00. Planning task for the employee 10:00 → 17:00. Clock-in 10:05.
Expected	Screen and `late_minutes` both 5.
Where	`ClockInFaceRecognitionPage.tsx`, machine save and `scheduleSave` call `entryToPayload(…, shift.start_time, shift.end_time)`; the table uses `specialTimes` (the planned task's times)
Type	Bug
Severity note	payroll
Suggested fix	Compute the payload's start/end the same way as the table (`specialTimes[...] ?? shift times`), ideally with one shared helper.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "saves the same delay as the one shown"

BUG-110 Marking someone with machine punches absent still saves their hours — MEDIUM

Area	Face-recognition clock-in
Effect	**An employee marked absent is still paid for the hours from the machine.**
What happens	`absent: true`, `work_hours: "08:00"`. Clock-in/out are cleared but the machine periods are kept, and the hours are recomputed from them.
Steps to reproduce	Punches 08:00 and 16:00 for employee 101 (saved automatically), then switch on "Absent".
Expected	Saved with `absent: true`, `work_hours: "00:00"`.
Where	`ClockInFaceRecognitionPage.tsx`, `toggleAbsent` / `confirmAbsence` with `entryToPayload` (hours recomputed from `entry.periods`)
Type	Bug
Severity note	payroll
Suggested fix	Clear `periods` and `workHours` when marking absent, or send `work_hours: "00:00"` whenever `absent` is true.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "does not save worked hours for an absent employee"

BUG-111 New machine punches never appear while the page is open — MEDIUM

Area	Face-recognition clock-in
Effect	**New punches from the clocking machine don't appear and aren't saved until someone reloads the page.**
What happens	The logs are fetched once. The minute timer only re-reads them if the operation date changes, and the machine status is polled every 30 s but not the logs. New punches are neither shown nor saved until someone reloads the page. The auto-save comment ("Every time the machine produces a new punch sequence … we call upsertWorktime()") cannot happen.
Steps to reproduce	Open the page with one punch (08:00). The machine records 12:05. Wait 5 minutes.
Expected	The page reads the machine again, shows clock-out 12:05 and saves it.
Where	`ClockInFaceRecognitionPage.tsx`, the "LOAD WORKTIME + MACHINE ATTENDANCE" effect (only runs when the date, employees, shifts or planning change)
Type	Bug
Suggested fix	Poll `getDeviceAttendanceForOperationalDate` (e.g. every 30–60 s) and update `deviceLogs`/`deviceEntries` without clearing the table.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "picks up new machine punches"

BUG-202 After a failed save, the employees list shows the error instead of the employees — MEDIUM

Area	Clock-in, history & employees
Effect	**After one failed save, the employee list disappears behind an error until the page is reloaded.**
What happens	The table shows "⚠ Couldn't save the employee …" in place of every row until the page is reloaded. The same `apiError` state is used for the load error and the save error.
Steps to reproduce	Add an employee, the server refuses (409), click Cancel.
Expected	The list of employees.
Where	`src/components/tables/BasicTableOne.tsx`, `handleSave` (`setApiError`) and the table body
Type	UX
Suggested fix	Keep a separate `saveError` for the drawer (cleared when it closes).
Proven by	`BasicTableOne.test.tsx` › "still lists the employees after a failed save is cancelled"

BUG-205 A failed load says "No shifts found" instead of showing the error — MEDIUM

Area	Clock-in, history & employees
Effect	**When loading fails, managers are told to create shifts that already exist, and the real error stays hidden.**
What happens	"No shifts found. Add shifts in Shifts Management first." The error is set but the early return comes before the banner, so people are sent to create shifts that already exist.
Steps to reproduce	`GET /employees` (or `/shifts`) answers 500.
Expected	"Couldn't load today's data …".
Where	`src/components/tables/ClockInPage.tsx`, the early `if (!loading && !shifts.length) return …`
Type	UX
Suggested fix	Render the error (with a retry) before the "no shifts" message.
Proven by	`ClockInPage.test.tsx` › "shows the load error when the employees can't be loaded"

BUG-207 Arriving after midnight on a night shift isn't counted as late — MEDIUM

Area	Clock-in, history & employees
Effect	**Night-shift staff arriving after midnight are never counted as late.**
What happens	00:00 (`30 - 1320` is negative, so 0).
Steps to reproduce	Shift 22:00–06:00, clock-in 00:30.
Expected	Delay 02:30.
Where	`src/components/tables/ClockInPage.tsx`, `calcLate`
Type	Bug (payroll)
Suggested fix	For an overnight shift, add 1440 to a clock-in earlier than the start when it is before the shift's end.
Proven by	`ClockInPage.test.tsx` › "counts the delay of a clock-in after midnight on a night shift"

BUG-208 The delay saved to the server isn't the one the page shows — MEDIUM

Area	Clock-in, history & employees
Effect	**The lateness saved (and paid against) differs from what the manager sees on screen.**
What happens	It shows 00:05 but saves `"125"` (measured from 08:00). Overtime has the same split (shown against the task end, saved against the shift end).
Steps to reproduce	Shift 08:00–16:00, planning task for Ali 10:00–14:00. He clocks in at 10:05.
Expected	The page shows Delay 00:05 and saves `late_minutes: "5"`.
Where	`src/components/tables/ClockInPage.tsx`, `scheduleSave` (`entryToPayload` gets the shift times) vs. the row render (`specialTimes`)
Type	Bug (payroll)
Suggested fix	Use the same effective start/end (task times when present) in `scheduleSave`/`confirmAbsence` as in the render.
Proven by	`ClockInPage.test.tsx` › "saves the same delay as the one shown"

BUG-210 "Reset" only clears the screen; the times come back on reload — MEDIUM

Area	Clock-in, history & employees
Effect	**'Reset' looks like it worked, but the times come back on reload. Payroll still uses the old times.**
What happens	No request is sent, and the cleared rows even show "✓ Saved". On reload the server's 08:00 is back. Payroll uses the server's copy, so the reset never happened.
Steps to reproduce	Ali's 08:00 clock-in is saved. Click Reset, confirm "All clock-in and clock-out times entered on this page today will be cleared.", reload.
Expected	The times stay cleared.
Where	`src/components/tables/ClockInPage.tsx`, `clearAllData`
Type	Bug
Suggested fix	Save the cleared entries (or delete the records) after confirmation, and mark them unsaved until that succeeds.
Proven by	`ClockInPage.test.tsx` › "doesn't bring the times back after a reset and a reload"

BUG-211	After changing the date, the new day's times are stored under the first day	MEDIUM
Area	Clock-in, history & employees	
Effect	**After switching dates, one day's times are saved under another day in the browser copy, so the wrong day shows as 'Unsaved'.**	
What happens	March 2 shows Ali clocked in at 08:05, "Unsaved". The local copy is written under the `currentDate` prop (the day the page opened), not `selectedDate`, and overwrites that day's copy with the other day's entries. `confirmAbsence` uses `selectedDate` correctly.	
Steps to reproduce	Open the page on March 2, pick March 3, clock Ali in (08:05), reload (back on March 2).	
Expected	March 2 shows Ali as not clocked in.	
Where	`src/components/tables/ClockInPage.tsx`, `updateEntry` (`saveEntriesToStorage(currentDate, …)`)	
Type	Bug	
Suggested fix	`saveEntriesToStorage(selectedDate, next)` (and add `selectedDate` to the dependencies).	
Proven by	`ClockInPage.test.tsx` › "doesn't show another day's clock-ins after a reload"	

BUG-212	Changing the date while a change is being saved crashes the page	MEDIUM
Area	Clock-in, history & employees	
Effect	**Changing the date right after an edit crashes the whole page (blank screen).**	
What happens	The whole page goes blank. The save timer writes `{ _saving: true, _dirty: false }` into the new day's entries; the entry has no `clockIn`, and `calcLate(undefined, …)` throws `Cannot read properties of undefined (reading 'split')` during render. When the save finishes it also puts the old day's record id into the new day's entry, so a later edit would update the old day's record.	
Steps to reproduce	Click Clock In, then pick another date within 0.8 s (before the debounced save starts), on a day where the employee is also planned.	
Expected	The other day's page is shown.	
Where	`src/components/tables/ClockInPage.tsx`, `scheduleSave` (`setEntries` with `prev[k]` of the new day)	
Type	Bug (crash)	
Suggested fix	Flush or cancel pending timers when the date changes, and ignore save results whose date isn't the selected one.	
Proven by	`ClockInPage.test.tsx` › "survives a date change while a clock-in is still being saved"	

BUG-213 The page opens on yesterday between midnight and 1 am — MEDIUM

Area	Clock-in, history & employees
Effect	**Between midnight and 1 am, the page opens on yesterday, so clock-ins go to the wrong day.**
What happens	2026-03-01 (the UTC date), so clock-ins made then go to the previous day's records.
Steps to reproduce	Algeria, March 2 at 00:30.
Expected	The date field shows 2026-03-02.
Where	`src/components/tables/ClockInPage.tsx`, default `currentDate = new Date().toISOString().slice(0, 10)`
Type	Bug
Severity note	only for night shifts
Suggested fix	Build the date from local parts (as `ClockInPageHistory`'s `formatDateForInput` does).
Proven by	`ClockInPage.test.tsx` › "opens on today's local date just after midnight"

BUG-215 A saved change still counts as "unsaved" after reload and hides the server's newer times — MEDIUM

Area	Clock-in, history & employees
Effect	**Newer clock-outs from the server are hidden by an outdated browser copy, and can later be overwritten by it.**
What happens	No clock-out and "Unsaved": the browser's copy still has `_dirty: true`, so the server's record is ignored. The stale entry is never re-sent either, so it stays like this until someone edits the row (which then overwrites the server's clock-out).
Steps to reproduce	Clock Ali in, wait for "✓ Saved". He clocks out on another device (the server now has 16:00). Reload.
Expected	Clock-out 16:00, "✓ Saved".
Where	`src/components/tables/ClockInPage.tsx`, `updateEntry` (stores `_dirty: true`) and `scheduleSave` (never updates the stored copy)
Type	Bug
Suggested fix	After a successful save, store the entry with `_dirty: false`; on load, prefer the server's copy unless the local one is newer.
Proven by	`ClockInPage.test.tsx` › "shows the server's times after a reload once a clock-in was saved"

BUG-219 Worked hours run from the first to the last punch, so breaks are paid — MEDIUM

Area	Clock-in, history & employees
Effect	**Unpaid breaks are counted as worked time, so employees are overpaid.**
What happens	`work_hours: "02:10"`: last punch minus first punch, break included. The table itself pairs the punches into periods, so the data to sum them is there.
Steps to reproduce	Punches 17:00, 18:00, 18:10 and 19:10 (the example in the comment on `upsertWorktime` in `worktime.api.ts`).
Expected	`work_hours: "02:00"`, as that comment says ("17:00 -> 18:00, 18:10 -> 19:10 becomes … work_hours = 02:00").
Where	`src/components/tables/ClockInPageHistory.tsx`, `addPunch` and `saveEditedPunch` ("CALCULATE WORK HOURS")
Type	Bug (payroll)
Severity note	High if breaks are unpaid
Suggested fix	Sum the paired periods (`sorted[i]` → `sorted[i+1]`) instead of last − first.
Proven by	`ClockInPageHistory.test.tsx` › "doesn't count a break between two periods as worked time"

BUG-220 Adding a punch between midnight and 1 am fails after saving it — MEDIUM

Area	Clock-in, history & employees
Effect	**Adding a punch between midnight and 1 am says it failed although it was saved. Retrying creates duplicate punches.**
What happens	The punch is saved (`2026-03-08T23:30Z`), then "Couldn't add the clock-in. The clock-in was saved, but no records were found for this employee." The worktime isn't updated, and trying again adds a duplicate punch. Same cause as BUG-222 (UTC date compared with a local date).
Steps to reproduce	Add a clock-in for March 9 at 00:30.
Expected	"Clock-in added …" and the day's worktime updated.
Where	`src/components/tables/ClockInPageHistory.tsx`, `addPunch` (filter `log.timestamp.substring(0, 10) === workDate`)
Type	Bug
Suggested fix	Compare dates in the same time zone (see BUG-222).
Proven by	`ClockInPageHistory.test.tsx` › "adds a punch made just after midnight"

BUG-222 — Punches between midnight and 1 am are grouped with the previous day — MEDIUM

Area	Clock-in, history & employees
Effect	**Punches between midnight and 1 am appear under the previous day as 'Not validated'.**
What happens	Two "Not validated" rows, because the punches are grouped by their UTC date while the table shows the Algiers date and time. The "Date" shown for the first row (09/03) doesn't match the group it was put in (08/03).
Steps to reproduce	Punches on March 9 at 00:30 (`2026-03-08T23:30Z`) and 08:00.
Expected	One row: 09/03/2026, 00:30 → 08:00, Validated.
Where	`src/components/tables/ClockInPageHistory.tsx`, `groupedLogs` (`log.timestamp.substring(0, 10)`)
Type	Bug
Suggested fix	Group by the Algiers date (`formatDateTime(...)` / `Intl.DateTimeFormat("en-CA", { timeZone: "Africa/Algiers" })`), the same zone the table displays.
Proven by	`ClockInPageHistory.test.tsx` › "pairs a punch just after midnight with the same morning's clock-out"

BUG-301 — Typing a new main employee without picking him shows his name but keeps the old employee — MEDIUM

Area	New planning
Effect	**Editing an assignment shows the new name but saves the old employee.**
What happens	The cell shows "Bob Brown" (`title: editTitle.trim()`) while its `id` is still Alice's, so Save stores Alice. With an empty field the cell shows an empty name.
Steps to reproduce	Edit Alice's assignment, click Remove (or type over the name), type "Bob Brown" but don't click him in the list, click Update.
Expected	Either the update is refused ("pick an employee from the list") or the cell keeps Alice's name.
Where	`src/hooks/useNewPlanning.ts`, `handleEdit`
Type	Bug / Data integrity
Suggested fix	In `handleEdit`, when `editSelectedEmployee` is null and the typed text differs from the current title, warn and return; or always use the employee record's name for `title`.
Proven by	`useNewPlanning.assign.test.tsx` › "never shows a name that differs from the employee who will be saved"

BUG-305 — An employee listed twice in an imported file is added twice to the same cell — MEDIUM

Area	New planning
Effect	**Importing a file that lists someone twice creates duplicate assignments, the same duplicate problem the recent cleanup was meant to fix.**
What happens	She is pushed twice; Save then sends two identical entries, which is the duplicate the "CleanPlanningFromDuplicates" commit set out to stop. The grid also renders two elements with the same React key.
Steps to reproduce	Excel with two `06H` rows both containing "Alice Martin" (or a PDF where `06H` / "Alice Martin" appears on two pages).
Expected	Alice appears once in the cell, as `handleSave`, `handleEdit` and the loader (fix 5feb993) guarantee everywhere else.
Where	`src/hooks/useNewPlanning.ts`, `handleImportFile` (Excel and PDF branches: `importedGrid[defaultPost.id][shift.id].push(currentEmployee)`)
Type	Bug / Data integrity
Suggested fix	Before pushing, look for an existing cell with the same `id`; if found, make it `currentEmployee` (so its "Backup:" lines still merge) instead of adding a new one.
Proven by	`useNewPlanning.import.test.tsx` › "imports an employee listed twice under the same hour only once" (Excel and PDF)

BUG-306 — PDF import puts employees of unlisted hours into the previous hour's shift — MEDIUM

Area	New planning
Effect	**In PDF imports, employees under hours like 18H are put on the wrong shift.**
What happens	`18H` is not recognised as an hour (13H and 17H–05H aren't either), so it is reported as an unknown employee and Bob is added to the 06:00 shift. Saving then stores him on the wrong shift.
Steps to reproduce	Shifts 06:00–14:00 and 18:00–23:00. PDF text: `06H`, `Alice Martin`, `18H`, `Bob Brown`.
Expected	Bob goes to the 18:00 shift (the Excel import accepts any hour).
Where	`src/hooks/useNewPlanning.ts`, `handleImportFile`, PDF branch (`/^(06|07|08|09|10|11|12|14|15|16)H$/i`)
Type	Bug
Suggested fix	Match any hour (`/^([01]?\d|2[0-3])H$/i`) and let `findShiftByHour` decide; when no shift matches, set `currentShiftId = null` (already done) so the names under it are skipped rather than misplaced.
Proven by	`useNewPlanning.import.test.tsx` › "puts the employees of an 18:00 shift in the 18:00 shift"

BUG-401 — A slow answer for the previous day replaces the planning of the selected day — MEDIUM

Area	View planning & shifts
Effect	**On a slow connection, the grid can show another day's planning under the selected date.**
What happens	The late answer is filtered with the 24th (from its closure) and replaces the grid. The page shows the 24th's planning (Ali Ben) while the 25th is selected. Clicking quickly through days on a slow connection shows the wrong day with no sign of it.
Steps to reproduce	Today is 24 October. Press "next day" before `GET /planning` for the 24th has answered. The answer for the 25th arrives first.
Expected	The grid shows the 25th's planning (Sara Kaci).
Where	`src/hooks/useViewPlanning.ts`, `fetchPlanning` and the effect that calls it
Type	Bug (race condition)
Suggested fix	Cancel stale requests in the effect cleanup (an `AbortController` or an `ignore` flag), so only the latest date writes the grid.
Proven by	`useViewPlanning.test.ts` › "shows the selected day even when the previous day's answer arrives last"

BUG-402 — In time zones ahead of Algeria, a picked day shows the previous day's planning — MEDIUM

Area	View planning & shifts
Effect	**Viewers in time zones ahead of Algeria see the previous day's planning for the day they picked.**
What happens	Local midnight in Paris (UTC+2) is 23:00 on the 19th in Algiers, so the 19th's planning is shown. The day buttons hold local dates, but the filter converts them to Algiers time. The company `utcOffset` setting is also ignored.
Steps to reproduce	Browser time zone `Europe/Paris`, 15 July 2026. Pick the 20th in the mini calendar, which runs `setCurrentDate(new Date(2026, 6, 20))`, local midnight.
Expected	The planning of 20 July.
Where	`src/hooks/useViewPlanning.ts`, `fetchPlanning` (`currentDate.toLocaleDateString('en-CA', { timeZone: 'Africa/Algiers' })`)
Type	Bug
Severity note	only browsers ahead of UTC+1, e.g. France or Spain in summer
Suggested fix	Build the day key from the local calendar date (`getFullYear/getMonth/getDate`). Or store the selected day as a `"YYYY-MM-DD"` string instead of a `Date`. Better still, ask the backend for `/planning?planDate=YYYY-MM-DD`.
Proven by	`useViewPlanning.test.ts` › "shows the picked day's planning for a manager in Paris in summer"

BUG-403 Deleting a shift that is still in use never asks to force the delete — MEDIUM

Area	View planning & shifts
Effect	**A shift used in any planning can never be deleted, and the error shown is raw JSON.**
What happens	`String(e)` is `"Error: 409 {…}"`, so `message.startsWith("409")` is never true. The dialog closes and the page shows "Could not delete this shift. Error: 409 {"message":"Shift in use","usageCount":3}". A shift used in any planning can never be deleted, and the force path (plus the warning in the page) is dead code.
Steps to reproduce	Archived tab › Delete › Delete. The backend answers `409 {"message":"Shift in use","usageCount":3}`.
Expected	The dialog stays open and says "This shift is used in 3 planning entries." A second Delete sends `DELETE /shifts/:id?force=true`.
Where	`src/hooks/ShiftsmanagmentHook.ts`, `confirmDelete`
Type	Bug
Suggested fix	Test `e.message.startsWith("409")` (or throw an `ApiError` with `status` from `apiFetch` and check `err.status === 409`). Parse the body with `JSON.parse` instead of a regex.
Proven by	`ShiftsmanagmentHook.test.ts` › "shows how often a shift in use is planned, then forces the delete" and "counts 0 uses when a conflict gives no count". `ShiftsManagment/page.test.tsx` › "warns that a shift is still planned and deletes it on a second confirmation"

BUG-405 A slow Active list replaces the Archived list after switching tabs — MEDIUM

Area	View planning & shifts
Effect	**After switching tabs, active shifts can show in the Archived list with a 'Delete' button, which makes accidental deletion likely.**
What happens	When the active answer arrives, it replaces the list. The Archived tab then shows active shifts with "Restore" and a permanent "Delete" button.
Steps to reproduce	Open the page and click "Archived" before `GET /shifts?status=active` has answered. The archived list arrives first.
Expected	The Archived tab keeps showing the archived shifts.
Where	`src/hooks/ShiftsmanagmentHook.ts`, `fetchShifts`
Type	Bug (race condition)
Suggested fix	Ignore stale answers: keep a request counter or an `AbortController` in `fetchShifts`, or cancel it in the effect cleanup (`let cancelled = false; return () => { cancelled = true }`).
Proven by	`ShiftsManagment/page.test.tsx` › "keeps showing the archived shifts when the active list answers late"

BUG-501 A slow answer for a previous range replaces the range chosen last — MEDIUM

Area	Reporting & payroll
Effect	**Switching months quickly can show the previous month's pay under the month just chosen.**
What happens	February's data and range are applied last, so the payroll shows the wrong month's net pay.
Steps to reproduce	Pick February, then March before February has loaded; February answers last.
Expected	March is shown.
Where	`load` in `useReportingOverview.ts`, `useMonthlyPayrollList.ts`, `useWeeklyAdvancesList.ts`, `useBonusesHistory.ts` (`useEmployeeReport.ts` already guards with a request id)
Type	Bug
Suggested fix	`const reqId = ++req.current`; ignore the answer when `reqId !== req.current`, as `useEmployeeReport` does.
Proven by	`useReportingOverview.test.ts` › "shows the last range chosen when an earlier request answers late", and the same-named tests in `useMonthlyPayrollList.test.ts`, `useWeeklyAdvancesList.test.ts` and `useBonuses.test.ts`

BUG-502 When the planning can't be loaded, the payroll and weekly advances lists are empty — MEDIUM

Area	Reporting & payroll
Effect	**If the planning fails to load, the payroll shows nobody and a total of 0 DA, as if no one had worked.**
What happens	The fallback is an empty set, so the table says "No employees found" and "Total Net Payout 0.00 DA". The toast only says "totals may be incomplete".
Steps to reproduce	`GET /planning` answers 500; everything else loads.
Expected	The employees who worked are still listed, with the warning.
Where	`src/hooks/useMonthlyPayrollList.ts`, `src/hooks/useWeeklyAdvancesList.ts` (`.catch(optionalData(new Set(), "The planning"))` + `.filter(emp => scheduledIds.has(...))`)
Type	Bug
Suggested fix	When the planning failed, list every employee with worktime rows in the range, or show a load error.
Proven by	`useMonthlyPayrollList.test.ts` / `useWeeklyAdvancesList.test.ts` › "still lists the employees who worked when the planning can't be loaded"

BUG-504 A double click on "Give Advance" gives the advance twice — MEDIUM

Area	Reporting & payroll
Effect	**A double click gives the same advance twice, and both are deducted from pay.**
What happens	Two POSTs. The button is only disabled while the existing advance is being checked, not while one is being saved. Both are deducted at month end.
Steps to reproduce	Click "Give Advance" twice before the server answers.
Expected	One `POST /advances`.
Where	`EmployeeDetailView.tsx` (`WeeklyAdvanceTab` button), `useEmployeeReport.ts` `giveAdvance`
Type	Bug (pay)
Suggested fix	A `saving` flag in `giveAdvance` that ignores repeat calls and disables the button.
Proven by	`EmployeeDetailView.test.tsx` › "gives the advance only once on a double click"

BUG-506 Hours worked by an employee without a planning entry are left out of the payroll — MEDIUM

Area	Reporting & payroll
Effect	**Hours worked without a planning entry are never paid, and the Overview and Monthly Payroll totals disagree.**
What happens	She is not listed, so her hours are never paid or advanced. The Overview counts her, so its gross and the Monthly Payroll total disagree for the same month.
Steps to reproduce	Nadia (125 DA/h) has 8 h on 2026-03-12 but no planning entry in March.
Expected	She is on the March payroll with gross 1 000 DA.
Where	`useMonthlyPayrollList.ts` and `useWeeklyAdvancesList.ts`, `.filter((emp) => scheduledIds.has(String(emp.emp_id)))`
Type	Bug (pay)
Severity note	needs product confirmation
Suggested fix	List employees who are scheduled **or** have worktime rows in the range.
Proven by	`useMonthlyPayrollList.test.ts` › "pays an employee who worked in the month even without a planning entry"

BUG-507 West of UTC, picked weeks start a day early or last 6 days — MEDIUM

Area	Reporting & payroll
Effect	**For companies west of UTC, weeks lose their last day, so that day is never paid or advanced.**
What happens	03-09..03-14 and 03-16..03-21 (the last day of the week is never paid or advanced), and 03-04..03-10. Same root cause as BUG-001 (`generateDateRange`, also used by the Overview trend).
Steps to reproduce	TZ `America/New_York`. Weekly Advances: week starting 2026-03-09 → Apply. Employee page: pick 16 March. Open Attendance.
Expected	03-09..03-15, 03-16..03-22, 03-05..03-11.
Where	`useAttendanceReport.ts computeRange` (`new Date(selectedDate)`), `RangePicker.tsx previewRange` (`new Date(weekStart)`), `EmployeeDetailView.tsx handleWeekChange` (`new Date(start)`)
Type	Bug
Severity note	only for companies west of UTC
Suggested fix	Parse with `new Date(${d}T00:00:00)`, as `DateInput` and `formatPretty` already do.
Proven by	`useAttendanceReport.test.ts` › "starts the week on the chosen day in a time zone behind UTC"; `RangePicker.test.tsx` › "ends the week 6 days later in a time zone behind UTC"; `EmployeeDetailView.test.tsx` › "ends the picked week 6 days later in a time zone behind UTC"

BUG-508 Advances and bonuses are deleted with one click, without confirmation — MEDIUM

Area	Reporting & payroll
Effect	**One stray click deletes an advance or bonus without asking, which changes the payroll.**
What happens	The `DELETE` is sent at once. A stray click removes a deduction from the payroll.
Steps to reproduce	Click "Revoke" next to an advance or bonus.
Expected	A `confirmDialog({ danger: true })`, as every other delete in the app uses, and nothing deleted until it is confirmed.
Where	`AdvancesView.tsx` ("Revoke"), `BonusesHistoryView.tsx` ("Revoke"), `WeeklyAdvancesView.tsx` ("Undo")
Type	UX / data loss
Suggested fix	`if (!(await confirmDialog({ title: "Revoke this advance?", danger: true }))) return;`
Proven by	`AdvancesView.test.tsx` / `BonusesViews.test.tsx` › "asks for confirmation before revoking"; `WeeklyAdvancesView.test.tsx` › "asks for confirmation before undoing an advance"

BUG-513 Typing a week start on the employee page scrambles the date — MEDIUM

Area	Reporting & payroll
Effect	**Typing a week date scrambles it and sends a burst of junk requests.**
What happens	One `/worktime` request per keystroke (`..NaN-NaN-NaN`, `2..2001-02-07`, `206..206-01-07`…). Answers overwrite the field mid-typing, which ends as `2060-6` ("2060-6 → 2060-06-07"). Picking from the calendar works.
Steps to reproduce	Clear "Week starting" and type `2026-03-16`.
Expected	The field keeps `2026-03-16` and week 03-16 → 03-22 loads.
Where	`EmployeeDetailView.tsx`, `WeeklyAdvanceTab`: `onChange` calls `handleWeekChange` on every keystroke, and an effect copies `week.range.start` back into the field
Type	Bug
Suggested fix	Only load complete valid dates (`/^\d{4}-\d{2}-\d{2}$/`), and don't overwrite the field while it is being edited.
Proven by	`EmployeeDetailView.test.tsx` › "loads the week whose start date is typed"

BUG-515 The attendance page loads two different weeks on open, and the slower one wins — MEDIUM

Area	Reporting & payroll
Effect	**The attendance table can show a different week from the one in the picker.**
What happens	The table shows 03-05..03-11 (55 late minutes) while the picker says 9–15 March. Which one wins depends on timing.
Steps to reproduce	Open `/reporting/attendance` on Wed 2026-03-11. Requests go out for 03-05..03-11 (hook) and 03-09..03-15 (page); the first answers last.
Expected	The table matches the picker (this week: 15 late minutes).
Where	`useAttendanceReport.ts` (mount effect loads `getLastWeekRange()`), `AttendanceView.tsx` (mount effect applies `getThisWeekRange()`)
Type	Bug
Suggested fix	Let the page pass its initial range to the hook, with no load in the hook's mount effect, and guard `fetchReport` with a request id.
Proven by	`AttendanceView.test.tsx` › "shows the week displayed in the picker even when the other request answers last"

BUG-605 Sign-in can redirect to another site through `?next=` — MEDIUM

Area	Admin, sign-in & kiosk
Effect	**A phishing link to the real sign-in page can send staff to a fake site right after they sign in, where they can be tricked into giving credentials or data.**
What happens	`router.replace("/\\evil.example")`. The check only refuses `//`, but URL parsers treat `/` as `//` and drop tabs and newlines, so the target resolves to `https://evil.example/`. `canOpen` allows it because it isn't a known page. A phishing link to the real sign-in page can send people, just signed in, to a look-alike site.
Steps to reproduce	Open `/signin?next=%2F%5Cevil.example` (i.e. `next=/\evil.example`) or `next=/%09/evil.example` (`/<tab>/evil.example`) and sign in.
Expected	`router.replace` goes to an in-app page (`/home`).
Where	`src/components/auth/SignInForm.tsx`, `destinationFor`
Type	Security (open redirect)
Suggested fix	Resolve the target and compare origins: `const url = new URL(next, window.location.origin); if (url.origin !== window.location.origin) …`, then use `url.pathname + url.search` (and run `canOpen` on `url.pathname`).
Proven by	`SignInForm.test.tsx` › "doesn't follow ?next= to another site disguised with a backslash" / "… with a tab"

BUG-701 The Modal's close button has no accessible name — MEDIUM

Area	UI kit, forms & help
Effect	**Screen-reader users hear only 'button' for a modal's close button.**
What happens	It only contains an SVG, so it's announced as "button".
Steps to reproduce	Open any modal that uses `<Modal>` (users, companies, planning, advances, bonuses…) with a screen reader.
Expected	The ✕ button is announced as "Close".
Where	`src/components/ui/modal/index.tsx`, close `<button>`
Type	Accessibility
Suggested fix	`aria-label={t("Close")}` on the button (and `aria-hidden` on the SVG).
Proven by	`ui.test.tsx` › "Modal › gives the close button an accessible name"

BUG-702 The Modal isn't exposed as a dialog — MEDIUM

Area	UI kit, forms & help
Effect	**Screen-reader users aren't told a dialog opened, and can wander into the page underneath.**
What happens	Plain `<div>`s; screen readers can still wander into the page underneath and aren't told a dialog opened. (Focus also isn't moved into the modal.)
Steps to reproduce	Open any modal.
Expected	An element with `role="dialog"` and `aria-modal="true"` (ideally labelled by its heading), so assistive tech knows a dialog opened and ignores the page behind it.
Where	`src/components/ui/modal/index.tsx`
Type	Accessibility
Suggested fix	Put `role="dialog" aria-modal="true"` on the content box, accept an `aria-labelledby`/`title` prop, and move focus into it on open.
Proven by	`ui.test.tsx` › "Modal › is announced as a modal dialog"

BUG-708 "Close" in a modal form submits the form — MEDIUM

Area	UI kit, forms & help
Effect	**Pressing 'Close' or 'Save' inside a modal form reloads the page and loses what was typed.**
What happens	A `submit` event is fired on the `<form>`. With no `onSubmit` handler the browser submits the form, i.e. reloads the page with the fields in the URL. `Button` can't be made `type="button"` because it doesn't accept or forward `type`.
Steps to reproduce	Open the "Form In Modal" example, click **Close** (or **Save Changes**).
Expected	The modal closes; the form isn't submitted.
Where	`src/components/ui/button/Button.tsx` (no `type` prop, so it's always a submit button); seen in `src/components/example/ModalExample/FormInModal.tsx`, the same pattern is in `src/components/user-profile/UserInfoCard.tsx`
Type	Bug
Suggested fix	Add `type?: "button" | "submit" | "reset"` to `Button` and pass it to the `<button>`. Use `type="button"` for Close/Cancel buttons inside forms (forms that rely on `Button` submitting keep working if the default stays `submit`, or pass `type="submit"` explicitly there).
Proven by	`modals.test.tsx` › "FormInModal › doesn't submit the form when Close is clicked"

Low severity · details

43 bugs, sorted by ID.

BUG-002 A company setting of 0 is ignored — LOW

Area	Core library & API helpers
Effect	**A company can't turn weekly advances off. After a super admin switches company, the previous company's ratio is applied to advance offers.**
What happens	`if (settings.weeklyAdvanceRatio)` treats 0 as "not set", so the previous value stays. Because the config is one shared object, a super admin switching company keeps the previous company's value.
Expected	`weeklyAdvanceRatio: 0` turns weekly advances off.
Where	`src/lib/payrollConfig.ts`, `applyCompanySettings`
Type	Bug
Suggested fix	`if (settings.x !== undefined)`, and reset to defaults before applying a company's settings.
Proven by	`payrollConfig.test.ts` › "accepts a weekly advance ratio of 0"

BUG-004 Date filters in the URL aren't validated — LOW

Area	Core library & API helpers
Effect	**Edited or broken links send invalid date ranges to the API, leading to empty or confusing reports.**
What happens	`?start=hello&end=2026-03-31` is accepted and sent to the API. A reversed range (`start > end`) is accepted too.
Where	`src/lib/rangeParams.ts`, `readRange`
Type	Bug
Suggested fix	Check `/^\d{4}-\d{2}-\d{2}$/` and `start <= end`, else return `undefined`.
Proven by	`rangeParams.test.ts` › "rejects values that are not YYYY-MM-DD dates"

BUG-005 Negative durations are converted wrongly — LOW

Area	Core library & API helpers
Effect	**Any negative correction in hours is converted wrongly (−1:30 becomes −0.5 h), which skews totals.**
What happens	`"-01:30"` → `-0.5` (should be `-1.5`). The minus sign only applies to the hours.
Where	`src/lib/reporting.ts`, `timeToDecimalHours`
Type	Bug
Severity note	only if the backend ever sends negative hours
Proven by	`reporting.test.ts` › "converts a negative duration"

BUG-006 Non-numeric values become NaN in worktime rows — LOW

Area	Core library & API helpers
Effect	**One bad value from the server turns whole totals (penalties, late minutes) into 'NaN', so the payroll screen becomes unusable.**
What happens	`Number("n/a")` is `NaN`, and one bad row turns every total (penalties, late minutes) into `NaN`.
Where	`src/lib/reporting.ts`, `normalizeRow`
Type	Bug
Suggested fix	A `toNumber(v)` helper returning 0 for non-finite values.
Proven by	`reporting.test.ts` › "never produces NaN for bad numeric fields"

BUG-008 A failed branding request is cached until the page is reloaded — LOW

Area	Core library & API helpers
Effect	**After a network hiccup, the sign-in page shows the default look instead of the company's branding until it is reloaded.**
What happens	A network error is cached as `null`, so the sign-in page keeps the default look until a full reload.
Where	`src/lib/branding.ts`, `fetchBrand`
Type	UX
Suggested fix	`cache.delete(slug)` in the `.catch`.
Proven by	`branding.test.ts` › "tries again after a network failure"

BUG-010 Downloading a file whose name contains "%" fails — LOW

Area	Core library & API helpers
Effect	**Exports whose filename contains '%' fail to download.**
What happens	`decodeURIComponent("100% sales.xlsx")` throws `URIError: URI malformed`, and the export fails.
Where	`src/lib/auth.ts`, `downloadFile`
Type	Bug
Suggested fix	Only decode the `filename*=` form, or wrap the decode in `try/catch`.
Proven by	`auth.test.ts` › "accepts a filename containing %"

BUG-011 A manager or admin with no company can open the activity log — LOW

Area	Core library & API helpers
Effect	**A manager without a company can open the activity log page. Only backend checks stop them from seeing other people's actions.**
What happens	The "no company" rule (`NO_COMPANY_PATHS`, meant for the super admin) is checked before the admin-only rule.
Where	`src/lib/auth.ts`, `canOpen`
Type	Bug / Security
Severity note	the backend should still refuse the data
Suggested fix	Only apply `NO_COMPANY_PATHS` to `superadmin`. Other roles without a company get `/account` and `/help` only.
Proven by	`auth.test.ts` › "a manager without a company can't open the activity log"

BUG-013 Worktime responses are printed to the browser console — LOW

Area	Core library & API helpers
Effect	**Anyone at a shared computer or kiosk can open the browser console and read employees' hours and penalties.**
What happens	Each call logs the path, method, status and full body (employee ids, hours, penalties). Upserts log the payload. Anyone at a shared kiosk can open DevTools and read them.
Where	`src/components/tables/worktime.api.ts`, `request()` and `upsertWorktime`
Type	Security / Cleanup
Severity note	privacy and noise
Suggested fix	Remove the `console.log` calls, or only log when `process.env.NODE_ENV === "development"`.
Proven by	`worktime.api.test.ts` › "doesn't print response bodies to the console"

BUG-014 Errors from `shifts.api.ts` and `worktime.api.ts` show raw server text — LOW

Area	Core library & API helpers
Effect	**Users see raw technical text (JSON) instead of a clear reason, so they can't tell what to fix.**
What happens	The prefix stops `friendlyError` from recognising the status, so people see `[worktime] 400 {"message":"Clock-out before clock-in"}`.
Expected	`friendlyError` shows the server's message, e.g. "Clock-out before clock-in".
Where	`shifts.api.ts` (`[api] 400 …`), `worktime.api.ts` (`[worktime] 400 …`), with `friendlyError` in `src/lib/errors.ts`
Type	UX
Suggested fix	Use `ensureOk` / `fetchJson` (throws `ApiError`) like the other API files.
Proven by	`shifts.api.test.ts` / `worktime.api.test.ts` › "its errors become readable messages"

BUG-107 With no employees the table says "Loading attendance..." for ever LOW

Area	Face-recognition clock-in
Effect	**With no employees, the page shows 'Loading...' forever instead of saying there is nobody to show.**
What happens	"Loading attendance..." never goes away. The "No employees found" message can never be shown.
Steps to reproduce	A company with shifts but no employees.
Expected	"No employees found in the database."
Where	`ClockInFaceRecognitionPage.tsx`, `attendanceLoading` starts `true` and is only cleared by the attendance effect, which returns early when `employees` is empty
Type	Bug / UX
Suggested fix	Set `attendanceLoading` to `false` in the early return (or start it at `false`).
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "says when there are no employees at all"

BUG-108 A failed save shows "✓ Saved" for employees with machine punches LOW

Area	Face-recognition clock-in
Effect	**A failed save still shows '✓ Saved', so managers believe penalties were recorded when they were lost.**
What happens	The banner shows the error but the row still says "✓ Saved", so once the banner is closed nothing shows that the penalty was lost. The same happens when the automatic machine save fails.
Steps to reproduce	Employee with punches (saved automatically). Type a penalty while the backend answers 500 to the save.
Expected	The row says "Unsaved".
Where	`ClockInFaceRecognitionPage.tsx`, `getEntry` (returns `_dirty: false` whenever the machine has data)
Type	Bug / UX
Suggested fix	In `getEntry`, keep `stored._dirty` instead of forcing `false`.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "shows that a change was not saved for an employee with machine punches"

BUG-112 Machine logs and saved payloads are printed to the browser console — LOW

Area	Face-recognition clock-in
Effect	**Anyone who opens the browser console on the manager's computer can read employee punch data.**
What happens	Every load prints all device logs (employee numbers and punch times) and every save prints the full payload and the backend response. Anyone who opens DevTools on the manager's computer can read them. Same problem as BUG-013 in `worktime.api.ts`.
Where	`ClockInFaceRecognitionPage.tsx`, `loadAttendance` and the machine save (about 40 `console.log`/`console.error` calls)
Type	Security / Cleanup
Severity note	privacy and noise
Suggested fix	Remove the logs, or only log when `process.env.NODE_ENV === "development"`.
Proven by	`ClockInFaceRecognitionPage.test.tsx` › "doesn't print attendance data to the console"

BUG-201 The "Last Name" column sorts by first name — LOW

Area	Clock-in, history & employees
Effect	**Sorting by last name actually sorts by first name.**
What happens	Ali first: both name columns use the `"name"` key (`firstName lastName`), and both headers show the active sort arrow.
Steps to reproduce	Ali Zerrouki and Sara Amrani; click "Last Name".
Expected	Amrani before Zerrouki.
Where	`src/components/tables/BasicTableOne.tsx`, column list (`{ label: "Last Name", key: "name" }`)
Type	Bug
Suggested fix	Separate `firstName` / `lastName` sort keys.
Proven by	`BasicTableOne.test.tsx` › "sorts by last name from the Last Name header"

BUG-203 Deleting the last employee on the last page leaves an empty page — LOW

Area	Clock-in, history & employees
Effect	**After deleting the last row on the last page, the list looks empty until the user goes back a page.**
What happens	"No employees found." and "Showing 6–5 of 5 entries" until Previous is clicked.
Steps to reproduce	6 employees, 5 per page. Go to page 2 and delete its only employee.
Expected	Page 1 with the 5 employees.
Where	`src/components/tables/BasicTableOne.tsx`, `handleDelete` / pagination (`currentPage` isn't clamped)
Type	UX
Suggested fix	Clamp `currentPage` to `totalPages` (e.g. in an effect or when computing `paginated`).
Proven by	`BasicTableOne.test.tsx` › "shows the previous page after the last row of the last page is deleted"

BUG-204 The employee form's fields have no accessible names — LOW

Area	Clock-in, history & employees
Effect	**Screen-reader users can't tell which field is which in the employee form.**
What happens	`<label>` has no `htmlFor` and the input no `id`, so screen readers announce unnamed text fields and clicking a label doesn't focus its field. (The history page's "Add a clock-in" form has the same problem: the tests find those fields by position.)
Where	`src/components/tables/BasicTableOne.tsx`, `Field`
Type	Accessibility
Suggested fix	`<label htmlFor={name}>` + `<input id={name}>`, or wrap the input in the label.
Proven by	`BasicTableOne.test.tsx` › "names each form field by its label"

BUG-214 A backup who is also planned on the shift is listed twice — LOW

Area	Clock-in, history & employees
Effect	**A backup who is also planned appears twice in the list, which is confusing and can cause double entries.**
What happens	Twice: once as "Backup for Ali Zerrouki" and once as herself. The check only looks at rows added so far, so it works when the backup is listed above the absent employee but not below. Both rows share one React key and one entry.
Steps to reproduce	Ali (listed first) is absent and replaced by Sara, who is also planned on the same shift.
Expected	Sara appears once.
Where	`src/components/tables/ClockInPage.tsx`, `getAttendanceRows` ("Prevent duplicate employee rows")
Type	Bug
Suggested fix	Check against all `employees` in the shift (or build the main rows first, then add backups).
Proven by	`ClockInPage.test.tsx` › "doesn't add a backup row for someone already listed on the shift"

BUG-216 The machine status always comes from http://localhost:3001 LOW

Area	Clock-in, history & employees
Effect	**The machine is always shown as 'Disconnected' in production, and the login token is sent to the viewer's own computer.**
What happens	"Disconnected": the page asks `http://localhost:3001/device/status`, i.e. the viewer's own computer, every 30 s. In production that is always unreachable (and blocked as mixed content on HTTPS). The auth wrapper also sends the bearer token there (see BUG-007).
Steps to reproduce	API at `https://api.test` reports the machine connected.
Expected	"Machine: Connected".
Where	`src/components/tables/ClockInPageHistory.tsx`, `checkDeviceStatus` (hard-coded URL); also `API_BASE_URL` falls back to `http://localhost:3001` instead of `@/lib/config`
Type	Bug / Config
Severity note	wrong status, nothing is lost
Suggested fix	`fetch(`${API_BASE_URL}/device/status`)` with `API_BASE_URL` from `@/lib/config`.
Proven by	`ClockInPageHistory.test.tsx` › "asks the API server for the machine status"

BUG-223 A punch without an id shows an open time editor instead of its time LOW

Area	Clock-in, history & employees
Effect	**Some punches show an open time editor instead of their time.**
What happens	With no edit in progress, `undefined === undefined` is true, so the row shows hour/minute dropdowns with ✓/✕ instead of the time.
Steps to reproduce	A log without `_id` (the code handles this case elsewhere, e.g. "has no ID" when deleting).
Expected	The time (08:00), as for other punches.
Where	`src/components/tables/ClockInPageHistory.tsx`, Clock In cell (`editingPunch?.logId === log.logs[0]?._id`)
Type	Bug
Suggested fix	`editingPunch !== null && editingPunch.logId === log.logs[0]?._id`.
Proven by	`ClockInPageHistory.test.tsx` › "shows the time of a punch that has no id"

BUG-303 — Days are off by one when the browser is in a time zone ahead of Algiers — LOW

Area	New planning
Effect	**Managers working from France or further east save plannings on the wrong days (for example 'every Saturday' writes onto Fridays).**
What happens	Dates are built at local midnight and then converted with `timeZone: "Africa/Algiers"`, which is 23:00 the previous day: it saves on 2, 9, 16, 23 (Fridays, overwriting them) and 31, and clicking 20 loads and saves 2026-10-19 while 20 is highlighted.
Steps to reproduce	`TZ=Europe/Paris` (UTC+2 in summer), today Saturday 24 Oct 2026. Click "Save to every Saturday", or click 20 in the mini calendar.
Expected	Saves on 3, 10, 17, 24, 31 Oct; clicking 20 loads 2026-10-20.
Where	`src/hooks/useNewPlanning.ts`, `getSameWeekdayDatesInMonth` / `handleSaveToAllWeekdays`; `src/components/calendar/NewPlanning.tsx`, mini calendar (`setCurrentDate(date)` with `getCalendarDays` dates)
Type	Bug
Severity note	Medium if managers use the app from France or further east
Suggested fix	Build these dates at noon (`new Date(y, m, d, 12)`), or format them with local `getFullYear/getMonth/getDate` instead of converting to Algiers time.
Proven by	`useNewPlanning.save.test.tsx` › "saves on Saturdays, not Fridays, for a manager whose browser is in Paris"; `NewPlanning.test.tsx` › "loads the clicked day, not the day before, for a manager whose browser is in Paris"

BUG-304 — A failed day in "Save to every / next weekday" shows the raw server reply — LOW

Area	New planning
Effect	**When one day fails during a bulk save, users see raw technical text instead of a clear reason.**
What happens	"Copied to 4 of 5 days (Saturday). 2026-10-10: 500 {"message":"Database is read-only"}". The date prefix stops `friendlyError` from recognising the `"<status> <body>"` format, so technical text is shown, against the rule in `src/lib/errors.ts`.
Steps to reproduce	One of the five `POST /planning/bulk` calls answers 500 `{"message":"Database is read-only"}`.
Expected	"Copied to 4 of 5 days (Saturday). Something went wrong on our side. Please try again in a moment."
Where	`src/hooks/useNewPlanning.ts`, `handleSaveToAllWeekdays` and `handleSaveToNextWeekdays` (`throw new Error(`${planDate}: ${res.status} ${errText}`)`)
Type	UX
Suggested fix	Use `await ensureOk(res)` (as `handleSavePlanning` does) and, if the date is wanted, add it outside the error message.
Proven by	`useNewPlanning.save.test.tsx` › "explains a failed day in plain words, without the raw server reply"

BUG-404 A failed shift delete shows the raw technical error — LOW

Area	View planning & shifts
Effect	**A failed delete shows raw technical text instead of a clear reason.**
What happens	"Could not delete this shift. Error: 500 {"statusCode":500,"message":"Internal server error"}".
Steps to reproduce	Delete an archived shift. The backend answers `500 {"statusCode":500,"message":"Internal server error"}`.
Expected	A friendly reason, as everywhere else ("Something went wrong on our side..."). `src/lib/errors.ts` says technical details are never shown.
Where	`src/hooks/ShiftsmanagmentHook.ts`, `confirmDelete` (`setError(t("Could not delete this shift.") + " " + message)`)
Type	Bug (UX)
Suggested fix	`setError(friendlyError(e, "Couldn't delete this shift"))`.
Proven by	`ShiftsManagment/page.test.tsx` › "explains a failed delete without technical details"

BUG-407 "Today" and the day arrows don't move the mini calendar, so the selected day can't be seen — LOW

Area	View planning & shifts
Effect	**Users can't see which day is displayed after using 'Today' or the arrows.**
What happens	The grid shows today's planning, but the mini calendar stays on December 2026. The date label is commented out, so nothing on screen shows which day is displayed. The same happens when the day arrows cross a month.
Steps to reproduce	Go to November in the mini calendar, pick the 3rd, go on to December, then press "Today".
Expected	The mini calendar goes back to October 2026 and highlights the 24th.
Where	`src/hooks/useViewPlanning.ts` (`goToToday`, `goPrev`, `goNext` only change `currentDate`); `ViewPlanning.tsx` (the `formattedDate` label is commented out)
Type	Bug (UX)
Suggested fix	Also call `setCalendarMonth` in `goToToday`, `goPrev` and `goNext` (or derive the month from `currentDate`). Restore the date label.
Proven by	`ViewPlanning.test.tsx` › "brings the mini calendar back to today's month with the Today button"

BUG-505 A failed "Undo" on the employee page is silent — LOW

Area	Reporting & payroll
Effect	**When undoing an advance fails, the user isn't told.**
What happens	The status flips back to "Advance given" with no message; the error only goes to the console.
Expected	An error toast, as on the Weekly Advances list.
Where	`useEmployeeReport.ts`, `revokeAdvance`
Type	UX
Suggested fix	`toast.error(friendlyError(err, "Couldn't remove the advance"))`.
Proven by	`useEmployeeReport.test.ts` › "tells the user when the revoke fails"

BUG-509 Total hours show floating-point noise — LOW

Area	Reporting & payroll
Effect	**Totals show floating-point noise such as '0.30000000000000004 h'.**
What happens	`0.30000000000000004 h`.
Steps to reproduce	0.1 h (`00:06:00`) + 0.2 h (`00:12:00`).
Expected	`0.3 h`
Where	`WeeklyAdvancesView.tsx`, `MonthlyPayrollView.tsx` totals row `{colTotals.hours} h`
Type	Bug (display)
Suggested fix	`{Number(colTotals.hours.toFixed(2))} h`.
Proven by	`WeeklyAdvancesView.test.tsx` / `MonthlyPayrollView.test.tsx` › "shows the total hours rounded"

BUG-510 The month picker ignores the month being shown — LOW

Area	Reporting & payroll
Effect	**The month picker opens on the current month, not the one shown, so Apply can jump to the wrong month.**
What happens	It shows March 2026; Apply jumps to March.
Steps to reproduce	Monthly Payroll opened on January (e.g. "Back to Monthly Payroll") while today is in March.
Expected	The picker shows January 2026.
Where	`RangePicker.tsx` (`year`/`month` state start from `new Date()`, not `range`)
Type	UX
Suggested fix	Initialise `year`/`month` from `range.start`.
Proven by	`RangePicker.test.tsx` › "starts on the month it was opened on"

BUG-511 The bonus totals row mixes filtered and unfiltered figures — LOW

Area	Reporting & payroll
Effect	**The bonus totals row doesn't match the filtered list.**
What happens	`Total | 2 | 850.50 DA`. It also includes employees who are no longer listed.
Steps to reproduce	Search "amine" (2 bonuses, 350.50 DA) while Sara has 500 DA.
Expected	`Total | 2 | 350.50 DA`
Where	`BonusesGiveView.tsx` totals row (`totalCount` from the filtered rows, `totalGiven` from all bonuses)
Type	Bug (display)
Suggested fix	Sum `employeeRows[].total` for the row.
Proven by	`BonusesViews.test.tsx` › "totals only the employees listed"

BUG-512 The Overview shows a rise as a fall when the previous value was negative — LOW

Area	Reporting & payroll
Effect	**The Overview shows a rise in net payroll as a fall (red ▼).**
What happens	"▼ 750.0%" in red.
Steps to reproduce	Previous net −400 DA (1 600 − 500 − 1 500), current 2 600 DA.
Expected	▲
Where	`OverviewView.tsx`, `pctChange`
Type	Bug
Suggested fix	Divide by `Math.abs(prev)`.
Proven by	`OverviewView.test.tsx` › "shows a rise in net payroll as a rise when the previous net was negative"

BUG-514 The employee page shows "0" in the Absent column for days worked — LOW

Area	Reporting & payroll
Effect	**A stray '0' appears in the Absent column for worked days.**
What happens	`0`. React renders `0 && …` as "0".
Expected	An empty cell.
Where	`EmployeeDetailView.tsx`, `DayTable` (`{r.absent && r.absent_comment && …}`)
Type	Bug (display)
Suggested fix	`{r.absent ? … : null}`.
Proven by	`EmployeeDetailView.test.tsx` › "leaves the Absent column empty on days worked"

BUG-601 A cancelled password reset pre-fills the next user's new password — LOW

Area	Admin, sign-in & kiosk
Effect	**A password typed for one user can be given to another by mistake, and it is shown in clear text.**
What happens	It still holds `meant-for-mia` (in clear text, the field is `type="text"`). One click on **Set password** gives Sam the password meant for Mia.
Steps to reproduce	Users › **Reset password** on Mia, type `meant-for-mia`, **Cancel**. Then **Reset password** on Sam.
Expected	The password field is empty.
Where	`src/components/users/UsersView.tsx`, reset-password modal (`newPassword` is cleared only after a successful save)
Type	Bug / Security
Suggested fix	Clear `newPassword` whenever the dialog opens or closes (e.g. in `setResetFor` callers or an effect on `resetFor`).
Proven by	`UsersView.test.tsx` › "starts with an empty password for the next user after a cancelled reset"

BUG-602 Clicking "Next" right after the list loads jumps back to page 1 — LOW

Area	Admin, sign-in & kiosk
Effect	**Paging through System errors or the Activity log jumps back to page 1, so admins lose their place.**
What happens	Page 2 shows, then the debounce timer started on mount fires and calls `setPage(1)` even though the search text hasn't changed, so the list jumps back to page 1.
Steps to reproduce	Open System errors (or Activity log) with more than 50 entries and click **Next** within 400 ms of the page opening.
Expected	Page 2 stays shown.
Where	`src/components/system-errors/SystemErrorsView.tsx` and `src/components/activity/ActivityLogView.tsx`, the search-debounce effect
Type	Bug
Suggested fix	Only reset the page when the search actually changes: `setFilters(f => f.search === search ? f : (setPage(1), { ...f, search }))`, or skip the effect on the first render.
Proven by	`SystemErrorsView.test.tsx` and `ActivityLogView.test.tsx` › "stays on page 2 when Next is clicked right after the list loads"

BUG-603 A kiosk account is stuck on "Loading…" when the company has clock-in switched off — LOW

Area	Admin, sign-in & kiosk
Effect	**A kiosk tablet gets stuck on 'Loading…' with no way to sign out. Someone has to clear the browser to use it again.**
What happens	`canOpen("/kiosk")` is false, so the view redirects to `homePathFor(user, company)`, which is `/kiosk` for every kiosk account. The page "redirects" to itself and shows "Loading…" forever; there is no Sign out button on that screen, so the tablet is stuck until someone clears the browser.
Steps to reproduce	Signed in as a kiosk account (`role: "employee"`) of a company whose features don't include `clockin`; open `/kiosk`.
Expected	A message that the kiosk is switched off, with a way to sign out (or a redirect to a page that can be opened).
Where	`src/components/kiosk/KioskView.tsx` (redirect effect), with `homePathFor` in `src/lib/auth.ts`
Type	Bug
Suggested fix	When a kiosk account can't open `/kiosk`, show "The clock-in kiosk is switched off for this company" and a Sign out button instead of redirecting.
Proven by	`KioskView.test.tsx` › "doesn't leave a kiosk account stuck when clock-in is switched off"

BUG-604 The kiosk list's loading text isn't translated — LOW

Area	Admin, sign-in & kiosk
Effect	**French and Arabic users see an English 'Loading…' on the kiosk.**
What happens	"Loading…" (the string isn't passed through `t()`; it is in `fr.ts`).
Steps to reproduce	Language French, open the kiosk while the employee list is loading.
Expected	"Chargement…"
Where	`src/components/kiosk/KioskView.tsx`, `{loadingList && <p …>Loading…</p>}`
Type	i18n
Suggested fix	`{t("Loading…")}`.
Proven by	`KioskView.test.tsx` › "shows the list's loading text in the kiosk's language"

BUG-606 The profile page shows a made-up person and its Save does nothing — LOW

Area	Admin, sign-in & kiosk
Effect	**Any admin or manager can open a profile page full of made-up template data, and its Save button silently does nothing.**
What happens	It shows the TailAdmin template's "Musharof Chowdhury", `randomuser@pimjo.com`, a phone number, an Arizona address, a tax ID and links to Pimjo's social accounts. **Save Changes** only runs `console.log("Saving changes...")` and closes the dialog. The page title is "Next.js Profile | TailAdmin".
Steps to reproduce	Signed in as "Mia Manager", open `/profile`; click **Edit**, change the first name, **Save Changes**.
Expected	The page shows Mia's name and email; a saved change is kept.
Where	`src/app/(admin)/(others-pages)/profile/page.tsx`, `src/components/user-profile/{UserMetaCard,UserInfoCard,UserAddressCard}.tsx`
Type	Bug / Leftover template
Severity note	the page isn't in the menu, but any signed-in admin or manager can open `/profile`
Suggested fix	Delete the route and the three cards (the account page already covers the password), or wire them to `useAuth()` and a real endpoint.
Proven by	`UserProfileCards.test.tsx` › "Profile page › shows the signed-in user's own name and email" and "saves an edited first name"

BUG-703 MultiSelect's arrow button never opens the list — LOW

Area	UI kit, forms & help
Effect	**The multi-select's arrow never opens its list (example page only).**
What happens	The click toggles twice (button, then the field it bubbles to), so nothing happens.
Steps to reproduce	Click the ▾ button.
Expected	The option list opens.
Where	`src/components/form/MultiSelect.tsx`, chevron `<button onClick={toggleDropdown}>` inside `<div onClick={toggleDropdown}>`
Type	Bug
Severity note	only used on the form-elements example page
Suggested fix	Remove the button's own `onClick`, or call `e.stopPropagation()` in it.
Proven by	`inputs.test.tsx` › "MultiSelect › opens the list with the arrow button"

BUG-704 Removing a MultiSelect chip opens the option list — LOW

Area	UI kit, forms & help
Effect	**Removing a chip unexpectedly opens or closes the list (example page only).**
What happens	The click bubbles to the field's `toggleDropdown`, so the list opens (or closes if it was open).
Steps to reproduce	With options selected and the list closed, click a chip's ×.
Expected	The chip is removed; the list stays closed.
Where	`src/components/form/MultiSelect.tsx`, chip × `onClick`
Type	Bug
Severity note	only used on the form-elements example page
Suggested fix	`e.stopPropagation()` in the × handler.
Proven by	`inputs.test.tsx` › "MultiSelect › doesn't open the list when a chip is removed"

BUG-705 A disabled MultiSelect still lets you remove options — LOW

Area	UI kit, forms & help
Effect	**A disabled multi-select can still be changed (example page only).**
What happens	The option is removed and `onChange([])` is called. `disabled` only blocks opening the list.
Steps to reproduce	`<MultiSelect disabled defaultSelected={["1"]} onChange={fn} />`, click the chip's ×.
Expected	Nothing changes; `onChange` isn't called.
Where	`src/components/form/MultiSelect.tsx`, `removeOption`
Type	Bug
Severity note	only used on the form-elements example page
Suggested fix	Return early from `removeOption` (and `handleSelect`) when `disabled`, and hide the ×.
Proven by	`inputs.test.tsx` › "MultiSelect › doesn't let a disabled field be changed"

BUG-706 Switch can't be used with the keyboard — LOW

Area	UI kit, forms & help
Effect	**The toggle switch can't be used with a keyboard (example page only).**
What happens	It's a `<label>` with `onClick` and two `<div>`s: nothing focusable, no role, no state.
Steps to reproduce	Tab to a switch and press Space.
Expected	It receives focus, is announced as a switch with its label and on/off state, and toggles.
Where	`src/components/form/switch/Switch.tsx`
Type	Accessibility
Severity note	only used on the form-elements example page
Suggested fix	Render `<button role="switch" aria-checked={isChecked}>` (or a visually hidden checkbox inside the label) and drop the label `onClick`.
Proven by	`inputs.test.tsx` › "Switch › can be toggled with the keyboard"

BUG-707 PhoneInput always starts on the US prefix — LOW

Area	UI kit, forms & help
Effect	**The phone field starts with a US prefix that isn't in its own country list (example page only).**
What happens	The select shows DZ (the browser falls back to the first option) but the field contains `+1`, a prefix that isn't in the list.
Steps to reproduce	`<PhoneInput countries={[{ code: "DZ", label: "+213" }, { code: "FR", label: "+33" }]} />`
Expected	The select shows DZ and the number starts with `+213`.
Where	`src/components/form/group-input/PhoneInput.tsx`, initial state `"US"` / `"+1"`
Type	Bug
Severity note	only used on the form-elements example page
Suggested fix	Initialise from `countries[0]` (or a `defaultCountry` prop).
Proven by	`inputs.test.tsx` › "PhoneInput › starts on the first listed country's prefix"

BUG-709 "Okay, Got It" doesn't close the alert modals — LOW

Area	UI kit, forms & help
Effect	**'Okay, Got It' buttons don't close their alert (example page only).**
What happens	The buttons have no `onClick`; nothing happens.
Steps to reproduce	Open "Success Alert", click "Okay, Got It".
Expected	The modal closes.
Where	`src/components/example/ModalExample/ModalBasedAlerts.tsx`, the four "Okay, Got It" buttons
Type	Bug
Severity note	template example page
Suggested fix	`onClick={successModal.closeModal}` (and the same for the other three).
Proven by	`modals.test.tsx` › "ModalBasedAlerts › closes the alert with Okay, Got It"

BUG-710 The language menu can't be closed with Escape — LOW

Area	UI kit, forms & help
Effect	**The language menu can't be closed with the Escape key.**
What happens	It stays open; `Dropdown` only closes on an outside mouse click.
Steps to reproduce	Open the language menu, press Escape.
Expected	The list closes (expected behaviour for an `aria-haspopup="listbox"` popup).
Where	`src/components/common/LanguageSwitcher.tsx` / `src/components/ui/dropdown/Dropdown.tsx`
Type	Accessibility
Suggested fix	Listen for `keydown` Escape in `Dropdown` (only while open) and call `onClose`; return focus to the toggle.
Proven by	`common.test.tsx` › "LanguageSwitcher › closes on Escape"

BUG-711 The theme toggle buttons have no accessible name — LOW

Area	UI kit, forms & help
Effect	**Screen-reader users can't tell what the theme button does.**
What happens	Icon-only `<button>` with no label: announced as "button".
Steps to reproduce	Tab to the moon/sun button in the header with a screen reader.
Expected	"Switch to dark mode" / "Switch to light mode" (or "Toggle theme").
Where	`src/components/common/ThemeToggleButton.tsx` (header on every page), `src/components/common/ThemeTogglerTwo.tsx`
Type	Accessibility
Suggested fix	`aria-label={t(theme === "dark" ? "Switch to light mode" : "Switch to dark mode")}`.
Proven by	`common.test.tsx` › "ThemeToggleButton › has an accessible name", "ThemeTogglerTwo › has an accessible name"

BUG-712 Tooltips can't be seen with the keyboard — LOW

Area	UI kit, forms & help
Effect	**Keyboard and touch users never see tooltip text (used in planning and shifts).**
What happens	Only `onMouseEnter`/`onMouseLeave` are handled, so keyboard and touch users never get the text.
Steps to reproduce	Tab to an element wrapped in `<Tooltip>`.
Expected	The tooltip text appears on focus (and is linked with `aria-describedby` / `role="tooltip"`).
Where	`src/components/common/Tooltip.tsx` (used in the planning and shifts pages)
Type	Accessibility
Suggested fix	Also show on `onFocus` and hide on `onBlur` (focus events bubble in React), give the bubble `role="tooltip"` and an id referenced by `aria-describedby`.
Proven by	`common.test.tsx` › "Tooltip › shows the text when the element gets keyboard focus"

BUG-713	The header's "more" button on phones has no name or state	LOW
Area	UI kit, forms & help	
Effect	**The phone header's 'more' button has no name or state for assistive technology.**	
What happens	Icon-only, no label, no `aria-expanded`.	
Steps to reproduce	On a phone-sized screen, reach the ⋯ button that shows the theme/language/user controls.	
Expected	A name (e.g. "More options") and `aria-expanded` reflecting whether the menu is shown.	
Where	`src/layout/AppHeader.tsx`, the ⋯ button that toggles `isApplicationMenuOpen`	
Type	Accessibility	
Suggested fix	`aria-label={t("More options")} aria-expanded={isApplicationMenuOpen}`.	
Proven by	`AppHeader.test.tsx` › "labels the application menu button"	