2016

TENET TECHNETRONICS

"Simplifying Technology for Life"

Tenet's ULN2803Darlington driver breakout



Contents

#9/3, Shree Lakshmi Complex, 2nd Floor, Opp. To Vivekananda Park, Girinagar, Bangalore - 560085.
Ph. No: 080-26722726., Website: www.tenettech.com, Email: info@tenettech.com

Introduction

The ULN2803A is a high-voltage, high-current Darlington transistor array. The device consists of eight NPN Darlington pairs that feature high-voltage outputs with common cathode clamp diodes for switching inductive loads. The collector-current rating of each Darlington pair is 500 mA. The Darlington pairs may be connected in parallel for higher current capability.



The ULN2803A has a 2.7-kΩ series base resistor for each Darlington pair for operation directly with TTL or 5-V CMOS devices.

Features

- 500-mA-Rated Collector Current(Single Output)
- High-Voltage Outputs: 50 V
- Output Clamp Diodes
- Inputs Compatible With VariousTypes of Logic
- Relay-Driver Applications
- Compatible with ULN2800A Series

Applications

- Relay driver
- Hammer drivers
- Display drivers

#9/3, Shree Lakshmi Complex, 2nd Floor, Opp. To Vivekananda Park, Girinagar, Bangalore - 560085.
Ph. No: 080-26722726., Website: www.tenettech.com, Email: info@tenettech.com

- Line drivers
- Logic drivers
- Logic buffers

Pin Configurations and Functions



Pin Functions

PIN		TYPE	DESCRIPTION
NAME	NO.		
<1:8>B	1 - 8	I	Channel 1 through 7 darlington base input
<1:8>C	18 - 11	O	Channel 1 through 7 darlington collector output
GND	7	—	Common Emmitter shared by all channels (typically tied to ground)
COM	8	I/O	Common cathode node for flyback diodes (required for inductive loads)

Specifications

Parameters	Specifications
Collector-emitter voltage	50V
Input voltage	30 V
Peak collector current	500mA
Output clamp current	500mA
Total substrate-terminal current	–2.5 A

#9/3, Shree Lakshmi Complex, 2nd Floor, Opp. To Vivekananda Park, Girinagar, Bangalore - 560085.
Ph. No: 080-26722726., Website: www.tenettech.com, Email: info@tenettech.com

Operating virtual junction temperature	–65 to150 °C
Vi	5 V
VCC	50V

#9/3, Shree Lakshmi Complex, 2nd Floor, Opp. To Vivekananda Park, Girinagar, Bangalore - 560085.
Ph. No: 080-26722726., Website: www.tenettech.com, Email: info@tenettech.com