



2016

# Handling Interrupt in MPLAB Xpress Evaluation Board



Siva A

Tenet Technetronics

## Contents

Introduction .....	2
Component Requirement.....	2
Procedure .....	3
Output: .....	15



## Introduction

MPLAB Xpress IDE cost free development platform. It's cloud Based IDE available from microchip supporting PIC-based microcontrollers. The platform is comprised of code editor, build automation tools, debugger, code configurator. MPLAB Xpress IDE is an end-to-end solution enabling engineers to develop their applications from initial evaluation to final production.

## Component Requirement

### ➤ Hardware:

- MPLAB Xpress evaluation tool
- LED
- Push button

### ➤ Software:

- MPLAB Xpress IDE

Note: we have on board LED and pushbutton



## Procedure

**Step 1:** Open your Browser and go to following link

<https://mplabxpress.microchip.com/mplabcloud/ide>




Figure 1 MPLAB Xpress IDE main window

**Step 2:** start creating our new project. Go to **File >> New Project**. Select **microchip embedded** as well as **standalone project** then click **next**




Figure 2 Open new project

**Step 3:** Select device **pic16f18855**, and click **next** .




Figure 3 select Device

**Step 4: then give project name and click finish.**




Figure 4 give project name

**Step 5:** Now choose mplab xpress code configurator if its not present in your Device please Download and install from following link. <http://www.microchip.com/mplab/mplab-code-configurator>




Figure 5 Select mplab xpress code configurator



**Step 6:** Now we can see our mlab xpress configuration window and select system module in mlab xpress configuration window.




Figure 6 select pin

## Step 7: select pin module in mplab xpress configuration window




Figure 7 pin configuration set

**Step 8:** Now click Generate option.




Figure 8 click Generate

Note: **If you didn't done above things please add all library files.**

### Source Code

```
void main(void)

{

    SYSTEM_Initialize();

    INTERRUPT_GlobalInterruptEnable();

    INTERRUPT_PeripheralInterruptEnable();

    while (1)

    {

        // application wrote on interrupt handler function

    }

}

/* end of your main function */
```

Note: following code is not your main code which is interrupt handler function

```
void interrupt INTERRUPT_InterruptManager (void)

{

    // interrupt handler

    if(PIE0bits.IOCIE == 1 && PIR0bits.IOCIF == 1)

    {
```



```
PIN_MANAGER_IOC();  
  
    RA0=~RA0; //toggle LED state  
  
    // clear global interrupt-on-change flag  
  
    PIR0bits.IOCIF = 0;  
  
}  
  
else  
  
{  
  
    //Unhandled Interrupt  
  
}  
  
}
```



**Step 9:** Go to your MPLAB xpress IDE Erase all existing code and copy above code past there and add header file from given file then make clean and build for Export . if you done this go to download you can see hex file for your project.





Figure 10 Build the project

**Step 10:** Now, if all goes well connect the Micro B cable to pic16f18855 (mplab xpress demonstration board) and connect it to your computer. If you done you can see your devise. And copy that Hex file to your device. And make hardware connection.



**Output:**




Figure 12 output

**For product link:**

<http://www.tenettech.com/product/8828/mplab-xpress-development-board>

For more information please visit: [www.tenettech.com](http://www.tenettech.com)

For technical query please send an e-mail: [info@tenettech.com](mailto:info@tenettech.com)