TENET TECHNETRONICS

2016

Interfacing Seven Segment Display With MPLAB Xpress Evaluation Board

Author: Siva A

Version: 1.0

Introduction:

MPLAB Xpress IDE cost free development platform. It's cloud Based IDE available from microchip supporting PIC-based microcontrollers. The platform is comprised of code editor, build automation tools, debugger, code configurator. MPLAB Xpress IDE is an end-to-end solution enabling engineers to develop their applications from initial evaluation to final production.

Components Requirement

- Hardware:
  - MPLAB Xpress Evaluation Tool
  - Micro B Cable
  - GPIO Board
  - Jumper wires
- Software:
  - MPLAB Xpress IDE

Step 1: Open your Browser and go to following link

https://mplabxpress.microchip.com/mplabcloud/ide



Figure 1 MPLAB Xpress IDE main window

Step 2: start creating our new project. Go to **File >> New Project.** Select **microchip embedded** as well as **standalone project** then click **next**



Figure 2 Open new project

Step 3: Select device **pic16f18855**, and click **next .**



Figure 3 select Device

Step 4: then give project name and click finish**.**



Figure 4 give project name

Step 5: Now choose MPLAB Xpress code configurator if its not present in your Device please [Download and install]



Figure 5 Select mplab xpress code configurator

Step 6: Now we can see our mplab xpress configuration window and select system module in mplab xpress configuration window .



Figure 6 Assign project name

Step 7: Make oscillator configuration in MPLAB Xpress configuration window



Figure 7 oscillator configuration

Step 8: select PORTA all pin and select pin module in MPLAB Xpress configuration window and deselect Analog in pin module window.



Figure 8 pin configuration set

Step 9: Now click Generate option.



Figure 9 click Generate

SOURCE CODE:

```
#include "mcc_generated_files/mcc.h"
Char siva_disp[]={0xF9,0XA4,0XB0,0X99,0X92,0X82,0XF8,0X80,0X98,0XC0,'\0'};
int i,j=0;
void main(void)
{
    SYSTEM_Initialize();            // initialize the device
    while (1)
    {
        for(j=0;j<10;j++)
        {
        PORTA=siva_disp[j];       //display the values
        for(i=0;i<=10000;i++);    //delay
        }
    }
}
```

Step 10: Go to your MPLAP Xpress IDE Erase all existing code and copy above code past there then make clean and build for Export. if you done this go to download you can see hex file for your project.



Figure 10 Build the project

Step 11: Now, if all goes well connect the Micro B cable to pic16f18855 (mplab xpress demonstration board) and connect it to your computer. If you done you can see your devise. And copy that Hex file to your device. And make hardware connection.



OUTPUT:



Figure 12 output

Pin connection:



For product link:

http://www.tenettech.com/product/8828/mplab-xpress-development-board

For more information please visit: www.tenettech.com

For technical query please send an e-mail: info@tenettech.com

9/3, 2nd floor, SreeLaksmi Complex, opp, to Vivekananda Park, Girinagar, Bangalore - 560085,
Email: info@tenettech.com, Phone: 080 - 26722726