

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 1 of 84

ISSUE HISTORY			
Issue	Description of Change	Originator	Effective Date
1	Initial Release	Nahom G/Michael	28/08/2017
2	Revision to Transform from OHSAS 18001:2007 to ISO 45001:2018	Manyahlhal Mahmud	01/01/2020
3	Revision Made to include Flood and Bitumen Handling	Tikuye A.	13/02/2026

REFERENCE DOCUMENTS	
DOCUMENT NUMBER	DOCUMENT TITLE
ISO 45001:2018 Clause 1	Scope
ISO 45001:2018 Clause 5.3	Organizational roles, responsibilities and authorities
ISO 45001:2018 Clause 5.4	Consultation and participation of workers
ISO 45001:2018 Clause 6.1.2	Hazard identification and assessment of risks and opportunities
ISO 45001:2018 Clause 6.1.3	Determination of legal requirements and other requirements
ISO 45001:2018 Clause 7.1	Resources
ISO 45001:2018 Clause 7.2	Competence
ISO 45001:2018 Clause 7.3	Awareness
ISO 45001:2018 Clause 7.4	Communication
ISO 45001:2018 Clause 7.5	Documented information
ISO 45001:2018 Clause 9.1	Monitoring, measurement, analysis and performance evaluation

CONTENTS	PAGE
0A ISSUE HISTORY	1
0B REFERENCE DOCUMENT	1
0C CONTENT	1
1. PURPOSE & SCOPE	2
2. CRITERION	2-56
3. DISTRIBUTION	56

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 2 of 84

1. PURPOSE

- The purpose of this document is to identify the hazards which can pose negative impact on health and safety of the workers.
- To establish, implement and maintain a procedure for the company hazard identification, risk assessment and determination of necessary controls.

2. SCOPE

The scope of this document is study plant operation by identifying individual tasks involved in carrying out the operations. The document also assist in identification of potential health and safety risks and determination of the level of risk combining the likelihood of a hazard occurring with the severity using the risk matrix.

3. DEFINITION

HAZARD anything that has a potential to cause harm including injury, disease, death, environmental, property and equipment damage,

HIRA is a process that consists of a number of sequential steps such as hazard identification, consequence and frequency assessment, risk estimation based on existing control and recommendation to reduce those risks which are not under acceptable limit.

4. CRITERION

Introduction

One of the "root causes" of workplace injuries, illnesses, and incidents is the failure to identify or recognize hazards that are present, or that could have been anticipated. A critical element of any effective safety and health program is a proactive, ongoing process to identify and assess such hazards.

OBJECTIVES

- Carryout a systematic critical appraisal of all potential hazards involving personnel, plant, services and operation methods
- Identify the existing safeguards available to control the risks due to the hazard

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESSMENT PROCEDURE	Revision No. 01	Page 3 of 84

- Suggest additional control measures to reduce risks to acceptable level
- Prepare a risk register that will help in continuously monitoring these risks
- To take into account for hazard identification and risk assessment:
 - Routine and non-routine activities;
 - Activities of all persons having access to the workplace (including sub-contractors and visitors)
 - human behaviour, capabilities and other human factors;
 - identified hazards originating outside the workplace capable of adversely affecting the health and safety of persons under the control of the organization within the workplace;
 - hazards created in the vicinity of the workplace by work-related activities under the control of the organisation;
 - infrastructure, equipment and materials at the workplace, whether provided by the organization or others
 - changes or proposed changes in the organization, its activities, or materials
 - modifications of the OH&S management system, including temporary changes, and their impacts on operations, processes, and activities;
 - any applicable legal obligations relating to risk assessment and implementation of necessary controls
 - The design of work areas, processes, installations, machinery/ equipment, operating procedures and work organization, including their adaptation to human capabilities.

Methodology for hazard identification and risk assessment:

- shall be defined with respect to its scope, nature and timing to ensure it is proactive rather than reactive; and
- provide for the identification, prioritization and documentation of risks, and the application of controls, as appropriate

For the management of change, the organization shall identify the OH&S hazards and OH&S risks associated with changes in the organization, the OH&S management system, or its activities, prior to the introduction of such changes.

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 4 of 84

The organization shall ensure that the results of this assessment are considered when determining controls.

When determining controls, or considering changes to existing controls, consideration shall be given to reducing the risks according to the following hierarchy:

1. elimination
2. substitution
3. engineering controls
4. signage/warnings and/ or administrative controls
5. personal protective equipment

The company shall document and keep the results of identification of hazards, risk assessments and determined controls up-to-date

The organization shall ensure that the OH&S risks and determined controls are taken into account when establishing, implementing and maintaining its OH&S management system.

RESPONSIBILITIES

Managers

- All managers in RAMA must have to ensure the safety of workers
- Take corrective action in order to improve safety of workers to the highest level.
- Facilitate training to employees according to their position
- Communicate your commitment to a safety and health program
- By establishing specific goals and objectives, management sets expectations for managers, supervisors and EHS officers about the program goals
- Allocate resources
- Expect performance by allocating roles and responsibilities for each officer.

EHS OFFICERS

- Conduct work place inspection regularly
- Check for the deviation of safety
- Manage risks by risk mitigation plan
- Identifying hazards associated with the operations and select worst case scenarios for estimation of consequences. Reputed software models will

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESSMENT PROCEDURE	Revision No. 01	Page 5 of 84

be used for consequence estimation. Based on the estimated frequency of occurrence, risk reduction measures will be suggested to the management for effective implementation.

- Group similar incidents and identify trends in injuries, illnesses, and hazards reported.
- Consider hazards associated with emergency or non-routine situations.
- Encourage workers to participate in the program
- Encourage workers to report safety and health concerns
- Give workers access to safety and health information
- Involve workers in all aspects of the program
- Remove barriers to participation

Hazard Prevention and Control

To effectively control and prevent hazards, RAMA should:

- Involve workers, who often have the best understanding of the conditions that create hazards and insights into how they can be controlled.
- Identify and evaluate options for controlling hazards, using a "hierarchy of controls."
- Use a hazard control plan to guide the selection and implementation of controls, and implement controls according to the plan.
- Develop plans with measures to protect workers during emergencies and non-routine activities.
- Evaluate the effectiveness of existing controls to determine whether they continue to provide protection, or whether different controls may be more effective. Review new technologies for their potential to be more protective, more reliable, or less costly.

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 6 of 84

HIRA PROCEDURE

i) Collect existing information about workplace hazards

Information on workplace hazards may already be available to employers and workers, from both internal and external sources.

How to accomplish it

Collect, organize, and review information with workers to determine what types of hazards may be present and which workers may be exposed or potentially exposed. Information available in the workplace

ii) Inspect the workplace for safety hazards

Hazards can be introduced over time as workstations and processes change, equipment or tools become worn, maintenance is neglected, or housekeeping practices decline. Setting aside time to regularly inspect the workplace for hazards can help identify shortcomings so that they can be addressed before an incident occurs.

How to accomplish it

- Conduct regular inspections of all operations, equipment, work areas and facilities. Have workers participate on the inspection team and talk to them about hazards that they see or report.
- Be sure to document inspections so you can later verify that hazardous conditions are corrected. Take photos or video of problem areas to facilitate later discussion and brainstorming about how to control them, and for use as learning aids.

iii) Identify health hazards

Identifying workers' exposure to health hazards is typically more complex than identifying physical safety hazards. For example, gases and vapours may be invisible, often have no odour, and may not have an immediately noticeable harmful health effect. Health hazards include chemical hazards (solvents, adhesives, paints, toxic dusts, etc.), physical hazards (noise, radiation, heat, etc.), biological hazards (infectious diseases), and

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESSMENT PROCEDURE	Revision No. 01	Page 7 of 84

ergonomic risk factors (heavy lifting, repetitive motions, vibration). Reviewing workers' medical records (appropriately redacted to ensure patient/worker privacy) can be useful in identifying health hazards associated with workplace exposures.

How to accomplish it:

- Identify *chemical hazards* –review SDS and product labels to identify chemicals in your workplace that have low exposure limits, are highly volatile, or are used in large quantities or in unventilated spaces. Identify activities that may result in skin exposure to chemicals.
- Identify *physical hazards* –identify any exposures to excessive noise (areas where you must raise your voice to be heard by others), elevated heat (indoor and outdoor), or sources of radiation (radioactive materials, X-rays, or radiofrequency radiation).
- Identify *biological hazards* –determine whether workers may be exposed to sources of infectious diseases, molds, toxic or poisonous plants, or animal materials (fur or scat) capable of causing allergic reactions or occupational asthma.
- Identify *ergonomic risk factors* –examine work activities that require heavy lifting, work above shoulder height, repetitive motions, or tasks with significant vibration.
- Conduct *quantitative exposure assessments* –when possible, using air sampling or direct reading instruments.
- *Review medical records* –to identify cases of musculoskeletal injuries, skin irritation or dermatitis, hearing loss, or lung disease that may be related to workplace exposures.

iv) Conduct incident investigations

Workplace incidents –including injuries, illnesses, close calls/near misses, and reports of other concerns– provide a clear indication of where hazards exist. By thoroughly investigating incidents and reports, you will identify hazards that are likely to cause future harm. The purpose of an investigation must always be to identify the root causes (and there is often more than one) of the incident or concern, in order to prevent future occurrences.

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 8 of 84

How to accomplish it

- Develop a clear plan and procedure for conducting incident investigations, so that an investigation can begin immediately when an incident occurs. The plan should cover items such as:
 - Who will be involved
 - Lines of communication
 - Materials, equipment, and supplies needed
 - Reporting forms and templates
 - Train investigative teams on incident investigation techniques, emphasizing objectivity and open-mindedness throughout the investigation process.
- v) Identify hazards associated with emergency and non-routine situations

Emergencies present hazards that need to be recognized and understood. Non routine or infrequent tasks, including maintenance and start-up/shutdown activities, also present potential hazards. Plans and procedures need to be developed for responding appropriately and safely to hazards associated with foreseeable emergency scenarios and non-routine situations.

How to accomplish it

- Identify foreseeable emergency scenarios and non-routine tasks, taking into account the types of material and equipment in use and the location within the facility. Scenarios such as the following may be foreseeable:
- vi) *Characterize the nature of identified hazards, identify interim control measures, and prioritize the hazards for control*

The next step is to assess and understand the hazards identified and the types of incidents that could result from worker exposure to those hazards. This information can be used to develop interim controls and to prioritize hazards for permanent control.

How to accomplish it

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 9 of 84

- Evaluate each hazard by considering the severity of potential outcomes, the likelihood that an event or exposure will occur, and the number of workers who might be exposed.
- Use interim control measures to protect workers until more permanent solutions can be *implemented*

9) Monitoring and evaluation

Once a safety and health program is established, it should be evaluated initially to verify that it is being implemented as intended. After that, employers should periodically, and at least annually, step back and assess what is working and what is not, and whether the program is on track to achieve its goals. Whenever these assessments identify opportunities to improve the program, employers, managers, and supervisors—in coordination with workers—should make adjustments and monitor how well the program performs as a result. Sharing the results of monitoring and evaluation within the workplace and celebrating successes will help to drive further improvement.

Communication and Coordination for employees and interested parties

We will use two strategies to communicate with our employees as well as interested parties

I) establish effective communication

RAMA establishes and implements a procedure to ensure the exchange of information about hazards present on site and the hazard control measures in place. Thus, all workers on the site are aware of worksite hazards, and the methods and procedures needed to control exposures to them.

How to accomplish it

- RAMA communicates with its employees to determine which among them will implement and maintain the various parts of the safety and health program, to ensure protection of all on-site workers before work begins. These determinations can be included in contract documents that define the relationships between the parties.

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 10 of 84

- RAMA establishes and implements procedures to exchange information with contractors and staffing agencies about hazards present in the workplace and the measures that have been implemented to prevent or control such hazards.
- The host employer gathers and disseminates information sufficient to enable each employer to assess hazards encountered by its workers and to avoid creating hazards that affect workers on the site.
- Sub-Contractors regularly give any information about injuries, illnesses, hazards, or concerns reported by their workers and the results of any tracking or trend analysis they perform to RAMA.
- Each sub-contractor establishes and implements a procedure for providing the host employer with information about the hazards and control measures associated with the work being done by its workers and the procedures it will use to protect workers on the site.

II) Establish effective coordination

RAMA coordinate on work planning, scheduling, and resolving program differences to identify and work out any concerns or conflicts that could impact safety or health.

How to accomplish it:

- Include in contracts and bid documents any safety-related specifications and qualifications and ensure that contractors and staffing agencies selected for the work meet those requirements.
- Identify issues that may arise during on-site work and include procedures to be used by the employer and subcontractors and/or staffing agencies for resolving any conflicts before work starts.

Host employers coordinate with contractors and staffing agencies to:

- Ensure that work is planned and scheduled to minimize impacts on safety.
- Ensure that staffing agency workers are adequately trained and equipped before arriving on the worksite.
- Harmonize their safety and health policies and procedures to resolve important differences, so that all workers at the site have the same protection and receive consistent safety information.

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 11 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
1	Transportation of tools, equipment, machine and machineries to the site	- Vehicle movement - Loading and unloading of machinery - traffic movement - contact with chemicals - manual handling	- Physical (traffic, heavy object injury) - Chemical (contact with petroleum products i.e. gasoline, grease) - Ergonomics (awkward posture, car seats not correctly installed)	- MSDs - Broken bones, Fracture, dislocation - muscle dislocation, separation, torn muscle - Contact dermatitis - Chemical inhalation - Systemic in toxicities - Death
2	Installing camps, cranes, machineries and equipment	- Construction of offices and accommodation - Working with machines - Manual handling	- Physical (traffic, heavy object injury) - Chemical (contact with petroleum products i.e. gasoline, grease)	- MSDs - Broken bones, Fracture, dislocation - muscle dislocation, separation, torn muscle

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 12 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
		- Contact with chemicals - Work at height - Heavy object lifting	- Ergonomics (design problems of equipment and machineries) - Biological hazards(bite with insect, bite with animal, toxic plant)	- Contact dermatitis - Chemical inhalation - Systemic in toxicities - Exposure to zoonotic disease - Death
3	Office work and furniture	- Work with computer computers, - Ergonomics - Lighting - Contact with electric city - Contact with chemical	- Ergonomics (working in awkward position, - Physical (heat, illumination, failure to acclimatize, trip over accident, fire, - Chemical (toner, printer ink, - Psychosocial (isolation, working in extended hour)	- MSDs - muscle dislocation, separation, - Contact dermatitis - Chemical inhalation - Systemic in toxicities - Stress related illness - Eye splash

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 13 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
4	Excavation	▪ Digging away ▪ Working with machinery ▪ Loading unloading ▪ Work at confined space	▪ Physical (wall collapse, vehicle and machinery trip overs and traffic accident, fall, falling object, noise, ▪ Ergonomic ((working in awkward position, confined space hazard) ▪ Psychosocial (fear of having structural/wall collapse)	▪ MSDs ▪ Bone fracture. Dislocation ▪ Muscle dislocation ▪ Temporary or permanent hearing loss ▪ Stress related illness ▪ Death
5	Form work fixing	▪ Contact with chemicals ▪ Work at height ▪ Work at confined space	▪ Physical (form work structure collapse, vehicle and machinery trip overs and traffic accident, fall hazard, falling object, noise	▪ MSDs ▪ Bone fracture. Dislocation ▪ Muscle dislocation

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 14 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
			- Ergonomic ((working in awkward position, confined space hazard) - Psychosocial (fear of having structural/wall collapse)	- Temporary or permanent hearing loss - Stress related illness - Death
6	Placing of steel reinforcement	- Work with steel - Bending steels - Lifting - Pulling - Contact with chemical	- Physical (form work structure collapse, sharp object injury, vehicle and machinery trip overs and traffic accident, fall hazard, falling object, noise - Ergonomic (working in awkward position, confined space hazard)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 15 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
			Psychosocial (fear of having structural/wall collapse)	- Stress related illness - Death
7	Assembling Spare parts	- Work with machinery - Rinsing with Grease - Manual handling - Contact with chemicals - Loading and unloading of spares	- Physical (falling injury, falling object, being caught by moving machinery, - Ergonomic (working in awkward position, static position work for a long time.) - Psychosocial (fear of having cut or caught by machinery)	- MSDs - Bone fracture and dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Temporary or permanent hearing loss
8	Introduction of new machinery or work systems	- Training - Continuous follow up	Depends on the type of machine(needs its own HIRA)	

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 16 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
		Monitoring and evaluation of activities		
8	Equipment inspection	- Work with machinery - Work at Confined space - Contact with chemical - Work at height	- Physical (sharp object injury, vehicle and machinery trip overs and traffic accident, fall hazard, falling object, noise, dust) - Ergonomic (working in awkward position, confined space hazard) - Chemical hazard(contact with hazardous chemical)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss - Stress related illness - Death

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 17 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
9	Concrete work	- Manual handling - Work at Confined space - Contact with chemical - Loading unloading - Manual handling - Work at height	- Physical (form work structure collapse, sharp object injury, vehicle and machinery trip overs and traffic accident, fall hazard, falling object, noise - Ergonomic (working in awkward position, confined space hazard,) - Psychosocial (fear of having structural/wall collapse)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss - Stress related illness - Death
10	Masonry works	- Manual handling - Work at Confined space	Physical (sharp object injury, and traffic, fall	- MSDs - Bone fracture. Dislocation

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 18 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
		- Contact with chemical - Loading unloading - Manual handling - Work at height	- hazard, falling object, noise, dust) - Ergonomic (working in awkward position, work in static position for a long time) - Psychosocial (fear of having being hit by concrete)	- Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss - Stress related illness - Death
11	Plastering and pointing	- Manual handling - Work at Confined space - Contact with chemical - Loading unloading - Manual handling - Work at height	- Physical (sharp object injury, fall hazard, falling object, noise, dust) - Ergonomic (working in awkward position, confined space hazard)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 19 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
			- Chemical hazard (contact with chemicals) - Psychosocial (fear of having structural/wall collapse)	- Temporary or permanent hearing loss - Stress related illness - Death
12	Pavior	- Manual handling - Work at Confined space - Contact with chemical - Loading unloading - Manual handling - Work at height	- Physical (form work structure collapse, sharp object injury, vehicle and machinery trip overs and traffic accident, fall hazard, falling object, noise) - Ergonomic (working in awkward position, confined space hazard)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 20 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
			Psychosocial (fear of having structural/wall collapse)	- Stress related illness - Death
13	Carpentry and joinery	- Manual handling - Work at Confined space - Contact with chemical - Loading unloading - Manual handling - Work at height	- Physical (form work structure collapse, sharp object injury, dust, fall hazard, falling object, noise, dust) - Ergonomic (working in awkward position, working in static position for a long time) - Psychosocial (fear of having structural/wall collapse, fear of having being hit by material)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss - Stress related illness - Death

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 21 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
14	Electromechanical works	- Manual handling - Work at Confined space - Contact with chemical - Loading unloading - Manual handling - Work at height - Contact with electric city	- Physical (form work structure collapse, sharp object injury, electrical shock, fall hazard, falling object, noise, burning injury, noise) - Ergonomic (working in awkward position, confined space hazard, work in static position) - Psychosocial (fear of having structural/wall collapse)	- MSDs - Bone fracture. Dislocation - Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss - Stress related illness - Death
15	Painting	- Manual handling - Work at Confined space	Physical (form work structure collapse, sharp object injury, vehicle and	- MSDs - Bone fracture. Dislocation

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 22 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
		- Contact with chemical - Loading unloading - Manual handling - Work at height	- machinery trip overs and traffic accident, fall hazard, falling object, dust) - Ergonomic (working in awkward position, confined space hazard) - Psychosocial (fear of having structural/wall collapse)	- Muscle dislocation - Excessive bleeding - Body part loss - Shock - Temporary or permanent hearing loss - Stress related illness - Death
17	Road materials production	- Contact with chemical - Outside working - Manual handling - Loading unloading - Work at confined space	Physical (form work structure collapse, sharp object injury, vehicle and machinery trip overs and traffic accident, fall	- MSD - Dermatitis - Respiratory infection - Body part loss

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 23 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
			hazard, falling object, noise, dust) - Ergonomic (working in awkward position, confined space hazard) - Psychosocial (fear of having structural/wall collapse)	- Temporary or permanent hearing loss - Stress related illness - Death
18	Disposal of old document	- Manual handling - Contact with chemical	- Environmental pollution - Soil and aquatic pollution	- Failure to adapt the environment - Aquatic disturbance which can be risk factor to hygiene related disease.
19	Supervision	Visiting	Physical (form work structure collapse, sharp	MSDs

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 24 of 84

Sr.no	Types of Activity, process and working environment	Aspect (process)	Hazard	Risk
		Taking corrective action	- object injury, vehicle and machinery trip overs and traffic accident, fall hazard, falling object, dust) - Ergonomic (working in awkward position, confined space hazard) - Psychosocial (fear of having being hit by vehicle or machinery)	- Bone fracture. Dislocation - Temporary or permanent hearing loss - Stress related illness

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 25 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence) Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Manual handling	ALL staff suffer this hazard	MSDs Back pain	3	3	9	Medium	PPE being supplied to all workers, tool boxes are given to workers	provision of appropriate lifting equipment reduce load of equipment less than 20kg provide training on proper manual handling method	3	1	3	Low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 26 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

000 Annex for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Stress	ALL staff suffer this hazard	Stress related illness	3	3	9	medium			3	1	3	Low
	Electrical	ALL staff suffer this hazard	Shock Fire Death	4	3	12	Medium		cable location and permit supply high voltage and low voltage cable plan planned inspection and maintenance	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 27 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

000 Annex for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
								of electric tools and equipment compliance with work at electric city					
	Fire	ALL staff suffer this hazard	Shock Fire Death	4	4	16	High	firefighting equipment provided staff trained on fire extinguisher operation	4	2	8	Medium	

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 28 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									control hot work permit system being implemented iv)mock drill for fire is done				
	Slips, trips and fall	ALL staff suffer this hazard		4	3	12	medium		compliance with workplace regulation ii)suitable access equipment provided,	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 29 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
								inspected maintained iii)signs and barriers correctly located					
	Musculoskeletal injuries	All workers	Muscle dislocation Bone dislocation Disability which can be permanent or temporary	3	3	9	Medium	PPE being supplied to all workers, tool boxes are given to workers Induction given to	Isolating workers from works which can potentially harm muscles. Arrange shift work Supply PPE	3	1	3	Low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 30 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Violence and threatening behaviour	All workers	Stress related illness	3	2	6	Medi um	all new staff Risk assessments conducted Site inspection carried out		3	1	3	Low
	Contact with steam, hot water, hot oil and hot surfaces	Cafeteri a workers in head office and projects , electrici ans, welders	Burning Wound Shock	3	3	9	Medi um		Avoid work at hot surfaces or chemicals Train on safe procedures to work with hot surface Supply PPE	3	1	3	Low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 31 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Contact with bleach and other cleaning chemicals	Janitors and cafeteri a workers are prone to these types of hazards.	Skin allergy and irritation may happen in prolonged exposure In case of inhalation or ingestion there may be some sever injury	4	3	12	Medi um			4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 32 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Workplace temperature	Workers in hot environment,	Heat stress Suffocation Faint	4	2	8	Medium			4	1	4	Medium
	Working at awkward posture	All staff	Joint pain	4	4	16	High			4	2	8	Medium
	Stacking and lifting			4	3	12	Medium			4	2	8	Medium
	Noise	Drivers, mixer operators, generators,	Temporary hearing loss	4	3	12	Medium			4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 33 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Likeliho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
		or operator s	Permanent hearing loss Lack of concentrat ion										
	Fire and explosion		Burning	4	3	12	Medi um			4	1	4	Medi um
	Unauthorize d use of machinery	All workers		4	4	16	High			4	2	8	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 34 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Trips and slips	All workers	Bone fracture Bone and muscle dislocation	4	4	16	High			4	2	8	Medi um
	Traffic hazards	All workers	Falling Bone fracture	4	4	16	High		segregate pedestrian from clothing provision and use of traffic sign	4	2	8	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 35 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									flag man in all required places provision and use of high visibility clothes				
	Work at Confined spaces	Concret e workers , excavati on workers , plasterin	Suffocatio n Asphyxiati on	4	2	8	Medi um		i)working methods, evacuation routes and emergency procedures to be	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 36 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

Risk Assessment for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
		g and pointing workers							established before entry ii)compliance with guidance of work at confined spaces must have to be done				
	contact with Contaminated soil/waste	Outside workers , project workers	Source of infectious waste	4	2	8	Medium		Compliance with Ethiopian environmental protection	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 37 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									authority proclamations proper management of any type of waste from generation to disposal iii)separate disposal system for waste				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 38 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Dust	All workers in the project	Respirator y infection Suffocatio n	3	3	9	Medi um		Substitute materials with the less dusty Isolate workers from dusty materials PPE like respiratory protection have to be provided	3	1	3	Low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 39 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									Making washing facilities available Minimize exposure time to dust or arranging shift work				
	Contaminati on of Ground water/sewa ge	Commu nity using	Respirator y problems Lung cancer	4	2	8	Medi um		obtain drainage plan prior inspection of work area	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 40 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

USE Annex 10 for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Welding fume	Welders	Fracture Temporary disability Permanent disability Death	4	4	16	High		provision of appropriate PPE using hot work permit system weld in well-ventilated area	4	2	8	Medium
	Failure to use PPE	All workers not using PPE	Different injuries Death happen	4	2	8	Medium		i)create awareness on the importance of PPE	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 41 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									II)close supervision of workers iii)procedures for encouraging those who use PPE regularly and punishment to those who do not must have to be in place				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 42 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Being caught by Moving objects	All workers	Smoke Respirator y problems	4	3	12	Medi um		I)keep at a safe distance from moving objects ii)SOP for each moving machinery must be in place iii)proper training on precautions that must have to be taken when	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 43 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									working with moving machinery Provide appropriate PPE to workers				
	Respiratory diseases	Welders , painters , cheaslin g workers	Accident Damage to different body parts	4	3	12	Medi um		Reduce exposure to substances which cause a disease Use PPE for prevention of inhalation	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 44 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			Lung cancer						Training on the symptoms of respiratory diseases for early prevention of diseases before causing large damage in a human body.				
	Work in trench	Excavati on workers		4	3	12	Medi um		i)trenches inspected prior to entry compliance with regulation of RAMA	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 45 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

USE Annex for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									Work permit for jobs to be done in trench must be in place				
	Head injuries	All workers	Sever bleeding Skull fracture death	5	4	20	High		observe site rules provide PPE Conduct mock drill for head injuries	5	2	10	Medium
	Failure to respect Site emergency	All workers not respecting	Accident happens due to	4	3	12	Medium		Restrict unauthorized entry to the site.	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 46 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

USE Annex 10 for Reference

HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	s/restricted access/egress	emergency procedure and site access plans	unauthorized entry to site.						identification of site responsibilities induction for new staff induction for visitors post safety signs				
	Falling objects	All workers	Head injury Severe bleeding	4	3	12	Medium		restrict access to areas below overhead protection	4	2	8	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 47 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20)								Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)					
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			Faint Death						use safety signs of work overhead prevention of falling object provide PPE				
	Work adjacent to water courses	Those who work in marshy areas		4	3	12	Medi um		spill control procedure obtain drainage plan prepare plan for material/waste	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 48 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Likeliho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									storage and disposal				
	Work adjacent to trees, affecting flora and fauna	All workers working in such environment will be affected , environmental impact will	Insect bite, being hit by trees, animal bite	3	4	12	Medi um		protect the flora and fauna of the environment Housekeeping must be conducted to prevent danger from toxic chemicals from	3	2	6	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 49 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
		disturb the environ ment,							animal and plants in that area. Wear appropriate PPE to prevent toxicity				
	Emission from street works plant	Road project workers	Respiratory problems/ infection	4	2	8	Medi um		location of plant and equipment duration of use of plant and equipment	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 50 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20)								Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)					
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									maintenance of plant and equipment				
	Being struck by internal transport (fork-lifts) or external transport (delivery	All workers	Head injury Injury to leg, and different body parts	4	3	12	Medi um		separate pedestrian and vehicle road Driving slowly in the work places Driving is allowed only for those who have license	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 51 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Likeliho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	trucks at loading bays)								Inspection of vehicles before driving				
	Ejection of material (from plastic moulding or woodworkin g machines)		Injury to hand Cutting and wound Disability which can be	4	4	16	High		Protecting workers from direct contact with the machinery Use of appropriator PPE to prevent inhalation	4	2	8	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 52 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			permanent or temporary .						Training on the safe use of equipment and what to do during operating				
	Contact with Hot substances or surfaces	Welders , cafeteri a workers ,	Burning injury	4	3	12	Medi um		proper signage of hot surfaces Provide appropriate PPE to prevent damage from hot	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 53 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

000 Annex for Reference														
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures					
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment						Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									Training for workers in first aid when danger happen					
	Suffocation by drowning or from exposure to carbon monoxide (from	Generator operators	Faint Death	4	2	8	Medium		Eliminating exposure to CO where there is limited supply of oxygen Use mouth mask to prevent inhalation of CO	4	1	4	Medium	

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 54 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20)								Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)					
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	portable generators)								Training on first aid in the case of emergency due to inhalation of CO				
	poor housekeeping	All workers	Infectious disease Falling injury Tetanus due to sharp	4	3	12	Medium		Inspection of work environment regularly Cleaning of work environment as required	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 55 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			object injury										
	Frost bite	All workers who work in high altitude	Cold cases	4	3	12	Medi um			4	1	4	Medi um
	Harmful substances	Painters , road construc tion workers , janitors	Skin cancer in long term exposure	4	3	12	Medi um		staff trained in control of substances hazardous to health	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 56 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
			Respiratory problems						MSDS should be posted on each chemical transcribed into local language provide suitable PPE for the chemicals				
	Cement dust	All project workers specially daily laborers	Infected by different diseases	4	3	12	Medium		Eliminate contact of workers with cement dust by	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 57 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			like cough, asthma						using mixer in all activities Reduce exposure to dust Using PPE to prevent inhalation and skin contact with cement dust Training on the health effect of PPE and measures that should be				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 58 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									taken to prevent the effect				
	Environmen tal emergencie s	All workers	Sever injuries Disability which can be permanent or temporary Death	4	3	12	Medi um		store materials in a safe location and label them limit the quantity of materials stored on site Allow entry of authorized personnel only.	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 59 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

Risk Assessment for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Splash in a chemical	Painters , store man, janitors	Skin problems like dermatitis Burning Death	3	3	9	Medium		Label every chemical to easily identify what measures should be taken in the case of emergency Use appropriate PPE to prevent further damage in case of emergency	3	1	3	Low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 60 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Splash in acid	Store man and those who engaged in garage work	Skin problem Dermatitis	4	3	12	Medium		Label any acid stored Use appropriate PPE in the case of emergency Training on first aid in the case of emergency from acid	4	1	4	Medium
	chest problems	Those frequently lift heavy objects,	Destruction of human	4	3	12	Medium		Reduce exposure to chemicals	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 61 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
		carpenters, masonry workers	and plants around Damage to property						Using chemicals which are likely to have less effect Prevent inhalation of chemicals by PPE				
	skin problems	Welders, janitors, daily laborers and Forman	Damage to skin Burning Wound	4	3	12	Medium		Use chemicals which have less effect on health	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 62 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									Use PPE to prevent contact with chemicals Training on first aid in the case of emergency				
	Bite with insect	All project workers	Exposure to protozoan diseases like malaria,	4	3	12	Medium		cleaning the work environment regularly use insecticides when it is find appropriate	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 63 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			trichonomi asis										
	Epidemics	All workers	Delay in project Decrease in immunity Death	4	3	12	Medi um		prevent contamination of food and water clean the environment give appropriate medication to those who travel to malaria prone area	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 64 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Bite with animal	All workers	Zoonotic disease infection	4	3	12	Medi um		House keeping Proper medication in the case of emergency Fencing the site	4	1	4	Medi um
	Contact with toxic or poisonous plants	All workers	skin irritation sensitizer causing	4	3	12	Medi um		House keeping Conducting environmental scanning before	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 65 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
			dermatitis						the beginning of every project Communicate with local peoples at which the project is operating				
	contact with infectious agents	All workers	skin irritation sensitizer causing dermatitis	4	3	12	Medi um		roper house keeping proper treatment of sick person he/she may be act as an agent	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 66 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									Provide medication to every worker who has observed any symptom of disease				
	Vibration	Welders , drivers, mixer operator s, generat or operator s	Muscle dizziness	3	3	9	Medi um		Lower the exposure to vibration Substitute with the least vibrating equipment Provide training to workers	3	1	3	Low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 67 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Standing, trips, twisting, or bending			4	3	12	Medi um		Elevate receiving container Rotate staff and tasks Take adequate breaks Anti-fatigue, anti-static, or rubber mats Have table and cart at the same height Minimize twisting or sharp movements Adjust table heights Platforms or stools	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 68 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Repetition, awkward wrist angle, lifting, bending, stirring, and long periods of standing	All workers		3	4	12	Medi um		Wrist supports Loosen lid with hammer Paint can opener, hatchet or vice grip for opening containers Switch hands to reduce fatigue Reduce work time Rotate the job task and shifts Hire additional staff	3	2	6	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 69 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

USE Annex 10 for reference

HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures					
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment						Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Neck strain		Tiredness Back pain	3	3	9	Medium		Change cartridge type from dual to chemical cartridge with a pre-filter Take breaks and limit the amount of use time	3	1	3	Low	
	Stress and isolation	Newly hired staff	Stress related illness	3	2	6	Medium		conduct informal meeting with workers regularly rotation of workers regularly in the work that they can do	3	1	3	Low	

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 70 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Sexual harassment	Female workers	Stress	4	3	12	Medi um		Train on positive behavior at work Assign females together	4	1	4	Medi um
	Social conflict	All workers	Delay in the finishing time of the project	4	2	8	Medi um		creating environment which workers do not interact in a negative manner awareness creation on	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 71 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
	Work load	All workers	Tiredness Anatomical abnormaliti es Muscle cramp Stress related illness	4	3	12	Medi um		Managing work in a proportional manner throughout the project life Following the schedule set for the project iii) Assist with each other in the case of work over load	4	1	4	Medi um

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 72 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) **Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)**
Use Annex for reference

Annex for Reference													
HAZARD DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	extremes of temperature	All workers in low altitude areas	Respiratory problems	4	3	12	Medium		Making work area well ventilated Minimize exposure time to temperature more than a room temperature Training on first aid in the case of impact arise from exposure to excessive temperature	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 73 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
	Some types of light (e.g. over-exposure to ultra-violet light)	Outside workers	Heat stress Shocking	4	2	8	Medium		Minimize exposure to UV radiation from the sun Use PPE to prevent exposure from UV	4	1	4	Medium
	Traffic accident out of projects	Workers , Management staff and drivers	Major accident of fracture and other	4	2	8	Medium		Provide awareness for drivers and passengers regarding control mechanisms of	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 74 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence) Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
			related even fatal						traffic hazards including speed limit and inspect the vehicle truck as per the requirement				
	The external accidents	Rama Workers working at the area.	accident of fracture and other related even fatal	4	2	8	Medium		Provide awareness for Rama workers to ensure their safety and not participate the	4	1	4	Medium

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 75 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									external hazard without any control measures.				
	Flood	All site workers	Serious physical injury even fatal case	4	3	12	medi um		Providing emergency preparedness plan on flood occurrence and provide awareness to all site workers. Assign indicators personnel during flood coming.	4	1	4	low

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 76 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence) Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									Assign suitable access from the river to safe area at both sides. Assign workers out of the river during rain time.				
	Bitumen handling	All site workers	Serious physical injury even fatal case	4	3	12	medium		Appropriate Safety Signage's to be displayed at work area. Separate Pedestrian route to be maintained, where required. One-way traffic to be				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 77 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Likeliho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									implemented to reduce risk of traffic incidents, where applicable. • Minimize dust emission due to the movement of equipment's/vehicles. • Water spraying trucks to be used where possible for dust suppression. • Ensure periodic maintenance and service of				

	Company Name RAMA CONSTRUCTION PLC		Document No. RAMA-CRD-049	
	Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE		Revision No. 01 Page 78 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence) Use Annex for reference													
HAZARDS	INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									equipment/vehicle used at site to reduce noise and vibration. Close supervision by Asphalt supervisor Trained & Appropriate Safety Signage's to be displayed at work area. Separate Pedestrian route to be maintained, where required. One-				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 79 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENC ES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Like liho od (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									way traffic to be implemented to reduce risk of traffic incidents, where applicable. Trained & Certified First aider and First aid kit available on site. Follow MSDS guidelines for the chemicals being used, use correct PPEs.				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 80 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence) Use Annex for reference													
HAZARDS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk			Severity (S)	Likelihood (P)	Outcome (S)x(P)	Residual Risk
									Establish good communication at all levels. Communicate all hazards and precautions to the work crew members Keep area diverted from surrounding live traffic, use banks man, barriers, night blinkers, signage, buffer zone etc.				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 81 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20) Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)													
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment					Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls			
				Sever ity (S)	Likeli hood (P)	Outco me (S)x(P)	Initial Risk			Severit y (S)	Likeliho od (P)	Outco me (S)x(P)	Resid ual Risk
									Ensure good supervision all the time. Operators shall be aware of potential hazards due to spillage They shall be trained in handling any spillage minor/major at site and need to be reported any kind of spillage to immediate supervisor				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
	Title HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 82 of 84

Risk: L = Low (1 - 3), M = Medium (4 - 15), H = High (16 - 20)								Risk Rating (RR) = S (Severity) x P (Likely hood of Occurrence)					
Use Annex for reference													
HAZAR DS	HAZARDS INVOLVED Describe all hazards identified for each task based on observations and experience Note: Additional hazards may be caused by interaction with other work	Without Control Measures						Existing Control Measures	With Control Measures				
		WHO MAY AT RISK?	RISK / CONSEQUENCES	Risk Assessment						Control Measures Describe fully all equipment, facility, and/or procedure controls applicable for each hazard. All controls must be valid in that they reduce severity, probability, or both.	Risk Assessment after controls		
				Severity (S)	Likelihood (P)	Outcome (S)x(P)	Initial Risk	Severity (S)			Likelihood (P)	Outcome (S)x(P)	Residual Risk
									and spillage should be immediate cleaned.				

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 83 of 84

Annex I

Risk Matrix and Tolerance Limit

Destruction Multiple Fatalities	5	10	15	20	25
Major Damage Some Fatalities	4	8	12	16	20
Serious Incident Major Injuries	3	6	9	12	15
Slight Incident Minor Injuries	2	4	6	8	10
Little Consequence	1	2	3	4	5

RISK TREATMENT

H		Stop Operation And Rectify Immediately
M		Accountable Manger Risk Decision Needed
M		With Management Review
L		Without Review

Almost Inconceivable
Very Unlikely to Occur
Unlikely but Possible to Occur
Likely to Occur Sometimes
Likely to Occur Many Times

	Company Name RAMA CONSTRUCTION PLC	Document No. RAMA-CRD-049	
Title	HAZARD IDENTIFICATION AND RISK ASSESMENT PROCEDURE	Revision No. 01	Page 84 of 84

3. RELATED DOCUMENTS

<u>Document Title</u>	<u>Document No.</u>
Hazard Identification Record Sheet	

4. DISTRIBUTION

- Managing Director
- General Manager
- Chief Operation Officer
- All Departments
- All Projects

Approval Name:	Signature:	Date: 13/02/2026
----------------------------------	-----------------------	---------------------