

Audion Browsers Portable

[Русский](#) · [User Guide](#)

Contents

- [Portable libraries](#)
- [Single-browser tools consolidated](#)
- [Why It Exists](#)
- [Official Downloads](#)
- [Who Is on the DLL Build List, and Why](#)
- [Next](#)
- [Technical Reference](#)
 - [What You Get](#)
 - [Updating](#)
 - [The Antivirus False Alarm](#)

One engine for the whole Chromium stack: downloads, unpacks, assembles portable browsers, and keeps them updated.

Portable libraries

The default library is [Proxy library](#) (x86/x64), with every optional switch in `App/version.ini` set to `0`. Alternatives are [Chrome++ \(DeftKing\)](#) and [Vivaldi++](#), both supporting x86/x64/ARM64. A failed release lookup or download falls back to a verified archive of the selected library in the project. The generated launcher starts in `App` so relative `Data` and `Cache` paths stay inside the build. Registry cleanup applies only to Chrome++.

Single-browser tools consolidated

`UPDATE` → `UPDATE DLL ONLY` refreshes the selected library in existing builds without downloading the browser. Browser files, `Data` and `Cache` stay in place. The same library keeps its INI; switching

libraries creates the standard INI, with all optional switches set to zero for Proxy library.

Build, check and update forms have optional Chrome/Yandex full-installer URLs under **Advanced**. Blank fields use official sources. Custom installers are downloaded afresh during build and update.

Disable Yandex updater is enabled by default and removes only **service_update.exe** inside Yandex's **App**. Update the browser through this program afterwards.

CERTIFICATE → **ADD TO BUILD** saves the two Russian Trusted CA certificates and install/revoke commands in an existing build. Installing Windows trust remains a separate command.

Why It Exists

A portable browser is wanted for two reasons: it leaves the system alone and it travels as a folder. But half the browsers have no portable build at all, and the other half have one that never updates. Building it by hand is possible; updating it by hand every three weeks is not.

Nothing is installed into Windows. The installer is not run but unpacked: what it intended to place into the system is taken out of it instead. The profile lives in the build folder, next to the browser.

Official Downloads

The **Downloads** tab saves original files under **Browser Downloads** in the Target folder: Cent Browser portable SFX (x86/x64), LibreWolf portable ZIP (x64/ARM64), Vivaldi installer (x86/x64/ARM64), and the regular DuckDuckGo installer (x64). For Vivaldi, manually choose Advanced → Install Standalone in the saved installer. The program does not run or unpack these files or replace their DLLs.

Repeat downloads verify the saved SHA256; DuckDuckGo's unversioned installer is downloaded to a temporary file and replaces the saved copy only when its hash changes. A source failure is reported for that browser while the remaining downloads continue. Zen is omitted because its current official Windows release has no portable package (checked 2026-10-01).

Who Is on the DLL Build List, and Why

One rule decides for the DLL builder: **the vendor has no portable build that updates itself.**

browser	why it is here
Google Chrome	no portable build at all
Yandex Browser	no portable build, and the Russian state root certificates are already embedded
Brave	third-party builds exist, none of them update
Chromium-Gost	speaks the GOST TLS that state portals require; an archive exists, updates do not
Ungoogled Chromium	an archive exists, an updater does not — that is the point of the project

Excluded from the DLL builder:

- **Vivaldi** — an official standalone install with working auto-update;
- **Cent Browser** — an official portable build with a built-in updater;
- **Opera** — no separate portable file, but auto-update packages ship beside the installer, so it can update itself;
- **Thorium** — tried and dropped: the main repository publishes releases without files, the fork builds 32-bit only, and the extension store does not work there — an ordinary ad blocker cannot be installed.

The logic is simple: if a browser can update itself, wrapping it means taking on work the vendor already does — and doing it worse.

Next

- [User Guide](#) — step by step.
- [Checklist](#) — what is run before a release (Russian).
- `tools\CHROME_PLUS_AND_DEFENDER.md` — Chrome++ and the antivirus false positive during builds (Russian).
- `tools\DECISIONS_EN.md` — decisions taken.

Technical Reference

What You Get

A build folder: the browser, the profile, a launcher, and a record of which versions are inside. It travels as a folder. With zero INI switches, registry writes and optional restrictions remain under browser control.

Updating

The engine compares what the vendor has released against what is in the build and updates only what changed. The profile is left alone.

The Antivirus False Alarm

A build can fail during packing with a file access error — this is neither the disk nor a corrupt archive, but the antivirus inspecting a freshly written executable. Covered in

`tools\CHROME_PLUS_AND_DEFENDER.md`.