

Audion Chrome Portable

Windows 10 | 11

release no releases or repo not found

downloads repo not found

license repo not found

Version 1.0.0 · 2026-08-24 · 81.6 MB

- [Direct download](#) — unmetered, no rate limits
- [Project page](#) — every version and how to install

SHA-256: c6516f95adb91ee351edbbe77d291a309c41b7d01797684c57c97ecfb516cfff

Builds a portable Google Chrome, updates a build it is given, keeps Chrome++ current, and can place the Russian Trusted CA certificates into the build along with two wrappers — install and uninstall. Nothing is installed into Windows: the standalone installer is unpacked rather than run.

How it works

```
ChromeStandaloneSetup64.exe (~120 MB)
└─ Chrome.7z
    └─ Chrome-bin\      → <build>\App\
        chrome.exe
        <version>\ and the rest
```

Google moves **Chrome.7z** around inside the installer from time to time, so the program does not trust a fixed path: it walks the candidates and probes them until the payload turns up.

Chrome++ provides the portability: its **version.dll** goes beside **chrome.exe**. The running process then carries **--portable** and **--user-data-dir**, the profile lands in **Data** beside **App** and the cache in **Cache**. An installed Chrome is unaffected — verified on a machine where one was running at the same time.

The wrapper is a choice: Chrome++, the proxy library ([neyrostalker/proksi-biblioteka](#) on GitFlic, pulled off the public pages without a token). The proxy library blocks registry writes instead of wiping the branch on exit and draws no complaint from Microsoft; it ships x86 and x64 only. The three engines and the VirusTotal check are covered in [docs/CHROME_PLUS_AND_DEFENDER.md](#).

Chrome++ is a long-standing, respected open-source project; antivirus sometimes mistakes its [version.dll](#) for a threat. Why that is a false positive and how the program works around it during a build — see [CHROME_PLUS_AND_DEFENDER.md](#).

A finished build:

```
Google Chrome Portable\  
  App\                  browser, version.dll, chrome++.ini  
  Data\                 profile  
  Cache\                cache  
  Certificates\         the certificates and their two wrappers  
  Google Chrome Portable.cmd launcher  
  Portable-Build.json   which versions are inside
```

The interface

The root window is a switcher of four tabs. A command with parameters unfolds on the tab itself: its own run button, named after the action, and its own fields. Service operations sit in a strip above the tabs. Choices are buttons — the chosen one washed with translucent blue, the rest outlined. Captions are short; the explanation lives in the tooltip.

Commands

Tab	Command	What it does
Install	Build	Downloads the installer and Chrome++, publishes a build into the Target folder.
Update	Check	Compares the published versions with the build. Downloads nothing.
Update	Update	Replaces App in the build Source points at, keeps Data and Cache .
Update	Chrome++	Replaces version.dll and chrome++.ini , leaves the browser alone.
Certificate	Check	Reports whether the user trusts them. Changes nothing.

Tab	Command	What it does
Certificate	Into the build	Places both files and the wrappers into the build. Adds no trust.
Certificate	Install	Adds them to the current user's stores.
Certificate	Revoke	Removes exactly those two, by fingerprint.
Service	7-Zip	Checks the unpacker and puts a portable copy into the project folder.

Updating

The published Chrome version comes from Google's version history API, so a check costs one small request and never the installer. The build's own version is read out of the folder (`FileVersion` of `chrome.exe` and of `version.dll`), so a build assembled elsewhere can be updated too.

The update happens **in place**: the build is refreshed in the folder Source points at rather than published anew into the Target folder, which is there for new builds. With nothing in Source, the program looks in `output\Portable`. `App` is swapped by renaming — the old folder steps aside, the new one takes its place, and only then is the old one deleted. When the browser is running and the rename fails, the operation says so and leaves the build alone.

Chrome++ is refreshed together with the browser and by its own command. The asset list comes from the GitHub API and, on any error from it, off the `releases/latest` and `releases/expanded_assets/<tag>` pages, where there is no quota: 60 anonymous API calls an hour run out quietly.

The certificate block

Chrome on Windows consults the **current user's** certificate stores alongside its own root store. So the certificates are added with

```
certutil -addstore -user -f Root russian_trusted_root_ca.crt
certutil -addstore -user -f CA russian_trusted_sub_ca.crt
```

No administrator rights, no effect on other accounts, and it is taken back by thumbprint. Both operations re-read the store afterwards rather than trusting an exit code.

The thumbprints are fixed in the program:

- `Russian Trusted Root CA` — `8FF915CC...AEC2F`, store `Root`;
- `Russian Trusted Sub CA` — `335D43F5...8A01`, store `CA` (intermediate).

An honest caveat: a certificate cannot live entirely "inside the folder" — Chrome on Windows reads the system stores, not a file beside itself. That is why trusting one is a separate, reversible step rather than part of the build.

Yandex Browser does not need this: it trusts that CA out of the box. It has its own program — Audion Yandex Portable.

What it leaves in the system

Chrome keeps counters in `HKCU\Software\Google\Chrome`. The build can wipe that branch on exit, but does **not** by default: the branch is shared with an installed Chrome, and most machines have one. Turn the checkbox on only where there is no installed Chrome.

Requirements

- Windows, the portable Python in `runtime\` (ships with the project).
- `tools\7zip\bin\7za.exe` — installed by the `7-Zip` command on the `Service` tab.
- About 120 MB of download and up to 700 MB while unpacking and publishing.

Running

```
launcher_gui.cmd
```