# Audion Media Tools — changelog

Русский · About · User guide

## 3.0.0 — 15 October 2026

**A new window.** The window is a program of its own — C# on Avalonia, `App\AudionMediaTools.exe`, started by `Start.exe`. The engine runs for the time of an operation and is gone after it; nothing stays in the background.

**The window is the face of the console command.** Every button is an operation of `media_cli.cmd`, and a run opens in the journal with the command that repeats it. The command does everything the window does:

- `describe` — the operations, their fields, choices, presets;
- `run --operation ID --set NAME=VALUE` with `--source`, `--target`, `--result` (the outcome as JSON), `--dry-run` (the commands it would start), `--cancel-file`, `--only`;
- `wrapper NAME`, `map`, `components`, `plan`, `version`;
- exit codes 0 done, 1 failed, 2 a wrong call or a run refused before it began, 130 stopped.

**An interlaced source becomes progressive.** EDITING, STORAGE, DELIVERY and COLOR turn a source of two fields into progressive frames by bwdif - by default a frame of each field, 50i to 50p; a frame of each frame, or the fields kept, are choices in Advanced. A progressive source is not touched, ARCHIVE keeps the fields.

**Sections and modes.** The ribbon holds AUDIO, ENCODE (archive, editing, storage, delivery), PACKAGE, CUT, FRAME RATE, COLOR and DOWNLOAD, each with its modes. DETAILS tells what the files of the Source are; SERVICE holds the checks and the installers. Every section and mode keeps its own form, remembered between launches; only the encoder and the decoder are shared. ↺ brings a mode back to its preset; COMMAND shows the commands of the run without running them.

**The header and SETTINGS.** The versions of yt-dlp, Deno, mpv, FFmpeg and the video card driver stand in the header; a newer yt-dlp, Deno or mpv is marked. SETTINGS: four looks, the fonts of the window and of the terminal, the components with UPDATE and INSTALL, the system — processor,

video card and driver, memory, the FFmpeg coders that passed the check, the disk. ABOUT names the version, the folders, the author and the licence of every part.

**The journal.** The lines of a run come in the colours of the program that writes them. FFmpeg's own progress line `frame= … speed=` stands under the `[PROGRESS]` bar, in the window and in a console, and its last word `Lsize=` ends the file. The journal widens, and its width is remembered. The COMMAND line at the bottom runs a command of your own in the PowerShell 7 of the program (`App\AudionPs.exe`) or in `cmd.exe`.

**The folders are `input` and `output`.** The Source by default is `input\`, the Target `output\`; downloads go to `output\Download`, the list of links is `input\urls.txt`. Beside the paths: history, pin, RESET, LIST, TO SOURCE (the result becomes the next Source) and CLEAR — through the Recycle Bin, after a question that names the folders.

**CUT.** The window drives mpv itself: open, take A and B, mark IN or OUT, a split point taken only forward, the points only of the file chosen. A timecode is typed through a mask — digits one after another, the separators come by themselves. A sound file is cut without loss by default.

**DOWNLOAD.** PASTE beside the link, the list file and the cookies file; ⓘ shows the formats a link offers without downloading; cookies come from a browser or from a file sealed with DPAPI (the shield). A link to a video in a playlist takes the video alone unless the playlist is asked for.

**The 95 wrappers of `Scripts\`** keep their names and run through `media_cli.cmd wrapper`. Each has its description in both languages, and the list of wrappers gives the same call through `run`.

**Documents made from the program.** Operations — every field, choice and preset with its tooltip — and Wrappers are written by `media_cli.cmd map --docs` from the data of the program. New: the console command and the guide for an AI agent.

**Fixed.**

- FRAME RATE and CUT take the declared rate of a constant-rate file: a ProRes LT averaging 24.016 at 23.976 was slowed by 0.17 %, and a cut missed the frame grid.
- "1080p H.264 with AAC" and "for upload" downloads took Opus sound; they take AAC now.
- The 5.1 downmix of the wrappers (front whole, centre −3, rear −6 dB, no LFE) is a field of AUDIO (`downmix_formula`); the plain `-ac 2` of FFmpeg is 7.6 dB quieter on full 5.1.
- The `_sync` wrappers even the timestamps again (`audio_resync`); the ProRes wrappers of COLOR encode the sound to AAC 384k.
- A wrapper of two runs (the sound of videos, then sound files) no longer fails on a folder of one kind: a run without files of its own is passed by.

- A file stopped halfway is never left under its final name: a file is written under `name.writing.ext` and takes its name only whole.
- Empty folders a run made in the Target are taken away after it.
- DETAILS tells an interlaced rate (`25i`) and a variable one (`VFR 30 (avg 28.875)`), and names a file it cannot read or that another program holds.
- `--dry-run` of an operation that cannot only say its commands is refused instead of running for real; a dry run sets only the dry-run field of its own operation.
- A second run into the same Target with Overwrite off no longer reads as written: a file already there is passed by before FFmpeg is started (`[SKIP] … already exists and Overwrite is off`) and counted in `skipped`, in ENCODE, AUDIO, PACKAGE, FRAME RATE and COLOR as in CUT.
- The bar of a run follows FFmpeg's own progress inside a file; it stood near 8 % through a one-file encode.
- Profile Doctor knows the wrappers of CUT: four `ff-trim-*` were reported as errors.
- The outcome of a download names the files it wrote (`downloaded`) and their count (`processed`).
- CUT keeps the frames asked for in a file whose timeline does not start at zero (MPEG-TS, an MP4 with an offset, ARRI MOV): the start of the file was added to the seek twice. The top-up of a short tail works with Overwrite off.
- A result that would be one of its own sources - by its path, a link or a hard link - is refused before FFmpeg starts.
- A file is written under a draft name of its own run: a file that only looks like a draft is never deleted, and a name with "%" is written whole like any other.
- `--result` is a `.json` file outside the Source and the settings; its draft is the run's own.
- `cleanup_project.cmd` refuses a folder that is a link and never walks through one.
- A lossless archive keeps the bits or refuses: x264 lossless turns down a 12-bit, RGB or alpha source (FFV1 keeps it), float PCM is copied instead of going to FLAC.
- A run with a failed file is a failure, a run stopped before its first file is a stop; STOP ends a child that prints nothing, together with what it started.
- Two sources of one stem write two files (`take.m4a`, `take_wav.m4a`).
- CUT takes a Source of one file.
- The loudness report of sound in a video measures every track.
- A copy of big-endian PCM goes to MKA: WAV does not hold it.
- A download repeated at once counts nothing as written; what was there is listed as `existing`.
- x264 keeps the fields and their order of an interlaced source.

**The environment.** Python carries only what the engine needs — PyYAML, pytest, pip-tools (59 MB). The scripts and the installers run in the PowerShell 7 of the program. The builder menu (`builder_main.cmd`) and the console menus on FZF stay.