

OMEinsumContractionOrders: A Julia package for tensor network contraction order optimization

Jin-Guo Liu^{1*}, Xuanzhao Gao^{2*}, and Richard Samuelson^{3*}

¹ Hong Kong University of Science and Technology (Guangzhou) ² Center of Computational Mathematics, Flatiron Institute ³ * These authors contributed equally.

DOI: [10.xxxxxx/draft](#)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Statement of need

OMEinsumContractionOrders (One More Einsum Contraction Orders, or OMECO) is a Julia package (Bezanson et al., 2012) that implements state-of-the-art algorithms for optimizing tensor network contraction orders. This paper presents its key features, integration with the Julia ecosystem, and performance benchmarks.




Figure 1: The ecosystem built around OMEinsumContractionOrders and its dependencies. OMECO serves as a core component of the tensor network contractor OMEinsum, which powers applications including Yao (quantum simulation), TensorQEC (quantum error correction), TensorInference (probabilistic inference), GenericTensorNetworks and TensorBranching (combinatorial optimization).

A *tensor network* is a mathematical framework that represents multilinear algebra operations as graphical structures, where tensors are nodes and shared indices are edges. This diagrammatic approach transforms complex high-dimensional contractions into visual networks that expose underlying computational structure.

The framework has remarkable universality across diverse domains: *einsum* notation (Harris et al., 2020) in numerical computing, *factor graphs* (Bishop & Nasrabadi, 2006) in probabilistic inference, *sum-product networks* in machine learning, and *junction trees* (Villegas et al., 2023) in graphical models. Tensor networks have enabled breakthroughs in quantum circuit simulation (Markov & Shi, 2008), quantum error correction (Piveteau et al., 2024), neural network compression (Qing et al., 2024), strongly correlated quantum materials (Haegeman et al., 2016), and combinatorial optimization problems (Liu et al., 2023). These applications are reflected in the ecosystem built around OMECO, as illustrated in Figure 1.

The computational cost of tensor network contraction depends critically on the *contraction order*—the sequence in which pairwise tensor multiplications are performed. This order

can be represented as a binary tree where leaves correspond to input tensors and internal nodes represent intermediate results. The optimization objective balances multiple complexity measures through the cost function:

$$\mathcal{L} = w_t \cdot tc + w_s \cdot \max(0, sc - sc_{\text{target}}) + w_{rw} \cdot rwc,$$

where w_t , w_s , and w_{rw} represent weights for time complexity (tc), space complexity (sc), and read-write complexity (rwc), respectively. In practice, memory access costs typically dominate computational costs, motivating $w_{rw} > w_t$. The space complexity penalty activates only when $sc > sc_{\text{target}}$, allowing unconstrained optimization when memory fits within available device capacity.

Finding the optimal contraction order—even when minimizing only time complexity—is NP-complete (Markov & Shi, 2008). This optimization problem has a deep mathematical connection to *tree decomposition* (Markov & Shi, 2008) of the tensor network’s line graph, where finding the optimal order corresponds to finding a weighted minimal-width tree decomposition. The logarithmic time complexity of the bottleneck contraction step equals the largest bag size in the tree decomposition, while the logarithmic space complexity equals the largest separator size (vertices shared between adjacent bags).

Despite this computational hardness, near-optimal solutions suffice for most practical applications and can be obtained efficiently through heuristic methods. Modern optimization algorithms have achieved remarkable scalability, handling tensor networks with over 10^4 tensors (Gray & Kourtis, 2021; Roa-Villescas et al., 2024).

OMEKO implements several optimization algorithms with complementary performance characteristics:

Optimizer	Description
GreedyMethod	Fast greedy heuristic with modest solution quality
TreeSA	Reliable simulated annealing optimizer (Kalachev et al., 2021) with high-quality solutions
PathSA	Simulated annealing optimizer for path decomposition
HyperND	Nested dissection algorithm for hypergraphs, requires KaHyPar or Metis
KaHyParBipartite	Graph bipartition method for large tensor networks (Gray & Kourtis, 2021), requires KaHyPar
SABipartite	Simulated annealing bipartition method, pure Julia implementation
ExactTreewidth	Exact algorithm with exponential runtime (Bouchitté & Todinca, 2001), based on TreeWidthSolver
Treewidth	Clique tree elimination methods from CliqueTrees package

The algorithms HyperND, Treewidth, and ExactTreewidth operate on the tensor network’s line graph and utilize the CliqueTrees and TreeWidthSolver packages, as illustrated in Figure 1. Additionally, the PathSA optimizer implements path decomposition by constraining contraction orders to path graphs, serving as a variant of TreeSA.

These methods balance optimization time against solution quality. Figure 2 displays benchmark results for the Sycamore quantum supremacy circuit, highlighting the Pareto front where contraction order quality is balanced with optimization runtime.




Figure 2: Time complexity (left) and space complexity (right) benchmark results for contraction order optimization on the Sycamore quantum circuit tensor network (Intel Xeon Gold 6226R CPU @ 2.90GHz, single-threaded). The x -axis shows contraction cost, y -axis shows optimization time. Each point represents a different optimizer configuration tested with varying parameters. TreeSA and HyperND achieve the lowest contraction costs, while GreedyMethod offers the fastest optimization time.

[JG: TODO: Please also cite CliqueTree paper.]

Optimizers prefixed with `cotengra_` are from the Python package `cotengra` (Gray & Kourtis, 2021); all others are OMECO implementations. For both optimization objectives (minimizing time and space complexity), OMECO optimizers dominate the Pareto front. Given sufficient optimization time, TreeSA consistently achieves the lowest time and space complexity. GreedyMethod provides the fastest optimization but yields suboptimal contraction orders, while HyperND offers a favorable balance between optimization time and solution quality.

OMECO has been integrated into the OMEinsum package and powers several downstream applications: Yao (Luo et al., 2020) for quantum circuit simulation, GenericTensorNetworks (Liu et al., 2023) and TensorBranching (TODO: add citation) for combinatorial optimization, TensorInference (Roa-Villescas & Liu, 2023) for probabilistic inference, and TensorQEC for quantum error correction. This infrastructure is expected to benefit other applications requiring tree or path decomposition, such as polynomial optimization (Magron & Wang, 2021).

Usage Example

OMECO provides two main functions: `optimize_code` for finding optimal contraction orders, and `slice_code` for trading time complexity for reduced space complexity through the slicing technique.

To demonstrate basic usage, we generate a random 3-regular graph with 100 vertices using the Graphs package, associating each vertex with a binary variable and each edge with a 2×2 tensor.

```
julia> using Graphs: random_regular_graph, edges, vertices
```

```
julia> using OMEinsumContractionOrders: EinCode, uniquelabels, contraction_complexity, o
```

```
julia> function demo_network(n::Int)
    g = random_regular_graph(n, 3)
    code = EinCode([e.src, e.dst] for e in edges(g)), Int[]
    sizes = Dict{i=>2 for i in uniquelabels(code)}
    tensors = [randn([sizes[index] for index in ix]...) for ix in code.ixs]
    return code, tensors, sizes
end
demo_network (generic function with 1 method)
```

```
julia> code, tensors, sizes = demo_network(100);
```

73 The tensor network topology is represented by an EinCode object with two fields: `ixs` (a
74 vector of index vectors for each input tensor) and `iy` (output indices). This structure defines
75 a hypergraph with potentially open edges. Combining this hypergraph with tensor sizes
76 determines the contraction complexity.

```
julia> contraction_complexity(code, sizes)
Time complexity: 2^100.0
Space complexity: 2^0.0
Read-write complexity: 2^9.231221180711184
```

77 The return type contains three fields (`tc`, `sc`, `rw`) for time, space, and read-write complexity.
78 Without optimization, the time complexity is 2^{100} , equivalent to brute-force enumeration.

79 We now use the TreeSA optimizer to find an improved contraction order.

```
julia> optcode = optimize_code(code, sizes, TreeSA(; score=ScoreFunction(tc_weight=1.0,

julia> cc = contraction_complexity(optcode, sizes)
Time complexity: 2^17.241796993093228
Space complexity: 2^13.0
Read-write complexity: 2^16.360864226366807
```

80 The `optimize_code` function takes three arguments: the EinCode object, tensor size dictionary,
81 and optimizer configuration. It returns a NestedEinsum object specifying the contraction tree
82 with three fields: `args` (child nodes), `tensorindex` (input tensor index for leaf nodes), and
83 `eins` (einsum notation for the node). The time complexity $\approx 2^{17.2}$ is dramatically improved
84 from the original 2^{100} . This result aligns with theory, as the treewidth of a 3-regular graph is
85 approximately upper bounded by $1/6$ of the number of vertices (Fomin & Høie, 2006). The
86 score keyword argument configures the cost function weights; here we set the read-write
87 weight to $10\times$ the time weight, reflecting the higher cost of memory access.

88 Space complexity can be further reduced using `slice_code`, which implements the slicing
89 technique to trade time for space.

```
julia> sliced_code = slice_code(optcode, sizes, TreeSASlicer(score=ScoreFunction(sc_targ

julia> sliced_code.slicing
3-element Vector{Int64}:
 14
 76
 60

julia> contraction_complexity(sliced_code, sizes)
Time complexity: 2^17.800899899920303
Space complexity: 2^10.0
Read-write complexity: 2^17.199595668955244
```

90 The `slice_code` function takes the NestedEinsum object, tensor sizes, and slicing strat-
91 egy, returning a SlicedEinsum object with two fields: `slicing` (sliced indices) and `eins` (a
92 NestedEinsum object). Using TreeSASlicer, we reduce space complexity by 2^3 (from 2^{13}
93 to 2^{10}) with only a modest increase in time complexity. The resulting SlicedEinsum object
94 maintains the same interface as NestedEinsum for contraction evaluation.

```
julia> @assert sliced_code(tensors...) ≈ optcode(tensors...)
```

95 [JG: TODO: Mention the API to convert between contraction graph and treewidth. (Xuan-Zhao
96 fill in), Remove?]

[JG: TODO: Show a plot about using slicing to reduce the space complexity (based on the above example). (Xuan-Zhao fill in)]

Real-world examples demonstrating applications to quantum circuit simulation, combinatorial optimization, and probabilistic inference are available in the [OMEinsumContractionOrders-Benchmark](#) repository. Optimizer performance is highly problem-dependent, with no single algorithm dominating across all metrics and graph topologies.

Acknowledgments

This work was partially funded by Google Summer of Code 2024 and the Open Source Promotion Plan (OSPP 2023). We thank Feng Pan for insightful discussions and code contributions on the slicing technique.

References

- Bezanson, J., Karpinski, S., Shah, V. B., & Edelman, A. (2012). Julia: A fast dynamic language for technical computing. *arXiv:1209.5145 [Cs]*. <https://doi.org/10.48550/arXiv.1209.5145>
- Bishop, C. M., & Nasrabadi, N. M. (2006). *Pattern recognition and machine learning* (Vol. 4). Springer.
- Bouchitté, V., & Todinca, I. (2001). Treewidth and minimum fill-in: Grouping the minimal separators. *SIAM Journal on Computing*, 31(1), 212–232.
- Fomin, F. V., & Høie, K. (2006). Pathwidth of cubic graphs and exact algorithms. *Information Processing Letters*, 97(5), 191–196. <https://doi.org/10.1016/j.ipl.2005.10.012>
- Gray, J., & Kourtis, S. (2021). Hyper-optimized tensor network contraction. *Quantum*, 5, 410. <https://doi.org/10.22331/q-2021-03-15-410>
- Haegeman, J., Lubich, C., Oseledets, I., Vandereycken, B., & Verstraete, F. (2016). Unifying time evolution and optimization with matrix product states. *Physical Review B*. <https://doi.org/10.1103/PhysRevB.94.165116>
- Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M., Peterson, P., ... Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. <https://doi.org/10.1038/s41586-020-2649-2>
- Kalachev, G., Panteleev, P., & Yung, M.-H. (2021). *Recursive multi-tensor contraction for XEB verification of quantum circuits*. <https://arxiv.org/abs/2108.05665>
- Liu, J.-G., Gao, X., Cain, M., Lukin, M. D., & Wang, S.-T. (2023). Computing solution space properties of combinatorial optimization problems via generic tensor networks. *SIAM Journal on Scientific Computing*, 45(3), A1239–A1270.
- Luo, X.-Z., Liu, J.-G., Zhang, P., & Wang, L. (2020). Yao. JI: Extensible, efficient framework for quantum algorithm design. *Quantum*, 4, 341.
- Magron, V., & Wang, J. (2021). TSSOS: A julia library to exploit sparsity for large-scale polynomial optimization. *arXiv:2103.00915*.
- Markov, I. L., & Shi, Y. (2008). Simulating Quantum Computation by Contracting Tensor Networks. *SIAM Journal on Computing*, 38(3), 963–981. <https://doi.org/10.1137/050644756>
- Piveteau, C., Chubb, C. T., & Renes, J. M. (2024). Tensor-Network Decoding Beyond 2D. *PRX Quantum*, 5(4), 040303. <https://doi.org/10.1103/PRXQuantum.5.040303>

- 140 Qing, Y., Li, K., Zhou, P.-F., & Ran, S.-J. (2024). *Compressing neural network by tensor*
141 *network with exponentially fewer variational parameters* (No. arXiv:2305.06058). arXiv.
142 <https://doi.org/10.48550/arXiv.2305.06058>
- 143 Roa-Villescas, M., Gao, X., Stuijk, S., Corporaal, H., & Liu, J.-G. (2024). Probabilistic
144 Inference in the Era of Tensor Networks and Differential Programming. *Physical Review*
145 *Research*, 6(3), 033261. <https://doi.org/10.1103/PhysRevResearch.6.033261>
- 146 Roa-Villescas, M., & Liu, J.-G. (2023). TensorInference: A julia package for tensor-based
147 probabilistic inference. *Journal of Open Source Software*, 8(90), 5700.
- 148 Villescas, M. R., Liu, J.-G., Wijnings, P. W. A., Stuijk, S., & Corporaal, H. (2023). Scaling
149 Probabilistic Inference Through Message Contraction Optimization. *2023 Congress in*
150 *Computer Science, Computer Engineering, & Applied Computing (CSCE)*, 123–130. <https://doi.org/10.1109/CSCE60160.2023.00025>
151

DRAFT