

OMEinsumContractionOrders: A Julia package for tensor network contraction order optimization

Jin-Guo Liu^{1*}, Xuanzhao Gao^{2*}, and Richard Samuelson^{3*}

¹ Hong Kong University of Science and Technology (Guangzhou) ² Center of Computational Mathematics, Flatiron Institute ³ * These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

OMEinsumContractionOrders (One More Einsum Contraction Orders, or OMECO) is a Julia package (Bezanson et al., 2012) that implements state-of-the-art algorithms for optimizing tensor network contraction orders. OMECO is designed to search for near-optimal contraction orders for exact tensor network contraction, and provides a comprehensive suite of optimization algorithms for tensor network contraction orders, including greedy heuristics, simulated annealing, and tree width solvers. In this paper, we present the key features of OMECO, its integration with the Julia ecosystem, and performance benchmarks.

Statement of need

A *tensor network* is a mathematical framework that represents multilinear algebra operations as graphical structures, where tensors are nodes and shared indices are edges. This diagrammatic approach transforms complex high-dimensional contractions into visual networks that expose underlying computational structure.

The framework has remarkable universality across diverse domains: *einsum* notation (Harris et al., 2020) in numerical computing, *factor graphs* (Bishop & Nasrabadi, 2006) in probabilistic inference, *sum-product networks* in machine learning, and *junction trees* (Villescas et al., 2023) in graphical models. Tensor networks have enabled breakthroughs in quantum circuit simulation (Markov & Shi, 2008), quantum error correction (Piveteau et al., 2024), neural network compression (Qing et al., 2024), strongly correlated quantum materials (Haegeman et al., 2016), and combinatorial optimization problems (J.-G. Liu et al., 2023).

The computational cost of tensor network contraction depends critically on the *contraction order*—the sequence in which pairwise tensor multiplications are performed. This order can be represented as a binary tree where leaves correspond to input tensors and internal nodes represent intermediate results. The optimization objective balances multiple complexity measures through the cost function:

$$\mathcal{L} = w_t \cdot \text{tc} + w_s \cdot \max(0, \text{sc} - \text{sc}_{\text{target}}) + w_{\text{rw}} \cdot \text{rwc},$$

where w_t , w_s , and w_{rw} represent weights for time complexity (tc), space complexity (sc), and read-write complexity (rwc), respectively. In practice, memory access costs typically dominate computational costs, motivating $w_{\text{rw}} > w_t$. The space complexity penalty activates only when $\text{sc} > \text{sc}_{\text{target}}$, allowing unconstrained optimization when memory fits within available device capacity.

Finding the optimal contraction order—even when minimizing only time complexity—is NP-complete (Markov & Shi, 2008). Algorithms for finding near-optimal contraction orders have been developed and achieve impressive scalability (Gray & Kourtis, 2021; Roa-Villescas

et al., 2024), handling tensor networks with over 10^3 tensors. While the Python package cotengra (Gray & Kourtis, 2021) has been widely adopted in the community, achieving optimal performance across diverse problem instances—particularly when balancing solution quality against optimization time constraints—remains an open challenge.

OMECO addresses this challenge through a unified and extensible framework that integrates multiple complementary optimization strategies, including greedy heuristics, simulated annealing, and tree-width-based solvers. This comprehensive approach enables more systematic exploration of the optimization time-solution quality trade-off space. OMECO has been integrated into the OMEinsum package and powers several downstream applications: Yao (Luo et al., 2020) for quantum circuit simulation, GenericTensorNetworks (J.-G. Liu et al., 2023) and TensorBranching for combinatorial optimization, TensorInference (Roa-Villescas & Liu, 2023) for probabilistic inference, and TensorQEC for quantum error correction. This infrastructure is expected to benefit other applications requiring tree or path decomposition, such as polynomial optimization (Magron & Wang, 2021). These applications are reflected in the ecosystem built around OMECO, as illustrated in Figure 1.




Figure 1: The ecosystem built around OMEinsumContractionOrders and its dependencies. OMECO serves as a core component of the tensor network contractor OMEinsum, which powers applications including Yao (quantum simulation), TensorQEC (quantum error correction), TensorInference (probabilistic inference), GenericTensorNetworks and TensorBranching (combinatorial optimization).

Features and benchmarks

The major feature of OMECO is contraction order optimization. OMECO provides several algorithms with complementary performance characteristics that can be simply called by the optimize_code function:

Optimizer	Description
GreedyMethod	Fast greedy heuristic with modest solution quality
TreeSA	Reliable simulated annealing optimizer (Kalachev et al., 2021) with high-quality solutions
PathSA	Simulated annealing optimizer for path decomposition
HyperND	Nested dissection algorithm for hypergraphs, requires KaHyPar or Metis
KaHyParBipartite	Graph bipartition method for large tensor networks (Gray & Kourtis, 2021), requires KaHyPar

Optimizer	Description
SABipartite	Simulated annealing bipartition method, pure Julia implementation
ExactTreewidth	Exact algorithm with exponential runtime (Bouchitté & Todinca, 2001), based on TreeWidthSolver
Treewidth	Clique tree elimination methods from CliqueTrees package (Samuelson & Fairbanks, 2025)

The algorithms HyperND, Treewidth, and ExactTreewidth are tree-width based solvers that operate on graphs. They first convert tensor networks to their line graph representation (Markov & Shi, 2008) and then find an optimized tree decomposition of the line graph using the CliqueTrees and TreeWidthSolver packages, as illustrated in Figure 1. Additionally, the PathSA optimizer optimizes path decomposition instead of tree decomposition. It is a variant of TreeSA by constraining contraction orders to path graphs, which is useful for applications requiring a linear contraction order.

These methods balance optimization time against solution quality. Figure 2 displays benchmark results for the tensor network of the Sycamore quantum circuit (Arute et al., 2019; Pan & Zhang, 2021) that widely used as a benchmark for quantum supremacy, which is believed to have an optimal space complexity of 52. The Pareto front highlights the optimal trade-off between optimization time and solution quality.




Figure 2: Time complexity (left) and space complexity (right) benchmark results for contraction order optimization on the Sycamore quantum circuit tensor network (Intel Xeon Gold 6226R CPU @ 2.90GHz, single-threaded). The x -axis shows contraction cost, y -axis shows optimization time. Each point represents a different optimizer configuration tested with varying parameters. TreeSA and HyperND achieve the lowest contraction costs, while GreedyMethod offers the fastest optimization time. The parameter setup for each optimizer is detailed in our benchmark repository [OMEinsumContractionOrdersBenchmark](#).

Optimizers prefixed with `cotengra_` are from the Python package `cotengra` (Gray & Kourtis, 2021); all others are OMECO implementations. For both optimization objectives (minimizing time and space complexity), OMECO optimizers dominate the Pareto front. Given sufficient optimization time, `TreeSA` consistently achieves the lowest time and space complexity. `GreedyMethod` and `Treewidth` (backed by minimum fill (MF) (Ng & Peyton, 2014), multiple minimum degree (MMD) (J. W. Liu, 1985), and approximate minimum fill (AMF) (Rothberg & Eisenstat, 1998)) provides the fastest optimization but yields suboptimal contraction orders, while `HyperND` offers a favorable balance between optimization time and solution quality.

More real-world examples demonstrating applications to quantum circuit simulation, combinatorial optimization, and probabilistic inference are available in the [OMEinsumContractionOrder-sBenchmark](#) repository. We find that optimizer performance is highly problem-dependent, with no single algorithm dominating across all metrics and graph topologies.

Another key feature of OMECO is index slicing, a technique that trades time complexity for reduced space complexity by explicitly looping over a subset of tensor indices. OMECO provides the `slice_code` interface for this purpose, currently supporting the `TreeSASlicer` algorithm, which implements dynamic slicing based on the `TreeSA` optimizer. [Figure 3](#) demonstrates this capability using the Sycamore quantum circuit, where slicing reduces the space complexity from 2^{52} to 2^{31} .




Figure 3: Trade-off between time complexity and target space complexity using `TreeSASlicer` on the Sycamore quantum circuit. The original network has a space complexity of 2^{52} .

The numerical experiments show that moderate slicing increases time complexity only slightly, while aggressive slicing can induce significant overhead. There is a critical transition point around 42 where the time complexity begins to increase significantly.

We thank the Julia community and all contributors to the `OMEinsum` and `OMEinsumContractionOrders` packages. We are grateful to Xiwei Pan for valuable writing suggestions that improved this manuscript.

References

- Arute, F., Arya, K., Babbush, R., Bacon, D., Bardin, J. C., Barends, R., Biswas, R., Boixo, S., Brandao, F. G., Buell, D. A., & others. (2019). Quantum supremacy using a programmable superconducting processor. *Nature*, 574(7779), 505–510. <https://www.nature.com/articles/s41586-019-1666-5>
- Bezanson, J., Karpinski, S., Shah, V. B., & Edelman, A. (2012). Julia: A fast dynamic language for technical computing. *arXiv:1209.5145 [Cs]*. <https://doi.org/10.48550/arXiv.1209.5145>
- Bishop, C. M., & Nasrabadi, N. M. (2006). *Pattern recognition and machine learning* (Vol. 4). Springer.
- Bouchitté, V., & Todinca, I. (2001). Treewidth and minimum fill-in: Grouping the minimal separators. *SIAM Journal on Computing*, 31(1), 212–232. <https://doi.org/10.1137/S0097539799359683>
- Gray, J., & Kourtis, S. (2021). Hyper-optimized tensor network contraction. *Quantum*, 5, 410. <https://doi.org/10.22331/q-2021-03-15-410>
- Haegeman, J., Lubich, C., Oseledets, I., Vandereycken, B., & Verstraete, F. (2016). Unifying time evolution and optimization with matrix product states. *Physical Review B*. <https://doi.org/10.1103/PhysRevB.94.165116>

- 111 Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau,
112 D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van
113 Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M., Peterson, P., ...
114 Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362.
115 <https://doi.org/10.1038/s41586-020-2649-2>
- 116 Kalachev, G., Pantelev, P., & Yung, M.-H. (2021). *Recursive multi-tensor contraction for*
117 *XEB verification of quantum circuits*. <https://arxiv.org/abs/2108.05665>
- 118 Liu, J. W. (1985). Modification of the minimum-degree algorithm by multiple elimination.
119 *ACM Transactions on Mathematical Software (TOMS)*, 11(2), 141–153. [https://doi.org/](https://doi.org/10.1145/214392.214398)
120 [10.1145/214392.214398](https://doi.org/10.1145/214392.214398)
- 121 Liu, J.-G., Gao, X., Cain, M., Lukin, M. D., & Wang, S.-T. (2023). Computing solution space
122 properties of combinatorial optimization problems via generic tensor networks. *SIAM Journal*
123 *on Scientific Computing*, 45(3), A1239–A1270. <https://doi.org/10.1137/22M1501787>
- 124 Luo, X.-Z., Liu, J.-G., Zhang, P., & Wang, L. (2020). Yao. JI: Extensible, efficient
125 framework for quantum algorithm design. *Quantum*, 4, 341. [https://doi.org/10.22331/](https://doi.org/10.22331/q-2020-10-11-341)
126 [q-2020-10-11-341](https://doi.org/10.22331/q-2020-10-11-341)
- 127 Magron, V., & Wang, J. (2021). TSSOS: A julia library to exploit sparsity for large-scale
128 polynomial optimization. *arXiv:2103.00915*. <https://arxiv.org/abs/2103.00915>
- 129 Markov, I. L., & Shi, Y. (2008). Simulating Quantum Computation by Contracting Tensor
130 Networks. *SIAM Journal on Computing*, 38(3), 963–981. [https://doi.org/10.1137/](https://doi.org/10.1137/050644756)
131 [050644756](https://doi.org/10.1137/050644756)
- 132 Ng, E. G., & Peyton, B. W. (2014). Fast implementation of the minimum local fill ordering
133 heuristic. *CSC14: The Sixth SIAM Workshop on Combinatorial Scientific Computing*, 4.
134 <https://doi.org/10.1137/070680680>
- 135 Pan, F., & Zhang, P. (2021). *Simulating the sycamore quantum supremacy circuits*. [https://](https://arxiv.org/abs/2103.03074)
136 arxiv.org/abs/2103.03074
- 137 Piveteau, C., Chubb, C. T., & Renes, J. M. (2024). Tensor-Network Decoding Beyond 2D.
138 *PRX Quantum*, 5(4), 040303. <https://doi.org/10.1103/PRXQuantum.5.040303>
- 139 Qing, Y., Li, K., Zhou, P.-F., & Ran, S.-J. (2024). *Compressing neural network by tensor*
140 *network with exponentially fewer variational parameters* (No. arXiv:2305.06058). arXiv.
141 <https://doi.org/10.48550/arXiv.2305.06058>
- 142 Roa-Villescas, M., Gao, X., Stuijk, S., Corporaal, H., & Liu, J.-G. (2024). Probabilistic
143 Inference in the Era of Tensor Networks and Differential Programming. *Physical Review*
144 *Research*, 6(3), 033261. <https://doi.org/10.1103/PhysRevResearch.6.033261>
- 145 Roa-Villescas, M., & Liu, J.-G. (2023). TensorInference: A julia package for tensor-based
146 probabilistic inference. *Journal of Open Source Software*, 8(90), 5700. [https://joss.theoj.](https://joss.theoj.org/papers/10.21105/joss.05700)
147 [org/papers/10.21105/joss.05700](https://joss.theoj.org/papers/10.21105/joss.05700)
- 148 Rothberg, E., & Eisenstat, S. C. (1998). Node selection strategies for bottom-up sparse
149 matrix ordering. *SIAM Journal on Matrix Analysis and Applications*, 19(3), 682–695.
150 <https://doi.org/10.1137/S0895479896302692>
- 151 Samuelson, R., & Fairbanks, J. (2025). *CliqueTrees.jl: A julia library for computing tree*
152 *decompositions and chordal completions of graphs*. [https://github.com/AlgebraicJulia/](https://github.com/AlgebraicJulia/CliqueTrees.jl)
153 [CliqueTrees.jl](https://github.com/AlgebraicJulia/CliqueTrees.jl)
- 154 Villescas, M. R., Liu, J.-G., Wijnings, P. W. A., Stuijk, S., & Corporaal, H. (2023). Scaling
155 Probabilistic Inference Through Message Contraction Optimization. *2023 Congress in*
156 *Computer Science, Computer Engineering, & Applied Computing (CSCE)*, 123–130. [https://](https://doi.org/10.1109/CSCE60160.2023.00025)
157 doi.org/10.1109/CSCE60160.2023.00025