Status: ADOPTED

Regulation 3514: Environmental Safety

Original Adopted Date: 11/20/2013 | Last Revised Date: 12/18/2019 | Last Reviewed Date: 12/18/2019

The Superintendent may designate and train one or more employees to oversee and coordinate the district's environmental safety program(s). The responsibilities of overseeing assessments of district facilities, recommending strategies for the prevention and mitigation of environmental health risks, ensuring effective implementat Superintendent regarding the district's progress in addressing environmental safety concerns.

Indoor Air Quality

In order to provide proper ventilation, humidity, and temperature in school facilities and to reduce indoor air contaminants, the following strategies shall be implemen

- 1. Mechanically driven heating, ventilation, and air conditioning systems shall be operated continuously during working hours except under the circumstances spe annually and problems corrected within a reasonable time. Where the air supply is filtered, the filters shall be replaced or cleaned regularly to prevent significar ventilation rates, and maintenance shall be retained for at least five years. (8 CCR 5142-5143)
 - Staff shall ensure that airflow is not obstructed by the blocking of ventilators with posters, furniture, books, or other obstacles.
- 2. School facilities shall be regularly inspected for water damage, spills, leaks in plumbing and roofs, poor drainage, and improper ventilation so as to preclude the unsafe conditions. Wet building materials and furnishings shall be dried within 48 hours if possible to prevent mold growth. When evidence of mold or mildew i water intrusion and remove or clean moldy materials.
- 3. Exterior wall and foundation cracks and openings shall be sealed as soon as possible to minimize seepage of radon into buildings from surrounding soils.
- 4. Least toxic pest management practices shall be used to control and manage pests at school sites. (Education Code 17608-17614; Food and Agriculture Code 1
- 5. A carbon monoxide detector or alarm shall be installed in all school buildings that contain a fuel-burning appliance, fireplace, or forced-air furnace, unless other shall be located in close proximity to the appliance in order to accurately detect and alert school personnel of any leakage of carbon monoxide. (24 CCR 915.1)
- 6. Schedules and practices for routine housekeeping and maintenance shall be designed to effectively reduce levels of dust, dirt, and debris. Plain water, soap and whenever possible. Aerosols, including air fresheners and other products containing ozone, shall be avoided to the extent possible.
- 7. Painting of school facilities and maintenance or repair activities that require the use of potentially harmful substances shall be limited to those times when scho be properly ventilated with adequate time allowed prior to reopening for use by any person.
- 8. Paints, adhesives, and solvents shall be used and stored in well-ventilated areas. These items shall be purchased in small quantities to avoid storage exposure.
- 9. To the extent possible, printing and duplicating equipment that may generate indoor air pollutants, such as methyl alcohol or ammonia, shall be placed in locatic staff.
- 10. The district's tobacco-free schools policy shall be consistently enforced in order to reduce the health risks caused by second-hand smoke.
- 11. Staff and students shall be asked to refrain from bringing common irritants such as furred or feathered animals, stuffed toys that may collect dust mites, scented cologne, scented lotion or hair spray, nail polish or nail polish remover, or other personal care products that are not fragrance-free in classrooms, school buses.

Outdoor Air Quality

The Superintendent or designee may coordinate with the local air resources control board and monitor local health advisories and outdoor air quality alerts to obtain radiation levels. and/or temperature and humidity.

Whenever a forecast indicates a significant health risk, the Superintendent or designee shall communicate with each principal so that outdoor activities, especially the limited in duration, or modified as necessary for all persons or for persons who may be particularly susceptible to the health risk involved.

Reduction of Vehicle Emissions

In order to reduce public exposure to toxic air contaminants, school bus drivers and other drivers of commercial motor vehicles shall limit unnecessary idling of vehicl Superintendent or designee may also request parents/guardians to turn off their vehicles when they are idling on school grounds and encourage students to walk and

Any school bus that is diesel-fueled, dual-fueled, or alternative diesel-fueled and has a gross vehicle weight rating over 14,000 pounds shall be equipped with a partic oxides of nitrogen emissions, and other pollutants. (13 CCR 2025)

Drinking Water Safety

The quality and safety of the district's drinking water sources shall be regularly assessed, and drinking fountains shall be regularly cleaned and maintained, to ensure the mold, lead, or other impurities or contaminants that may cause serious health concerns.

Whenever any contaminants in the drinking water are determined to be a concern, the Superintendent or designee shall take reasonable steps to identify the source safe drinking water. As needed, the Superintendent or designee shall provide alternative sources of drinking water, such as bottled water or on-site water filtration, to mealtimes and at other times throughout the day.

Whenever testing of drinking water finds concentrations of lead that exceed federal and state standards, the Superintendent or designee shall notify parents/guardiai inoperable any fountains or faucets where excess lead levels may exist.

Prevention of Lead Exposure

In addition to testing for the presence of lead in drinking water in district schools, the following steps shall be taken to minimize potential exposure to lead in school f

- 1. School facilities shall be kept as dust-free and clean as possible.
- 2. Lead-based paint, lead plumbing and solders, or other potential sources of lead contamination shall not be used in the construction of any new school facility or facility. (Education Code 32244)

- 3. Lead exposure hazards shall be evaluated before any renovation or remodeling is begun, and children shall not be allowed in or near buildings in which these ac comply with state and federal standards related to the handling and disposal of lead debris and the clean-up and containment of dust within the construction ar
- 4. Lead-based painted surfaces that are in good condition shall be kept intact. If lead-based paint is peeling, flaking, or chalking, contractors or workers shall follow minimize contamination when removing the paint.
- 5. Soil with low lead content may be covered with grass, other plantings, concrete, or asphalt. For soil with high lead content, removal and abatement are requirec

Any action to abate existing lead hazards shall be taken only by contractors, inspectors, and workers certified by the California Department of Public Health in accord

The Superintendent or designee shall notify parent/guardians, teachers, and staff members if significant risk factors for lead exposure are found. (Education Code 32.

Prevention of Mercury Exposure

The Superintendent or designee shall identify any mercury-containing products that are present in district facilities and, to the extent possible, shall replace them witl

Staff shall receive information about proper procedures to follow in the event of a mercury spill. Clean-up instructions, a clearly labeled kit with necessary clean-up s

In the event of a spill, staff shall evacuate all students from the immediate area of the spill, ensure that any clothing or other items with mercury on them remain in th parts of the school. Staff who are trained in proper clean-up procedures may carefully clean a small spill. As needed for larger or difficult-to-clean spills, the Superinte referred by the local health department or environmental agency.

Any products containing mercury shall be properly disposed at an appropriate hazardous waste collection facility.

Asbestos Management

The Superintendent shall designate an employee who shall ensure that the district's responsibilities related to asbestos inspection and abatement are implemented in shall receive adequate training to perform these duties, including, as necessary, training on the health effects of asbestos; detection, identification, and assessment of asbestos-containing building materials; asbestos management programs; and relevant federal and state regulations. (40 CFR 763.84)

The designated employee shall ensure that the district complies with the following requirements:

- 1. School facilities shall be inspected for asbestos-containing building materials as necessary in accordance with the following:
 - a. Any school building that is leased, acquired, or otherwise used by the district shall be inspected for asbestos-containing building materials prior to its use (40 CFR 763.85, 763.99)
 - b. At least once every six months, the district shall conduct a periodic surveillance consisting of a visual inspection of each school building that contains or is (40 CFR 763.92)
 - c. At least once every three years, the district shall conduct a re-inspection of all known or assumed asbestos-containing building materials in each school be
- Based on the results of the inspection, an appropriate response which is sufficient to protect human health and the environment shall be determined from amc select the least burdensome response, taking into consideration local circumstances, including occupancy and use patterns within the school building and econc CFR 763.90)
- 3. An asbestos management plan for each school site shall be maintained and regularly updated to keep it current with ongoing operations and maintenance, peric activities. (15 USC 2643; 40 CFR 763.93)
 - The asbestos management plan shall be available for inspection in district and school offices during normal business hours. Parent/guardian, teacher, and emple of these plans. (40 CFR 763.84, 763.93)
- 4. Staff, students, and parents/guardians shall be informed at least once each school year about any inspections, response actions, and post-response actions, incliplanned or in progress. (40 CFR 763.84)
- 5. Inspections, re-inspections, periodic surveillance, and response actions, including operations and maintenance, shall be conducted in compliance with state and and all other individuals. (Education Code 49410.5; 40 CFR 763.84, 763.90)
 - Asbestos inspection and abatement work, preparation of a management plan, and any maintenance activities that may disturb asbestos-containing building mat duration maintenance activities, shall be completed by state-certified asbestos inspectors or contractors. (15 USC 2646; 40 CFR 763.84, 763.85, 763.91)
- 6. All custodial and maintenance employees shall be properly trained in accordance with applicable federal and/or state regulations. (40 CFR 763.84)
 - All district maintenance and custodial staff who may work in a building that contains asbestos-containing building materials, regardless of whether they are required hours of related asbestos awareness training. New maintenance and custodial staff shall receive such training within 60 days after beginning employment. Any disturb asbestos-containing building materials shall receive 14 hours of additional training. The trainings shall address the topics specified in 40 CFR 763.92. (1)
- 7. Short-term workers, such as telephone repair workers, utility workers, or exterminators, who may come in contact with asbestos in a school shall be provided in asbestos-containing building materials. (40 CFR 763.84)
- 8. Warning labels shall be posted immediately adjacent to any known or suspected asbestos-containing building material located in routine maintenance areas in a

The district shall maintain, in both the district and school offices and for a period of three years, records pertaining to each preventive measure and response action to operations, and maintenance activities; and any fiber release episode. (40 CFR 763.94)