Date ...../...../.....
Page .....
Puffin

Assignment-2

Section-A

Ans 2(a) **History of Php**

Php was conceived something in the fall of 1994 by Rasmus Lerdorf, but the php that people use today is quite different from the initial version. To understand how PHP got when it is today, it is useful to know the historical evolution of the language.

(b) **Application of Php**

- It is used to develop Web Application.
- It is used to encrypt data.
- It is used to create, open, read and write files on the server.
- It is also used to sent email.
- Also used to insert, delete, modify data into data-base.

(c) **Client-side scripting** :- A client-side script is a program that is processed within the client browser. These kinds of scripts are small programs which are downloaded, compiled and run by the browser. Java Script is a important client-side

Scanned by CamScanner

Date __/__/__
Page _____
Puffin

scripting language and widely used in dynamic websites.

(d) **Interface in PHP**

Interface allow you to specify what methods a class should implement. Interface makes it easy to use a variety of different classes in the same way. When one or more classes use the same interface, it is referred to as "polymorphism".

(e) **Apache web server** is used to compile PHP code. Compiling from source is simple but you end up with a directory structure that is completely different from the Ubuntu packaged version.

Section-B

Que **Basic PHP syntax**

A PHP script can be placed anywhere in the document. A PHP script starts with <?php and ends with ?>:

```
<?php
// PHP code goes here
?>
```

The default file extension for PHP files is ".php". A PHP file normally contains HTML tags, and some

Scanned by CamScanner

Date ..../..../....
Page .....
Puffin

PHP scripting code.

Example

```
<!DOCTYPE html>
<html>
<body>
<h1> My first PHP Page</h1>
<?php
echo " Hello World! ";
?>
</body>
</html>
```

Ques2 Variables :. A variable can have a short name (like x and y) or a more descriptive name (age, carname)

Rules for PHP variables :.

- A variable starts with the $ sign, followed by the name of the variable.
- A variable name must start with a letter or the underscore character.
- A variable name cannot start with a number.
- A variable name can only contain alpha numeric characters and underscores (A-z, 0-9, and _)
- Variable names are case-sensitive ($age and $AGE are two different variables)

Scanned by CamScanner

Date __/__/__
Page _____
Puffin

Creating PHP Variables

In PHP, a variable starts with the $ sign followed by the name of the variable:

Example

```
<?php
$txt = "Hello world";
$x = 5;
$y = 10.5;
?>
```

Output Variables

The PHP echo statement is often used to output data to the screen.

Example:

```
<?php
$student_name = "Rohit";
echo ("$student_name");
?>
```

Section-C

Que 5 Operators in PHP

It is a special symbol which is used to perform logical or mathematical operation on data or variable.

operand

X + Y

operator

Scanned by CamScanner

Date ..../..../....
Page .....
Puffin

Types of operator

- Arithmetic operator
- Relational operator
- Assignment operator
- Logical operator
- String operator
- Array operator
- Increment/Decrement operator.

Arithmetic operator :- The PHP arithmetic operator are used with numeric values of perform common arithmetical operations, such as addition, subtraction, multiplication etc.

Symbol	Operation	Example
+	Addition	x+y
-	Subtraction	x-y
*	Multiplication	x*y
/	Division	x/y
%	Modulus	x%y

~~The Comp~~ Relational operator :- The PHP comparison operator are used to compare two values (number or string):

Scanned by CamScanner

Date __/__/__
Page _____
Puffin

Symbol	Operation	Example
==	Equal to	2==3 return 0
!=	No equal to	2 != 3 return 0
>	Greater than	2 > 3 return 0
<	Less than	2 < 3 return 1
>=	Greater than or equal to	2 >= 3 return 0
<=	Less than or equal to	2 <= 3 return 1

⇒ **Logical operator**:- The PHP logical operators are used to combine conditional statements.

Symbol	Operation	Example
&&	Logical AND	if (x>y && x>z)
||	Logical OR	if (x>y || x>z)
!	Logical Not	if (!(x>y))

⇒ **Assignment operator**:- The PHP assignment operators are used with numeric value to write a value to a variable.

The basic assignment operator in PHP is "=".

Symbol	Example	Same as
=	x = y	x = y
+=	x += y	x = x+y
-=	x -= y	x = x-y
*=	x *= y	x = x*y
/=	x /= y	x = x/y
%=	x %= y	x = x%y

Scanned by CamScanner

⇒ **String Operator :-** PHP has two operators that are specially designed for strings.

Operator	Name	Example
.	Concatenation	$ txt 1 .
		$ txt 2
.=	Concatenation	$ txt 1 .=
	assignment	$ txt 2

⇒ **Array Operators :-** The PHP array operators are used to compare arrays.

Operators	Name	Example
+	Union	$ x + $ y
==	Equality	$ x == $ y
===	Identity	$ x === $ y
!=	Inequality	$ x != $ y
<>	Inequality	$ x <> $ y
!==	Non-identity	$ x !== $ y

⇒ **Incremental / Decremental Operators :-** The PHP incremental operators are used to increment a variable's value. The PHP decrement operators are used to decrement a variable's value.

Symbol	Name	Function	Example
+ +	Increment	It increment the value by 1	+ + x
- -	Decrement	It decrement the value by 1	- - x

Scanned by CamScanner