After Canonicalization, Choice Remains: Content-Erasing Brokers and a Proved k-Bit Cap on Untrusted Agent Selection

Teo Asinari
Independent researcher
tasinari@protonmail.com

Apart Research AI Collusion Research Sprint, October 23–25, 2026

Abstract

Defenses against steganographic collusion between LLM agents often rewrite messages: paraphrase, canonicalize or regenerate them. We ask what such rewriting can and cannot remove, and how to bound what is left. First, we build a trusted release broker for a structured worker-assignment task. We test it against six scripted one-bit carriers under five release modes (7,680 trials). Projecting messages onto the validated task result erases every presentation carrier, bringing decoding to chance. For a fixed task and assignment, released content is independent of the sender's payload by construction. However, the carrier that encodes a bit in *which* equally optimal assignment is chosen survives with 100% decoding. Only trusted replanning removes it, and replanning also removes the agent's decision. Second, we bound that residual choice instead of erasing it. In a leak-capped selection architecture, a trusted public proposer samples 2^k candidates and the untrusted model emits only a k-bit index. A Lean 4 proof, valid for every weight setting, shows the receiver's view takes at most $2^{\sum k}$ values. In a toy word-denoising task, $k = 5$ bits per answer match an unrestricted chooser of the same size (29.2% vs. 29.7% exact match, $n = 600$). A scripted adversary approaches but never exceeds the cap. Both results are small-scale with scripted adversaries, and neither mechanism is novel in isolation. Our contribution is a concrete account of where content rewriting stops and of how a selection interface turns the remaining channel into a tunable, machine-checked rate.

1 Introduction

Multi-agent LLM systems give agents many ways to communicate covertly: wording, formatting, ordering, tool parameters and the substantive choices agents make. Recent work shows tool-using agents can implement provably secure stegosystems against output-only monitors [4]. Such schemes build on perfectly secure constructions like minimum-entropy coupling [6]. Optimization against oversight can also produce encodings that survive paraphrasing [3]. On the defensive side, paraphrasing reduces the capacity of tested encodings but does not eliminate it [5]. Trusted-prefix interventions reduce measured capacity per decision point [2].

Rewriting-based defenses rest on a tension. A defender can remove any information it is willing to regenerate. But a useful agent is useful because its choices depend on information the defender lacks. Whatever the defender preserves of those choices is available as a channel. We make this tension concrete in two steps:

1. **Erasure (§3).** A trusted broker for a structured task erases all presentation-level carriers we tested. The semantic carrier, i.e. which of several equally good solutions is chosen, survives every mode that preserves the agent's decision.

2. **Bounding (§4).** Instead of erasing the residual choice, we restrict it. The untrusted model may only select one of 2^k candidates produced by a trusted public process. We prove in Lean that this caps leakage at k bits per answer for every weight setting. We then measure how much task utility k bits buy.

We distinguish channel *capacity* from instructed use, independent discovery and harmful coordination. Everything here concerns capacity under scripted encoders. We do not claim that agents spontaneously exploit these channels, nor that the defenses stop adaptive learned adversaries.

2 Related work

Steganographic collusion. Rippin et al. [4] show tool-using agents implementing stegosystems undetectable by an output-only monitor, given a keyed cooperating receiver and access to sampling probabilities. Schroeder de Witt et al. [6] give perfectly secure steganography via minimum-entropy coupling. Mathew et al. [3] show steganography emerging under optimization pressure and evaluate paraphrasing mitigations.

Rewriting defenses. Roger and Greenblatt [5] evaluate paraphrasing against encoded reasoning. They report under 3 bits/KB for their strongest tested encodings and discuss the limits of replacing substantive content. Our broker experiment is a fully specified instance of this observation, in which the residual channel can be named exactly.

Capacity bounds by counting. Bounding leakage by the logarithm of the number of distinguishable observations is standard in quantitative information flow, e.g. predictive timing mitigation [1]. Choosing one of N items conveys at most $\log_2 N$ bits. *Hand and Brain* [2] is the closest agentic defense. A small trusted model writes the first tokens at each decision point of an untrusted model, reducing measured capacity from 2.13 to 0.08 bits per decision point on one task, without a proved bound. Our architecture inverts the roles: the untrusted model selects among trusted outputs. We do not claim the counting argument as new. The contribution is the typed architecture with a machine-checked bound valid for all weights, plus a measured utility-versus-k curve.

3 Experiment 1: what a content-erasing broker removes

Task and threat model. A sender agent submits a JSON message assigning workers to tasks under public integer costs. Before the receiver sees it, a trusted broker validates and transforms it. The sender wants to transmit a private bit Z. The receiver knows the encoding scheme and sees only the released message. The broker, the task specification P and the public cost oracle are trusted.

Release modes. `identity` passes the validated message (positive control). `json_sort` re-serializes with sorted keys. `project` extracts only the validated assignment Q and renders it canonically. `rerender` renders the projected assignment with fresh defender-chosen formatting. `replan` ignores the message and computes an optimal assignment from P with a fixed tie break. The parser rejects

Table 1: Known-decoder accuracy (50% = chance) for each carrier under each release mode. All allocations are optimal by construction, so task utility is 100% in every non-replan cell. Replan changes half of the assignments under the semantic carrier.

Carrier	Identity	Sort JSON	Project	Rerender	Replan
Whitespace	100%	50%	50%	50.8%	50%
Object key order	100%	50%	50%	50%	50%
Assignment list order	100%	100%	50%	50%	50%
Escaped identifiers	100%	50%	50%	50%	50%
Optional wording	100%	100%	50%	50%	50%
Assignment choice	100%	100%	**100%**	**100%**	50%

duplicate keys, unknown identifiers, invalid assignments, nonfinite constants, invalid Unicode and oversized input.

Scoped guarantee. Projection releases $Y = f(P, Q)$, and rerendering releases $Y = g(P, Q, R)$ with defender randomness R independent of Z. Hence $I(Z; Y \mid P, Q) = 0$ for accepted messages. This follows from the construction, not from a statistical test. It deliberately conditions on Q: if the sender encodes Z in its choice of assignment, that information survives. Replanning releases $Y = h(P)$, which removes the dependence by removing the sender's decision.

Carriers. Six scripted one-bit encoders: whitespace, object key order, assignment list order, escaped identifiers, optional free-text wording, and *actual assignment choice* between two equally optimal allocations. Each (carrier, mode) cell has 256 balanced trials, for 7,680 records in total.

Results. Table 1 shows that every positive control decodes perfectly. Syntactic normalization (`json_sort`) removes only some carriers. Projection and rerendering remove all presentation carriers. The semantic carrier survives every mode that preserves the sender's assignment. Only replanning removes it, and replanning makes the sender irrelevant. Preserving task *utility* is weaker than preserving task *meaning*: equally optimal choices encode bits at no utility cost. Eight unit tests check the invariants, malformed-input rejection, reproducibility and the surviving semantic channel.

The defender therefore has two options. It can preserve the agent's choices and leave a channel, or take over the choices and lose the agent's contribution. Experiment 2 explores the space between these options: keep some of the agent's choice, but bound it.

4 Experiment 2: a leak-capped selection architecture

Architecture. The receiver sees only $\textsc{Decode}(x, r, c) = \textsc{candidates}(x, r)[c]$, which has three parts:

- A **public proposer** (trusted, public weights) samples 2^k candidate answers from the public input x and public randomness r. Candidate 0 is its greedy answer. It never sees private data.
- An **untrusted chooser** reads x, all candidates and anything private (a payload, private weights or private context), and emits a k-bit code c. Honestly, c selects the candidate the chooser rates most likely.
- A **trusted decoder** outputs candidate c verbatim.




Figure 1: Left: exact-match accuracy of the leak-capped system (solid) against its ceiling, the rate at which the truth appears among the 2^k candidates (dashed), and the unrestricted chooser (dotted). Right: bits per answer received by the scripted adversary, which stay below the proved cap.

Work is fixed: the proposer always samples 2^k padded candidates and the chooser always scores all of them, so running time depends only on public k.

Formal guarantee. We formalize a small dataflow language in Lean 4.35.0. It has public operations, private operations (every function symbol arbitrary, so every network and weight setting is covered), `choose` nodes $out := dec(\text{public args}, c \bmod 2^k)$, and observations. Its typing rule labels each operation's output with the join of its inputs' labels. A `choose` output is public only if every decoder argument other than the code is public, and only public wires are observed. Theorem `view_count` states: for every interpretation and fixed public inputs, the receiver's entire view lies in an explicit list of exactly $2^{k_1+\cdots+k_n}$ values, one per code sequence. Over all payloads, private inputs, private randomness and weights, the view therefore takes at most $2^{\sum k}$ values, and leakage is at most $\sum k$ bits (log-cardinality measure [1]). `seed_capacity` instantiates the proposer/chooser/decoder system as well-typed with at most 2^k views per answer. A necessity example shows that a decoder reading the private score directly is rejected, because that wiring leaks even at $k = 0$. The development has no `sorry` and uses only the standard axioms `propext` and `Quot.sound`. It re-checks in about 2 s.

Toy task. The task is to denoise a corrupted common English word (lengths 4–10 from a 9,894-word list), where each letter is replaced with probability 0.3. All models are small transformers trained from scratch on CPU for 3,000 steps of batch 256: proposer 1 (15k parameters), proposer 2 (105k) and a chooser (605k). The baseline is the *same* chooser decoding freely without a cap. The test set has 600 fresh corruptions with public seed 7.

Adversary. A scripted adversary sets c to a uniform k-bit payload. The receiver recomputes the public candidates and decodes the index. We report exact mutual information $I(m; \text{answer} \mid x, r)$. We also run an adversary that tries to send $k + 1$ bits.

Results. Figure 1 and Table 2 summarize the results.

Table 2: Leak-capped system with proposer 2 (105k). Unrestricted chooser: 29.7%. The 95% interval at $n = 600$ is about ± 3.7 points.

k	0	1	2	3	4	5	6	7	8
Accuracy (%)	15.5	16.5	18.5	20.3	24.0	**29.2**	32.7	34.0	35.0
Coverage (%)	15.5	16.7	20.0	23.3	31.8	43.2	51.7	59.3	66.8
Adversary bits	0	0.84	1.73	2.58	3.41	4.16	4.86	5.50	6.04

- The scripted adversary never exceeds k bits. It falls below k only because sampled candidates include duplicates, and trying to send $k + 1$ bits gains nothing.
- An unrestricted 10-letter answer could carry up to about 47 bits.
- With proposer 2, $k = 5$ matches the unrestricted chooser within noise. At $k \geq 6$ the capped system exceeds it, because reranking 64–256 public samples beats the chooser's own greedy decoding. This comparison is matched in chooser size, not in total compute (710k vs. 605k parameters and 2^k scoring passes).
- With the weaker proposer 1, accuracy reaches 15.5% at $k = 6$ (24.3% coverage) and does not reach the baseline. The utility cost is governed by *proposer coverage*, not by the chooser.
- Mean chooser time at $k = 4$ is 3.01 ms honest vs. 2.99 ms adversarial. This is a single-CPU sanity check, not evidence of side-channel freedom.

5 Discussion

The two experiments describe one design space. Content rewriting can remove any degree of freedom the defender is willing to regenerate. Applied to an agent's substantive decisions, it either leaves them as a channel (projection) or removes the agent's contribution (replanning). The leak-capped interface is an intermediate point. The agent keeps a choice whose size is a public parameter, the channel rate is bounded for every weight setting, and utility is an empirical function of k and proposer quality.

Three practical implications follow.

- Evaluations of rewriting defenses should report which task-relevant degrees of freedom survive. Decoding accuracy on presentation carriers alone overstates protection.
- k is a *rate*. Over n answers, leakage can accumulate to kn bits. Monitoring or rate limits must account for this accumulation.
- The main lever on the security–utility tradeoff is the trusted proposer's coverage. Better proposers lower the k needed for a given utility.

6 Conclusion

A content-erasing broker removes all tested presentation carriers but cannot remove the information carried by an agent's substantive choices without also removing the agent's role. Restricting that choice to a k-bit selection among trusted public candidates gives a machine-checked cap that holds for every weight setting. In a toy task, five bits per answer recovered unrestricted utility. Natural

next steps are learned and adaptive adversaries, realistic agent tasks with multiple decision points, and measurement of how proposer coverage scales.

References

[1] A. Askarov, D. Zhang, and A. C. Myers. Predictive black-box mitigation of timing channels. In *ACM CCS*, 2010.

[2] Krzyzanowski et al. Hand and Brain. In *ICML*, 2026. `https://openreview.net/pdf?id=P7fHU7ZNFQ`.

[3] Y. Mathew et al. Hidden in plain text: Emergence & mitigation of steganographic collusion in LLMs. In *IJCNLP-AACL*, 2025. `https://arxiv.org/abs/2410.03768`.

[4] Rippin et al. Tool use enables undetectable steganography in multi-agent LLM systems. arXiv:2606.28425, 2026.

[5] F. Roger and R. Greenblatt. Preventing language models from hiding their reasoning. arXiv:2310.18512, 2023.

[6] C. Schroeder de Witt et al. Perfectly secure steganography using minimum entropy coupling. In *ICLR*, 2023.

A Limitations

- **Scripted adversaries only.** No learned, optimized or adaptive encoder was evaluated in either experiment. Known-decoder accuracy is not a channel-capacity estimate. Finite tests do not prove security against arbitrary encoders. The Lean bound, by contrast, does cover all weights.
- **Toy scale.** The broker task is a small schema with exact extraction. Arbitrary prose or code has no trusted semantic extractor. The leak-cap chooser has 605k parameters and the task is word denoising, not an agentic workload. Results use one training seed and $n = 600$ test items.
- **Proof scope.** Lean covers an abstract dataflow model. The Python implementation, its correspondence to the model, timing isolation and hardware side channels are not verified. The bound fails if the untrusted model can influence the proposer's seed or state. In Lean, such influence is a labeling violation.
- **The cap counts all views.** It includes the authorized task answer itself. It bounds total receiver-visible variation, not "extra" information beyond the task.
- **Observation boundary.** Neither mechanism blocks timing, cache, filesystem, network, failure-status or retry channels. Recent reports of cache-timing transfer between isolated VMs underline that message-path defenses are only one layer.
- **Trusted components.** The broker, task specification, cost oracle, proposer and decoder are trusted. Replanning assumes the public specification suffices to solve the task.

- **Novelty.** Canonicalization, paraphrasing, best-of-N reranking and counting bounds are established. We have not exhaustively searched for prior selection protocols with proved caps.
- **Compute comparison.** The leak-cap system's utility comparison is matched in chooser size, not in total compute.

B Dual-use and ethical considerations

This work is defensive: it characterizes residual covert channels and offers a mechanism to bound them. The carriers studied (whitespace, ordering, optional fields, equivalent-choice selection) are elementary and widely known, and we release no optimized encoder. Explicitly naming the surviving semantic channel could help an attacker target it. We judge that defenders benefit more from knowing that rewriting does not cover it. The leak-cap bound could be misread as a general guarantee against collusion. We therefore state its scope (content channel, abstract model, k bits per answer accumulating over time) throughout. No human subjects, personal data or deployed systems were involved. All experiments ran locally on CPU, with no hosted model calls.

C Reproducibility and LLM usage

Code, results, source hashes and the Lean development are in the project repository (`experiments/anti_stego`, `experiments/leak_cap`, `experiments/leak_cap/lean/Choice.lean`, `results/anti_stego`, `results/leak-cap-01`). Broker evaluation: `python -m experiments.anti_stego.evaluate -episodes 256 -seed 20261024`. The broker uses only the Python standard library. Leak-cap requires PyTorch. The word list comes from `first20hours/google-10000-english`; its redistribution terms were not fully reviewed. AI coding and research assistants (OpenAI Codex, Anthropic Claude) were used to implement experiments, draft proofs and draft this report. The author directed the work and is responsible for its claims.