

# Vigenere Cipher Cracking and Simplified Data Encryption Standard implementation

## Abstract

Redact this part later

## 1 Vigenere Cipher Cracking

We are given the following cipher :

```
BQZRMQ KLBOXE WCCEFL DKRYYL BVEHIZ NYJQEE BDYFJO PTLOEM EHOMIC
UYHHTS GKNJFG EHIMK  NIHCTI HVRIHA RSMGQT RQCSXX CSWTNK PTMNSW
AMXVCY WEOGSR FFUEEB DKQLQZ WRKUCO FTPLOT GOJZRI XEPZSE ISXTCT
WZRMXI RIHALE SPRFAE FVYORI HNITRG PUHITM CFCDLA HIBKLH RCDIMT
WQWTOR DJCNDY YWMJCN HDUWOF DPUPNG BANULZ NGYPQU LEUXOV FFDCEE
YHQUXO YOXQUO DDCVIR RPJCAT RAQVFS AWMJCN HTSOXQ UODDAG BANURR
REZJGD VJSXOO MSDNIT RGPUHN HRSSSF VFSINH MSGPCM ZJCSLY GEWGQT
DREASV FPXEAR IMLPZW EHQGMG WSEIXE GQKPRM XIBFWL IPCHYM OTNXVY
FFDCEE YHASBA TEXCJZ VTSGBA NUDYAP IUGTLD WLKVRI HWACZG PTRYCE
VNQCUP AOSPEU KPCSNQ RIHLRI KUMGFC YTDQES DAHCKP BDUJPX KPYMBD
IWDQEF WSEVKT CDDWLI NEPZSE OPYIW
```

We know that this english message has been encrypted by a polyalphabetic substitution cipher, and that the encryption key is not longer than 10 characters. To break this cipher, one approach could be to try to guess the key length. To do so, we are looking for repeating sequences, which have a high probability of corresponding to a repetition of the key. This method is called kasiski examination.<sup>1</sup>

To perform this examination, I implemented a Python method which loops through the whole cipher, and searches for patterns which appear again in the rest of the cipher. If an occurrence of the current pattern is found, the distance between the two patterns is added to the possible keys list. Note that all divisors of the distance are also added to the list, as the key could have repeated multiple times between the two occurrences of the pattern. The `get_divisors()` subroutine does not return divisors which are greater than the maximum key length.

```
def kasiski_examination(cipher):
    possible_key_lengths = []

    for pattern_length in range(MIN_PATTERN_LENGTH, MAX_PATTERN_LENGTH):
        for index in range(len(cipher)):
            substring = cipher[index:index+pattern_length]
            distance = cipher[index+pattern_length:].find(substring)

            if distance != -1:
                possible_key_lengths.extend(get_divisors(distance + pattern_length))
```

```
probable_key_lengths = {length:possible_key_lengths.count(length) for length in
                        possible_key_lengths}

return sorted(probable_key_lengths.items(), key=lambda x:x[1], reverse=True)
```

When executed on the given ciphertext, we get the following output.

```
key length : 2 -> 115 occurrences
key length : 4 -> 115 occurrences
key length : 8 -> 115 occurrences
key length : 3 -> 57 occurrences
key length : 6 -> 54 occurrences
key length : 7 -> 31 occurrences
key length : 9 -> 19 occurrences
key length : 5 -> 2 occurrences
key length : 10 -> 2 occurrences
```

Which implies that the key is probably of length 2, 4 or 8. Since 2 and 4 are divisors of 8, it is safe to assume that they appear so often here because the `get_divisors` method returns all divisors smaller than the maximum key length. Our guess is therefore that the key is of length 8. Next, we perform a frequency analysis for each set of character with an equal position in the ciphertext, modulo the key length. These sets will be called columns from now on, because they each represent a column of the ciphertext when it is splitted every key length characters.

This frequency analysis is implemented in the following method.

```
def frequency_analysis(cipher, key_length):
    candidates = []

    for column in range(key_length):
        frequencies = char_frequency(message[column::key_length])
        column_candidates = []

        for most_common in frequencies[:5]:
            E_offset = (LETTERS.find(most_common[0]) - LETTERS.find('E')) % 26
            column_candidates.append(LETTERS[E_offset])
        print("key[{}] candidates : {}".format(column, column_candidates))
        candidates.append(column_candidates)

    return candidates
```

This method computes character frequency for each column, and returns the key character which would have encrypted this column if the most common character corresponds to the letter E.

```
key[0] candidate : ['B']
key[1] candidate : ['D']
key[2] candidate : ['A']
key[3] candidate : ['A']
key[4] candidate : ['E']
key[5] candidate : ['T']
key[6] candidate : ['C']
key[7] candidate : ['Y']
```

This gives us the following possible key : "BDAAETCY". We then try to decrypt the ciphertext with this key using the following method.

```
def poly_decrypt(cipher, key):

    # make sure key and cipher are in uppercase and without whitespace
    cipher = cipher.upper().replace(' ', '')
    key = key.upper().replace(' ', '')

    # expand the key so that it matches the length of the cipher
    expanded_key = ''.join(key[i % len(key)] for i in range(len(cipher)))

    decrypted_message = ''

    for cipher_letter, key_letter in zip(cipher, expanded_key):
        decrypted_index = (LETTERS.find(cipher_letter) - LETTERS.find(key_letter)) % 26
        decrypted_message += LETTERS[decrypted_index]

    return decrypted_message
```

When using this method on the given ciphertext with the key "BDAAETCY", we can do a first decryption of the message. If we format the output by columns, we get the following output

```
01234567
-----
ANZRIXIN
ALXESJAG
EIDKNFWN
ASEHEGLA
INEEXKWH
...
CRJPTRNA
LYDISKOG
ETSERRRE
CAWLEUCR
YPEOLFGY
```

This is not the original message, but we can clearly identify possible words in this text, like CRYPTANALYSIS or CRYPTOLOGY. However, it seems that columns 2 and 5 are offset by the wrong key. To find the right key, we try matching the last 10 characters of the ciphertext (EPZSEOPYIW) to the guessed word (CRYPTOLOGY).

For the first character mismatch, we search the key such that T encrypts to E, and for the second, the key such that O encrypts to Y. By reading a Vignre table, we can see that these unknown key parts we are looking for are L and K. By decrypting the ciphertext with the new key "BDLAEKCY", we get the original message.

AN ORIGINAL MESSAGE IS KNOWN AS THE PLAINTEXT WHILE THE CODED MESSAGE IS CALLED THE CIPHERTEXT. THE PROCESS OF CONVERTING FROM PLAINTEXT TO CIPHERTEXT IS KNOWN AS ENCIPHERING OR ENCRYPTION, RESTORING THE PLAINTEXT FROM THE CIPHERTEXT IS DECIPHERING OR DECRYPTION. THE MANY SCHEMES USED FOR ENCRYPTION CONSTITUTE THE AREA OF STUDY KNOWN AS CRYPTOGRAPHY. SUCH A SCHEME IS KNOWN AS A CRYPTOGRAPHIC SYSTEM OR A CIPHER. TECHNIQUES USED FOR DECIPHERING A MESSAGE WITHOUT ANY KNOWLEDGE OF THE ENCIPHERING DETAILS FALL INTO THE AREA OF CRYPTANALYSIS. CRYPTANALYSIS IS WHAT THE LAY PERSON CALLS BREAKING THE CODE. THE AREAS OF CRYPTOGRAPHY AND CRYPTANALYSIS TOGETHER ARE CALLED CRYPTOLOGY.

## 2 Simplified DES Implementation

### 2.1 Test cases

The following table sums up the results of the test cases in task 1.

Raw Key	Plaintext	Ciphertext
000000000	00000000	11110000
000001111	11111111	11100001
001001111	11111100	10011101
001001111	10100101	10010000
111111111	11111111	00001111
000001111	00000000	01000011
100010110	00111000	00011100
000001111	00000000	01000011

The following table sums up the results of the test cases in task 2.

Raw Key 1	Raw Key 2	Plaintext	Ciphertext
100010110	011010110	11010111	10111001
100010110	011010110	10101010	11100100
111111111	111111111	00000000	11101011
000000000	000000000	01010010	10000000
100010110	011010110	11111101	11100110
101110111	011010110	01001111	01010000
111111111	111111111	10101010	00000100
000000000	000000000	00000000	11110000

### 2.2 SDES cracking

## 3 Conclusion

## References

- [1] Wikipedia contributors. Vigenre cipher — Wikipedia, the free encyclopedia. [https://en.wikipedia.org/w/index.php?title=Vigen%C3%A8re\\_cipher](https://en.wikipedia.org/w/index.php?title=Vigen%C3%A8re_cipher), 2019. [Online].