HIRSCH

SPR332 v2.0

Secure Class 2 Pin Pad Reader



Hirsch's SPR332 v2.0 Secure Class 2 PIN Pad Reader allows securely executed authentication processes within the device, protecting the entered data from various attacks. The reader supports secure e-commerce, e-health, and similar applications when securing private data is the key.

The extended card data transmission rate of up to 600 kbps with the support of TA1=97 enables the shortest possible transaction time for maximum end-user convenience. The Hirsch-specific SmartOS™ features easy and complete support of all major contact smart cards. The Hirsch driver platform and Windows® Plug-and-Play driver support allow seamless integration into any end-user environment with very little or no administration.

With SPR332 v2.0, the end-user experiences convenience, transaction-time efficiency, security, and reliability for applications including digital signature, authentication and verification, and other applications requiring secure PIN entry.

High-Security Features

Secure Pin Entry

- Prevents unauthorized access while connected to the network

Application Ready

- Supports all major smart card ICs and technologies in just one device

Fast

- Transaction time optimized for maximum end user acceptance

Convenient

- Robust user friendly design

SMARTOS™ Powered

- Field upgradable firmware

SPECIFICATIONS

PARAMETER	SPR332 V2.0
HOST INTERFACE	
HOST INTERFACE	USB 2.0 CCID (USB 1.1/3.0 compliant)
COMMUNICATION SPEED	12 Mbps (USB 2.0 full speed)
SMART CARD INTERFACE	
SUPPORTED STANDARDS	ISO/IEC 7816 Part 1 to 4
SUPPORTED TAG ICS	All major ISO/IEC 7816 compliant smart card IC support
PROTOCOLS	T=0, T=1
INTERFACE SPEED	Up to 600 kbps (depending on card) · TA1=97
CLOCK FREQUENCY	ISO/IEC 7816 compliant. Supports clock up to 12 MHz
SUPPORTED SMART CARD TYPES	5V, 3V and 1.8V, ISO/IEC 7816 Class A/B/C
POWER TO SMART CARD	60mA in Class A, 55mA in Class B, 35mA in Class C
SMART CARD DETECTION	Card present switch · Short circuit protection
CARD SIZE	ID-1
CONTACT TYPE	Landing contact
PC/SC DRIVER	PC/SC Specification Ver. 2.01.14 for: · Windows® 7/8/10,11 (32 / 64 bit) / Windows® Server 2008/2012/2016/2019/2022 · Windows 10 Enterprise Device Guard compatible · macOS 10.10.x - 15.x · Linux 2.x - 6.x (32 / 64 bit) · Android 8.0 and higher · Chrome OS
HUMAN INTERFACE	Dual LED and buzzer indicating status · 3x4 +1 keypad
SOFTWARE	PC/SC API · CT-API (through wrapper on top of PC/SC) · Synchronous-API (through wrapper on top of PC/SC) · M-Card API (through wrapper on top of PC/SC) · Hirsch Android CCID library · Compatible with ActivClient with latest hotfixes for PINpad support

SPECIFICATIONS

PARAMETER	SPR332 V2.0
OPERATING CONDITIONS	
POWER SUPPLY	<12mA, excluding smart card, <800µA in standby mode
DIMENSIONS	120 x 70 x 40 mm
WEIGHT	250 g
OPERATING TEMPERATURE RANGE	0° to 50° C (32° to 122° F)
STORAGE TEMPERATURE RANGE	-20° to 60° C (-4° to 140° F)
OPERATING HUMIDITY RANGE	Up to 95% RH non-condensing
DURABILITY	Landing contact 200,000 card insertions
MTBF	500,000 hours
CABLE AND CONNECTOR	USB cable 1.50 m long with type A connector
FIRMWARE	SmartOS™
FIRMWARE IN-FIELD UPGRADEABLE	Yes
CERTIFICATIONS	
SYSTEMS/STANDARDS	EMV 2011 Ver 4.3 Level 1 (ready, pending approval), ISO/IEC 7816, USB 2.0 Full Speed, CCID, Microsoft® WHQL
REGULATORY/ENVIRONMENTAL	CE, FCC, UL 60950, IEC 62368-1, BIS, KCC, VCCI, NOM, RCM, TAA (USA), RoHS3, REACH, WEEE
ORDERING INFORMATION	
PRODUCT PART NUMBER	905127-1

We are committed to ensuring that all of our products are PFAS-free and that the minerals used are responsibly sourced. Through rigorous due diligence and adherence to industry standards, we strive to provide products that are safe, sustainable, and ethically produced.

Hirsch is a global technology leader, revolutionizing physical security solutions, video intelligence, and digital identification systems.
For more information, visit hirschsecure.com or email sales@hirschsecure.com.

© Hirsch, Inc. | All rights reserved. This document is Hirsch public information.