

Coolselector2

Project information


Project name: Evaporator 5 - Unit G
 Comments:
 Created by:
 Coolselector2 version: 3.7.1. Database: 52.52.2.23.8.33
 Printed: Tuesday, February 4, 2020
 Preferences used: All applications

Evap. 5

Operating conditions

Refrigerant:	R134a	Cooling capacity:	14.10 kW
Mass flow in line:	0.1074 kg/s	Heating capacity:	19.35 kW
Evaporating temperature:	-4.0 °C	Condensing temperature:	50.0 °C
Evaporating pressure:	2.527 bar	Condensing pressure:	13.17 bar
Useful superheat:	5.0 K	Subcooling:	2.0 K
Additional superheat:	0 K	Additional subcooling:	0 K
Discharge temperature:	71.3 °C		

System and line: Dry - Suction line



Line total

Pressure drop	0.708 bar
Saturation temperature drop	8.4 K

Position 1. Piping: Copper pipe DIN-EN 35



Length	0.10 m
Angle	0 deg
Pressure drop	0.000 bar
Saturation temperature drop	0.0 K
Velocity, in	10.93 m/s
Connection	OK

Coolselector2

Position 2. Control valve: KVP 35



Offset	0.948	bar
Pressure drop	0.675	bar
Saturation temperature drop	8.0	K
Velocity, in	10.94	m/s
Valve state	Open	
Connection	OK	

Position 3. Piping: Copper pipe DIN-EN 35



Length	0.17	m
Angle	0	deg
Pressure drop	0.001	bar
Saturation temperature drop	0.0	K
Velocity, in	15.11	m/s
Connection	OK	

Position 4. Piping: Copper bend 90 DIN-EN 35



Number	1	
Pressure drop	0.002	bar
Saturation temperature drop	0.0	K
Velocity, in	14.22	m/s
Connection	OK	

Position 5. Piping: Copper pipe DIN-EN 35



Length	0.70	m
Angle	0	deg
Pressure drop	0.003	bar
Saturation temperature drop	0.0	K
Velocity, in	15.13	m/s
Connection	OK	

Position 6. Piping: Copper bend 90 DIN-EN 35



Number	1	
Pressure drop	0.002	bar
Saturation temperature drop	0.0	K
Velocity, in	14.26	m/s
Connection	OK	

Coolselector2

Position 7. Piping: Copper pipe DIN-EN 35



Length	5.50 m
Angle	0 deg
Pressure drop	0.025 bar
Saturation temperature drop	0.3 K
Velocity, in	15.18 m/s
Connection	OK