

互联网数据库开发-个人作业1-Web前端初探

作业内容

1. 针对任意网页，调研其不同方式请求

1. GET请求：


The screenshot shows a web browser with the URL `https://search.jd.com/Search?keyword=耳机&enc=utf-8&wq=erji&pvid=77a4572547`. The developer tools are open, showing the network tab. The first request is a GET to `search.jd.com`. The right pane shows the response details, including status 200 OK, content-type text/html, and various headers.

2. POST请求


The screenshot shows a web browser with the URL `lmooc.chaoxing.com/space/index?t=1633795493548`. The developer tools are open, showing the network tab. The first request is a POST to `passport2.chaoxing.com`. The right pane shows the response details, including status 200 OK, content-type application/json, and various headers.

2. 针对任意网页，使用Jquery，触发某一事件（共三条语句）


1. 选课系统网页如下，在开发模式状态下查找网页标签，可发现左侧导航栏均为a标签，且a[24]为“交流学分申请”。



使用 `$("a")[24].click()` 语句实现点击后，成功跳转至“交流学分申请”页面，如下图：




2. 还是在选课系统中，用同样的方法，执行语句 `$("a")[21].click(alert("选课暂未开放!"))`，即手动实现点击“选课”选项并弹出窗口，效果如下



弹出口：



3. 打开百度搜索，同上一个方法，执行语句 `$("a")[28].click(alert("欢迎来到百度搜索！"))`



弹出口：



```
<!DOCTYPE html>
<html>
<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <meta http-equiv="X-UA-Compatible" content="ie=edge" />
  <title>Easy Notes</title>
  <style type="text/css">
    body{margin:0;padding:0}
    textarea {
      width:320px;
      height:300px;
      resize:none;
      color:rgba(0,0,0,.85);
      min-height:120px;
      padding:16px;
      font-size:14px;
      box-sizing:border-box;
      line-height:1.42857143;
      background-color:#eaf0e5;
    }
  </style>

```

```

border:1px solid #cc8316;
background-image:none;
border:0;outline:0;
appearance:none;
-webkit-appearance:none;
-webkit-tap-highlight-color:rgb(255, 223, 223)
}
::-webkit-scrollbar {
  -webkit-appearance:none
}
::-webkit-scrollbar:vertical {
  width:3px
}
::-webkit-scrollbar:horizontal{
  height:0
}
::-webkit-scrollbar-thumb {
  background-color:rgba(0,0,0,.2)
}
</style>
</head>
<body>
  <textarea id="note" spellcheck="false"></textarea>
  <script src="./main.js"></script>
</body>
</html>

```

main.js

```

var textarea = document.getElementById("note")
var cacheVal = localStorage.getItem('EasyNote')
textarea.value = cacheVal

textarea.addEventListener('input', function (val) {
  var val = textarea.value
  localStorage.setItem('EasyNote', val)
})

```

浏览器实现效果:

