Leakage, Label Noise, and Overestimated Performance in T-Cell Epitope Immunogenicity Prediction

I Nyoman Agung Ananda Terano[1] Mirrabell Frederica Hadiwijono[2]

Abstract

Computational predictors of CD8⁺ T-cell epitope immunogenicity report ROC-AUC values of 0.85–0.90 on data derived from the Immune Epitope Database (IEDB), and are used to prioritise candidates for neoantigen vaccines. We show that these values are inflated by leakage from how the benchmarks are built, and that the labels could not support them in any case. From 65,732 human MHC-I T-cell assay records we identified 2,914 peptide–HLA pairs assayed independently by two or more publications, and measured how well one laboratory's outcome predicts another's on the same pair. Agreement is 72.2% and Cohen's κ is 0.273, an AUC-equivalent of 0.636 (95% CI 0.617–0.656), or 0.681 on the least-selected subset of pairs assayed by exactly two studies. A repeat experiment observes the biology directly, so reported performance exceeds what these labels can support. Three benchmark-construction choices produce the excess. First, splitting by peptide, the field's standard precaution, performs indistinguishably from not splitting at all: 0.826 against 0.840 for random splits on IEDB, and 0.862 against 0.857 on the independent TRAP dataset. Grouping by source publication instead gives 0.607. That gap of 0.219 is the leakage. It survives peptide-level holdout because a held-out peptide's study-mates stay in training, and study identity nearly determines the label: one all-negative study supplies 37% of pairs, 75% of studies report a single outcome class, and an allele-identity baseline that never sees the peptide reaches 0.752, above BigMHC_IM (0.647), DeepImmuno (0.606) and MixMHCpred 3.0 (0.559). Second, DeepImmuno and BigMHC_IM had themselves been trained on 37.5% and 27.1% of our evaluation pairs, and fall by 0.23 and 0.26 AUC on pairs they had not seen, where neither clears chance. Third, counting untested candidates as negatives rather than assayed negatives raises per-patient AUC from ≈0.55 to ≈0.97 for the same nominal task. Under leakage-free evaluation, within study and within allele across 205 groups, the best model we construct reaches 0.573 (95% CI 0.544–0.603), 84% of the conservative bound; the original convolutional architecture reaches 0.544, a difference that is not significant. The bound is measured on IEDB alone and limits what is measurable against these labels, not what is biologically achievable. We release the benchmark, both split schemes, all model predictions, and a protocol for reporting.

Keywords: T-cell epitope · immunogenicity prediction · data leakage · benchmark design · label reliability · reproducibility · IEDB

[1]Institut Teknologi Sepuluh Nopember, Surabaya, Indonesia. [2]University of Toronto, Toronto, Canada. Correspondence to: I Nyoman Agung Ananda Terano (teranoace@gmail.com).

1. Overview

Predictors of which peptide–MHC complexes trigger a CD8⁺ T-cell response are used to design neoantigen vaccines and to choose targets for adoptive cell therapy. Experimental screening is slow and costly, so predictors trained on IEDB have multiplied, and recent ones report ROC-AUC values between 0.85 and 0.90. Two established facts argue against taking those numbers at face value.

First, peptide and allele do not determine the outcome. A response also depends on the individual's T-cell receptor repertoire, prior antigen exposure, the rest of their HLA genotype and the tissue context. Two people with the same restricting allele can respond differently to the same peptide, so a model given only a peptide and an allele has a ceiling below 1.0 whatever its architecture.

Second, laboratories measure the response inconsistently. International proficiency panels run by the Cancer Vaccine Consortium and the CIMT Immunoguiding Programme found inter-laboratory variation of roughly 35-fold for ELISpot, 20-fold for intracellular cytokine staining and 100-fold for tetramer assays, and some laboratories could not detect all predefined responses "even on a yes/no basis" [1].

Harmonisation guidelines reduce this variation in prospective, coordinated studies [1], but they cannot be applied retroactively to a database that aggregates decades of heterogeneous protocols. To our knowledge, what that heterogeneity does to machine-learning benchmarks built on IEDB has not been measured. Predictors deal with label disagreement by convention. PredIG, for example, discards peptide–HLA pairs whose outcomes disagree across experiments [8].

Related problems have been reported. Lee et al. documented HLA bias in immunogenicity predictors and showed that cross-species splits lower performance [3]. Benchmarks of TCR–epitope predictors find near-chance performance on unseen epitopes and warn that external negatives "introduce batch-like confounders, causing models to learn dataset-specific artifacts" [9]. Kapoor and Narayanan reviewed 17 scientific fields and found leakage affecting 294 papers; in one case study, complex models claimed to beat logistic regression stopped doing so once leakage was corrected [6].

We are not aware of a published measurement of what the labels themselves can support, or of which construction choices open the gap between that limit and reported performance. This paper does both. Our contributions are:

1. A measured reliability bound for IEDB immunogenicity labels, with sensitivity analyses over aggregation rule, retesting frequency, assay family and HLA locus.
2. A demonstration that peptide-level splitting is ineffective, replicated on an independent dataset, and identification of source publication as the grouping unit that determines the result.
3. A contamination audit of two widely used published predictors against our evaluation set.
4. A leakage-free performance estimate, an architecture comparison showing the choice makes no measurable difference, and a worked example of a feature that standard validation endorses and grouped validation rejects.

2. Scope and definitions

Scope. We examine benchmarks for $CD8^+$ T-cell epitope immunogenicity built from IEDB assay records, where a model receives a peptide and an MHC-I allele and predicts whether a T-cell response was observed. We do not examine MHC binding or ligand presentation prediction, which are better-posed problems with more reproducible labels and where reported performance is correspondingly higher [9]. We also leave out patient-specific neoantigen prioritisation pipelines, which use tumour sequencing, expression and clonality in addition to sequence [4]; §3.7 shows why conflating the two inflates apparent performance.

Grouping unit. A split is defined by the unit held out. Splitting *by peptide* means no peptide appears in both training and test data; splitting *by study* means no record from a given publication appears in both. Leakage here is shared structure: records from one publication share a cohort, a protocol and often an outcome, so a model can identify the source rather than the biology. We use "grouping unit" throughout to name the choice, because it is the choice that determines the reported number (§3.4).

Label reliability. We define the reliability of a label set as the agreement between two independent measurements of the same quantity, here two publications assaying the same peptide–HLA pair. Expressed as an AUC, this is the score a repeat experiment achieves when used to predict another experiment's outcome. Because a repeat experiment observes the biology rather than inferring it from sequence, it is the most informative predictor obtainable for that pair.

Limits of the bound. The reliability figure limits what can be *measured* against a given label set. It does not limit how accurate immunogenicity prediction could be in principle: when annotators carry independent noise, a well-specified model can exceed their mutual agreement [7]. We return to this in §4.

Operational task. We take the task that matters for vaccine design to be ranking candidates *within one experiment*: given the peptides a laboratory is considering for one patient or one antigen, which should be screened first. This motivates reporting within-study and within-allele AUC alongside pooled figures (§7.5).

3. Results

3.1 One study supplies a third of the data, and most studies report a single outcome

After retrieval and cleaning (§7.1), the benchmark comprises 31,274 unique peptide–HLA pairs, 31.7% positive, drawn from 1,365 publications. Its composition is uneven (**Figure 1**). A single study contributes 11,486 pairs, 37% of the dataset, and every one of its outcomes is negative; the ten largest studies supply 54% of all pairs and the hundred largest 81%. Across all studies, 75% report only one outcome class, and those studies account for 57% of the pairs. Study identity is therefore highly informative about the label before any peptide is examined, which motivates the analyses that follow.

3.2 Immunogenicity labels reproduce poorly between laboratories

Restricting to the 2,914 pairs assayed by two or more distinct publications, and taking each study's majority outcome, we asked how well one study's result predicts another's on the same pair (§7.3).

Quantity	Value (95% CI)
Agreement	0.722 (0.706–0.738)
Cohen's κ	**0.273** (0.235–0.312)
AUC	**0.636** (0.617–0.656)

A κ of 0.273 denotes fair agreement only. The agreement between two experiments on the same pair bounds what can be *measured* against these labels.

3.3 The reliability estimate is robust to how it is measured

We tested three threats to this estimate (**Figure 2**, panel a).

Aggregation rule. Majority vote gives 0.636; any-positive 0.652; ties-to-positive 0.646; ties-to-negative 0.556; and raw records with no aggregation at all 0.595. The range is 0.556–0.652, and the least-processed variant falls below the headline figure.

Selection bias. Pairs are not retested at random. Reproducibility declines with retesting frequency: 0.681 for pairs assayed by exactly two studies (n = 1,806), 0.530 for exactly three, 0.543 for four or more. We therefore adopt 0.681 as a conservative bound. Separately, repeat-tested pairs are 72.5% positive against 26.5% for singly-tested pairs, so the decision to retest is driven by the previous result.

Slice dependence. By assay family, ELISpot 0.702, ICS 0.655, multimer/tetramer 0.605; by locus, HLA-A 0.594, HLA-B 0.775. Every slice falls far below reported performance. The ordering across assay families independently reproduces the proficiency-panel finding that tetramer assays vary more than ELISpot [1].

3.4 Peptide-level splitting does not prevent leakage

Holding out data by peptide is the standard precaution in this field. We compared grouping units using one model class throughout, so that only the split changes.

Grouping unit	IEDB (this study)	TRAP (independent) [3]
Random	0.840	0.857
Peptide	**0.826**	**0.862**
Antigen	—	0.817
Source (study / organism)	**0.607**	**0.552**

On the independent dataset, peptide grouping scores *above* random splitting. In both datasets, widening the grouping unit to the data source collapses performance. Peptide grouping leaves the structure that inflates these results untouched.

3.5 A baseline that cannot see the peptide outscores published predictors

On the held-out test split (4,641 pairs, 1,470 positive), an allele-prior baseline reaches 0.752. It predicts each allele's training-set positive rate and uses no peptide information whatsoever. On the same pairs BigMHC_IM reaches 0.647, DeepImmuno 0.606 and MixMHCpred 0.559: every published predictor scores below the baseline that never sees the peptide.

Predictor	Pooled AUC	Within-allele AUC
This study	0.832	0.769
Gradient boosting on engineered features	0.810	0.721
DeepImmuno architecture, retrained here	0.792	0.661
Allele prior (no peptide information)	**0.752**	0.500
BigMHC_IM [9]	0.647	0.609
DeepImmuno [2]	0.606	0.633
MixMHCpred 3.0 (binding only) [11]	0.559	0.570

The two DeepImmuno rows are different models and the gap between them is itself a result: the published checkpoint scores 0.606, while the same architecture retrained on our training split reaches 0.792. The architecture is not what

separates them; exposure to this dataset's study structure is.

The allele prior is constant within an allele, so its within-allele AUC is 0.500 by construction: the entire 0.752 is allele frequency. Holding the allele fixed costs the models trained here between 0.06 and 0.13 AUC, which is the allele signal they had been using. It costs the externally trained predictors nothing, and DeepImmuno and MixMHCpred score marginally *higher* within allele than pooled, because they never learned this dataset's allele skew in the first place. What looks like an advantage for the local models over published ones is, to a large extent, that signal.

A peptide-blind baseline that beats published predictors is diagnostic: on this benchmark, allele identity and dataset structure carry more signal than the peptide sequence does.

3.6 Published predictors were trained on the evaluation data

Intersecting our evaluation pairs with released training sets (§7.5) shows substantial overlap, and performance falls sharply outside it.

Predictor	Evaluation pairs it had seen	Seen	Unseen
DeepImmuno [2]	37.5% (shared peptide)	0.746	**0.512**
BigMHC_IM [9]	27.1% (shared peptide)	0.807	**0.549**

On the 778 lung-cancer-associated pairs whose sequence appears in neither training set, every published predictor's interval includes chance: DeepImmuno 0.528 (0.476–0.583), BigMHC 0.502 (0.438–0.561), MixMHCpred 0.446 (0.383–0.502), allele prior 0.465 (0.415–0.514).

3.7 The definition of a negative changes the task by ≈0.4 AUC

Using the harmonised multi-cancer resource of Müller et al. [4], across 99 patients:

What counts as a negative	Peptides compared	Per-patient AUC
Every candidate neo-peptide, screened or not	1,780,481 (76% never assayed)	≈ 0.97
Assayed negatives only	**421,017 assayed (23.6% of candidates)**	**≈ 0.55**

Of the 421,017 screened peptides, 178 were immunogenic. Ranking those 178 against *all* candidates gives per-patient AUC ≈ 0.97; discriminating them from assayed negatives gives ≈ 0.55. Both are published as immunogenicity prediction. Most "negatives" in the former are peptides nobody screened, overwhelmingly non-binders that any filter rejects.

3.8 Leakage-free performance approaches the measured ceiling, and architecture is immaterial

We scored every model from study-grouped out-of-fold predictions, within study and allele, across 205 groups, bootstrapping over studies (**Figure 2**, panel b):

Training scheme	AUC	95% CI
Ranking objective, no engineered features	**0.573**	0.544–0.603
Ranking objective, with features	0.557	0.526–0.588
CNN (original Conv2D architecture)	**0.544**	0.516–0.572
Study reweighting	0.548	0.519–0.576
Pointwise, no features	0.538	0.511–0.566
Pointwise baseline	0.532	0.504–0.560

All intervals clear chance, and the best result is 84% of the conservative reliability bound (0.681). Given identical pretraining, folds and seeds, the convolutional model differs from the attention model by +0.013 (95% CI −0.017 to +0.043), which is not significant. Architecture made no measurable difference. Only one comparison reaches significance: the ranking objective beats pointwise training by +0.035 (CI +0.001 to +0.069). The lower bound sits almost on zero, so we call that result marginal.

Study-aware reweighting recovers much of the loss on pooled metrics (0.623 → 0.700) and costs less than a bespoke objective.

3.9 A worked example: a feature that standard validation endorses and grouped validation rejects

Self-similarity to the human proteome looks strongly predictive under standard validation. Pooled across lung-cancer-associated pairs it reaches AUC 0.671 (CI 0.630–0.712), and under peptide-grouped validation it raised within-allele AUC by +0.034.

Grouping by study removes the effect. Within study its AUC is 0.483, and no study scores above chance. Withholding the whole feature block changes within-study AUC by +0.005 (CI −0.015 to +0.024) and within-study-and-allele AUC by −0.007; neither is significant. The feature tells studies apart, and says nothing about which peptides within a study are immunogenic.

Of nine feature families tested within study, only two clear chance: mean hydrophobicity 0.550 (0.518–0.582) and aromatic content 0.542 (0.517–0.568), both consistent with known determinants of TCR recognition [8].

4. Discussion

Reported AUCs of 0.85–0.90 are higher than the measured reliability of the labels (0.636, or 0.681 under the conservative bound) and higher than any model we could build under leakage-free evaluation (0.573). We attribute the gap to three things: peptide-level splitting, which behaves like no splitting; training-set overlap, which we found in both audited predictors; and negatives defined as untested candidates, which changes the task.

AUC is measured against noisy labels. A model that learns only transferable biology should therefore score near the label reliability, and one that scores well above it is probably also fitting the noise. Our results place that noise at the level of the study.

Agreement as a bound. Agreement between annotators does not cap model performance in general. If annotators err independently, a well-specified model can beat their mutual agreement [7]. Our figures therefore describe performance against these labels, not how accurate prediction could be in principle. Random label noise would make a high measured AUC unattainable. High AUCs are attainable here, which indicates that the noise is systematic and learnable, as §3.4–3.6 show.

Relation to prior work. Kapoor and Narayanan documented this pattern across 17 fields [6], and ours is an instance in computational immunology. In their case study, complex models claimed to beat logistic regression and ceased to do so once leakage was corrected; in ours, published predictors are outscored by a baseline that cannot see the peptide. Our setting also lets us measure the reliability of the labels directly instead of assuming it, because IEDB records which publication produced each measurement and some pairs were measured more than once. We extend Lee et al. [3], who identified HLA bias and cross-species degradation, by identifying the source publication as the operative grouping unit and by quantifying the label ceiling.

What bounds performance here. At 0.573 against a conservative bound of 0.681, we are at 84% of what the labels permit, leaving ≈0.11 AUC of headroom. We do not think architecture can recover it: the convolutional and attention models are statistically indistinguishable, and methods that do substantially better use information that sequence-only benchmarks lack, such as tumour expression, clonality, or the patient's own tumour-infiltrating repertoire [4]. Approaches that add TCR sequence without patient context report near-chance performance on unseen epitopes [9], so the limit is not specific to sequence-only models.

Raising the ceiling requires harmonised assays of the kind proficiency panels have shown to reduce variance [1]. Broadening coverage requires more distinct epitopes, currently limited by peptide-library production, and patient-specific prediction requires patient-specific measurement.

4.1 Recommendations

1. Split by source publication, not only by peptide, and state the grouping unit used.
2. Report within-study and within-allele AUC alongside any pooled figure.
3. Include a peptide-blind allele-prior baseline. If it is competitive, the benchmark is measuring dataset structure.
4. State the negative-set definition explicitly; untested candidates and assayed negatives are different tasks.
5. Audit training-set overlap before reporting comparative performance.
6. Bootstrap over studies, not rows; peptides within a study are not independent.

5. Limitations

- Label reliability is measured on IEDB alone. The independent dataset available to us lacks publication identifiers, so §3.4 but not §3.2 could be replicated externally.
- Repeat-tested pairs are a selected subset. We address this by stratification and adopt the most favourable bound, but the estimate remains conditional on that subset.
- MixMHCpred's training set is not public and could not be audited for contamination.
- Our protocol is stricter than the usual one, but we do not show that it predicts clinical success better. That would require prospective experimental validation.
- Analysis is restricted to 9–10mers and HLA-A/B/C, inherited from the encoding of the predictor we reimplemented.
- We propose no improved predictor. Our best model is a leakage-free reference point, and its apparent advantage over published tools on the peptide-grouped split (0.832 against 0.606 for DeepImmuno's released checkpoint) is an artifact of the split we argue against, and of our model having been fitted to this dataset's study structure.

6. Conclusion

The labels underlying T-cell epitope immunogenicity benchmarks reproduce across laboratories at AUC 0.636 (κ = 0.273; conservatively 0.681). Published predictors report 0.85–0.90. We trace the difference to peptide-level splitting that provides no protection, training-set contamination of 26–38%, and negative-set definitions that alter the task being measured. A leakage-free model reaches 0.573, attaining 84% of what the labels permit, and the original convolutional architecture is statistically indistinguishable from it. Progress in this area is currently limited by measurement reproducibility and epitope coverage, and model architecture is not the constraint.

7. Methods

7.1 Data retrieval and cleaning

T-cell assay records were retrieved from the IEDB Query API restricted to MHC class I, human host, and linear peptides of length 9–10 (92,721 records). Records were required to carry a four-digit HLA-A/B/C allele present in our pseudo-sequence table and a canonical twenty-letter peptide, leaving 65,732 records over 32,167 unique pairs. Any *Positive** qualitative measure was mapped to 1 and *Negative* to 0. Records were collapsed to one label per pair by majority vote; 893 exact ties were dropped, giving 31,274 pairs, 31.7% positive. A further 400,000 MHC binding and ligand-elution records were retrieved under the same constraints for encoder pretraining.

7.2 Split schemes

Two schemes are stored in the same table: *split*/*fold* grouped by peptide, and *study_split*/*study_fold* grouped by *reference_id*. Each uses a 15% grouped hold-out and 10 grouped CV folds.

7.3 Reliability measurement

Pairs assayed in ≥2 distinct publications were identified. Each study contributes its majority outcome for that pair; within-study ties are dropped. Two studies are drawn at random per pair, and we compute agreement, Cohen's κ, and the AUC of study A's label predicting study B's. The point estimate is the mean over 200 random pairings of the full set, so it does not depend on one arbitrary draw. The interval is a separate bootstrap that resamples the pairs themselves with replacement, 2,000 times, drawing a fresh pairing each time; percentiles taken across re-pairings of one fixed set of pairs would capture only how the two studies are chosen and would be about half as wide. Because both labels are binary, this AUC equals balanced accuracy. Sensitivity was assessed over four aggregation rules plus an unaggregated variant, over assay families, over HLA locus, and stratified by the number of studies testing a pair.

7.4 Models

Published predictors. DeepImmuno [2] (two-branch Conv2D), scored through its released *cnn_model_331_3_7* checkpoint, which we verified byte-identical to the copy in this repository; BigMHC_IM [9] (seven-network ensemble, presentation-pretrained then transfer-learned); MixMHCpred 3.0 [11] (binding only, included as a control). PRIME 2.0 was obtained but its bundled Windows binary did not execute; it is excluded and documented. Where a table reports the DeepImmuno architecture retrained by us, it is labelled as such and is a different set of weights from the released checkpoint.

Baselines. An allele prior predicting each allele's training-set positive rate, using no peptide information; gradient boosting on the AAindex/PCA encoding.

This study. A bidirectional cross-attention network (65,987 parameters): learned residue and position embeddings, self-attention within the 10-position peptide and the 46-residue HLA pseudo-sequence, then cross-attention in both directions, a dense trunk and a sigmoid output. Pretrained on the binding corpus (held-out binding AUC 0.958) and fine-tuned on immunogenicity.

Training schemes. Pointwise cross-entropy; dropping the dominant study; study-size reweighting; training on mixed-outcome studies only; and a study-stratified pairwise ranking objective over (immunogenic, non-immunogenic) pairs sharing a study and an allele. The CNN was trained from fresh initialisation, never from the published checkpoint, with identical pretraining, folds, class weighting and seeds.

7.5 Evaluation

Pooled AUC is reported with two stricter quantities: within-allele AUC, computed inside each allele; and within-study and within-study-and-allele AUC, computed inside each source publication. Groups require ≥10 pairs and both outcome classes. Confidence intervals for within-study quantities bootstrap over studies rather than rows. Models are scored from study-grouped out-of-fold predictions. Published training sets were intersected with our evaluation pairs by exact peptide and by exact peptide–HLA pair.

Figures

Figure 1. How the benchmark is distributed across its source studies. Pairs contributed per study against study rank, both axes logarithmic (solid, left axis), with the cumulative share of all pairs (dashed, right axis). The largest study contributes 11,486 pairs, 37% of the benchmark, and reports no positive outcome; the ten largest supply 54% of the data and the hundred largest 81%. Studies reporting a single outcome class account for 57% of all pairs.

Figure 2. What the labels can support, and what a leakage-free model achieves. Both panels are AUC on one scale, so the two reference bands run through both and are labelled once: the light band is the measured reliability of the labels (0.636– 0.681), the dark band the 0.85–0.90 range reported in the literature. The dashed line is chance. **(a)** AUC of one study's outcome predicting another's on the same pair, with 95% confidence intervals, under three robustness checks: the rule used to aggregate repeat records, how often the pair was retested, and the assay family and HLA locus. Filled markers are the headline estimate (0.636) and the conservative bound adopted in the text (0.681), which are the edges of the light band. No variant approaches the dark one. **(b)** Within-study, within-allele AUC for six training schemes, with intervals bootstrapped over studies. Every interval clears chance; the best reaches 84% of the conservative bound from panel (a) and leaves 0.28 AUC between itself and the reported range.

Data and code availability

All analyses are reproducible from *docs/PIPELINE.md*, and *notebooks/Reproduce_Manuscript.ipynb* reproduces every number and figure. Code is organised as *src/data* (retrieval, cleaning, splits), *src/models* (architectures, training) and *src/analysis* (all reported analyses). The curated benchmark, both split schemes and all model predictions are released with the repository, together with the outputs of every audited third-party predictor on our pairs, so the comparisons in §3.5 and §3.6 can be reproduced without installing those tools. DeepImmuno's released checkpoint is scored directly; *python -m src.models.deepimmuno* prints its held-out AUC in one command.

Archived at Zenodo: *10.5281/zenodo.23719454* for all versions, and *10.5281/zenodo.23719455* for v1.0.0, the release that produced every number reported here. Repository: *https://github.com/Terano24/Deep-Learning-Research-Project*. Code is released under the MIT licence; redistributed third-party data retains its own terms, listed in *LICENSE*.

External resources: IEDB Query API; UniProt UP000005640; TRAP [3]; the harmonised datasets of Müller et al. [4]; the public releases of DeepImmuno [2], BigMHC [9] and MixMHCpred [11].

Author contributions

Both authors contributed to study design and manuscript preparation. I Nyoman Agung Ananda Terano is the corresponding author and handles submission and correspondence.

Competing interests

The authors declare no competing interests.

Funding

This research received no specific grant from any funding agency.

Declaration of generative AI and AI-assisted technologies in the writing process

During the preparation of this work the authors used Claude (Anthropic) to draft and edit the manuscript text. The research question, the study design, the choice of analyses and the interpretation of the results are the authors' own. The authors reviewed and edited all AI-assisted content and take full responsibility for the content of the published article.

References

1. Janetzki S, Panageas KS, Ben-Porat L, Boyer J, Britten CM, et al. Results and harmonization guidelines from two large-scale international Elispot proficiency panels conducted by the Cancer Vaccine Consortium (CVC/SVI). *Cancer Immunol Immunother* 2008;57(3):303–315. doi:10.1007/s00262-007-0380-6
2. Li G, Iyer B, Prasath VBS, Ni Y, Salomonis N. DeepImmuno: deep learning-empowered prediction and generation of immunogenic peptides for T-cell immunity. *Brief Bioinform* 2021;22(6):bbab160. doi:10.1093/bib/bbab160
3. Lee CH, Huh J, Buckley PR, Jang M, Pinho MP, et al. A robust deep learning workflow to predict $CD8^+$ T-cell epitopes. *Genome Med* 2023;15:70. doi:10.1186/s13073-023-01225-z
4. Müller M, Huber F, Arnaud M, Kraemer AI, Ricart Altimiras E, et al. Machine learning methods and harmonized datasets improve immunogenic neoantigen prediction. *Immunity* 2023;56(11):2650–2663.e6. doi:10.1016/j.immuni.2023.09.002
5. Wells DK, van Buuren MM, Dang KK, Hubbard-Lucey VM, Sheehan KCF, et al. Key parameters of tumor epitope immunogenicity revealed through a consortium approach improve neoantigen prediction. *Cell* 2020;183(3):818–834.e13. doi:10.1016/j.cell.2020.09.015
6. Kapoor S, Narayanan A. Leakage and the reproducibility crisis in machine-learning-based science. *Patterns* 2023;4(9):100804. doi:10.1016/j.patter.2023.100804
7. Richie R, Grover S, Tsui FR. Inter-annotator agreement is not the ceiling of machine learning performance: evidence from a comprehensive set of simulations. *Proc BioNLP Workshop, ACL* 2022:275–284.
8. Calis JJA, Maybeno M, Greenbaum JA, Weiskopf D, De Silva AD, Sette A, Peters B, Keşmir C. Properties of MHC class I presented peptides that enhance immunogenicity. *PLoS Comput Biol* 2013;9(10):e1003266.
9. Albert BA, Yang Y, Shao XM, Singh D, Smith KN, Anagnostou V, Karchin R. Deep neural networks predict MHC-I epitope presentation and transfer learn neoepitope immunogenicity. *Nat Mach Intell* 2023;5:861–872.
10. Gfeller D, Schmidt J, Croce G, Guillaume P, Bobisse S, et al. Improved predictions of antigen presentation and TCR recognition with MixMHCpred2.2 and PRIME2.0. *Cell Syst* 2023;14(1):72–83.
11. Tadros DM, et al. Predicting MHC-I ligands across alleles and species: how far can we go? *Genome Med* 2025. (MixMHCpred 3.0 -- the version run here. This is the citation the tool's own output header requests; full author list and volume are still to be confirmed against the publisher record.)

Reference details were verified against CrossRef and PubMed records where available. Entries 8–11 should be re-checked against the publisher record before journal submission; entry 11 in particular is taken from the MixMHCpred 3.0 output header and its author list and volume are unconfirmed.