C4D05120E

Silicon Carbide Schottky Diode

Z-Rec® Rectifier

V_{RRM}	=	1200 V
I_F (T_C=135˚C)	=	9.5 A
Q_c	=	27 nC

Features

- 1.2kV Schottky Rectifier
- Zero Reverse Recovery Current
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Extremely Fast Switching
- Positive Temperature Coefficient on V_F

Benefits

- Replace Bipolar with Unipolar Rectifiers
- Essentially No Switching Losses
- Higher Efficiency
- Reduction of Heat Sink Requirements
- Parallel Devices Without Thermal Runaway

Applications

- Switch Mode Power Supplies (SMPS)
- Boost diodes in PFC or DC/DC stages
- Free Wheeling Diodes in Inverter stages
- LED Lighting Power Supplies
- AC/DC converters

Package

TO-252-2

Halogen-Free

RoHS

Part Number	Package	Marking
C4D05120E	TO-252-2	C4D05120

Maximum Ratings (T_C=25°C unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions	Note
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V		
V_{RSM}	Surge Peak Reverse Voltage	1300	V		
V_{DC}	DC Blocking Voltage	1200	V		
I_F	Continuous Forward Current	19 9.5 5	A	T_C=25˚C T_C=135˚C T_C=161˚C	Fig. 3
I_{FRM}	Repetitive Peak Forward Surge Current	26 18	A	T_C=25˚C, t_P=10 ms, Half Sine pulse T_C=110˚C, t_P=10 ms, Half Sine pulse	
I_{FSM}	Non-Repetitive Peak Forward Surge Current	46 36	A	T_C=25˚C, t_P=10 ms, Half Sine pulse T_C=110˚C, t_P=10 ms, Half Sine pulse	Fig. 8
$I_{F,Max}$	Non-Repetitive Peak Forward Current	400 320	A	T_C=25˚C, t_P=10 µs, Pulse T_C=110˚C, t_P=10 µs, Pulse	Fig. 8
P_{tot}	Power Dissipation	100 43	W	T_C=25˚C T_C=110˚C	Fig. 4
dV/dt	Diode dV/dt ruggedness	200	V/ns	V_R=0-960V	
$\int i^2dt$	i^2t value	10.6 6.5	A^2s	T_C=25˚C, t_P=10 ms T_C=110˚C, t_P=10 ms	
T_J , T_{stg}	Operating Junction and Storage Temperature	-55 to +175	˚C		

Electrical Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
V_F	Forward Voltage	1.4 1.9	1.8 3	V	I_F = 5 A T_J=25°C I_F = 5 A T_J=175°C	Fig. 1
I_R	Reverse Current	20 40	150 300	µA	V_R = 1200 V T_J=25°C V_R = 1200 V T_J=175°C	Fig. 2
Q_C	Total Capacitive Charge	27		nC	V_R = 800 V, I_F = 5A di/dt = 200 A/µs T_J = 25°C	Fig. 5
C	Total Capacitance	390 27 20		pF	V_R = 0 V, T_J = 25°C, f = 1 MHz V_R = 400 V, T_J = 25°C, f = 1 MHz V_R = 800 V, T_J = 25°C, f = 1 MHz	Fig. 6
E_C	Capacitance Stored Energy	8.0		µJ	V_R = 800 V	Fig. 7

Note: This is a majority carrier diode, so there is no reverse recovery charge.

Thermal Characteristics

Symbol	Parameter	Typ.	Unit	Note
$R_{\theta JC}$	Thermal Resistance from Junction to Case	1.5	°C/W	Fig. 9

Typical Performance



Figure 1. Forward Characteristics



Figure 2. Reverse Characteristics

Typical Performance



Figure 3. Current Derating



Figure 4. Power Derating



Figure 5. Recovery Charge vs. Reverse Voltage



Figure 6. Capacitance vs. Reverse Voltage

Typical Performance



Figure 7. Typical Capacitance Stored Energy



Figure 8. Non-repetitive peak forward surge current versus pulse duration (sinusoidal waveform)



Figure 9. Transient Thermal Impedance

Package Dimensions

Package TO-252-2



SYMBOL	MILLIMETERS	
	MIN	MAX
A	2.159	2.413
A1	0	0.13
b	0.64	0.89
b2	0.653	1.143
b3	5.004	5.6
c	0.457	0.61
c2	0.457	0.864
D	5.867	6.248
D1	5.21	-
E	6.35	7.341
E1	4.32	-
e	4.58 BSC	
H	9.65	10.414
L	1.106	1.78
L2	0.51 BSC	
L3	0.889	1.27
L4	0.64	1.01
θ	0°	8°

Recommended Solder Pad Layout



all units are in millimeters

TO-252-2

Part Number	Package	Marking
C4D05120E	TO-252-2	C4D05120

Note: Recommended soldering profiles can be found in the applications note here:
http://www.wolfspeed.com/power_app_notes/soldering

Diode Model



$$Vf_T = V_T + If * R_T$$

$$V_T = 0.96 + (T_j * -1.22*10^{-3})$$

$$R_T = 0.08 + (T_j * 8.5*10^{-4})$$

Note: T_J = Diode Junction Temperature in Degrees Celsius, valid from 25°C to 175°C

Notes

- **RoHS Compliance**
  The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Wolfspeed representative or from the Product Ecology section of our website at http://www.wolfspeed.com/power/tools-and-support/product-ecology.

- **REACh Compliance**
  REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future,please contact a Cree representative to insure you get the most up-to-date REACh SVHC Declaration. REACh banned substance information (REACh Article 67) is also available upon request.

- This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control systems.

Related Links

- Cree SiC Schottky diode portfolio: http://www.wolfspeed.com/Power/Products#SiCSchottkyDiodes
- Schottky diode Spice models: http://www.wolfspeed.com/power/tools-and-support/DIODE-model-request2
- SiC MOSFET and diode reference designs: http://go.pardot.com/l/101562/2015-07-31/349i

Copyright © 2017 Cree, Inc. All rights reserved.
The information in this document is subject to change without notice.
Cree, the Cree logo, and Zero Recovery are registered trademarks of Cree, Inc.

Cree, Inc.
4600 Silicon Drive
Durham, NC 27703
USA Tel: +1.919.313.5300
Fax: +1.919.313.5451
www.cree.com/power

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cree, Inc.:
C4D05120E