TPS22916xx 1-V – 5.5-V, 2-A, 60-mΩ Ultra-Low Leakage Load Switch

1 Features

- Input Operating Voltage Range (V_{IN}): 1 V–5.5 V
- Maximum Continuous Current (I_{MAX}): 2 A
- ON-Resistance (R_{ON}):
  - 5 V_{IN} = 60 mΩ (typ), 100 mΩ (85°C max)
  - 1.8 V_{IN} = 100 mΩ (typ), 150 mΩ (85°C max)
  - 1 V_{IN} = 200 mΩ (typ), 325 mΩ (85°C max)
- Ultra-Low Power Consumption:
  - ON State (I_Q): 0.5 µA (typ), 1 µA (max)
  - OFF State (I_{SD}): 10 nA (typ), 100 nA (max)
  - TPS22916CL (I_{SD}): 100 nA (typ), 300 nA (max)
- Smart ON Pin Pull Down (R_{PD}):
  - ON ≥ V_{IH} (I_{ON}): 10 nA (max)
  - ON ≤ V_{IL} (R_{PD}): 750 kΩ (typ)
- Slow Timing in C Version Limits Inrush Current:
  - 5-V Turnon time (t_{ON}): 1400 µs at 5 mV/µs
  - 1.8-V Turnon time (t_{ON}): 3000 µs at 1 mV/µs
  - 1-V Turnon time (t_{ON}): 6500 µs at 0.3 mV/µs
- Fast Timing in B Version Reduces Wait Time:
  - 5-V Turnon time (t_{ON}): 115 µs at 57 mV/µs
  - 1.8-V Turnon time (t_{ON}): 250 µs at 12 mV/µs
  - 1-V Turnon time (t_{ON}): 510 µs at 3.3 mV/µs
- Always-ON True Reverse Current Blocking (RCB):
  - Activation Current (I_{RCB}): –500 mA (typ)
  - Reverse Leakage ($I_{IN,RCB}$): –300 nA (max)
- Quick Output Discharge (QOD): 150 Ω (typ) (N version has no QOD)
- Active Low Enable Option (L Version)

2 Applications

- Wearables
- Smartphones
- Tablets
- Portable Speakers

3 Description

The TPS22916xx is a small, single channel load switch using a low leakage P-Channel MOSFET for minimum power loss. Advanced gate control design supports operating voltages as low as 1 V with minimal increase in ON-Resistance and power loss.

Multiple timing options are available to support various system loading conditions. For heavy capacitive loads, the slow turnon timing in the C version minimizes the inrush current. In cases with light capacitive loads, the fast timing in the B version reduces required wait time.

The switch ON state is controlled by a digital input that is capable of interfacing directly with low-voltage control signals. Both Active High and Active Low (L) versions are available. When power is first applied, a Smart Pull Down is used to keep the ON pin from floating until system sequencing is complete. Once the ON pin is deliberately driven high (≥V_{IH}), the Smart Pull Down is disconnected to prevent unnecessary power loss.

The TPS22916xx is available in a small, space saving 0.74-mm × 0.74-mm, 0.4-mm pitch, 0.5-mm height 4-pin Wafer-Chip-Scale (WCSP) package (YFP). The device is characterized for operation over a temperature range of –40°C to +85°C.

Device Information[1]

PART NUMBER	PACKAGE	BODY SIZE (NOM)
TPS22916xx	WCSP (4)	0.74 mm × 0.74 mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.

Device Comparison Table

VERSION	TIMING	QOD	ENABLE (ON)
TPS22916B	Fast	Yes	Active High
TPS22916C	Slow	Yes	Active High
TPS22916CN	Slow	No	Active High
TPS22916CL	Slow	Yes	Active Low

Simplified Schematic



Copyright © 2017, Texas Instruments Incorporated

An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.

Table of Contents

4 Revision History

Changes from Original (July 2017) to Revision A **Page**

- Changed device document from Advanced Info to Production Data ... 1

Copyright © 2017, Texas Instruments Incorporated

5 Pin Configuration and Functions

YFP Package
4-Pin WSON
Laser Marking View



YFP Package
4-Pin WSON
Bump View



TPS22916xx Pin Functions

PIN		TYPE	DESCRIPTION
NO.	NAME		
A1	VOUT	Power	Switch output
A2	VIN	Power	Switch input
B1	GND	Ground	Device ground
B2	ON	Digital input	Device enable

Copyright © 2017, Texas Instruments Incorporated

6 Specifications

6.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)(1)

		MIN	MAX	UNIT
V_{IN}	Input voltage	–0.3	6	V
V_{OUT}	Output voltage	–0.3	6	V
V_{ON}	Enable voltage	–0.3	6	V
I_{MAX}	Maximum continuous switch current		2	A
I_{PLS}	Maximum pulsed switch current, pulse < 300-µs, 2% duty cycle		2.5	A
$T_{J,MAX}$	Maximum junction temperature		125	°C
T_{STG}	Storage temperature	–65	150	°C
T_{LEAD}	Maximum Lead temperature (10-s soldering time)		300	°C

(1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001(1)	±2000	V
		Charged-device model (CDM), per JEDEC specification JESD22-C101(2)	±500	

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 500-V HBM is possible with the necessary precautions. Pins listed as ±2000 V may actually have higher performance.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 250-V CDM is possible with the necessary precautions. Pins listed as ±500 V may actually have higher performance.

6.3 Recommended Operating Conditions

Over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V_{IN}	Input voltage	1	5.5	V
V_{OUT}	Output voltage	0	5.5	V
V_{IH}	High-level input voltage, ON	1	5.5	V
V_{IL}	Low-level input voltage, ON	0	0.35	V
T_A	Operating free-air temperature	–40	85	°C

6.4 Thermal Information

Thermal Parameters(1)		TPS22916xx YFP (WCSP) 4 PINS	UNIT
θ_{JA}	Junction-to-ambient thermal resistance	193	°C/W
θ_{JCtop}	Junction-to-case (top) thermal resistance	2.3	°C/W
θ_{JB}	Junction-to-board thermal resistance	36	°C/W
ψ_{JT}	Junction-to-top characterization parameter	12	°C/W
ψ_{JB}	Junction-to-board characterization parameter	36	°C/W

(1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report.

Copyright © 2017, Texas Instruments Incorporated

6.5 Electrical Characteristics

Unless otherwise noted, the specification in the following table applies for all variants over the entire recommended power supply voltage range of 1 V to 5.5 V unless noted otherwise. Typical Values are at 25°C.

PARAMETER		TEST CONDITIONS		T_J	MIN	TYP	MAX	UNIT
INPUT SUPPLY (VIN)								
$I_{Q,VIN}$	V_{IN} Quiescent current	Enabled, V_{OUT} = Open		–40°C to +85°C		0.5	1.0	µA
$I_{SD,VIN}$	V_{IN} Shutdown current	Disabled, V_{OUT} = GND (TPS22916B/C/CN)		–40°C to +85°C		10	100	nA
		Disabled, V_{OUT} = GND (TPS22916CL)		–40°C to +85°C		100	300	nA
ON-RESISTANCE (R_{ON})								
R_{ON}	ON-Resistance	I_{OUT} = 200 mA	V_{IN} = 5 V	25°C		60	80	mΩ
				–40°C to +85°C			100	
				–40°C to +105°C			120	
			V_{IN} = 3.6 V	25°C		70	90	
				–40°C to +85°C			120	
				–40°C to +105°C			140	
			V_{IN} = 1.8 V	25°C		100	125	
				–40°C to +85°C			150	
				–40°C to +105°C			175	
			V_{IN} = 1.2 V	25°C		150	200	
				–40°C to +85°C			250	
				–40°C to +105°C			300	
			V_{IN} = 1 V	25°C		200	275	
				–40°C to +85°C			325	
				–40°C to +105°C			375	
ENABLE PIN (ON)								
I_{ON}	ON Pin leakage	Enabled		–40°C to +85°C	–10		10	nA
R_{PD}	Smart Pull Down Resistance	Disabled		–40°C to +85°C		750		kΩ
REVERSE CURRENT BLOCKING (RCB)								
I_{RCB}	RCB Activation Current	Enabled, $V_{OUT} > V_{IN}$		–40°C to +85°C		-500		mA
t_{RCB}	RCB Activation time	Enabled, $V_{OUT} > V_{IN}$ + 200mV		–40°C to +85°C		10		µs
V_{RCB}	RCB Release Voltage	Enabled, $V_{OUT} > V_{IN}$		–40°C to +85°C		25		mV
$I_{IN,RCB}$	VIN Reverse Leakage Current	0 V ≤ V_{IN} + V_{RCB} ≤ V_{OUT} ≤ 5.5 V		–40°C to +85°C	–300			nA
QUICK OUTPUT DISCHARGE (QOD)								
QOD (1)	Output discharge resistance	Disabled (Not in TPS22916CN)		–40°C to +85°C		150		Ω

(1) For more information on which devices include quick output discharge, see the *Device Functional Modes* section.

6.6 Switching Characteristics

Unless otherwise noted, the typical characteristics in the following table applies over the entire recommended power supply voltage range of 1 V to 5.5 V at 25°C with a load of C_L = 0.1µF, R_L = 10Ω.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
TPS22916B						
t_{ON}	Turn On Time	V_{IN} = 5 V		115		µs
		V_{IN} = 3.6 V		140		
		V_{IN} = 1.8 V		250		
		V_{IN} = 1.2 V		350		
		V_{IN} = 1 V		510		
t_{RISE}	Rise Time	V_{IN} = 5 V		70		µs
		V_{IN} = 3.6 V		80		
		V_{IN} = 1.8 V		130		
		V_{IN} = 1.2 V		190		
		V_{IN} = 1 V		240		
SR_{ON}	Slew Rate	V_{IN} = 5 V		57		mV/µs
		V_{IN} = 3.6 V		36		
		V_{IN} = 1.8 V		12		
		V_{IN} = 1.2 V		5.1		
		V_{IN} = 1 V		3.3		
t_{OFF}	Turn Off Time	V_{IN} = 5 V		5		µs
		V_{IN} = 3.6 V		5		
		V_{IN} = 1.8 V		10		
		V_{IN} = 1.2 V		15		
		V_{IN} = 1 V		25		
t_{FALL}	Fall Time	C_L = 0.1 µF, R_L = 10 Ω(1)		2.3		µs
		C_L = 1µF, R_L = Open(1)		315		

(1) See the *Fall Time (t_{FALL}) and Quick Output Discharge (QOD)* section for information on how R_L and C_L affect Fall Time.

Copyright © 2017, Texas Instruments Incorporated

Switching Characteristics (continued)

Unless otherwise noted, the typical characteristics in the following table applies over the entire recommended power supply voltage range of 1 V to 5.5 V at 25°C with a load of C_L = 0.1µF, R_L = 10Ω.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
TPS22916C, TPS22916CN, TPS22916CL						
t_{ON}	Turn On Time	V_{IN} = 5 V		1400		µs
		V_{IN} = 3.6 V		1700		
		V_{IN} = 1.8 V		3000		
		V_{IN} = 1.2 V		5000		
		V_{IN} = 1 V		6500		
t_{RISE}	Rise Time	V_{IN} = 5 V		800		µs
		V_{IN} = 3.6 V		900		
		V_{IN} = 1.8 V		1400		
		V_{IN} = 1.2 V		2300		
		V_{IN} = 1 V		3000		
SR_{ON}	Slew Rate	V_{IN} = 5 V		5		mV/µs
		V_{IN} = 3.6 V		3.2		
		V_{IN} = 1.8 V		1		
		V_{IN} = 1.2 V		0.4		
		V_{IN} = 1 V		0.3		
t_{OFF}	Turn Off Time	V_{IN} = 5 V		5		µs
		V_{IN} = 3.6 V		5		
		V_{IN} = 1.8 V		10		
		V_{IN} = 1.2 V		15		
		V_{IN} = 1 V		25		
t_{FALL}	Fall Time(2)	C_L = 0.1 µF, R_L = 10 Ω(1)		2.3		µs
		CL = 10µF, RL = Open(1)		3150		

(2) Devices without Quick Output Discharge (QOD) may not discharge completely.

Copyright © 2017, Texas Instruments Incorporated

6.7 Typical Characteristics

6.7.1 Typical Electrical Characteristics

The typical characteristics curves in this section apply to all devices unless otherwise noted.



Enabled

Figure 1. ON-Resistance vs Temperature



Enabled

Figure 2. ON-Resistance vs Input voltage



TPS22916C, TPS22916CN, TPS22916B $V_{ON} \le V_{IL}$

Figure 3. Shutdown Current



TPS22916CL $V_{ON} \ge V_{IH}$

Figure 4. Shutdown Current (Active Low)



Enabled

Figure 5. Quiescent Current



–40°C to +85°C

Figure 6. ON Pin Threshold

Copyright © 2017, Texas Instruments Incorporated

Typical Electrical Characteristics (continued)



$V_{ON} \leq V_{IL}$

Figure 7. ON Pin Smart Pull Down



TPS22916C TPS22916CL TPS22916B

Figure 8. Quick Output Discharge

6.7.2 Typical Switching Characteristics

The typical data in this section apply to all devices at 25°C unless otherwise noted.



C_L = 0.1 µF R_L = 10 Ω

Figure 9. Fast Turn On Time



TPS22916B V_{IN} = 5 V C_L = 0.1 µF R_L = 10 Ω

Figure 10. Fast Turn On at 5 V



C_L = 0.1 µF R_L = 10 Ω

Figure 11. Fast Rise Time



TPS22916B V_{IN} = 3.6 V C_L = 0.1 µF R_L = 10 Ω

Figure 12. Fast Turn On at 3.6 V



C_L = 0.1 µF R_L = 10 Ω

Figure 13. Fast Slew Rate



TPS22916B V_{IN} = 1 V C_L = 0.1 µF R_L = 10 Ω

Figure 14. Fast Turn on at 1 V

Copyright © 2017, Texas Instruments Incorporated

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.



R_L = 10 Ω TPS22916B

Figure 15. Fast Turn On vs Load Capacitance



C_L = 10 µF TPS22916B

Figure 16. Fast Turn On vs Load Resistance



R_L = 10 Ω TPS22916B

Figure 17. Fast Rise Time vs Load Capacitance



C_L = 10 µF TPS22916B

Figure 18. Fast Rise Time vs Load Resistance



R_L = 10 Ω TPS22916B

Figure 19. Fast Slew Rate vs Load Capacitance



C_L = 10 µF TPS22916B

Figure 20. Fast Slew Rate vs Load Resistance

Copyright © 2017, Texas Instruments Incorporated

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.



C_L = 0.1 µF R_L = 10 Ω

Figure 21. Slow Turn on Time



TPS22916C V_{IN} = 5 V C_L = 0.1 µF R_L = 10 Ω

Figure 22. Slow Turn on at 5 V



C_L = 0.1 µF R_L = 10 Ω

Figure 23. Slow Rise Time



TPS22916C V_{IN} = 3.6 V C_L = 0.1 µF R_L = 10 Ω

Figure 24. Slow Turn On at 3.6 V



C_L = 0.1 µF R_L = 10 Ω

Figure 25. Slow Slew Rate



TPS22916C V_{IN} = 1 V C_L = 0.1 µF R_L = 10 Ω

Figure 26. Slow Turn On at 1 V

Copyright © 2017, Texas Instruments Incorporated

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.



R_L = 10 Ω TPS22916C TPS22916CN TPS22916CL

Figure 27. Slow Turn On vs Load Capacitance



C_L = 100 µF TPS22916C TPS22916CN TPS22916CL

Figure 28. Slow Turn On vs Load Resistance



R_L = 10 Ω TPS22916C TPS22916CN TPS22916CL

Figure 29. Slow Rise Time vs Load Capacitance



C_L = 100 µF TPS22916C TPS22916CN TPS22916CL

Figure 30. Slow Rise Time vs Load Capacitance



R_L = 10 Ω TPS22916C TPS22916CN TPS22916CL

Figure 31. Slow Slew Rate vs Load Capacitance



C_L = 100 µF TPS22916C TPS22916CN TPS22916CL

Figure 32. Slow Slew Rate vs Load Resistance

Copyright © 2017, Texas Instruments Incorporated

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.



Figure 33. Turn Off Time



TPS22916CL V_{IN} = 5 V C_L = 0.1 µF R_L = 10 Ω

Figure 34. Turn Off at 5 V (Active Low)



V_{IN} = 1 V to 5.5 V TPS22916C TPS22916CL TPS22916B

Figure 35. Fall Time

Copyright © 2017, Texas Instruments Incorporated

7 Parameter Measurement Information



Copyright © 2017, Texas Instruments Incorporated

Figure 36. TPS22916 Test Circuit



Figure 37. TPS22916 Timing Waveform

8 Detailed Description

8.1 Overview

This family of devices are single channel, 2-A load switches in ultra-small, space saving 4-pin WCSP package. These devices implement a low resistance P-channel MOSFET with a controlled rise time for applications that need to limit inrush current.

These devices are designed to have very low leakage current during off state. This prevents downstream circuits from pulling high standby current from the supply. Integrated control logic, driver, power supply, and output discharge FET eliminates the need for additional external components, which reduces solution size and BOM count.

8.2 Functional Block Diagram



Copyright © 2017, Texas Instruments Incorporated

8.3 Feature Description

8.3.1 On and Off Control

The ON pin controls the state of the switch. The ON pin is compatible with standard GPIO logic threshold. It can be used with any microcontroller with 1.2-V, 1.8-V, 2.5-V, 3.3-V, or 5.5-V GPIO.

8.3.2 Fall Time (t_{FALL}) and Quick Output Discharge (QOD)

The TPS22916B/C/CL include a Quick Output Discharge feature. When the switch is disabled, a discharge resistor is connected between VOUT and GND. This resistor has a typical value of QOD and prevents the output from floating while the switch is disabled.

As load capacitance and load resistance increase: t_{FALL} increases. The larger the load resistance or load capacitance is, the longer it takes to discharge the capacitor, resulting in a longer fall time.

Copyright © 2017, Texas Instruments Incorporated

Feature Description (continued)

The output fall time is determined by how quickly the load capacitance is discharged and can be found using Equation 1 .

$$t_{FALL} = - (R_{DIS}) \times C_L \times \ln(V_{10\%}/V_{90\%}) \quad (1)$$

Where

- $V_{10\%}$ is 10% of the initial output voltage
- $V_{90\%}$ is 90% of the initial output voltage
- R_{DIS} is the result of the QOD resistance in parallel with the Load Resistance R_L
- C_L is the load capacitance

With the Quick Output Discharge feature, the QOD resistance is in parallel with R_L. This provides a lower total load resistance as seen from the load capacitance which discharges the capacitance faster resulting in a smaller t_{FALL}.

8.3.3 Full-Time Reverse Current Blocking

In a scenario where the device is enabled and V_{OUT} is greater than V_{IN} there is potential for reverse current to flow through the pass FET or the body diode. When the reverse current threshold (I_{RCB}) is exceeded, the switch is disabled within t_{RCB}. The Switch will remain off and block reverse current as long as the reverse voltage condition exists. Once V_{OUT} has dropped below the V_{RCB} release threshold the TPS22916xx will turn back on with slew rate control.

8.4 Device Functional Modes

Table 1 describes the state for each variant as determined by the ON pin

Table 1. Device Function Table

ON	TPS22916B	TPS22916C	TPS22916CN	TPS22916CL
≤ V_{IL}	Disabled	Disabled	Disabled	Enabled
≥ V_{IH}	Enabled	Enabled	Enabled	Disabled

Table 2 shows when QOD is active for each variant.

Table 2. QOD Function Table

Device	TPS22916B	TPS22916C	TPS22916CN	TPS22916CL
Enabled	No	No	No	No
Disabled	Yes	Yes	No	Yes

Table 3 shows when the ON Pin Smart Pull Down is active.

Table 3. Smart-ON Pull Down

V_{ON}	Pull Down
≤ V_{IL}	Connected
≥ V_{IH}	Disconnected

Copyright © 2017, Texas Instruments Incorporated

9 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

9.1 Application Information

This section highlights some of the design considerations when implementing this device in various applications. A PSPICE model for this device is also available in the product page of this device.

9.1.1 Typical Application



Copyright © 2017, Texas Instruments Incorporated

Figure 38. Typical Application

9.1.1.1 Design Requirements

For this design example, below, use the input parameters shown in Table 4.

Table 4. Design Parameters

Design Parameter	Example Value
Input Voltage (V_{IN})	3.6 V
Load Capacitance (C_L)	47 µF
Maximum Inrush Current (I_{RUSH})	300 mA

9.1.1.2 Detailed Design Procedure

9.1.1.2.1 Maximum Inrush Current

When the switch is enabled, the output capacitors must be charged up from 0-V to VIN voltage. This charge arrives in the form of inrush current. Inrush current can be calculated using the following equation:

$$I_{RUSH} = C_L \times SR_{ON} \quad (2)$$

$$I_{RUSH} = 47\mu F \times 3.2mV/\mu s \quad (3)$$

$$I_{RUSH} = 150mA \quad (4)$$

The TPS22916x offers multiple rise time options to control the inrush current during turn-on. The appropriate device can be selected based upon the maximum acceptable slew rate which can be calculated using the design requirements and the inrush current equation. In this case, the TPS22916C provides a slew rate slow enough to limit the inrush current to the desired amount.

Copyright © 2017, Texas Instruments Incorporated

9.1.1.3 Application Curve



V_{IN} = 3.6 V C_L = 47µF R_L = Open
TPS22916C T_A = 25°C

Figure 39. Inrush Current

10 Power Supply Recommendations

The device is designed to operate with a VIN range of 1 V to 5.5 V. The VIN power supply must be well regulated and placed as close to the device terminal as possible. The power supply must be able to withstand all transient load current steps. In most situations, using an input capacitance (C_{IN}) of 1 µF is sufficient to prevent the supply voltage from dipping when the switch is turned on. In cases where the power supply is slow to respond to a large transient current or large load current step, additional bulk capacitance may be required on the input.

Copyright © 2017, Texas Instruments Incorporated

11 Layout

11.1 Layout Guidelines

For best performance, all traces must be as short as possible. To be most effective, the input and output capacitors must be placed close to the device to minimize the effects that parasitic trace inductances may have on normal operation. Using wide traces for VIN, VOUT, and GND helps minimize the parasitic electrical effects.

11.2 Layout Example

Equation 3 shows an example for these devices. Notice the connection to system ground between the V_{OUT} Bypass Capacitor ground and the GND pin of the load switch, this creates a ground barrier which helps to reduce the ground noise seen by the device.



Figure 40. TPS22916xx Layout

11.3 Thermal Considerations

The maximum IC junction temperature must be restricted to 125°C under normal operating conditions. To calculate the maximum allowable dissipation, $P_{D(max)}$ for a given output current and ambient temperature, use Equation 5 as a guideline:

$$P_{D(MAX)} = \frac{T_{J(MAX)} - T_A}{R_{\theta JA}} \quad (5)$$

Where,

$P_{D(max)}$ = maximum allowable power dissipation
$T_{J(max)}$ = maximum allowable junction temperature
T_A = ambient temperature for the device
θ_{JA} = junction to air thermal impedance. See the *Thermal Information* section.

Copyright © 2017, Texas Instruments Incorporated

12 Device and Documentation Support

12.1 Documentation Support

12.1.1 Related Documentation

For related documentation see the following:

TPS22916 Load Switch Evaluation Module

12.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

12.3 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

TI E2E™ Online Community ***TI's Engineer-to-Engineer (E2E) Community.*** Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

Design Support ***TI's Design Support*** Quickly find helpful E2E forums along with design support tools and contact information for technical support.

12.4 Trademarks

E2E is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

12.5 Electrostatic Discharge Caution

This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

12.6 Glossary

SLYZ022 — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

13 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2017, Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TPS22916BYFPR	ACTIVE	DSBGA	YFP	4	3000	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	BA	Samples
TPS22916BYFPT	ACTIVE	DSBGA	YFP	4	250	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	BA	Samples
TPS22916CLYFPR	ACTIVE	DSBGA	YFP	4	3000	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	B9	Samples
TPS22916CLYFPT	ACTIVE	DSBGA	YFP	4	250	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	B9	Samples
TPS22916CNYFPR	ACTIVE	DSBGA	YFP	4	3000	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	B8	Samples
TPS22916CNYFPT	ACTIVE	DSBGA	YFP	4	250	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	B8	Samples
TPS22916CYFPR	ACTIVE	DSBGA	YFP	4	3000	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	B7	Samples
TPS22916CYFPT	ACTIVE	DSBGA	YFP	4	250	Green (RoHS & no Sb/Br)	Call TI	Level-1-260C-UNLIM	-40 to 85	B7	Samples

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".
RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.
Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS22916BYFPR	DSBGA	YFP	4	3000	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916BYFPT	DSBGA	YFP	4	250	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916CLYFPR	DSBGA	YFP	4	3000	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916CLYFPT	DSBGA	YFP	4	250	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916CNYFPR	DSBGA	YFP	4	3000	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916CNYFPT	DSBGA	YFP	4	250	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916CYFPR	DSBGA	YFP	4	3000	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1
TPS22916CYFPT	DSBGA	YFP	4	250	180.0	8.4	0.86	0.86	0.59	4.0	8.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS22916BYFPR	DSBGA	YFP	4	3000	182.0	182.0	20.0
TPS22916BYFPT	DSBGA	YFP	4	250	182.0	182.0	20.0
TPS22916CLYFPR	DSBGA	YFP	4	3000	182.0	182.0	20.0
TPS22916CLYFPT	DSBGA	YFP	4	250	182.0	182.0	20.0
TPS22916CNYFPR	DSBGA	YFP	4	3000	182.0	182.0	20.0
TPS22916CNYFPT	DSBGA	YFP	4	250	182.0	182.0	20.0
TPS22916CYFPR	DSBGA	YFP	4	3000	182.0	182.0	20.0
TPS22916CYFPT	DSBGA	YFP	4	250	182.0	182.0	20.0

PACKAGE OUTLINE

YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



4223507/A 01/2017

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:50X



SOLDER MASK DETAILS
NOT TO SCALE

4223507/A 01/2017

NOTES: (continued)

3. Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints.
For more information, see Texas Instruments literature number SNVA009 (www.ti.com/lit/snva009).

EXAMPLE STENCIL DESIGN

YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:50X

4223507/A 01/2017

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

IMPORTANT NOTICE

Texas Instruments Incorporated (TI) reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

TI's published terms of sale for semiconductor products (http://www.ti.com/sc/docs/stdterms.htm) apply to the sale of packaged integrated circuit products that TI has qualified and released to market. Additional terms may apply to the use or sale of other types of TI products and services.

Reproduction of significant portions of TI information in TI data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such reproduced documentation. Information of third parties may be subject to additional restrictions. Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyers and others who are developing systems that incorporate TI products (collectively, "Designers") understand and agree that Designers remain responsible for using their independent analysis, evaluation and judgment in designing their applications and that Designers have full and exclusive responsibility to assure the safety of Designers' applications and compliance of their applications (and of all TI products used in or for Designers' applications) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to their applications, Designer has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any applications that include TI products, Designer will thoroughly test such applications and the functionality of such TI products as used in such applications.

TI's provision of technical, application or other design advice, quality characterization, reliability data or other services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using TI Resources in any way, Designer (individually or, if Designer is acting on behalf of a company, Designer's company) agrees to use any particular TI Resource solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

Designer is authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNER AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Unless TI has explicitly designated an individual product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949 and ISO 26262), TI is not responsible for any failure to meet such industry standard requirements.

Where TI specifically promotes products as facilitating functional safety or as compliant with industry functional safety standards, such products are intended to help enable customers to design and create their own applications that meet applicable functional safety standards and requirements. Using products in an application does not by itself establish any safety features in the application. Designers must ensure compliance with safety-related requirements and standards applicable to their applications. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

TI may expressly designate certain products as completing a particular qualification (e.g., Q100, Military Grade, or Enhanced Product). Designers agree that it has the necessary expertise to select the product with the appropriate qualification designation for their applications and that proper product selection is at Designers' own risk. Designers are solely responsible for compliance with all legal and regulatory requirements in connection with such selection.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2017, Texas Instruments Incorporated