

# Dickinson User Guide

Vanessa McHale

## Contents

<b>Introduction</b>	<b>2</b>
<b>Installing Dickinson</b>	<b>2</b>
Editor Integration . . . . .	2
<b>Program Structure</b>	<b>2</b>
Example . . . . .	2
Comments . . . . .	3
Definitions & Names . . . . .	3
Branching . . . . .	3
Interpolation . . . . .	4
Multi-Line Strings . . . . .	4
Expressions . . . . .	4
Lambdas . . . . .	5
Matches & Tuples . . . . .	5
Tags . . . . .	6
Types . . . . .	7
<b>REPL</b>	<b>7</b>
Saving & Restoring States . . . . .	8
Builtins . . . . .	8
<b>Lints</b>	<b>9</b>
<b>Libraries</b>	<b>9</b>
Using Libraries . . . . .	9
Example . . . . .	9
Writing Libraries . . . . .	9
<b>Scripting</b>	<b>10</b>
<b>Examples</b>	<b>10</b>
Cowsay . . . . .	10
Noun Declension . . . . .	10

Shakespearean Insult Generator . . . . .	11
Lyrics Bot . . . . .	12

## Introduction

Dickinson is a text-generation language for generative literature. Each time you run your code, you get back randomly generated text.

It provides a language to define random texts like the Magical Realism Bot or fortune program.

## Installing Dickinson

First, install cabal and GHC. Then:

```
cabal install language-dickinson
```

This provides `emd`, the command-line interface to the Dickinson language.

You may also wish to install manpages for reference information about `emd`. Manpages are installed at

```
emd man
```

## Editor Integration

A vim plugin is available.

## Program Structure

Dickinson files begin with `%-`, followed by definitions.

## Example

Here is a simple Dickinson program:

```
%-

(:def main
  (:oneof
    (| "heads")
    (| "tails")))
```

Save this as `gambling.dck`. Then:

```
emd run gambling.dck
```

which will display either `heads` or `tails`.

The `:oneof` construct selects one of its branches with equal probability.

In general, when you `emd run` code, you'll see the result of evaluating `main`.

## Comments

Comments are indicated with a `;` at the beginning of the line. Anything to the right of the `;` is ignored. So

```
%-  
  
; This returns one of 'heads' or 'tails'  
(:def main  
  (:oneof  
    (| "heads")  
    (| "tails")))
```

is perfectly valid code and is functionally the same as the above.

## Definitions & Names

We can define names and reference them later:

```
%-  
  
(:def gambling  
  (:oneof  
    (| "heads")  
    (| "tails")))  
  
(:def main  
  gambling)
```

We can `emd run` this and it will give the same results as above.

## Branching

When you use `:oneof`, Dickinson picks one of the branches with equal probability. If this is not what you want, you can use `:branch`:

```
%-

(:def unfairCoin
  (:branch
    (| 1.0 "heads")
    (| 1.1 "tails")))

(:def main
  unfairCoin)
```

This will scale things so that picking "tails" is a little more likely.

## Interpolation

We can recombine past definitions via string interpolation:

```
%-

(:def adjective
  (:oneof
    (| "beautiful")
    (| "auspicious")
    (| "cold")))

(:def main
  "What a ${adjective}, ${adjective} day!")
```

## Multi-Line Strings

For large blocks of text, we can use multi-line strings.

```
(:def twain
  '''
    Truth is the most valuable thing we have - so let us economize it.
    - Mark Twain
  ''')
```

Multiline strings begin and end with `'''`.

## Expressions

Branches, strings, and interpolations are expressions. A `:def` can attach an expression to a name.

```
%-
```

```
(:def color
  (:oneof
    (| "yellow")
    (| "blue")))

(:def adjective
  (:oneof
    (| "beautiful")
    (| "auspicious")
    (| color)))
```

```
(:def main
  "What a ${adjective}, ${adjective} day!")
```

Branches can contain any expression, including names that have been defined previously (such as `color` in the example above).

## Lambdas

Lambdas are how we introduce functions in Dickinson.

```
(:def sayHello
  (:lambda name text
    "Hello, ${name}."))
```

Note that we have to specify the type of `name` - here, it stands in for some string, so it is of type `text`.

We can use `sayHello` with `$` (pronounced “apply”).

```
(:def name
  (:oneof
    (| "Alice")
    (| "Bob")))

(:def main
  ($ sayHello name))
```

We can `emd` run this:

Hello, Bob.

`$ f x` corresponds to `f x` in ML.

## Matches & Tuples

Suppose we want to randomly pick quotes. First we define a function to return a quote by Fiona Apple:

```
(:def fionaAppleQuote
  (:oneof
    (|
      ""
      "You're more likely to get cut with a dull tool than a sharp one."
      '')
    (|
      ""
      "You forgot the difference between equanimity and passivity."
      '''))))
```

Then we can define `quote`, which returns a quote as well as the person who said it.

```
(:def quote
  (:oneof
    (| ("« Le beau est ce qu'on désire sans vouloir le manger. »", "Simone Weil"))
    (| (fionaAppleQuote, "Fiona Apple"))))
```

Each branch returns a tuple.

We can use the `:match` construct to format the result of `quote`, viz.

```
(:def formatQuote
  (:lambda q (text, text)
    (:match q
      [(quote, name)
        ""
        "${quote}"
        - "${name}"
        '''])))
```

```
(:def main
  $ formatQuote quote)
```

We can `emd` run this:

```
"You forgot the difference between equanimity and passivity."
- Fiona Apple
```

Note the use of the `:lambda` in `formatQuote`; we specify the type `(text, text)`.

## Tags

Tags can be used to split things based on cases.

```
tydecl number = Singular | Plural
```

```
(:def indefiniteArticle
```

```
(:lambda n number
  (:match n
    [Singular "a"]
    [Plural "some"])))
```

Note that we specify the type `number` in `(:lambda n number ...)`.

Tags themselves must begin with a capital letter while types begin with a lowercase letter.

Tags are a restricted form of sum types.

## Types

## REPL

To enter a REPL:

```
emd repl
```

This will show a prompt

```
emd>
```

If we have

```
%-
```

```
(:def gambling
  (:oneof
    (| "heads")
    (| "tails")))
```

in a file `gambling.dck` as above, we can load it with

```
emd> :l gambling.dck
```

We can then evaluate `gambling` if we like

```
emd> gambling
```

or manipulate names that are in scope like so:

```
emd> "The result of the coin toss is: ${gambling}"
```

We can also create new definitions:

```
emd> (:def announcer "RESULT: ${gambling}")
emd> announcer
```

Inspect the type of an expression with `:type`:

```
emd> :type announcer
text
```

We can define types in the REPL:

```
emd> tydecl case = Nominative | Oblique | Possessive
emd> :type Nominative
case
```

## Saving & Restoring States

We can save the REPL state, including any definitions we've declared during the session.

```
emd> :save replSt.emdi
```

If we exit the session we can restore the save definitions with

```
emd> :r replSt.emdi
emd> announcer
```

For reference information about the Dickinson REPL:

```
:help
```

## Builtins

Dickinson has several builtin functions. You can see all names in scope (including builtins) with `:list`, viz.

```
emd> :list
oulipo
allCaps
capitalize
titleCase
```

We can inspect the type like defined names:

```
emd> :type allCaps
(-> text text)
```

Try it out:

```
emd> $ allCaps "Guilt and self-laceration are indulgences"
GUILT AND SELF-LACERATION ARE INDULGENCES
```



## Lints

`emd` has a linter which can make suggestions based on probable mistakes. We can invoke it with `emd lint`:

```
emd lint silly.dck
```

## Libraries

Dickinson allows pulling in definitions from other files with `:include`.

### Using Libraries

#### Example

The `color` module is bundled by default:

```
(:include color)
```

```
%-
```

```
(:def main
  "Today's mood is ${color}")
```

Which gives:

```
Today's mood is citron
```

The `:include` must come before the `%-`; definitions come after the `%-`.

`color.dck` contains:

```
%-
```

```
(:def color
  (:oneof
    (| "aubergine")
    (| "cerulean")
    (| "azure")
    ...
```

### Writing Libraries

Libraries can contain definitions and type declarations.

You can run `emd check` on a library file to validate it.

## Scripting

`emd` ignores any lines starting with `#!`; put

```
#!/usr/bin/env emd
```

and the top of a file to use `emd` as an interpreter. As an example, here is an implementation of the Unix fortune program as a script:

```
#!/usr/bin/env emd
```

```
%-
```

```
(:def adjective
  (:oneof
    (| "good")
    (| "bad")))

(:def main
  "You will have a ${adjective} day")
```

## Examples

### Cowsay

Here is a variation on cowsay:

```
(:def cowsay
  (:lambda txt text
    '''

    ${txt}
    -----
      \      ^__^
       \    (oo)\_____
          (__)\       )\/\
              ||----w |
              ||     ||

    '''))
```

### Noun Declension

We can use tuples and tags to model nouns and noun declension.

```

tydecl case = Nominative | Accusative | Dative | Genitive | Instrumental

tydecl gender = Masculine | Feminine | Neuter

tydecl number = Singular | Plural

; demonstrative pronouns
; "this" or "these"
(:def decline
  (:lambda x (case, gender, number)
    (:match x
      [(Nominative, Masculine, Singular) "pes"]
      [(Accusative, Masculine, Singular) "pisne"]
      [(Genitive, (Masculine|Neuter), Singular) "pisses"]
      [(Dative, (Masculine|Neuter), Singular) "pissum"]
      [(Instrumental, (Masculine|Neuter), Singular) "pys"]
      [((Nominative|Accusative), Neuter, Singular) "pis"]
      [(Nominative, Feminine, Singular) "peos"]
      [(Accusative, Feminine, Singular) "pas"]
      [((Genitive|Dative|Instrumental), Feminine, Singular) "pisse"]
      [((Nominative|Accusative), _, Plural) "pas"]
      [(Genitive, _, Plural) "pissa"]
      [(Dative, _, Plural) "pissum"]
    )))

```

In the REPL:

```

emd> $ decline (Nominative, Feminine, Singular)
peos

```

This actually has no element of randomness but such capabilities are important for agreement in longer generative texts.

For guidance:

```

emd> :type decline
(-> (case, gender, number) text)

```

## Shakespearean Insult Generator

Inspired by the Shakespeare Insult Kit's insult table, we can generate our own insults.

%-

```

(:def adjective
  (:oneof
    (| "artless")
  )

```

```

(| "base-court")
(| "bawdy")
(| "bat-fowling")
...

(:def noun
  (:oneof
    (| "apple-john")
    (| "baggage")
    (| "barnacle")
    (| "bladder")
    ...

(:def main
  ("Thou ${adjective} ${adjective} ${noun}!"))

```

Run it get something like:

Thou beslubbering clouted hedge-pig!

See the full example in `examples/shakespeare.dck`.

## Lyrics Bot

Lyrics bots sample lyrics from some particular artist; see the africa by toto bot for an example.

We can make our own Fiona Apple bot, viz.

```

%-

(:def fiona
  (:oneof
    (| "You forgot the difference between equanimity and passivity.")
    (| "You're more likely to get cut with a dull tool than a sharp one.")
    (| "The child is gone.")
    (|
      ''
      Oh darling, it's so sweet
      You think you know how crazy, how crazy I am.
      ''')
    ...

(:def main
  fiona)

```

See the full example in `examples/fionaBot.dck`