

Dickinson User Guide

Vanessa McHale

Contents

Introduction	1
Installing Dickinson	2
Editor Integration	2
Program Structure	2
Example	2
Comments	2
Definitions & Names	3
Branching	3
Interpolation	3
Multi-Line Strings	4
Expressions	4
Lambdas	5
REPL	5
Saving & Restoring States	5
Lints	6
Libraries	6
Using Libraries	6
Example	6
Writing Libraries	7
Scripting	7
Examples	7

Introduction

Dickinson is a text-generation language for generative literature. Each time you run your code, you get back randomly generated text.

Installing Dickinson

First, install cabal and GHC. Then:

```
cabal install language-dickinson
```

This provides `emd`, the command-line interface to the Dickinson language.

You may also wish to install manpages for reference information about `emd`.
Manpages are installed at

```
emd man
```

Editor Integration

A vim plugin is available.

Program Structure

Dickinson files begin with `%-`, followed by definitions.

Example

Here is a simple Dickinson program:

```
%-
```

```
(:def main
  (:oneof
    (| "heads")
    (| "tails")))
```

Save this as `gambling.dck`. Then:

```
emd run gambling.dck
```

which will display either `heads` or `tails`.

The `:oneof` construct selects one of its branches with equal probability.

In general, when you `emd run` code, you'll see the result of evaluating `main`.

Comments

Comments are indicated with a `;` at the beginning of the line. Anything to the right of the `;` is ignored. So

```
%-

; This returns one of 'heads' or 'tails'
(:def main
  (:oneof
    (| "heads")
    (| "tails")))

```

is perfectly valid code and is functionally the same as the above.

Definitions & Names

We can define names and reference them later:

```
%-

(:def gambling
  (:oneof
    (| "heads")
    (| "tails")))

(:def main
  gambling)

```

We can `emd run` this and it will give the same results as above.

Branching

When you use `:oneof`, Dickinson picks one of the branches with equal probability. If this is not what you want, you can use `:branch`:

```
%-

(:def unfairCoin
  (:branch
    (| 1.0 "heads")
    (| 1.1 "tails")))

(:def main
  unfairCoin)

```

This will scale things so that picking `"tails"` is a little more likely.

Interpolation

We can recombine past definitions via string interpolation:

```
%-

(:def adjective
  (:oneof
    (| "beautiful")
    (| "auspicious")
    (| "cold")))

(:def main
  "What a ${adjective}, ${adjective} day!")
```

Multi-Line Strings

For large blocks of text, we can use multi-line strings.

```
(:def twain
  '''
  Truth is the most valuable thing we have - so let us economize it.
  - Mark Twain
  ''')
```

Multiline strings begin and end with `'''`.

Expressions

Branches, strings, and interpolations are expressions. A `:def` can attach an expression to a name.

```
%-

(:def color
  (:oneof
    (| "yellow")
    (| "blue")))

(:def adjective
  (:oneof
    (| "beautiful")
    (| "auspicious")
    (| color)))

(:def main
  "What a ${adjective}, ${adjective} day!")
```

Branches can contain any expression, including names that have been defined previously (such as `color` in the example above).

Lambdas

Lambdas are how we introduce functions in Dickinson.

REPL

To enter a REPL:

```
emd repl
```

This will show a prompt

```
emd>
```

If we have

```
%-
```

```
(:def gambling
  (:oneof
    (| "heads")
    (| "tails")))

```

in a file `gambling.dck` as above, we can load it with

```
emd> :l gambling.dck
```

We can then evaluate `gambling` if we like

```
emd> gambling
```

or manipulate names that are in scope like so:

```
emd> "The result of the coin toss is: ${gambling}"
```

We can also create new definitions:

```
emd> (:def announcer "RESULT: ${gambling}")
emd> announcer
```

Saving & Restoring States

We can save the REPL state, including any definitions we've declared during the session.

```
emd> :save replSt.emdi
```

If we exit the session we can restore the save definitions with

```
emd> :r replSt.emdi
emd> announcer
```

For reference information about the Dickinson REPL:

```
:help
```

Lints

`emd` has a linter which can make suggestions based on probable mistakes. We can invoke it with `emd lint`:

```
emd lint silly.dck
```

Libraries

Dickinson allows pulling in definitions from other files with `:include`.

Using Libraries

Example

The `color` module is bundled by default:

```
(:include color)
```

```
%-
```

```
(:def main  
  "Today's mood is ${color}")
```

The `:include` must come before the `%-`; definitions come after the `%-` as above.

`color.dck` contains:

```
%-
```

```
(:def color  
  (:oneof  
    (| "aubergine")  
    (| "cerulean")  
    (| "azure")  
    ...
```

Writing Libraries

Scripting

`emd` ignores any lines starting with `#!`; put

```
#!/usr/bin/env emd
```

and the top of a file to use `emd` as an interpreter. As an example, here is an implementation of the Unix fortune program as a script:

```
#!/usr/bin/env emd
```

```
%-
```

```
(:def adjective  
  (:oneof  
    (| "good")  
    (| "bad")))
```

```
(:def main  
  "You will have a ${adjective} day")
```

Examples