

# Dickinson User Guide

Vanessa McHale

## Contents

<b>Introduction</b>	<b>2</b>
<b>Installing Dickinson</b>	<b>2</b>
Editor Integration . . . . .	2
<b>Program Structure</b>	<b>2</b>
Example . . . . .	2
Comments . . . . .	3
Definitions & Names . . . . .	3
Branching . . . . .	3
Interpolation . . . . .	4
Multi-Line Strings . . . . .	4
Expressions . . . . .	4
Lambdas . . . . .	5
<b>REPL</b>	<b>5</b>
Saving & Restoring States . . . . .	6
<b>Lints</b>	<b>6</b>
<b>Libraries</b>	<b>6</b>
Using Libraries . . . . .	6
Example . . . . .	6
Writing Libraries . . . . .	7
<b>Scripting</b>	<b>7</b>
<b>Examples</b>	<b>8</b>
Cowsay . . . . .	8

## Introduction

Dickinson is a text-generation language for generative literature. Each time you run your code, you get back randomly generated text.

## Installing Dickinson

First, install cabal and GHC. Then:

```
cabal install language-dickinson
```

This provides `emd`, the command-line interface to the Dickinson language.

You may also wish to install manpages for reference information about `emd`. Manpages are installed at

```
emd man
```

## Editor Integration

A vim plugin is available.

## Program Structure

Dickinson files begin with `%-`, followed by definitions.

## Example

Here is a simple Dickinson program:

```
%-
```

```
(:def main
  (:oneof
    (| "heads")
    (| "tails")))
```

Save this as `gambling.dck`. Then:

```
emd run gambling.dck
```

which will display either `heads` or `tails`.

The `:oneof` construct selects one of its branches with equal probability.

In general, when you `emd run` code, you'll see the result of evaluating `main`.

## Comments

Comments are indicated with a `;` at the beginning of the line. Anything to the right of the `;` is ignored. So

```
%-  
  
; This returns one of 'heads' or 'tails'  
(:def main  
  (:oneof  
    (| "heads")  
    (| "tails"))))
```

is perfectly valid code and is functionally the same as the above.

## Definitions & Names

We can define names and reference them later:

```
%-  
  
(:def gambling  
  (:oneof  
    (| "heads")  
    (| "tails")))  
  
(:def main  
  gambling)
```

We can `emd` run this and it will give the same results as above.

## Branching

When you use `:oneof`, Dickinson picks one of the branches with equal probability. If this is not what you want, you can use `:branch`:

```
%-  
  
(:def unfairCoin  
  (:branch  
    (| 1.0 "heads")  
    (| 1.1 "tails")))  
  
(:def main  
  unfairCoin)
```

This will scale things so that picking `"tails"` is a little more likely.

## Interpolation

We can recombine past definitions via string interpolation:

```
%-

(:def adjective
  (:oneof
    (| "beautiful")
    (| "auspicious")
    (| "cold")))

(:def main
  "What a ${adjective}, ${adjective} day!")
```

## Multi-Line Strings

For large blocks of text, we can use multi-line strings.

```
(:def twain
  '''
    Truth is the most valuable thing we have - so let us economize it.
    - Mark Twain
  ''')
```

Multiline strings begin and end with `'''`.

## Expressions

Branches, strings, and interpolations are expressions. A `:def` can attach an expression to a name.

```
%-

(:def color
  (:oneof
    (| "yellow")
    (| "blue")))

(:def adjective
  (:oneof
    (| "beautiful")
    (| "auspicious")
    (| color)))

(:def main
```

```
"What a ${adjective}, ${adjective} day!")
```

Branches can contain any expression, including names that have been defined previously (such as `color` in the example above).

## Lambdas

Lambdas are how we introduce functions in Dickinson.

```
(:def sayHello
  (:lambda name text
    "Hello, ${name}."))
```

Note that we have to specify the type of `name` - here, it stands in for some string, so it is of type `text`.

We can use `sayHello` with `$` (pronounced “apply”)

```
(:def name
  (:oneof
    (| "Alice")
    (| "Bob")))

(:def main
  ($ sayHello name))
```

## REPL

To enter a REPL:

```
emd repl
```

This will show a prompt

```
emd>
```

If we have

```
%-
```

```
(:def gambling
  (:oneof
    (| "heads")
    (| "tails")))
```

in a file `gambling.dck` as above, we can load it with

```
emd> :l gambling.dck
```

We can then evaluate `gambling` if we like

```
emd> gambling
```

or manipulate names that are in scope like so:

```
emd> "The result of the coin toss is: ${gambling}"
```

We can also create new definitions:

```
emd> (:def announcer "RESULT: ${gambling}")
```

```
emd> announcer
```

## Saving & Restoring States

We can save the REPL state, including any definitions we've declared during the session.

```
emd> :save replSt.emdi
```

If we exit the session we can restore the save definitions with

```
emd> :r replSt.emdi
```

```
emd> announcer
```

For reference information about the Dickinson REPL:

```
:help
```

## Lints

emd has a linter which can make suggestions based on probable mistakes. We can invoke it with `emd lint`:

```
emd lint silly.dck
```

## Libraries

Dickinson allows pulling in definitions from other files with `:include`.

## Using Libraries

### Example

The `color` module is bundled by default:

```
(:include color)
```

```
%-
```

```
(:def main  
  "Today's mood is ${color}")
```

The `:include` must come before the `%-`; definitions come after the `%-` as above.

`color.dck` contains:

```
%-
```

```
(:def color  
  (:oneof  
    (| "aubergine")  
    (| "cerulean")  
    (| "azure")  
    ...
```

## Writing Libraries

## Scripting

`emd` ignores any lines starting with `#!`; put

```
#!/usr/bin/env emd
```

and the top of a file to use `emd` as an interpreter. As an example, here is an implementation of the Unix fortune program as a script:

```
#!/usr/bin/env emd
```

```
%-
```

```
(:def adjective  
  (:oneof  
    (| "good")  
    (| "bad")))
```

```
(:def main  
  "You will have a ${adjective} day")
```

## Examples

### Cowsay

Here is a variation on cowsay:

```
(:def cowsay
  (:lambda txt text
    '''

    ${txt}
    -----
      \      ^__^
       \      (oo)\_____
          (__) \              )\/\
              ||----w |
              ||     ||

    '''))
```