

# Kempe Compiler & Language Manual

Vanessa McHale

## Contents

<b>Introduction</b>	<b>1</b>
<b>Installing kc</b>	<b>2</b>
Editor Integration . . . . .	2
<b>Kempe Language</b>	<b>2</b>
Types . . . . .	2
Polymorphism . . . . .	2
Literals . . . . .	2
Builtins . . . . .	3
If Blocks . . . . .	4
Sum Types . . . . .	4
Pattern Matching . . . . .	4
Recursion . . . . .	4
Non-Features . . . . .	4
<b>Programming in Kempe</b>	<b>5</b>
Invoking the Compiler . . . . .	5
Internals . . . . .	5
C Calls . . . . .	5
Kempe ABI . . . . .	6
<b>Examples</b>	<b>6</b>
Splitmix Pseudorandom Number Generator . . . . .	6
GCD . . . . .	6

## Introduction

Kempe is a stack-based language, and `kc` is a toy compiler for `x86_64`.

## Installing kc

First, install cabal and GHC. Then:

```
cabal install kempe
```

This provides `kc`, the Kempe compiler.

## Editor Integration

A vim plugin is available.

To install with vim-plug:

```
Plug 'vmchale/kempe' , { 'rtp' : 'vim' }
```

## Kempe Language

### Types

Kempe has a stack-based type system. So if you see a type signature:

```
next : Word -- Word Word
```

that means that the stack must have a `Word` on it for `next` to be invoked, and that it will have two `Words` on the stack after it is invoked.

### Polymorphism

Kempe allows polymorphic functions. So we can define:

```
id : a -- a
  =: [ ]
```

The Kempe typechecker basically works though unification is slow.

### Literals

Integer literals have type `-- Int`.

Positive literals followed by a `u` have type `-- Word`, e.g. `1u`.

Negative integer literals are indicated by an underscore, `_`, i.e. `_1` has type `-- Int`.

## Builtins

The Kempe compiler has a few builtin functions that you can use for arithmetic and for shuffling data around. Many of them are familiar to stack-based programmers:

- `dup : a -- a a`
- `swap : a b -- b a`
- `drop : a --`

For arithmetic:

- `+` : `Int Int -- Int`
- `*` : `Int Int -- Int`
- `-` : `Int Int -- Int`
- `/` : `Int Int -- Int`
- `%` : `Int Int -- Int`
- `>>` : `Int Int8 -- Int`
- `<<` : `Int Int8 -- Int`
- `xori` : `Int Int -- Int`
- `+~` : `Word Word -- Word`
- `*~` : `Word Word -- Word`
- `/~` : `Word Word -- Word`
- `%~` : `Word Word -- Word`
- `>>~` : `Word Int8 -- Word`
- `<<~` : `Word Int8 -- Word`
- `xoru` : `Word Word -- Word`
- `popcount` : `Word -- Int`
- `=` : `Int Int -- Bool`
- `>` : `Int Int -- Bool`
- `<` : `Int Int -- Bool`
- `!=` : `Int Int -- Bool`
- `<=` : `Int Int -- Bool`
- `>=` : `Int Int -- Bool`
- `&` : `Bool Bool -- Bool`
- `||` : `Bool Bool -- Bool`
- `xor` : `Bool Bool -- Bool`
- `~` : `Int -- Int`

There is one higher-order construct, `dip`, which we illustrate by example:

```
nip : a b -- b
     =: [ dip(drop) ]
```

## If Blocks

If-blocks are atoms which contain two blocks of atoms on each arm. If the next item on the stack is `True`, the first will be executed, otherwise the second.

```
loop : Int Int -- Int
      =: [ swap dup 0 =
          if( drop
              , dup 1 - dip(*) swap loop )
          ]

fac_tailrec : Int -- Int
            =: [ 1 loop ]
```

## Sum Types

Kempe supports sum types, for instance:

```
type Either a b { Left a | Right b }
```

## Pattern Matching

Sum types are taken apart with pattern matching, viz.

```
isRight : ((Either a) b) -- Bool
        =: [
          { case
            | Right -> drop True
            | Left  -> drop False
          }
        ]
```

## Recursion

kc optimizes tail recursion.

## Non-Features

Kempe is missing a good many features, such as:

- Modules/imports
- Floats
- Dynamically sized data types
- Strings

- Recursive data types
- Pointers
- Operator overloading

## Programming in Kempe

### Invoking the Compiler

`kc` cannot be used to produce executables. Rather, the Kempe compiler will produce `.o` files which contain functions.

Kempe functions can be exported with a C ABI:

```
fac : Int -- Int
  =: [ dup 0 =
      if( drop 1
        , dup 1 - fac * )
    ]
```

```
%foreign cabi fac
```

This would be called with a C wrapper like so:

```
#include <stdio.h>

extern int fac(int);

int main(int argc, char *argv[]) {
    printf("%d", fac(3));
}
```

Unlike the frontend and type checker, the backend is dodgy.

### Internals

Kempe maintains its own stack and stores the pointer in `rbp`.

Kempe procedures do not require any registers to be preserved across function calls.

### C Calls

When exporting to C, `kc` generates code that initializes the Kempe data pointer (`rbx`). Thus, one should avoid calling into Kempe code too often!

Note that the Kempe data pointer is static, so calling different Kempe functions in different threads will fail unpredictably.

## Kempe ABI

## Examples

### Splitmix Pseudorandom Number Generator

The generator in question comes from a recent paper.

Implementation turns out to be quite nice thanks to Kempe's multiple return values:

```
; given a seed, return a random value and the new seed
next : Word -- Word Word
    =: [ 0x9e3779b97f4a7c15u +~ dup
        dup 30i8 >>~ xoru 0xbf58476d1ce4e5b9u *~
        dup 27i8 >>~ xoru 0x94d049bb133111ebu *~
        dup 31i8 >>~ xoru
      ]
```

```
%foreign kabi next
```

Note that 30i8 is an Int8 literal; shifts take an Int8 as the exponent.

Compare the C implementation:

```
#include <stdint.h>

// modified to have "multiple return" since C doesn't really have that
uint64_t next(uint64_t x, uint64_t* y) {
    uint64_t z = (x += 0x9e3779b97f4a7c15);
    z = (z ^ (z >> 30)) * 0xbf58476d1ce4e5b9;
    z = (z ^ (z >> 27)) * 0x94d049bb133111eb;
    *y = x;
    return z ^ (z >> 31);
}
```

## GCD

```
gcd : Int Int -- Int
    =: [ dup 0 =
        if( drop
            , dup dip(%) swap gcd )
      ]
```