Command Reference > SCPI Command Reference > [SENSe:] Commands > [SENSe:]
CORRection... > [SENSe<Ch>:]CORRection:COLLect:AUTO:CONFigure

[SENSe<Ch>:]CORRection:COLLect:AUTO:CONFigure <CalType>, <Characterization>

Selects a calibration type and a cal unit characterization (cal kit file) for an automatic calibration with "Multiple Port Assignments".

Suffix:

<Ch>	Channel number of the calibrated channel

Parameters:

<CalType>	FNPort | FOPort | OPTPort | FRTRans | FTRans | RTRans | UTRans | REFL | RSHort | PFNPort
	FNPort – full n-port (UOSM) calibration
	FOPort – full one-port ("Refl OSM") calibration
	SFTPort – separate full two-port calibrations
	OPTPort – one path two ports calibration
	PFNPort – full n-port (UOSM) calibration for SMARTerCal
<Characterization>	Location of the characterization (cal kit file) to be used for the automatic calibration (string parameter):
	– The empty string (' ') refers to the factory calibration of (and stored on) the active calibration unit.
	– A VNA cal kit file name `*.calkit` without path refers to a specific cal kit file stored in the internal memory of the active calibration unit.
	– A VNA cal kit file name without path but prefixed with "SD:" refers to a specific cal kit file stored on the SD card inserted at the active calibration unit.
	– A VNA cal kit file name `*.calkit` with path refers to a specific cal kit file stored in an arbitrary directory on the analyzer.

Example: See `[SENSe<Ch>:]CORRection:COLLect:AUTO:`
                      `ASSignment<Asg>:DEFine`.

Manual operation: See "Characterization"

Top