

TECHNICAL DATA SHEET

Date of issue: 01 September 2021
Date of revision: 01 February 2024
Product name: HYDROBLOCK

tERRANOVA

Surface that hold a room together.

DESCRIPTION

HYDROBLOCK is natural, non-toxic and non-synthetic powder.

HYDROBLOCK is European technology using physical principles (not chemical principles).

HYDROBLOCK is powder additive used for mixing with conventional plaster (cement, sand and water) at construction site.

HYDROBLOCK changes conventional plaster into Rain Resistant System or shortly Plaster.

ADVANTAGES OF PLASTER

- Plasticizing effect – excellent workability and minimum waste during application
- Excellent adhesion to the substrate
- Applicable on damp surface
- Contains PP fibers which helps to prevent hairline cracks
- Resistant against penetration of water from heavy rain / monsoon rain
- Does not become wet, remains permanently dry
- Highly breathable – allows moisture to evaporate outside from the wall
- Prevents creation of molds and fungi
- No additional waterproof membrane / paint needed
- If painted, plaster increases lifespan of paint and makes paint more durable / long-lasting

TECHNICAL DATA

PROPERTY / PARAMETER	SPECIFICATION VALUE
Appearance / color	Powder / light grey
Packaging	2 kg sealed bag
Shelf life	Minimum 24 months
Technical parameters	Technical parameters such as compressive strength, adhesive strength etc. of Plaster are comparable to conventional plaster (with same cement + sand ratio, without). does not significantly affect such parameters of plaster.
USAGE	MIXING FORMULA
Exterior wall	Exterior wall: 2kg HYDROBLOCK + 250 kg plaster (250 kg of both cement + sand in 1:4) + water
Interior wall Bathroom (wall and floor) Roof deck	Interior wall, Bathroom (wall and floor), Roof deck: 5kg HYDROBLOCK + 250 kg plaster (250 kg of both cement + sand in 1:4) + water

MIXING

HYDROBLOCK plaster can be mixed manually or in gravity mixer. Water amount depends on humidity of sand and must be adjusted during mixing until correct applicable consistency of plaster is achieved.

SUITABLE SUBSTRATE

Every substrate must be thoroughly wetted before application of HYDROBLOCK Plaster. Plaster is applicable on following substrates:

- 1) Clay (red) brick – wall
- 2) Concrete bricks or concrete hollow blocks – wall
- 3) AAC block or CLC block – wall (in this case, it is recommended to use spritz (kamprot) as first layer to create bridge between HYDROBLOCK substrate and Plaster and apply HYDROBLOCK Plaster when spritz (kamprot) layer is partly hardened)
- 4) Concrete slab – floor (bathroom, roof deck)

It is not recommended to apply HYDROBLOCK Plaster on existing plaster, skim coat, paint or waterproof membrane.

TECHNICAL DATA SHEET: HYDROBLOCK

SUBSTRATE PREPARATION

Substrate must be solid, released from free parts and paintings. It must not be greasy, acid, water-repellent or alcoholic base. Substrate must be suitably wetted with water before application of HYDROBLOCK Plaster.

APPLICATION

HYDROBLOCK Plaster is applied in the same way as conventional plaster. Minimum recommended thickness:

10 mm (exterior wall, bathroom wall), 20 mm (bathroom floor, roof deck). Surface is finished according the requirements using sponge or foam trowel. In case of application on roof deck, it is recommended to use fiberglass mesh (145 g / m², 5 mm x 5 mm) embedded in the surface of fresh HYDROBLOCK Plaster and it is recommended to cover freshly applied HYDROBLOCK Plaster with tarpouline for minimum 7 days.

AFTER APPLICATION

HYDROBLOCK Plaster may remain exposed without additional skim coat, paint or waterproof membrane. If tiles need to be installed on top of HYDROBLOCK Plaster, it is recommended to let HYDROBLOCK Plaster cure for minimum 2 weeks and proceed with installation of tiles. If HYDROBLOCK Plaster need to be painted, it is recommended to let HYDROBLOCK plaster cure for minimum 2 weeks and proceed with painting (or skim coat and painting). Since HYDROBLOCK Plaster remains permanently dry, it increases lifespan of paint and make paint more durable / long-lasting.

CLEANING

Clear water is used for disposal of HYDROBLOCK Plaster from the tools and equipment. Hardened material can be disposed only in mechanical way.

IMPORTANT NOTES

- Do not use HYDROBLOCK as admixture for structural concrete
- Do not use HYDROBLOCK in plaster which is mixed with sea sand
- Do not use HYDROBLOCK with instant products such as instant plaster, instant render, instant skim coat etc.
- Such instant products contain synthetic polymers (RDP) which are not compatible with HYDROBLOCK / may affect functionality of HYDROBLOCK
- Do not use HYDROBLOCK mixed only with cement to smooth the surface of rough plaster

LEGAL NOTICE

The information and, in particular, the recommendations relating to the application and final use of HYDROBLOCK / HYDROBLOCK Plaster are provided in good faith, resulting from the present knowledge and experience with the product when properly stored, handled and used under normal conditions in accordance with the recommendations of manufacturer or distributor. As long as the use and processing of the product is not subject to our direct influence, we are not liable for any damages caused by misuse. We reserve the right to make changes resulting from technical progress.

SAFETY, HEALTH PROTECTION, HYGIENIC RULES AND FIRST AID

The product is safe when used properly. Normal hygiene conditions shall be followed when working with the product. Do not drink, do not eat, do not smoke during work. Use proper working clothes, protective gloves and, if necessary, protective glasses or face protection. If the product is accidentally eaten, do not induce vomiting, seek medical help and show them labeling on the package. If eye contact occurs, wash immediately with plenty of clean water. In the event of an allergic reaction or other difficulties, seek immediate medical help. Follow the usual safety guidelines. Do not mix with unknown substances. Detailed safety and health information and precautions are provided in Safety Data Sheet (SDS).

STORAGE

Store in cold and dry places at temperature from + 5 ° C to + 30 ° C protected against high temperatures and direct sunlight.

MANUFACTURER