

## Overview of logs

- Video: Welcome to week 41 min
- Video: The importance of logs4 min
- Reading: Best practices for log collection and management20 min
- Practice Quiz: Test your knowledge: Overview of logs4 questions
- Video Reference: Learn new tools and technologies2 min
- Video: Variations of logs3 min
- Reading: Overview of log file formats20 min
- Ungraded Plugin: Identify, Match log files to their file format10 min
- Practice Quiz: Test your knowledge: Log components and formats4 questions

## Overview of intrusion detection systems (IDS)

## Overview of security information event management (SIEM)

## Review: Network traffic and logs using IDS and SIEM tools

## Congratulations on completing Course 4!

# Overview of log file formats

You've learned about how logs record events that happen on a network, or system. In security, logs provide key details about activities that occurred across an organization, like who signed into an application at a specific point in time. As a security analyst, you'll use **log analysis**, which is the process of examining logs to identify events of interest. It's important to know how to read and interpret different log formats so that you can uncover the key details surrounding an event and identify unusual or malicious activity. In this reading, you'll review the following log formats:

- JSON
- Syslog
- XML
- CSV
- CEF

## JavaScript Object Notation (JSON)

JavaScript Object Notation (JSON) is a file format that is used to store and transmit data. JSON is known for being lightweight and easy to read and write. It is used for transmitting data in web technologies and is also commonly used in cloud environments. JSON syntax is derived from JavaScript syntax. If you are familiar with JavaScript, you might recognize that JSON contains components from JavaScript including:

- Key-value pairs
- Commas
- Double quotes
- Curly brackets
- Square brackets

## Key-value pairs

A **key-value pair** is a set of data that represents two linked items: a key and its corresponding value. A key-value pair consists of a key followed by a colon, and then followed by a value. An example of a key-value pair is "Alert": "Malware".

**Note:** For readability, it is recommended that key-value pairs contain a space before or after the colon that separates the key and value.

## Commas

Commas are used to separate data. For example: "Alert": "Malware", "Alert code": 1090, "severity": 10.

## Double quotes

Double quotes are used to enclose *text* data, which is also known as a string, for example: "Alert": "Malware". Data that contains numbers is not enclosed in quotes, like this: "Alert code": 1090.

## Curly brackets

Curly brackets enclose an **object**, which is a data type that stores data in a comma-separated list of key-value pairs. Objects are often used to describe multiple properties for a given key. JSON log entries start and end with a curly bracket. In this example, User is the object that contains multiple properties:

```
"User": {
  "id": "1234",
  "name": "sue",
  "role": "engineer"
}
```

## Square brackets

Square brackets are used to enclose an **array**, which is a data type that stores data in a comma-separated ordered list. Arrays are useful when you want to store data as an ordered collection, for example: ["Administrators", "Users", "Engineering"].

## Syslog

Syslog is a standard for logging and transmitting data. It can be used to refer to any of its three different capabilities:

- Protocol:** The syslog protocol is used to transport logs to a centralized log server for log management. It uses port 514 for plaintext logs and port 6514 for encrypted logs.
- Service:** The syslog service acts as a log forwarding service that consolidates logs from multiple sources into a single location. The service works by receiving and then forwarding any syslog log entries to a remote server.
- Log format:** The syslog log format is one of the most commonly used log formats that you will be focusing on. It is the native logging format used in Unix systems. It consists of three components: a header, structured data, and a message.

## Syslog log example

Here is an example of a syslog entry that contains all three components: a header, followed by structured data, and a message:

```
<236>1 2022-03-21T01:11:11.003Z virtual.machine.com eventlog - ID01 [user@32473
 1] "eventSource=Application" eventID=9999"]
This is a log entry!
```

## Header

The header contains details like the timestamp, the hostname, which is the name of the machine that sends the log, the application name, and the message ID.

- Timestamp:** The timestamp in this example is 2022-03-21T01:11:11.003Z, where 2022-03-21 is the date in YYYY-MM-DD format. T is used to separate the date and the time. 01:11:11.003 is the 24-hour format of the time and includes the number of milliseconds 003. Z indicates the timezone, which is Coordinated Universal Time (UTC).
- Hostname:** virtual.machine.com
- Application:** eventlog
- Message ID:** ID01

## Structured data

The structured data portion of the log entry contains additional logging information. This information is enclosed in square brackets and structured in key-value pairs. Here, there are three keys with corresponding values: [user@32473 1] "eventSource=Application" eventID=9999].

## Message

The message contains a detailed log message about the event. Here, the message is This is a log entry!.

## Priority (PRI)

The priority (PRI) field indicates the urgency of the logged event and is contained with angle brackets. In this example, the priority value is <236>. Generally, the lower the priority level, the more urgent the event is.

**Note:** Syslog headers can be combined with JSON and XML formats. Custom log formats also exist.

## XML (eXtensible Markup Language)

XML (eXtensible Markup Language) is a language and a format used for storing and transmitting data. XML is a native file format used in Windows systems. XML syntax uses the following:

- Tags
- Elements
- Attributes

## Tags

XML uses tags to store and identify data. Tags are pairs that must contain a start tag and an end tag. The start tag encloses data with angle brackets, for example <tag>, whereas the end of a tag encloses data with angle brackets and a backslash like this: </tag>.

## Elements

XML elements include both the data contained inside of a tag and the tags itself. All XML entries must contain at least one root element. Root elements contain other elements that sit underneath them, known as child elements.

Here is an example:

```
<Event>
  <EventID>4688</EventID>
  <Version>5</Version>
</Event>
```

In this example, <Event> is the root element and contains two child elements <EventID> and <Version>. There is data contained in each respective child element.

## Attributes

XML elements can also contain attributes. Attributes are used to provide additional information about elements. Attributes are included as the second part of the tag itself and must always be quoted using either single or double quotes.

For example:

```
<EventData>
  <Data Name="SubjectEventId">8-2-3-11-160321</Data>
  <Data Name="SubjectEventName">JMSDB</Data>
  <Data Name="SubjectDomainName">ADCSDB</Data>
  <Data Name="SubjectLogonId">0x1c112</Data>
  <Data Name="NewProcessId">0x1404</Data>
</EventData>
```

In the first line for this example, the tag is <Data> and it uses the attribute Name="SubjectEventId" to describe the data enclosed in the tag 8-2-3-11-160321.

## CSV (Comma Separated Value)

CSV (Comma Separated Value) uses commas to separate data values. In CSV logs, the position of the data corresponds to its field name, but the field names themselves might not be included in the log. It's critical to understand what fields the source device (like an IPS, firewall, scanner, etc.) is including in the log.

Here is an example:

```
2009-11-24T21:27:09.534259,ALERT,192.168.2.7,
1041,x,x,250,50,80,TCP,ALLOWED,1,2001999-9,"BT MALWARE RTGrab.com Spyware Downloading
Ad",1
```

## CEF (Common Event Format)

**Common Event Format (CEF)** is a log format that uses key-value pairs to structure data and identify fields and their corresponding values. The CEF syntax is defined as containing the following fields:

```
CEF:Version|Device|Vendor|Device|Product|Device|Version|Signature
ID|Name|Severity|Extension
```

Fields are all separated with a pipe character |. However, anything in the Extension part of the CEF log entry must be written in a key-value format. Syslog is a common method used to transport logs like CEF. When Syslog is used a timestamp and hostname will be prepended to the CEF message. Here is an example of a CEF log entry that details malicious activity relating to a worm infection:

```
Sep 29 08:26:10 host: CEF:1|Security|threatmanager|1.0|100|worm successfully
stopped|10|src=10.0.0.2|dst=1.2.2.2|app=1232
```

Here is a breakdown of the fields:

- Syslog Timestamp:** Sep 29 08:26:10
- Syslog Hostname:** host
- Version:** CEF:1
- Device Vendor:** Security
- Device Product:** threatmanager
- Device Version:** 1.0
- Signature ID:** 100
- Name:** worm successfully stopped
- Severity:** 10
- Extension:** This field contains data written as key-value pairs. There are two IP addresses, src=10.0.0.2 and dst=1.2.2.2, and a source port number app=1232. Extensions are not required and are optional to add.

This log entry contains details about a security application called threatmanager that successfully stopped a worm from spreading from the internal network at 10.0.0.2 to the external network 2.1.2.2 through the port 1232. A high severity level of 10 is reported.

**Note:** Extensions and syslog prefix are optional to add to a CEF log.

## Key takeaways

There is no standard format used in logging, and many different log formats exist. As a security analyst, you will analyze logs that originate from different sources. Knowing how to interpret different log formats will help you determine key information that you can use to support your investigations.

## Resources for more information

- To learn more about the syslog protocol including priority levels, check out [The Syslog Protocol](#).
- If you would like to explore generating log formats, check out this open-source [log data generator tool](#).
- To learn more about timestamp formats, check out [Date and Time on the Internet: Timestamps](#).

## Mark as completed

Like Dislike Report an issue