

Quiz 9


Name: _____

1. [4 marks] Examine each of the following snippets of code and list the output expected. Write '- error -' if you think the code will crash (i.e. raise an error) during execution. Write '- nothing -' if you think the code will not produce any output.

Code	Output
<pre># Part 1 def test_one(x): print('alpha') return x > 4 def test_two(x): print('beta') return x <= 8 for i in range(4, 6): if test_one(i) and test_two(i): print("apple") elif test_one(i) or test_two(i): print("orange") print('--')</pre>	<p>alpha beta orange -- alpha beta apple --</p>

2. [3 marks] Given that the variables x, y and z are of type int, and ch is of type char. Write a new boolean expression that is the **NEGATION** of each of the following Boolean expressions that is simplified. You need to apply De Morgan's laws to simplify the expression.

	Expression	Negation of Expression
(e.g.)	$x > 1$	Acceptable: $x \leq 1$ Not acceptable: $\text{not } (x > 1)$
(a)	$\text{not } (x < 5) \text{ and } (y \geq 7)$ $x \geq 5 \text{ and } y \geq 7$	$x < 5 \text{ or } y < 7$
(c)	$\text{ch} < '0' \text{ or } \text{ch} > '9'$	$\text{ch} > '0' \text{ and } \text{ch} < '9'$
(d)	$x > 2 \text{ and } y > 3 \text{ or } z > 4$?



3. [3 marks] Implement the `sort_odd_even` function. The function takes in an array of non-negative integers, `numbers` and returns an array consisting of all the even elements of `numbers`, followed by all the odd elements of `numbers`. You **MUST** preserve the order the digit appears in `numbers`.

For example, given the following script:

```
from q2 import sort_odd_even

print("Test 1")
result = sort_odd_even([1, 2, 3, 4, 5])
print("Expected:[2, 4, 1, 3, 5]")
print(f"Actual   :{result}")
print()

print("Test 2")
result = sort_odd_even([9, 7, 7, 4, 5])
print("Expected:[4, 9, 7, 7, 5]")
print(f"Actual   :{result}")
print()

print("Test 3")
result = sort_odd_even([2, 6, 8, 12, 14])
print("Expected:[2, 6, 8, 12, 14]")
print(f"Actual   :{result}")
print()

print("Test 4")
result = sort_odd_even([9, 5, 1])
print("Expected:[9, 5, 1]")
print(f"Actual   :{result}")
print()

print("Test 5")
result = sort_odd_even([1, 2, 3, 4, 5])
print("Expected:<class 'list'> <class 'int'>")
print(f"Actual   :{type(result)} {type(result[0])}")
print()
```

It will generate the following output:

```
Test 1
Expected:[2, 4, 1, 3, 5]
Actual   :[2, 4, 1, 3, 5]

Test 2
Expected:[4, 9, 7, 7, 5]
Actual   :[4, 9, 7, 7, 5]

Test 3
Expected:[2, 6, 8, 12, 14]
Actual   :[2, 6, 8, 12, 14]

Test 4
Expected:[9, 5, 1]
Actual   :[9, 5, 1]

Test 1
Expected:<class 'list'> <class 'int'>
Actual   :<class 'list'> <class 'int'>
```

Answer

```
def sort_odd_even(numbers):
    even=[]
    odd=[]
    for n in numbers:
        if n%.2 == 0:
            even.append(n)
        else:
            odd.append(n)

    final = even + odd
    return final
```

