



INSTITUTE FOR DEFENSE ANALYSES

## **JSM 2023: Comparing Normal and Binary D-Optimal Design of Experiments by Statistical Power**

Rebecca M. Medlin, Project Leader

Addison D. Adams

August 2023

Public release approved. Distribution is  
unlimited.

IDA Document 3000032

INSTITUTE FOR DEFENSE ANALYSES  
730 East Glebe Road  
Alexandria, Virginia 22305



The Institute for Defense Analyses is a nonprofit corporation that operates three Federally Funded Research and Development Centers. Its mission is to answer the most challenging U.S. security and science policy questions with objective analysis, leveraging extraordinary scientific, technical, and analytic expertise.

#### About This Publication

This work was conducted by the Institute for Defense Analyses (IDA) under contract HQ0034-19-D-0001, Task C9082, "Statistics and Data Science Working Group." The views, opinions, and findings should not be construed as representing the official position of either the Department of Defense or the sponsoring organization. CRP Statistics WorkGroup

#### Acknowledgments

The IDA Technical Review Committee was chaired by Dr. V. Bram Lillard and consisted of Dr. Kelly M. Avery, Dr. Keyla Pagan-Rivera, and Dr. Jason P. Sheldon from the Operational Evaluation Division.

#### For more information:

Dr. Rebecca M. Medlin, Project Leader  
rmedlin@ida.org • 703-845-6731

Dr. V. Bram Lillard, Director, Operational Evaluation Division  
vlillard@ida.org • (703) 845-2230

#### Copyright Notice

© 2022 Institute for Defense Analyses  
730 East Glebe Road, Alexandria, Virginia 22305 • (703) 845-2000

This material may be reproduced by or for the U.S. Government pursuant to the copyright license under the clause at DFARS 252.227-7013 [Feb. 2014].

Rigorous Analysis | Trusted Expertise | Service to the Nation

INSTITUTE FOR DEFENSE ANALYSES

IDA Document 3000032

**JSM 2023: Comparing Normal and Binary D-Optimal  
Design of Experiments by Statistical Power**

Rebecca M. Medlin, Project Leader

Addison D. Adams

## Executive Summary

---


In many applications binary response variables are unavoidable. Many have considered D-optimal design of experiments for generalized linear models. However, little consideration has been given to assessing how these new designs perform in terms of statistical power for a given hypothesis test. Monte Carlo simulations and exact power calculations suggest that D-optimal designs generally yield higher power than binary D-optimal designs, despite using logistic regression in the analysis after data have been collected. Results from using statistical power to compare designs contradict traditional design of experiments comparisons, which employ D-efficiency ratios and fractional design space plots. Power calculations suggest that practitioners that are primarily interested in the resulting statistical power of a design should use normal D-optimal designs over binary D-optimal designs when logistic regression is to be used in the data analysis after data collection.



# JSM 2023: Comparing Normal and Binary D-Optimal Designs by Statistical Power

Addison D. Adams

August 2023



**Institute for Defense Analyses**

730 East Glebe Road • Alexandria, Virginia 22305


# Institute for Defense Analyses (IDA)

*We answer challenging questions using scientific, technical, and analytic expertise.*

IDA is a private, nonprofit corporation headquartered in Alexandria, Virginia



IDA operates three Federally Funded Research and Development Centers




CARD – Cost Analysis and Research Division; ITSD – Information Technology and Systems Division; IAD – Intelligence Analyses Division; OED – Operational Evaluation Division; STD – Science and Technology Division; SFRD – Strategy, Forces and Resources Division; SED – System Evaluation Division

# The Test Science Team provides expertise to all warfare areas in OED

We develop, apply, and disseminate statistical, psychological, and data science methodologies


## Core Areas of Expertise



**TestScience**  
Data . Driven . Defense

OED: Operational Evaluation Division; T&E: Test and Evaluation

# Central Question: How should an operational test event be planned when the response of interest is a success or failure?



- Compare two designs
  - Normal D-optimal design
  - Binary D-optimal design: special case of DOE for GLM



## Key findings

- We advocate to compare design by statistical power.
- Standard design comparisons favor a binary design.
- Generally, a normal D-optimal design results in higher statistical power than a binary D-optimal design.

# Experimental design for torpedo hit probabilities

- **D-optimal:** A design which minimizes the generalized variance of the parameter estimates

- **Hypothetical:** An operational test event is to be planned to explore condition effects on torpedo hit probability against an adversary submarine
- **Response:** Did the torpedo hit or miss the target boat?




# Experimental design for torpedo hit probabilities

- Hypothetical Factors:

- 2 categorical
- 1 continuous

- Navy is interested in how the following factors affect the chance of hitting the target

- Location of the target submarine
  - (deep/shallow)
- Target submarine evasion maneuvers
  - (evasive maneuver/no evasive maneuver)
- Target submarine speed
  - (ranges from min. speed to max. speed)



# Experimental design for torpedo hit probabilities

## Analysis Model:


$$y_i \sim \text{Bernoulli}(\pi_i)$$
$$\text{where } \pi_i = \frac{\exp(x_i^T \boldsymbol{\beta})}{1 + \exp(x_i^T \boldsymbol{\beta})}$$

## Hypothesis Test:


$$H_0: \beta_1 = \beta_2 = \beta_3 = 0 \quad \text{vs} \quad H_A: \text{At least one } \beta_i \neq 0 \text{ for } i = 1, 2, 3$$

## Example:

- $\beta_0$  corresponds to a baseline hit probability
  - (deep, evasive, minimum speed)
- $\beta_1$  corresponds to a change in hit probability for a shallow target boat
- $\beta_2$  corresponds to a change in hit probability for a target boat not employing evasive maneuver
- $\beta_3$  corresponds to a change in hit probability as the target boat speed increases




Binary D-optimal design anticipates binary data, whereas the normal D-optimal design does not




	Normal Design	Binary Design
Response Model	$y_i = x_i^T \boldsymbol{\beta} + \epsilon_i$ where $\epsilon_i \sim N(0, \sigma^2)$	$y_i \sim \text{Bernoulli}(\pi_i)$ where $\pi_i = \frac{\exp(x_i^T \boldsymbol{\beta})}{1 + \exp(x_i^T \boldsymbol{\beta})}$
D-Criterion	Maximize the determinant of the information matrix	Maximize the determinant of the information matrix
Information Matrix	$X^T X$	$X^T V_B X$ where $V_B$ depends on $\boldsymbol{\beta}$
Data Collection	Collects binary response variable	Collects binary response variable
Analysis Model	Logistic Regression	Logistic Regression

# The binary D-optimal design is unbalanced

Binary Design



Normal Design




$$\boldsymbol{\beta} = (\beta_0, \beta_1, \beta_2, \beta_3) = (-0.5, 1.61, 1.1, 0.205)$$



# Standard DOE comparisons favor the binary D-optimal design

- Standard DOE comparisons favor the binary design including:
  - D-efficiency: binary D-optimal is 1.064x more efficient than normal D-optimal
- Fraction of Design Space (FDS) plot




## Approximate designs to exact designs

Location	Maneuver	Speed	Normal Design Weight	Binary Design Weight
deep	no evasion	minimum	12.50%	16.42%
deep	no evasion	maximum	12.50%	16.23%
deep	evasion	minimum	12.50%	16.72%
deep	evasion	maximum	12.50%	16.52%
shallow	no evasion	minimum	12.50%	4.40%
shallow	no evasion	maximum	12.50%	0.00%
shallow	evasion	minimum	12.50%	16.12%
shallow	evasion	maximum	12.50%	13.54%

- Approximate designs to exact designs
  - (Pukelsheim, 1993) method
- Statistic used:
  - Likelihood ratio



# Binary design underperforms in power analysis



\* Using likelihood ratio statistic ( $\alpha = 0.05$ )


# Study power over parameter space

## Two continuous factors


- $\eta_i = x_i^T \boldsymbol{\beta}$
- $\boldsymbol{\beta} = (\beta_0, \beta_1, \beta_2)^T$
- $x_i^T = (1, x_1, x_2)$ 
  - Where  $x_1$  and  $x_2$  are continuous variables in  $[-1,1]$
- Fix sample size  $n = 12$
- $\mathcal{B} = \{\boldsymbol{\beta}: \beta_0 \in \{0,1,2\}, \beta_1, \beta_2 \in [-3,3]\}$
- For each  $\boldsymbol{\beta} \in \mathcal{B}$  over a fine grid,
  - A local binary D-optimal design is found at  $\boldsymbol{\beta}$
  - We calculate power for the local binary D-optimal and for the normal design at  $\boldsymbol{\beta}$

**For  $\beta_0 = 0$  the normal D-optimal design results in higher power everywhere**

Binary D-optimal designs




Normal D-optimal design




**For  $\beta_0 = 1$  the normal D-optimal design results in higher power everywhere**

Binary D-optimal designs




Normal D-optimal design




**For  $\beta_0 = 2$  the normal D-optimal design results in higher power nearly everywhere**

Binary D-optimal designs



Normal D-optimal design



There is a small, low-power area where local binary D-optimal designs result in slightly higher power than the normal D-optimal design

# Where the binary D-optimal design outperforms the normal D-optimal design

Three problems where the binary D-optimal design outperforms the normal D-optimal design:

1. The binary D-optimal design outperforms the normal D-optimal design in low-power regions
2. The binary D-optimal design is constructed using the unknown parameter values
3. As sample size increases, the advantage of the binary D-optimal design dissipates

## Fix $\beta$ and increase sample size $n$

Largest increase for binary  
D-opt

- $\beta' = (2, -1.31, 1.31)$
- The binary D-optimal design at  $\beta'$  results in power  $\approx 0.39$  at  $\beta'$
- The normal D-optimal design results in power  $\approx 0.29$  at  $\beta'$
- Take the approx. designs at  $\beta'$  and increase sample size


Binary D-optimal design at  $\beta'$

Factor 1	Factor 2	Design Weights
1	0.75	1/3
0.64	-1	1/6
1	-0.64	1/6
-0.75	-1	1/3

Normal D-optimal design

Factor 1	Factor 2	Design Weights
1	1	1/4
1	-1	1/4
-1	1	1/4
-1	-1	1/4

# The binary D-optimal power advantage disappears with an increasing sample size





# Primary Findings and Discussion

- Normal D-optimal designs generally result in higher power than the binary D-optimal designs
- Standard DOE comparisons favor the binary D-optimal design
- Similar findings with interactions and quadratic terms

\* Performance is measured by power calculations.

DOE: Design of Experiments

# References

- Box, G. E.; Hunter, W. H.; & Hunter, S. (1978). *Statistics for experimenters* (Vol. 664). New York: John Wiley and sons.
- Burke, S. E.; Montgomery, D. C.; Anderson-Cook, C. M.; Silvestrini, R. T.; & Borrer, C. M. (2021). Optimal designs for dual response systems for the normal and binomial case. *Quality and Reliability Engineering International*, 37(7), 3034-3054.
- Firth, D. (1993). Bias reduction of maximum likelihood estimates. *Biometrika*, 80(1), 27-38.
- Hothorn, T., Zeileis, A.; Farebrother, R. W.; Cummins, C.; Millo, G.; Mitchell, D.; & Zeileis, M. A. (2015). Package 'lmtest'. *Testing linear regression models*. <https://cran.r-project.org/web/packages/lmtest/lmtest.pdf>. Accessed, 6.
- Johnson, R. T., & Montgomery, D. C. (2009). Choice of second-order response surface designs for logistic and Poisson regression models. *International Journal of Experimental Design and Process Optimisation*, 1(1), 2-23.
- McCullagh, P., & Nelder, J. A. (2019). *Generalized linear models*. Routledge.
- Morgan-Wall, T., & Khoury, G. (2021). Optimal Design Generation and Power Evaluation in R: The skpr Package. *Journal of Statistical Software*, 99, 1-36.
- Ozol-Godfrey, A.; Anderson-Cook, C.; & Robinson, T. J. (2008). Fraction of design space plots for generalized linear models. *Journal of Statistical Planning and Inference*, 138(1), 203-219.
- Pukelsheim, F. (1993). *Optimal Design of Experiments*. New York: John Wiley & Sons.
- Russell, K. G. (2018). *Design of experiments for generalized linear models*. Chapman and Hall/CRC.
- Zahran, A.; Anderson-Cook, C. M.; & Myers, R. H. (2003). Fraction of design space to assess prediction capability of response surface designs. *Journal of Quality Technology*, 35(4), 377-386.

# How Power Analysis was conducted

- Power analysis is conducted via Monte Carlo simulation using the anticipated parameters
- Null Hypothesis: All non-intercept parameters are zero
  - Alternative Hypothesis: At least one non-intercept parameter is non-zero
- Test Statistic is Likelihood Ratio (R package lmtest)
- Parameter estimation is done using the firth correction
  - R package mbest to modify the glm object

REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p>						
1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE			3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (Include area code)	