```
No.     Time          Source            Destination          Protocol Length Info
    73 9.464303       128.119.245.12    192.168.0.105        HTTP     491    HTTP/1.1 200 OK  (text/html)
Frame 73: 491 bytes on wire (3928 bits), 491 bytes captured (3928 bits) on interface \Device\NPF_{B55B4C7A-E955-4C9F-
B575-97AD6A298347}, id 0
    Interface id: 0 (\Device\NPF_{B55B4C7A-E955-4C9F-B575-97AD6A298347})
        Interface name: \Device\NPF_{B55B4C7A-E955-4C9F-B575-97AD6A298347}
        Interface description: Wi-Fi
    Encapsulation type: Ethernet (1)
    Arrival Time: Jun  8, 2020 17:15:53.021541000 Фінляндія (літо)
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1591625753.021541000 seconds
    [Time delta from previous captured frame: 0.008360000 seconds]
    [Time delta from previous displayed frame: 0.123643000 seconds]
    [Time since reference or first frame: 9.464303000 seconds]
    Frame Number: 73
    Frame Length: 491 bytes (3928 bits)
    Capture Length: 491 bytes (3928 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:tcp:http:data-text-lines]
    [Coloring Rule Name: HTTP]
    [Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: Tp-LinkT_ea:e1:3c (7c:8b:ca:ea:e1:3c), Dst: IntelCor_be:59:29 (00:28:f8:be:59:29)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.105
Transmission Control Protocol, Src Port: 80, Dst Port: 55358, Seq: 1, Ack: 496, Len: 437
Hypertext Transfer Protocol
Line-based text data: text/html (3 lines)
```