

## SLL Question Bank Answers for April 2024

### **MAKE SURE TO DO THIS!!**

**First super user by typing 'su' then enter password as sll731**

#### **1. Configure Apache Web Server.**

**yum install httpd**

y then enter if package not installed

**systemctl start httpd**

**gedit /var/www/html/index.html**

Do some basic html coding:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title> Page Title</title>
```

```
</head>
```

```
<body>
```

```
<h1> This is H1 Heading</h1>
```

```
<p>This is a paragraph</p>
```

```
</body>
```

```
</html>
```

Make sure to save the file.

Then open firefox and type **127.0.0.0:5000** in the address bar.

If that doesn't work, go to terminal and type

**ip a**

and enter the ip you got from the command:

It usually starts with **192.168.100.////**

**2. a) Create a text file. Infer the file permissions.**

```
touch file.txt
```

```
ls -l file.txt
```

**b) Using the Octal mode change the permission on a particular file as rw-rw-r--**

```
chmod 664 file.txt
```

```
ls -l file.txt
```

**c) Using the Symbolic mode change the permission on a particular file as rw-rw-r--**

```
chmod g=0 file.txt
```

```
ls -l file.txt
```

### **3. Configure SSH server.**

Run the following commands on Server and Client.

***(Server is where you will access the files and Client is from where you will connect to the server to access the files)***

#### **Server:**

```
yum install openssh-server  
systemctl start sshd  
systemctl status sshd  
systemctl stop firewalld
```

You can create a file or folder that the client can access in the server using **touch**

Get ip of the server pc by doing **ip a**  
It usually starts with **192.168.100.///**

#### **Client:**

```
ssh sfit@IP  
sll731
```

Now you can run various commands and check the directory with **ls** and **cd**

**4. a) Create a user by assigning the primary group explicitly.**

```
groupadd mygroup  
useradd -g username mygroup
```

If the above doesn't work for you

```
useradd username  
usermod -g groupname username
```

**b) Demonstrate the account status using the password aging settings and infer on the various account status.**

```
passwd -S username
```

**c) Demonstrate locking and unlocking of the user password**

```
passwd -l username  
passwd -u username
```

## **5. Configure NFS server-client.**

Run the following commands on Server and Client.

***(Server is where you will access the files and Client is from where you will connect to the server to access the files)***

```
yum install nfs-utils libnfsidmap
systemctl enable rpcbind nfs-server
systemctl start rpcbind rpc-statd nfs-server nfs-idmapd
systemctl stop firewalld
```

### **Server:**

Create a directory for demonstration:

```
mkdir foldername
chmod a+rwX foldername
ls
```

```
gedit /etc/exports
write following line in file:
/foldername client_ip(rw,sync,no_root_squash)
Save the file
```

```
exportfs -rv
```

### **Client:**

```
mkdir /mnt/directory_name
```

```
mount server_ip:/foldername /mnt/directory_name
```

Make sure to enter the **foldername** same as you created in the server

```
df -h
```

To unmount the directory

```
umount /mnt/directory_name
```

**6. a) Write a shell script to reverse the word order in a list of strings. For example, if the input is Hello World, output should be World Hello.**

**gedit 6a.sh**

```
#!/bin/bash
```

```
read -p "Enter number: " number
```

```
reverse=0
```

```
digit=0
```

```
while [ $number -gt 0 ]; do
```

```
    digit=$(( $number % 10 ))
```

```
    reverse=$(( $reverse * 10 + $digit ))
```

```
    number=$(( $number / 10 ))
```

```
done
```

```
echo "Reversed number: $reverse"
```

**bash 6a.sh**

**b) Write a shell script to convert the user-given temperature in Celsius to Fahrenheit using a bash calculator**

**gedit 6b.sh**

```
#!/bin/bash
```

```
read -p "Enter temperature in Celcius: " celsius
```

```
farheneit=$(echo "scale=2; ($celsius *9/5) + 32" | bc)
```

```
echo "$celsius in Farheneit is $farheneit."
```

**bash 6b.sh**

## ***7. Establish Telnet communication on port 43897.***

Run the following commands on Server and Client.

***(Server is where you will access the files and Client is from where you will connect to the server to access the files)***

```
yum install telnet telnet-server  
systemctl start telnet.socket  
systemctl status telnet.socket  
systemctl stop firewalld
```

On server side edit the following file

```
gedit usr/lib/systemd/system/telnet.socket
```

Change the ListenStream value to number **43897**

Find **IP** with **ip a**

It usually starts with **192.168.100.///**

On client side:

```
telnet IP 43897
```

**8. Perform the following operations using yum package manager and interpret the output of command used: a) List all installed packages**

**yum list installed**

**b) Describe the info of a package**

**yum info package\_name**

**c) Find out which package installed a particular file**

**yum deplist package\_name**



### ***9. Demonstrate fdisk and df commands and interpret it's output***

#### ***FDISK:-***

1. View all Disk Partitions in Linux

**fdisk -l**

2. View Specific Disk Partition in Linux

**fdisk -l /dev/sda**

3. Check all Available fdisk Commands

**fdisk /dev/sda**

#### ***DF:-***

1. Display all the file system

**df -a**

2. Show the file system type

**df -T**

3. Show the disc space usage in a readable format

**df -h**

## **10. Configure Telnet server-client.**

Run the following commands on Server and Client.

***(Server is where you will access the files and Client is from where you will connect to the server to access the files)***

```
yum install telnet telnet-server  
systemctl start telnet.socket  
systemctl status telnet.socket  
systemctl stop firewalld
```

On server side edit the following file

```
gedit usr/lib/systemd/system/telnet.socket
```

Change the ListenStream value to number **4000**

Find **IP** with **ip a**

It usually starts with **192.168.100.///**

On client side:

```
telnet IP 4000
```

**11. a) Write a shell script that consists of a function that displays the number of files in the present working directory. Name this function “file\_count” and call it in your script.**

**gedit 11a.sh**

```
#!/bin/bash
```

```
file_count() {  
    local count=$(ls -1 | wc -l)  
    echo "Number of files in the current directory: $count"  
}
```

```
file_count
```

**bash 11a.sh**

**b) Write a shell script to terminate the script if invoked by non-root user using function and appropriate exit codes.**

**gedit 11b.sh**

```
#!/bin/bash
```

```
check_root() {  
    if [ "$(id -u)" != "0" ]; then  
        echo "Error: This script must be run as root."  
        exit 1  
    fi  
}
```

```
check_root  
echo "Script executed successfully by root user."
```

**bash 11b.sh**

## **12. Write a shell script to check the system status.**

**gedit 12.sh**

```
#!/bin/bash
```

```
machine()
```

```
{  
    echo -e "\e[29;44m***** HOSTNAME INFORMATION *****\e[0m"  
    hostnamectl  
    echo " "  
    echo -e "\e[29;44m***** FILE SYSTEM DISK SPACE USAGE *****\e[0m"  
    df -h  
    echo " "  
    echo -e "\e[29;44m***** FREE & USED MEMORY *****\e[0m"  
    free  
    echo " "  
    echo -e "\e[1;32m***** SYSTEM UPTIME $ LOAD *****\e[0m"  
    uptime  
    echo " "  
    echo -e "\e[29;44m***** CURRENTLY LOGGED-IN USERS *****\e[0m"  
    who  
    echo " "  
    echo -e "\e[29;44m***** TOP 5 MEMORY-CONSUMING PROCESSES *****\e[0m"  
    ps -eo %mem,%cpu,comm --sort=-%mem | head -n 6  
    echo " "  
    echo -e "\e[1;32mDone.\e[0m"  
}
```

```
machine
```

**bash 12.sh**

## **13. Configure FTP server.**

```
yum install vsftpd  
systemctl start vsftpd  
systemctl status vsftpd
```

```
gedit /etc/vsftpd/vsftpd.conf
```

Make following changes in file:

- Change

```
anonymous_enable=YES to anonymous_enable=NO
```

- uncomment

```
ascii_upload_enable=YES & ascii_Ddownload_enable=YES
```

- uncomment

```
Welcome to blah ftp service
```

- add at the end of file

```
use_localtime=YES
```

```
systemctl start vsftpd  
systemctl enable vsftpd  
systemctl stop firewalld
```

To connect to server from client side:

```
yum install ftp
```

Find **IP** with **ip a**

It usually starts with **192.168.100.///**

**ftp IP**

***14. Write a shell script to automate the following a) Adding a user***

## ***b) Changing the group of the user***

### **gedit 14.sh**

```
#!/bin/bash
```

```
add_user() {  
    read -p "Enter username: " username  
    read -p "Enter fullname: " userfullname  
    echo ""  
    read -p "Enter group name: " groupname  
  
    groupadd $groupname  
    useradd -g $groupname -c "$userfullname" $username  
  
    echo "User $username added successfully to group $groupname."  
}
```

```
change_group() {  
    read -p "Enter username: " username  
    read -p "Enter new group name: " new_groupname  
  
    sudo usermod -g $new_groupname $username  
    echo "Group of user $username changed to $new_groupname."  
}
```

```
echo "Select an option:"  
echo "1. Add a user"  
echo "2. Change group of a user"  
read -p "Enter your choice: " choice
```

```
case $choice in  
    1) add_user ;;  
    2) change_group ;;  
    *) echo "Invalid choice. Please select 1 or 2." ;;  
esac
```

### **15. Establish SSH communication on port 41101.**

Run the following commands on Server and Client.

**(Server is where you will access the files and Client is from where you will connect to the server to access the files)**

**Server:**

```
yum install openssh-server  
systemctl start sshd  
systemctl status sshd  
systemctl stop firewalld
```

Create a file or folder that the client can access in the server using **touch**


Get ip of the server pc by doing **ip a**

It usually starts with **192.168.100.///**

To configure port to 41101 type

**gedit /etc/ssh/sshd\_config**

And uncomment the Port and type 41101.



```
# Include drop-in configurations  
Include /etc/ssh/sshd_config.d/*.conf  
  
# This is the sshd server system-wide configuration file. See  
# sshd_config(5) for more information.  
  
# This sshd was compiled with PATH=/usr/local/sbin:/usr/local/bin:/usr/bin  
  
# The strategy used for options in the default sshd_config shipped with  
# OpenSSH is to specify options with their default value where  
# possible, but leave them commented. Uncommented options override the  
# default value.  
  
Port 41101  
#AddressFamily any  
#ListenAddress 0.0.0.0  
#ListenAddress ::
```

uncomment and change from 22 to 41101

**Client:**

```
ssh sfit@IP  
sll731
```

Now you can run various commands and check the directory with **ls** and **cd**

For 41101 port:

```
ssh sfit@IP -p 41101
```

### **16. Write a shell script to automate the following**

- a. Installing a package using yum***
- b. Checking package info using yum***

**gedit 16.sh**

```
#!/bin/bash
```

```
install_package() {  
    read -p "Enter the name of the package to install: " package_name  
    sudo yum install $package_name -y  
    echo "Package $package_name installed successfully."  
}  
  
check_package_info() {  
    read -p "Enter the name of the package to check info: " package_name  
    sudo yum info $package_name  
}  
  
echo "Select an option:"  
echo "1. Install a package using yum"  
echo "2. Check package info using yum"  
read -p "Enter your choice: " choice  
  
case $choice in  
    1) install_package ;;  
    2) check_package_info ;;  
    *) echo "Invalid choice. Please select 1 or 2." ;;  
esac
```

**bash 16.sh**

## ***17. Configure NFS server-client.***



Run the following commands on Server and Client.

*(Server is where you will access the files and Client is from where you will connect to the server to access the files)*

```
yum install nfs-utils libnfsidmap
systemctl enable rpcbind nfs-server
systemctl start rpcbind rpc-statd nfs-server nfs-idmapd
systemctl stop firewalld
```

### Server:

Create a directory for demonstration:

```
mkdir foldername
chmod a+rwX foldername
ls
```

```
gedit /etc/exports
write following line in file:
/foldername client_ip(rw,sync,no_root_squash)
Save the file
```

```
exportfs -rv
```

### Client:

```
mkdir /mnt/directory_name
```

```
mount server_ip:/foldername /mnt/directory_name
```

Make sure to enter the **foldername** same as you created in the server

```
df -h
```

To unmount the directory

```
umount /mnt/directory_name
```

**18. Write a shell script to check if the user is root.**

**gedit 18.sh**

```
#!/bin/bash
```

```
# Check if the user is root
if [ "$(id -u)" = "0" ]; then
    echo "User is root."
else
    echo "User is not root."
fi
```

**bash 18.sh**