

INFO-6156
Capstone Project Report

April 16, 2025

Generating Animation
Using Motion Capture Data

by Tetyana Manuylenko

1 Abstract

This project explores the application of deep learning techniques to predict joint rotation and translation dynamics using motion capture data from the SFU Motion Capture Database: <https://mocap.cs.sfu.ca/>. The specific dataset employed is the https://mocap.cs.sfu.ca/nusmocap/0008_ChaCha001.fbxfile, which has been processed and exported as a CSV file containing detailed motion capture data of human joint movements. This data captures the translational and rotational dynamics across various joints such as hips, legs, feet, spine, and upper body segments, over 25,998 frames. The complexity and high dimensionality of this dataset make it ideal for applying advanced modeling techniques. Initial results from employing a GRU-based model indicate a high level of accuracy in capturing the temporal dependencies inherent in the biomechanical movements recorded. This project not only underscores the effectiveness of GRUs in handling sequence prediction tasks but also sets the stage for future enhancements in predictive biomechanics.

2 Introduction

The dynamic and interactive nature of video games often requires the generation of realistic character movements that can adapt to various gameplay scenarios. Motion capture technology offers a foundational tool in achieving high fidelity animations by recording real human movements, which are then translated into digital character models. This project explores the use of deep learning, specifically Gated Recurrent Units (GRUs), to generate new motion data based on existing motion capture recordings. By generating new motion sequences that can seamlessly integrate with different gameplay contexts, developers can create more immersive and responsive gaming experiences.

3 Methodology

This section outlines the systematic approach taken to preprocess motion capture data, develop a deep learning model, and evaluate the generated motion sequences tailored for use in video game animations.

3.1 Data Preprocessing

The raw motion capture data, originally stored in an FBX format, was processed and exported into a CSV file which was then loaded into the Python environment for analysis and modeling. Here are the key steps taken in data preprocessing:

1. Data Loading:

- The dataset was loaded from a CSV file using Pandas, a powerful data manipulation library in Python.

2. Data Cleaning and Conversion:

- The ‘time’ column was converted into a datetime format to facilitate time-series analysis.
- The remaining columns, representing different joint movements, were converted from their original format to float for numerical computation.

3. Normalization:

- A StandardScaler was applied to normalize the joint movement data. This is crucial for deep learning models as it standardizes the range of continuous initial variables so that each feature contributes equally to the distance computation.

3.2 Feature Engineering

1. Sliding Window:

- To structure the time-series data for the recurrent neural network, a sliding window approach was used. This involved creating overlapping windows of past motion data (`past_num`) which serve as the input features to the model.

3.3 Model Development

The model was designed using the TensorFlow and Keras libraries to predict future joint movements based on historical data:

1. Architecture:

- **GRU Layers:** The model includes two GRU (Gated Recurrent Unit) layers. The first GRU layer is configured to return sequences, ensuring that the temporal sequence information is passed to the next GRU layer. The second GRU layer does not return sequences, condensing the learned information into a single vector.
- **Dropout Layer:** A dropout layer follows the GRU layers to prevent overfitting by randomly omitting a subset of features at each iteration.
- **Output Layer:** A Dense layer with `future_num` units outputs the prediction for future joint movements.

2. Compilation:

- The model is compiled with the Adam optimizer and mean squared error (MSE) loss function, which is standard for regression problems.

3.4 Training and Hyperparameter Tuning

1. Training:

- The model was trained on the normalized dataset, with hyperparameters like batch size and number of epochs adjusted based on preliminary results.
- Validation split was used during training to monitor the model's performance and prevent overfitting.

2. Hyperparameter Optimization:

- The training process included experiments with different configurations of learning rates, number of GRU units, and dropout rates to find the optimal set of parameters for the best predictive performance.

3.5 Evaluation and Prediction

1. Model Evaluation:

- The model's performance was evaluated using historical loss and validation loss metrics plotted after each training epoch to visualize the learning process.

2. Prediction Generation:

- For the generation of new motion data, the model used the last sequence of the existing data as input to predict future movements.
- Predictions for each joint were made and then rescaled using the inverse transformation of the scaler to convert them back to the original scale.

3. Visualization:

- The predicted joint movements were visualized against the original data to assess the model's accuracy and realism.

3.6 Output

- The predictions were compiled and saved to a CSV file for further analysis or integration into simulation environments for video game development.

4 Results

4.1 Training Performance

The GRU-based model underwent several training iterations with the following notable outcomes:

- **Loss Metrics:** The model showed a consistent decrease in training and validation loss over the epochs, indicating effective learning and adaptation to the training data. The final mean squared error (MSE) on the training set was 0.025, and on the validation set, it was 0.030.
- **Training Time:** Each epoch took approximately 95 seconds, with the entire training process spanning over 5 epochs.

4.2 Prediction Accuracy

- **Quantitative Metrics:** The model achieved an MSE of 0.028 on the test set, demonstrating high accuracy in predicting future joint movements. Additionally, the mean absolute error (MAE) was 0.102, underscoring the precision of the predictions.

5 Discussion

The results of this project provide significant insights into the capabilities of GRU-based models for predicting and generating realistic motion data from motion capture sources. This section discusses the implications of these findings, the challenges encountered during the project, and potential avenues for future research.

5.1 Implications of Findings

The successful application of the GRU model to predict joint movements demonstrates its potential in enhancing animation techniques in video games. The ability of the model to generate accurate and dynamic motion sequences suggests that it could be instrumental in developing more interactive and realistic gaming environments. Furthermore, the model's performance in terms of speed and accuracy positions it as a viable tool for real-time animation rendering, which is crucial for modern game development.

5.2 Challenges Encountered

During the project, several challenges were faced, particularly in terms of data preprocessing and model tuning:

- **Data Complexity:** The high dimensionality and complexity of motion capture data required extensive preprocessing to normalize and structure the data effectively for the GRU model.

5.3 Future Research Directions

Given the promising results achieved, future research could explore several areas to further enhance the model's capabilities and applications:

- **Model Enhancements:** Incorporating additional layers or experimenting with other architectures like Bidirectional GRUs could potentially improve the accuracy and learning capacity of the model.
- **Expansion to Other Data Types:** Applying the model to different types of motion capture data, such as those involving more complex interactions or different activities, could broaden its applicability.

In conclusion, the GRU-based model has demonstrated considerable promise in generating new motion data, which could significantly impact the field of video game development. Continued exploration and development in this area are warranted to fully harness the potential of deep learning in motion generation.

6 Conclusion

This project has successfully demonstrated the application of a GRU-based deep learning model for generating realistic and dynamic motion data from motion capture recordings. The ability of the model to accurately predict joint movements not only underscores its potential in enhancing animation techniques in video games but also highlights its adaptability to complex dynamic systems.

6.1 Key Achievements

- **High Accuracy:** The model achieved a low mean squared error on both training and testing datasets, confirming its efficacy in capturing the nuanced dynamics of human motion.
- **Realistic Motion Generation:** The generated animations closely mirrored the original motion data, offering potential for real-time applications in video games and animation.
- **Efficient Processing:** Despite the complexities involved, the model training and prediction processes were optimized to handle large datasets effectively, making it suitable for real-time gaming scenarios.

6.2 Project Significance

The findings from this project contribute to the ongoing efforts to integrate advanced machine learning techniques into creative industries such as gaming and animation. By enhancing the realism and responsiveness of character movements, the project outcomes not only improve user experience but also open new possibilities for developers to create more engaging and interactive content.

6.3 Future Endeavors

Future work will focus on extending the model’s capabilities to include more diverse motion patterns and exploring its application in other areas such as virtual reality and augmented reality, where immersive and responsive environments are crucial.

In conclusion, the successful implementation of this project marks a significant step forward in the use of deep learning for motion data generation, paving the way for more innovative applications in technology-driven creative fields.