-

m

## general

Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Solid models of this enclosure available in STEP or IGES.
Contact Factory mjm@hammondmfg.com

## NOTE

Purchased Assembly includes top and bottom cover, front and end aluminum panels (alloy 5052-H32, SPV coating on one side), 2 cover screws, and 4 nubber feet.

ned on Bosses

8.83

Se	94-VO)	1598GBK	1598GGY	1598RGBK	3 (UL94-HB)	1598GSGY	1598GSGYPBK		1598PLGBK	142172	1591MS100	1591TS100	1598ATS100	
1598G Instrument Case	FLAME RETARDANT ABS (UL94-VO)	Parents with Aluminum Panels	Black Enclosure with Aluminum Panels	Grey Enclosure Wilker Shielded	NON-FLAME RETARDANT GPABS (UL94-HB)	Paris with Aluminum Panels	Grey Enclosure With Black Plastic Panels	Grey Enclosure with Disconsisters	Diack Diactic Panels	Black Flastic English 24)	FOLUTION [M3 - 0.5 x 10mm]	Cover Screws (Trig 160) [ms. For 1598 GPABS   (15.9mm)]	Cover Screws (Frg 100) [#7 x 3/4" (6.4mm)]	DOB SCIENS (PKg 100) 120

X

Ø3.51 X 4

[.138]

1598G

www.hammondmfg.com

lastic d Panels