

Elementary Toposes

Jure Smolar

July 22, 2025

1 Introduction

An *elementary topos* is a Cartesian closed category with finite limits and a subobject classifier. The goal of this project is to formalise this definition in a suitable way. Namely, in `mathlib` Cartesian closed categories are defined via *chosen* finite products, which realise finite products as an algebraic operation in a category; for each finite product diagram we *choose* a specific object to serve as the product, rather than only asking for the existence of such a product. Classically, we can still, using the axiom of choice, get chosen limits from existence.

The first part of the project will be extending this to define finite chosen limits in general – this will allow us to work more naturally in a topos, and keep with the existing definition of Cartesian closedness by getting an instance for chosen finite products from limits.

The second part will be defining a subobject classifier, which we will again see as a chosen subobject classifier – an object of truth values Ω in the category with a monomorphism $\text{true} : 1 \rightarrow \Omega$ and a unique characteristic morphism $\chi_U : X \rightarrow \Omega$ for any monomorphism $U \rightarrow X$.

If time permits, we will also define a chosen natural numbers object, allowing us to also consider NNO-topoi.

After the definition, the goal will be to apply it and give instances for some common examples, like finite sets, `Type`, presheaves, and sheaves.

2 Chosen Finite Limits

The first step is to generalise chosen finite products to general finite limit cones.

Definition 1 (Chosen Limit). Let $F : J \rightarrow C$ be a functor. A *chosen limit* for F is a specified limit cone for F .

3 Subobject Classifiers

test

- 4 Elementary Toposes
- 5 Natural Numbers Objects (Optional)
- 6 Examples
 - 6.1 Finite Sets
 - 6.2 The Category of Types
 - 6.3 Presheaves
 - 6.4 Sheaves
- 7 Further Developments