F2802x0 Peripheral Driver Library

USER'S GUIDE

Copyright

Texas Instruments
13905 University Boulevard
Sugar Land, TX 77479
http://www.ti.com/c2000

Revision Information

This is version 3.06.00.00 of this document, last updated on Tue Oct 29 00:37:27 IST 2024.

Table of Contents

1   Introduction

The Texas Instruments® C2000Ware® Peripheral Driver Library is a set of drivers for accessing the peripherals found on the Piccolo Entryline family of C2000 microcontrollers. While they are not drivers in the pure operating system sense (that is, they do not have a common interface and do not connect into a global device driver infrastructure), they do provide a mechanism that makes it easy to use the device's peripherals.

The capabilities and organization of the drivers are governed by the following design goals:

They are written entirely in C except where absolutely not possible.

They demonstrate how to use the peripheral in its common mode of operation.

They are easy to understand.

They are reasonably efficient in terms of memory and processor usage.

They are as self-contained as possible.

Where possible, computations that can be performed at compile time are done there instead of at run time.

Some consequences of these design goals are:

The drivers are not necessarily as efficient as they could be (from a code size and/or execution speed point of view). While the most efficient piece of code for operating a peripheral would be written in assembly and custom tailored to the specific requirements of the application, further size optimizations of the drivers would make them more difficult to understand.

The drivers do not support the full capabilities of the hardware. Some of the peripherals provide complex capabilities which cannot be utilized by the drivers in this library, though the existing code can be used as a reference upon which to add support for the additional capabilities.

For many applications, the drivers can be used as is. But in some cases, the drivers will have to be enhanced or rewritten in order to meet the functionality, memory, or processing requirements of the application. If so, the existing driver can be used as a reference on how to operate the peripheral.

This device support release also contains the traditional peripheral register header files and associated software. Please see chapter 2 of this guide for more information on this software. For future development we recommend the use of this driver infrastructure instead of the traditional header files.

Source Code Overview

The following is an overview of the organization of the peripheral driver library source code.

`common/source/` This directory contains the source code for the drivers.

`common/include/` This directory contains the header files for the drivers. These headers define not only values used in the drivers and calls to drivers but also define the register structure of each peripheral.

`common/ccs/`   This directory contains the CCS project for the driver library. The driver library can be rebuilt if modifications are made by importing and building this project.

2   Programming Model

The peripheral driver library provides support for two programming models: the direct register access model and the software driver model. Each model can be used independently or combined, based on the needs of the application or the programming environment desired by the developer.

Each programming model has advantages and disadvantages. Use of the direct register access model generally results in smaller and more efficient code than using the software driver model. However, the direct register access model requires detailed knowledge of the operation of each register and bit field, as well as their interactions and any sequencing required for proper operation of the peripheral; the developer is insulated from these details by the software driver model, generally requiring less time to develop applications. In the direct register access model, the peripherals are programmed by the application by writing values directly into the peripheral's registers. Every register is defined in a peripherals corresponding header file contained in `f2802x0/headers/include`. These headers define the locations of each register relative to the other registers in a peripheral as well as the bit fields within each register. All of this is implemented using structures. The header files only define these structure; they do not declare them. To declare the structures a C source file must be included in each project `f2802x0/headers/source/F2802x0_GlobalVariableDefs.c`. This file declares each structure (and in some cases multiple instances when there are multiple instances of a peripheral) as well as declaring and associating each structure with a code section for the linker. The final piece of the puzzle is a special linker command file that associates each section defined in `F2802x0_GlobalVariableDefs.c` with the physical memory of the device. There are two version of this linker command file, one for use with SYS/BIOS and one for use without, but both can be found in `f2802x0/headers/cmd`. One of this linker command files as well as your normal application linker command file should be used to link your project.

Applications that wish to use the direct register access model should define the root of the f2802x0 directory to be an include path and include the file `DSP28x_Project.h` in each source file where register accesses are made.

In practice accessing peripheral registers and bitfields is extremely easy. Below are a few examples: GpioCtrlRegs.GPAPUD.bit.GPIO0 = 0; GpioCtrlRegs.GPAMUX1.bit.GPIO0 = 1;

In the software driver model, the API provided by the peripheral driver library is used by applications to control the peripherals. Because these drivers provide complete control of the peripherals in their normal mode of operation, it is possible to write an entire application without direct access to the hardware. This method provides for rapid development of the application without requiring detailed knowledge of how to program the peripherals.

Before a driver for a peripheral can be used that peripherals driver header file should be included and a handle to that peripheral initialized: $GPIO_H andlemyGpio; myGpio = GPIO_init((void*)GPIO_BASE_ADDR, sizeof(GPIO_Obj));$

In subsequent calls to that peripheral's driver the initialized handle as well as any parameters are passed to the function: $GPIO_setPullUp(myGpio, GPIO_Number_0, GPIO_PullUp_Enable); GPIO_setMode(myGpio, GPIO_Number_0, GPIO$

As you can see from the above sample, using the driver library makes one's code substantially more readable.

In addition to including the appropriate header files for the drivers you are using, the project

should also have driverlib.lib linked into it. A CCS project as well as the lib file can be found in `f2802x0/common/ccs`. The driver library also contains some basic helper functions that many projects will use as well as the direct register access model source file `F2802x0_GlobalVariableDefs.c` which allows you to use the header files without having to directly compile this source file into your project.

The drivers in the peripheral driver library are described in the remaining chapters in this document. They combine to form the software driver model. The direct register access model and software driver model can be used together in a single application, allowing the most appropriate model to be applied as needed to any particular situation within the application. For example, the software driver model can be used to configure the peripherals (because this is not performance critical) and the direct register access model can be used for operation of the peripheral (which may be more performance critical). Or, the software driver model can be used for peripherals that are not performance critical (such as a UART used for data logging) and the direct register access model for performance critical peripherals.

To use both models interchangeably in your application:

Link `driverlib.lib` into your application

Include `DSP28x_Project.h` in files you wish to use the direct register access model

Add `C2000Ware_version/device_support/f2802x0/` to your projects include path (Right click on project, Build Properties, Include Path)

Include driver header files from `f2802x0/common/include` in any source file that makes calls to that driver.

3   Analog to Digital Converter (ADC)

The Analog to Digital Converter (ADC) APIs provide a set of functions for accessing the Piccolo F2802x0 ADC modules.

This driver is contained in `f2802x0/common/source/adc.c`, with `f2802x0/common/include/adc.h` containing the API definitions for use by applications.

3.1   ADC

Data Structures

_ADC_Obj_

Macros

ADC_ADCCTL1_ADCBGPWD_BITS

ADC_ADCCTL1_ADCBSY_BITS

ADC_ADCCTL1_ADCBSYCHAN_BITS

ADC_ADCCTL1_ADCENABLE_BITS

ADC_ADCCTL1_ADCPWDN_BITS

ADC_ADCCTL1_ADCREFPWD_BITS

ADC_ADCCTL1_ADCREFSEL_BITS

ADC_ADCCTL1_INTPULSEPOS_BITS

ADC_ADCCTL1_RESET_BITS

ADC_ADCCTL1_TEMPCONV_BITS

ADC_ADCCTL1_VREFLOCONV_BITS

ADC_ADCSAMPLEMODE_SEPARATE_FLAG

ADC_ADCSAMPLEMODE_SIMULEN0_BITS

ADC_ADCSAMPLEMODE_SIMULEN10_BITS

ADC_ADCSAMPLEMODE_SIMULEN12_BITS

ADC_ADCSAMPLEMODE_SIMULEN14_BITS

ADC_ADCSAMPLEMODE_SIMULEN2_BITS

ADC_ADCSAMPLEMODE_SIMULEN4_BITS

ADC_ADCSAMPLEMODE_SIMULEN6_BITS

ADC_ADCSAMPLEMODE_SIMULEN8_BITS

ADC_ADCSOCxCTL_ACQPS_BITS

ADC_ADCSOCxCTL_CHSEL_BITS

ADC_ADCSOCxCTL_TRIGSEL_BITS

ADC_BASE_ADDR

ADC_dataBias

ADC_DELAY_usec

ADC_INTSELxNy_INTCONT_BITS

ADC_INTSELxNy_INTE_BITS

ADC_INTSELxNy_INTSEL_BITS

ADC_INTSELxNy_LOG2_NUMBITS_PER_REG

ADC_INTSELxNy_NUMBITS_PER_REG

Enumerations

ADC_IntMode_e

ADC_IntNumber_e

ADC_IntPulseGenMode_e

ADC_IntSrc_e

ADC_ResultNumber_e

ADC_SampleMode_e

ADC_SocChanNumber_e

ADC_SocNumber_e

ADC_SocSampleWindow_e

ADC_SocTrigSrc_e

ADC_VoltageRefSrc_e

Functions

void ADC_clearIntFlag (ADC_Handle adcHandle, const ADC_IntNumber_e intNumber)

void ADC_disable (ADC_Handle adcHandle)

void ADC_disableBandGap (ADC_Handle adcHandle)

void ADC_disableInt (ADC_Handle adcHandle, const ADC_IntNumber_e intNumber)

void ADC_disableRefBuffers (ADC_Handle adcHandle)

void ADC_disableTempSensor (ADC_Handle adcHandle)

void ADC_enable (ADC_Handle adcHandle)

void ADC_enableBandGap (ADC_Handle adcHandle)

void ADC_enableInt (ADC_Handle adcHandle, const ADC_IntNumber_e intNumber)

void ADC_enableRefBuffers (ADC_Handle adcHandle)

void ADC_enableTempSensor (ADC_Handle adcHandle)

void ADC_forceConversion (ADC_Handle adcHandle, const ADC_SocNumber_e socNumber)

bool_t ADC_getIntStatus (ADC_Handle adcHandle, const ADC_IntNumber_e intNumber)

ADC_SocSampleWindow_e ADC_getSocSampleWindow (ADC_Handle adcHandle, const ADC_SocNumber_e socNumber)

int16_t ADC_getTemperatureC (ADC_Handle adcHandle, int16_t sensorSample)

int16_t ADC_getTemperatureK (ADC_Handle adcHandle, int16_t sensorSample)

ADC_Handle ADC_init (void ∗pMemory, const size_t numBytes)

void ADC_powerDown (ADC_Handle adcHandle)

void ADC_powerUp (ADC_Handle adcHandle)

uint_least16_t ADC_readResult (ADC_Handle adcHandle, const ADC_ResultNumber_e result-Number)

void ADC_reset (ADC_Handle adcHandle)

void ADC_setIntMode (ADC_Handle adcHandle, const ADC_IntNumber_e intNumber, const ADC_IntMode_e intMode)

void ADC_setIntPulseGenMode (ADC_Handle adcHandle, const ADC_IntPulseGenMode_e pulse-Mode)

void ADC_setIntSrc (ADC_Handle adcHandle, const ADC_IntNumber_e intNumber, const ADC_IntSrc_e intSrc)

void ADC_setSampleMode (ADC_Handle adcHandle, const ADC_SampleMode_e sampleMode)

void ADC_setSocChanNumber (ADC_Handle adcHandle, const ADC_SocNumber_e socNumber, const ADC_SocChanNumber_e chanNumber)

void ADC_setSocSampleWindow (ADC_Handle adcHandle, const ADC_SocNumber_e socNumber, const ADC_SocSampleWindow_e sampleWindow)

void ADC_setSocTrigSrc (ADC_Handle adcHandle, const ADC_SocNumber_e socNumber, const ADC_SocTrigSrc_e trigSrc)

void ADC_setVoltRefSrc (ADC_Handle adcHandle, const ADC_VoltageRefSrc_e voltRef)

3.1.1 Detailed Description

3.1.2 Data Structure Documentation

3.1.2.1 _ADC_Obj_

Definition:

```
typedef struct
{
    uint16_t ADCRESULT[16];
    uint16_t rsvd_1[26096];
    uint16_t ADCCTL1;
    uint16_t rsvd_2[3];
    uint16_t ADCINTFLG;
    uint16_t ADCINTFLGCLR;
    uint16_t ADCINTOVF;
    uint16_t ADCINTOVFCLR;
    uint16_t INTSELxNy[5];
    uint16_t rsvd_3[3];
    uint16_t SOCPRICTRL;
    uint16_t rsvd_4;
    uint16_t ADCSAMPLEMODE;
    uint16_t rsvd_5;
    uint16_t ADCINTSOCSEL1;
    uint16_t ADCINTSOCSEL2;
    uint16_t rsvd_6[2];
    uint16_t ADCSOCFLG1;
    uint16_t rsvd_7;
    uint16_t ADCSOCFRC1;
    uint16_t rsvd_8;
    uint16_t ADCSOCOVF1;
    uint16_t rsvd_9;
    uint16_t ADCSOCOVFCLR1;
    uint16_t rsvd_10;
    uint16_t ADCSOCxCTL[16];
    uint16_t rsvd_11[16];
    uint16_t ADCREFTRIM;
    uint16_t ADCOFFTRIM;
    uint16_t rsvd_12[13];
    uint16_t ADCREV;
```

```
}
_ADC_Obj_
```

Members:

 ADCRESULT ADC result registers.

 rsvd_1 Reserved.

 ADCCTL1 ADC Control Register 1.

 rsvd_2 Reserved.

 ADCINTFLG ADC Interrupt Flag Register.

 ADCINTFLGCLR ADC Interrupt Flag Clear Register.

 ADCINTOVF ADC Interrupt Overflow Register.

 ADCINTOVFCLR ADC Interrupt Overflow Clear Register.

 INTSELxNy ADC Interrupt Select x and y Register.

 rsvd_3 Reserved.

 SOCPRICTRL ADC Start Of Conversion Priority Control Register.

 rsvd_4 Reserved.

 ADCSAMPLEMODE ADC Sample Mode Register.

 rsvd_5 Reserved.

 ADCINTSOCSEL1 ADC Interrupt Trigger SOC Select 1 Register.

 ADCINTSOCSEL2 ADC Interrupt Trigger SOC Select 2 Register.

 rsvd_6 Reserved.

 ADCSOCFLG1 ADC SOC Flag 1 Register.

 rsvd_7 Reserved.

 ADCSOCFRC1 ADC SOC Force 1 Register.

 rsvd_8 Reserved.

 ADCSOCOVF1 ADC SOC Overflow 1 Register.

 rsvd_9 Reserved.

 ADCSOCOVFCLR1 ADC SOC Overflow Clear 1 Register.

 rsvd_10 Reserved.

 ADCSOCxCTL ADC SOCx Control Registers.

 rsvd_11 Reserved.

 ADCREFTRIM ADC Reference/Gain Trim Register.

 ADCOFFTRIM ADC Offset Trim Register.

 rsvd_12 Reserved.

 ADCREV ADC Revision Register.

Description:

 Defines the analog-to-digital converter (ADC) object.

4 Capture (CAP)

The Enhanced Capture (CAP) API provides a set of functions and data structs for configuring and capturing data as well as generating PWMs with the capture peripheral.

This driver is contained in `f2802x0/common/source/cap.c`, with `f2802x0/common/include/cap.h` containing the API definitions and data structs for use by applications.

4.1 CAP

Data Structures

struct _CAP_Obj_

Macros

#define CAP_ECCTL1_CAP1POL_BITS

#define CAP_ECCTL1_CAP2POL_BITS

#define CAP_ECCTL1_CAP3POL_BITS

#define CAP_ECCTL1_CAP4POL_BITS

#define CAP_ECCTL1_CAPLDEN_BITS

#define CAP_ECCTL1_CTRRST1_BITS

#define CAP_ECCTL1_CTRRST2_BITS

#define CAP_ECCTL1_CTRRST3_BITS

#define CAP_ECCTL1_CTRRST4_BITS

#define CAP_ECCTL1_FREESOFT_BITS

#define CAP_ECCTL1_PRESCALE_BITS

#define CAP_ECCTL2_APWMPOL_BITS

#define CAP_ECCTL2_CAPAPWM_BITS

#define CAP_ECCTL2_CONTONESHOT_BITS

#define CAP_ECCTL2_REARM_BITS

#define CAP_ECCTL2_STOP_WRAP_BITS

#define CAP_ECCTL2_SWSYNC_BITS

#define CAP_ECCTL2_SYNCIEN_BITS

#define CAP_ECCTL2_SYNCOSEL_BITS

#define CAP_ECCTL2_TSCTRSTOP_BITS

#define CAP_ECCxxx_CEVT1_BITS

#define CAP_ECCxxx_CEVT2_BITS

#define CAP_ECCxxx_CEVT3_BITS

#define CAP_ECCxxx_CEVT4_BITS

#define CAP_ECCxxx_CTRCOMP_BITS

#define CAP_ECCxxx_CTROVF_BITS

#define CAP_ECCxxx_CTRPRD_BITS

#define CAP_ECCxxx_INT_BITS

#define CAPA_BASE_ADDR

Typedefs

typedef struct _CAP_Obj_ ∗ CAP_Handle

typedef struct _CAP_Obj_ CAP_Obj

Enumerations

enum CAP_Event_e { CAP_Event_1, CAP_Event_2, CAP_Event_3, CAP_Event_4 }

enum CAP_Int_Type_e {
CAP_Int_Type_CTR_CMP, CAP_Int_Type_CTR_PRD, CAP_Int_Type_CTR_OVF,
CAP_Int_Type_CEVT4,
CAP_Int_Type_CEVT3, CAP_Int_Type_CEVT2, CAP_Int_Type_CEVT1, CAP_Int_Type_Global,
CAP_Int_Type_All }

enum CAP_Polarity_e { CAP_Polarity_Rising, CAP_Polarity_Falling }

enum CAP_Prescale_e {
CAP_Prescale_By_1, CAP_Prescale_By_2, CAP_Prescale_By_4, CAP_Prescale_By_6,
CAP_Prescale_By_8, CAP_Prescale_By_10, CAP_Prescale_By_12, CAP_Prescale_By_14,
CAP_Prescale_By_16, CAP_Prescale_By_18, CAP_Prescale_By_20, CAP_Prescale_By_22,
CAP_Prescale_By_24, CAP_Prescale_By_26, CAP_Prescale_By_28, CAP_Prescale_By_30,
CAP_Prescale_By_32, CAP_Prescale_By_34, CAP_Prescale_By_36, CAP_Prescale_By_38,
CAP_Prescale_By_40, CAP_Prescale_By_42, CAP_Prescale_By_44, CAP_Prescale_By_46,
CAP_Prescale_By_48, CAP_Prescale_By_50, CAP_Prescale_By_52, CAP_Prescale_By_54,
CAP_Prescale_By_56, CAP_Prescale_By_58, CAP_Prescale_By_60, CAP_Prescale_By_62 }

enum CAP_Reset_e { CAP_Reset_Disable, CAP_Reset_Enable }

enum CAP_RunMode_e

enum CAP_Stop_Wrap_e { CAP_Stop_Wrap_CEVT1, CAP_Stop_Wrap_CEVT2, CAP_Stop_Wrap_CEVT3, CAP_Stop_Wrap_CEVT4 }

enum CAP_SyncOut_e { CAP_SyncOut_SyncIn, CAP_SyncOut_CTRPRD, CAP_SyncOut_Disable }

Functions

void CAP_clearInt (CAP_Handle capHandle, const CAP_Int_Type_e intType)

void CAP_disableCaptureLoad (CAP_Handle capHandle)

void CAP_disableInt (CAP_Handle capHandle, const CAP_Int_Type_e intType)

void CAP_disableSyncIn (CAP_Handle capHandle)

void CAP_disableTimestampCounter (CAP_Handle capHandle)

void CAP_enableCaptureLoad (CAP_Handle capHandle)

void CAP_enableInt (CAP_Handle capHandle, const CAP_Int_Type_e intType)

void CAP_enableSyncIn (CAP_Handle capHandle)

void CAP_enableTimestampCounter (CAP_Handle capHandle)

uint32_t CAP_getCap1 (CAP_Handle capHandle)

uint32_t CAP_getCap2 (CAP_Handle capHandle)

uint32_t CAP_getCap3 (CAP_Handle capHandle)

uint32_t CAP_getCap4 (CAP_Handle capHandle)

CAP_Handle CAP_init (void ∗pMemory, const size_t numBytes)

void CAP_rearm (CAP_Handle capHandle)

void CAP_setApwmCompare (CAP_Handle capHandle, const uint32_t compare)

void CAP_setApwmPeriod (CAP_Handle capHandle, const uint32_t period)

void CAP_setApwmShadowPeriod (CAP_Handle capHandle, const uint32_t shadowPeriod)

void CAP_setCapContinuous (CAP_Handle capHandle)

void CAP_setCapEvtPolarity (CAP_Handle capHandle, const CAP_Event_e event, const CAP_Polarity_e polarity)

void CAP_setCapEvtReset (CAP_Handle capHandle, const CAP_Event_e event, const CAP_Reset_e reset)

void CAP_setCapOneShot (CAP_Handle capHandle)

void CAP_setModeApwm (CAP_Handle capHandle)

void CAP_setModeCap (CAP_Handle capHandle)

void CAP_setStopWrap (CAP_Handle capHandle, const CAP_Stop_Wrap_e stopWrap)

void CAP_setSyncOut (CAP_Handle capHandle, const CAP_SyncOut_e syncOut)

4.1.1 Detailed Description

4.1.2 Enumeration Type Documentation

4.1.2.1 enum **CAP_Event_e**

Enumeration to define the capture (CAP) events.

Enumerator
>   ***CAP_Event_1*** Capture Event 1.
>   ***CAP_Event_2*** Capture Event 2.
>   ***CAP_Event_3*** Capture Event 3.
>   ***CAP_Event_4*** Capture Event 4.

4.1.2.2 enum **CAP_Int_Type_e**

Enumeration to define the capture (CAP) interrupts.

Enumerator
>   ***CAP_Int_Type_CTR_CMP*** Denotes CTR = CMP interrupt.
>   ***CAP_Int_Type_CTR_PRD*** Denotes CTR = PRD interrupt.
>   ***CAP_Int_Type_CTR_OVF*** Denotes CTROVF interrupt.
>   ***CAP_Int_Type_CEVT4*** Denotes CEVT4 interrupt.
>   ***CAP_Int_Type_CEVT3*** Denotes CEVT3 interrupt.
>   ***CAP_Int_Type_CEVT2*** Denotes CEVT2 interrupt.
>   ***CAP_Int_Type_CEVT1*** Denotes CEVT1 interrupt.
>   ***CAP_Int_Type_Global*** Denotes Capture global interrupt.
>   ***CAP_Int_Type_All*** Denotes All interrupts.

4.1.2.3 enum **CAP_Polarity_e**

Enumeration to define the capture (CAP) event polarities.

Enumerator
>   ***CAP_Polarity_Rising*** Rising Edge Triggered.
>   ***CAP_Polarity_Falling*** Falling Edge Triggered.

4.1.2.4 enum **CAP_Prescale_e**

Enumeration to define the capture (CAP) prescaler values.

Enumerator

CAP_Prescale_By_1	Divide by 1.
CAP_Prescale_By_2	Divide by 2.
CAP_Prescale_By_4	Divide by 4.
CAP_Prescale_By_6	Divide by 6.
CAP_Prescale_By_8	Divide by 8.
CAP_Prescale_By_10	Divide by 10.
CAP_Prescale_By_12	Divide by 12.
CAP_Prescale_By_14	Divide by 14.
CAP_Prescale_By_16	Divide by 16.
CAP_Prescale_By_18	Divide by 18.
CAP_Prescale_By_20	Divide by 20.
CAP_Prescale_By_22	Divide by 22.
CAP_Prescale_By_24	Divide by 24.
CAP_Prescale_By_26	Divide by 26.
CAP_Prescale_By_28	Divide by 28.
CAP_Prescale_By_30	Divide by 30.
CAP_Prescale_By_32	Divide by 32.
CAP_Prescale_By_34	Divide by 34.
CAP_Prescale_By_36	Divide by 36.
CAP_Prescale_By_38	Divide by 38.
CAP_Prescale_By_40	Divide by 40.
CAP_Prescale_By_42	Divide by 42.
CAP_Prescale_By_44	Divide by 44.
CAP_Prescale_By_46	Divide by 46.
CAP_Prescale_By_48	Divide by 48.
CAP_Prescale_By_50	Divide by 50.
CAP_Prescale_By_52	Divide by 52.
CAP_Prescale_By_54	Divide by 54.
CAP_Prescale_By_56	Divide by 56.
CAP_Prescale_By_58	Divide by 58.
CAP_Prescale_By_60	Divide by 60.
CAP_Prescale_By_62	Divide by 62.

4.1.2.5 enum **CAP_Reset_e**

Enumeration to define the capture (CAP) event resets.

Enumerator

CAP_Reset_Disable	Disable counter reset on capture event.
CAP_Reset_Enable	Enable counter reset on capture event.

4.1.2.6 enum **CAP_Stop_Wrap_e**

Enumeration to define the capture (CAP) Stop/Wrap modes.

Enumerator

CAP_Stop_Wrap_CEVT1	Stop/Wrap after Capture Event 1.
CAP_Stop_Wrap_CEVT2	Stop/Wrap after Capture Event 2.
CAP_Stop_Wrap_CEVT3	Stop/Wrap after Capture Event 3.
CAP_Stop_Wrap_CEVT4	Stop/Wrap after Capture Event 4.

4.1.2.7 enum **CAP_SyncOut_e**

Enumeration to define the Sync Out options.

Enumerator

CAP_SyncOut_SyncIn	Sync In used for Sync Out.
CAP_SyncOut_CTRPRD	CTR = PRD used for Sync Out.
CAP_SyncOut_Disable	Disables Sync Out.

4.1.3 Function Documentation

4.1.3.1 void CAP_clearInt (

CAP_Handle capHandle,

const **CAP_Int_Type_e** intType) `[inline]`

Clears capture (CAP) interrupt flag.

[1]Parameters in *capHandle* The capture (CAP) object handle

in *intType* The capture interrupt to be cleared

References _CAP_Obj_::ECECLR.

4.1.3.2 void CAP_disableCaptureLoad (

CAP_Handle capHandle)

Disables loading of CAP1-4 on capture event.

[1]Parameters in *capHandle* The capture (CAP) object handle

4.1.3.3 void CAP_disableInt (

CAP_Handle capHandle,

const **CAP_Int_Type_e** intType)

    Disables capture (CAP) interrupt source.

    [1]Parameters in *capHandle* The capture (CAP) object handle

---

    in *intType* The capture interrupt type to be disabled

4.1.3.4   void CAP_disableSyncIn (

CAP_Handle capHandle)

    Disables counter synchronization.

    [1]Parameters in *capHandle* The capture (CAP) object handle

---

4.1.3.5   void CAP_disableTimestampCounter (

CAP_Handle capHandle)

    Disables Time Stamp counter from running.

    [1]Parameters in *capHandle* The capture (CAP) object handle

---

4.1.3.6   void CAP_enableCaptureLoad (

CAP_Handle capHandle)

    Enables loading of CAP1-4 on capture event.

    [1]Parameters in *capHandle* The capture (CAP) object handle

---

4.1.3.7   void CAP_enableInt (

CAP_Handle capHandle,

const **CAP_Int_Type_e** intType)

    Enables capture (CAP) interrupt source.

    [1]Parameters in *capHandle* The capture (CAP) object handle

---

    in *intType* The capture interrupt type to be enabled

4.1.3.8   void CAP_enableSyncIn (

CAP_Handle capHandle)

Enables counter synchronization.

[1]Parameters `in` *capHandle* The capture (CAP) object handle

4.1.3.9   void CAP_enableTimestampCounter (

CAP_Handle capHandle)

Enables Time Stamp counter to running.

[1]Parameters `in` *capHandle* The capture (CAP) object handle

4.1.3.10   uint32_t CAP_getCap1 (

CAP_Handle capHandle) `[inline]`

Gets the CAP1 register value.

[1]Parameters `in` *capHandle* The capture (CAP) object handle

References _CAP_Obj_::CAP1.

4.1.3.11   uint32_t CAP_getCap2 (

CAP_Handle capHandle) `[inline]`

Gets the CAP2 register value.

[1]Parameters `in` *capHandle* The capture (CAP) object handle

References _CAP_Obj_::CAP2.

4.1.3.12   uint32_t CAP_getCap3 (

CAP_Handle capHandle) `[inline]`

Gets the CAP3 register value.

[1]Parameters `in` *capHandle* The capture (CAP) object handle

References _CAP_Obj_::CAP3.

4.1.3.13 uint32_t CAP_getCap4 (

CAP_Handle capHandle) `[inline]`

Gets the CAP4 register value.

[1]Parameters in *capHandle* The capture (CAP) object handle

References _CAP_Obj_::CAP4.

4.1.3.14 **CAP_Handle** CAP_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the capture (CAP) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the CAP registers

in *numBytes* The number of bytes allocated for the CAP object, bytes

Returns The capture (CAP) object handle

4.1.3.15 void CAP_rearm (

CAP_Handle capHandle) `[inline]`

(Re-)Arm the capture module

[1]Parameters in *capHandle* The capture (CAP) object handle

References CAP_ECCTL2_REARM_BITS, and _CAP_Obj_::ECCTL2.

4.1.3.16 void CAP_setApwmCompare (

CAP_Handle capHandle,

const uint32_t compare) `[inline]`

Sets the APWM compare value.

[1]Parameters in *capHandle* The capture (CAP) object handle

in *compare* The APWM compare value

References _CAP_Obj_::CAP2.

722.7

in *polarity* The polarity to configure the event for

4.1.3.21   void CAP_setCapEvtReset (

CAP_Handle capHandle,

const **CAP_Event_e** event,

const **CAP_Reset_e** reset)

Sets the capture event counter reset configuration.

[1]Parameters in *capHandle* The capture (CAP) object handle

---

in *event* The event to configure

---

in *reset* Whether the event should reset the counter or not

4.1.3.22   void CAP_setCapOneShot (

CAP_Handle capHandle)

Sets up for one-shot Capture.

[1]Parameters in *capHandle* The capture (CAP) object handle

4.1.3.23   void CAP_setModeApwm (

CAP_Handle capHandle)

Sets capture peripheral up for APWM mode.

[1]Parameters in *capHandle* The capture (CAP) object handle

4.1.3.24   void CAP_setModeCap (

CAP_Handle capHandle)

Sets capture peripheral up for capture mode.

[1]Parameters in *capHandle* The capture (CAP) object handle

4.1.3.25   void CAP_setStopWrap (

CAP_Handle capHandle,

const **CAP_Stop_Wrap_e** stopWrap)

Set the stop/wrap mode.

[1]Parameters in *capHandle* The capture (CAP) object handle

in *stopWrap* The stop/wrap mode to set

4.1.3.26   void CAP_setSyncOut (

CAP_Handle capHandle,

const **CAP_SyncOut_e** syncOut)

Set the sync out mode.

[1]Parameters in *capHandle* The capture (CAP) object handle

in *syncOut* The sync out mode to set

5 Device Clocking (CLK)

The CLK API provides functions to control the clocking subsystem of the device. Clock dividers and prescalers as well as peripheral clocks can all be set or enabled via this API.

This driver is contained in `f2802x0/common/source/clk.c`, with `f2802x0/common/include/clk.h` containing the API definitions for use by applications.

5.1 CLK

Data Structures

struct _CLK_Obj_

Macros

#define CLK_BASE_ADDR

#define CLK_CLKCTL_INTOSC1HALTI_BITS

#define CLK_CLKCTL_INTOSC1OFF_BITS

#define CLK_CLKCTL_INTOSC2HALTI_BITS

#define CLK_CLKCTL_INTOSC2OFF_BITS

#define CLK_CLKCTL_NMIRESETSEL_BITS

#define CLK_CLKCTL_OSCCLKSRC2SEL_BITS

#define CLK_CLKCTL_OSCCLKSRCSEL_BITS

#define CLK_CLKCTL_TMR2CLKPRESCALE_BITS

#define CLK_CLKCTL_TMR2CLKSRCSEL_BITS

#define CLK_CLKCTL_WDCLKSRCSEL_BITS

#define CLK_CLKCTL_WDHALTI_BITS

#define CLK_CLKCTL_XCLKINOFF_BITS

#define CLK_CLKCTL_XTALOSCOFF_BITS

#define CLK_LOSPCP_LSPCLK_BITS

#define CLK_PCLKCR0_ADCENCLK_BITS

#define CLK_PCLKCR0_ECANAENCLK_BITS

#define CLK_PCLKCR0_HRPWMENCLK_BITS

#define CLK_PCLKCR0_I2CAENCLK_BITS

#define CLK_PCLKCR0_LINAENCLK_BITS

#define CLK_PCLKCR0_SCIAENCLK_BITS

#define CLK_PCLKCR0_SPIAENCLK_BITS

#define CLK_PCLKCR0_SPIBENCLK_BITS

#define CLK_PCLKCR0_TBCLKSYNC_BITS

#define CLK_PCLKCR1_ECAP1ENCLK_BITS

#define CLK_PCLKCR1_EPWM1ENCLK_BITS

#define CLK_PCLKCR1_EPWM2ENCLK_BITS

#define CLK_PCLKCR1_EPWM3ENCLK_BITS

#define CLK_PCLKCR1_EPWM4ENCLK_BITS

#define CLK_PCLKCR1_EPWM5ENCLK_BITS

#define CLK_PCLKCR1_EPWM6ENCLK_BITS

#define CLK_PCLKCR1_EPWM7ENCLK_BITS

#define CLK_PCLKCR1_EQEP1ENCLK_BITS

#define CLK_PCLKCR3_CLA1ENCLK_BITS

#define CLK_PCLKCR3_COMP1ENCLK_BITS

#define CLK_PCLKCR3_COMP2ENCLK_BITS

#define CLK_PCLKCR3_COMP3ENCLK_BITS

#define CLK_PCLKCR3_CPUTIMER0ENCLK_BITS

#define CLK_PCLKCR3_CPUTIMER1ENCLK_BITS

#define CLK_PCLKCR3_CPUTIMER2ENCLK_BITS

#define CLK_PCLKCR3_GPIOINENCLK_BITS

#define CLK_XCLK_XCLKINSEL_BITS

#define CLK_XCLK_XCLKOUTDIV_BITS

Typedefs

typedef struct _CLK_Obj_ ∗ CLK_Handle

typedef struct _CLK_Obj_ CLK_Obj

Enumerations

enum CLK_ClkInSrc_e

enum CLK_ClkOutPreScaler_e { CLK_ClkOutPreScaler_SysClkOut_by_4, CLK_ClkOutPreScaler_SysClkOut_by_2, CLK_ClkOutPreScaler_SysClkOut_by_1, CLK_ClkOutPreScaler_Off }

enum CLK_CompNumber_e { CLK_CompNumber_1, CLK_CompNumber_2, CLK_CompNumber_3 }

enum CLK_CpuTimerNumber_e { CLK_CpuTimerNumber_0, CLK_CpuTimerNumber_1, CLK_CpuTimerNumber_2 }

enum CLK_LowSpdPreScaler_e { CLK_LowSpdPreScaler_SysClkOut_by_1, CLK_LowSpdPreScaler_SysClkOut_by_2, CLK_LowSpdPreScaler_SysClkOut_by_4, CLK_LowSpdPreScaler_SysClkOut_by_6, CLK_LowSpdPreScaler_SysClkOut_by_8, CLK_LowSpdPreScaler_SysClkOut_by_10, CLK_LowSpdPreScaler_SysClkOut_by_12, CLK_LowSpdPreScaler_SysClkOut_by_14 }

enum CLK_Osc2Src_e { CLK_Osc2Src_Internal, CLK_Osc2Src_External }

enum CLK_OscSrc_e { CLK_OscSrc_Internal, CLK_OscSrc_External }

enum CLK_Timer2PreScaler_e { CLK_Timer2PreScaler_by_1, CLK_Timer2PreScaler_by_2, CLK_Timer2PreScaler_by_4, CLK_Timer2PreScaler_by_8, CLK_Timer2PreScaler_by_16 }

enum CLK_Timer2Src_e { CLK_Timer2Src_SysClk, CLK_Timer2Src_ExtOsc, CLK_Timer2Src_IntOsc1, CLK_Timer2Src_IntOsc2 }

enum CLK_WdClkSrc_e { CLK_WdClkSrc_IntOsc1, CLK_WdClkSrc_ExtOscOrIntOsc2 }

Functions

void CLK_disableAdcClock (CLK_Handle clkHandle)

void CLK_disableClaClock (CLK_Handle clkHandle)

void CLK_disableClkIn (CLK_Handle clkHandle)

void CLK_disableCompClock (CLK_Handle clkHandle, const CLK_CompNumber_e compNumber)

void CLK_disableCpuTimerClock (CLK_Handle clkHandle, const CLK_CpuTimerNumber_e cpuTimerNumber)

void CLK_disableCrystalOsc (CLK_Handle clkHandle)

void CLK_disableEcanaClock (CLK_Handle clkHandle)

void CLK_disableEcap1Clock (CLK_Handle clkHandle)

void CLK_disableEqep1Clock (CLK_Handle clkHandle)

void CLK_disableGpioInputClock (CLK_Handle clkHandle)

void CLK_disableHrPwmClock (CLK_Handle clkHandle)

void CLK_disableI2cClock (CLK_Handle clkHandle)

void CLK_disableLinAClock (CLK_Handle clkHandle)

void CLK_disableOsc1 (CLK_Handle clkHandle)

void CLK_disableOsc1HaltMode (CLK_Handle clkHandle)

void CLK_disableOsc2 (CLK_Handle clkHandle)

void CLK_disableOsc2HaltMode (CLK_Handle clkHandle)

void CLK_disablePwmClock (CLK_Handle clkHandle, const PWM_Number_e pwmNumber)

void CLK_disableSciaClock (CLK_Handle clkHandle)

void CLK_disableSpiaClock (CLK_Handle clkHandle)

void CLK_disableSpibClock (CLK_Handle clkHandle)

void CLK_disableTbClockSync (CLK_Handle clkHandle)

void CLK_disableWatchDogHaltMode (CLK_Handle clkHandle)

void CLK_enableAdcClock (CLK_Handle clkHandle)

void CLK_enableClaClock (CLK_Handle clkHandle)

void CLK_enableClkIn (CLK_Handle clkHandle)

void CLK_enableCompClock (CLK_Handle clkHandle, const CLK_CompNumber_e compNumber)

void CLK_enableCpuTimerClock (CLK_Handle clkHandle, const CLK_CpuTimerNumber_e cpuTimerNumber)

void CLK_enableCrystalOsc (CLK_Handle clkHandle)

void CLK_enableEcanaClock (CLK_Handle clkHandle)

void CLK_enableEcap1Clock (CLK_Handle clkHandle)

void CLK_enableEqep1Clock (CLK_Handle clkHandle)

void CLK_enableGpioInputClock (CLK_Handle clkHandle)

void CLK_enableHrPwmClock (CLK_Handle clkHandle)

void CLK_enableI2cClock (CLK_Handle clkHandle)

void CLK_enableLinAClock (CLK_Handle clkHandle)

void CLK_enableOsc1 (CLK_Handle clkHandle)

void CLK_enableOsc1HaltMode (CLK_Handle clkHandle)

void CLK_enableOsc2 (CLK_Handle clkHandle)

void CLK_enableOsc2HaltMode (CLK_Handle clkHandle)

void CLK_enablePwmClock (CLK_Handle clkHandle, const PWM_Number_e pwmNumber)

void CLK_enableSciaClock (CLK_Handle clkHandle)

void CLK_enableSpiaClock (CLK_Handle clkHandle)

void CLK_enableSpibClock (CLK_Handle clkHandle)

void CLK_enableTbClockSync (CLK_Handle clkHandle)

void CLK_enableWatchDogHaltMode (CLK_Handle clkHandle)

CLK_Handle CLK_init (void ∗pMemory, const size_t numBytes)

void CLK_setClkOutPreScaler (CLK_Handle clkHandle, const CLK_ClkOutPreScaler_e preScaler)

void CLK_setLowSpdPreScaler (CLK_Handle clkHandle, const CLK_LowSpdPreScaler_e preScaler)

void CLK_setOsc2Src (CLK_Handle clkHandle, const CLK_Osc2Src_e src)

void CLK_setOscSrc (CLK_Handle clkHandle, const CLK_OscSrc_e src)

void CLK_setTimer2PreScaler (CLK_Handle clkHandle, const CLK_Timer2PreScaler_e preScaler)

void CLK_setTimer2Src (CLK_Handle clkHandle, const CLK_Timer2Src_e src)

void CLK_setWatchDogSrc (CLK_Handle clkHandle, const CLK_WdClkSrc_e src)

5.1.1   Detailed Description

5.1.2   Enumeration Type Documentation

5.1.2.1   enum **CLK_ClkOutPreScaler_e**

Enumeration to define the external clock output frequency.

Enumerator
    CLK_ClkOutPreScaler_SysClkOut_by_4   Denotes XCLKOUT = SYSCLKOUT/4.
    CLK_ClkOutPreScaler_SysClkOut_by_2   Denotes XCLKOUT = SYSCLKOUT/2.
    CLK_ClkOutPreScaler_SysClkOut_by_1   Denotes XCLKOUT = SYSCLKOUT/1.
    CLK_ClkOutPreScaler_Off   Denotes XCLKOUT = Off.

5.1.2.2 enum **CLK_CompNumber_e**

Enumeration to define the comparator numbers.

Enumerator
   CLK_CompNumber_1 Denotes comparator number 1.
   CLK_CompNumber_2 Denotes comparator number 2.
   CLK_CompNumber_3 Denotes comparator number 3.

5.1.2.3 enum **CLK_CpuTimerNumber_e**

Enumeration to define the CPU timer numbers.

Enumerator
   CLK_CpuTimerNumber_0 Denotes CPU timer number 0.
   CLK_CpuTimerNumber_1 Denotes CPU timer number 1.
   CLK_CpuTimerNumber_2 Denotes CPU timer number 2.

5.1.2.4 enum **CLK_LowSpdPreScaler_e**

Enumeration to define the low speed clock prescaler, which sets the clock frequency.

Enumerator
   CLK_LowSpdPreScaler_SysClkOut_by_1 Denotes Low Speed Clock = SYSCLKOUT/1.
   CLK_LowSpdPreScaler_SysClkOut_by_2 Denotes Low Speed Clock = SYSCLKOUT/2.
   CLK_LowSpdPreScaler_SysClkOut_by_4 Denotes Low Speed Clock = SYSCLKOUT/4.
   CLK_LowSpdPreScaler_SysClkOut_by_6 Denotes Low Speed Clock = SYSCLKOUT/6.
   CLK_LowSpdPreScaler_SysClkOut_by_8 Denotes Low Speed Clock = SYSCLKOUT/8.
   CLK_LowSpdPreScaler_SysClkOut_by_10 Denotes Low Speed Clock = SYSCLKOUT/10.

   CLK_LowSpdPreScaler_SysClkOut_by_12 Denotes Low Speed Clock = SYSCLKOUT/12.

   CLK_LowSpdPreScaler_SysClkOut_by_14 Denotes Low Speed Clock = SYSCLKOUT/14.

5.1.2.5 enum **CLK_Osc2Src_e**

Enumeration to define the clock oscillator 2 source.

Enumerator
   CLK_Osc2Src_Internal Denotes an internal oscillator 2 source.
   CLK_Osc2Src_External Denotes an external oscillator 2 source.

5.1.2.6   enum **CLK_OscSrc_e**

Enumeration to define the clock oscillator source.

Enumerator
>   ***CLK_OscSrc_Internal***   Denotes an internal oscillator source.
>   ***CLK_OscSrc_External***   Denotes an external oscillator source.

5.1.2.7   enum **CLK_Timer2PreScaler_e**

Enumeration to define the timer 2 prescaler, which sets the timer 2 frequency.

Enumerator
>   ***CLK_Timer2PreScaler_by_1***   Denotes a CPU timer 2 clock pre-scaler value of divide by 1.
>   ***CLK_Timer2PreScaler_by_2***   Denotes a CPU timer 2 clock pre-scaler value of divide by 2.
>   ***CLK_Timer2PreScaler_by_4***   Denotes a CPU timer 2 clock pre-scaler value of divide by 4.
>   ***CLK_Timer2PreScaler_by_8***   Denotes a CPU timer 2 clock pre-scaler value of divide by 8.
>   ***CLK_Timer2PreScaler_by_16***   Denotes a CPU timer 2 clock pre-scaler value of divide by 16.

5.1.2.8   enum **CLK_Timer2Src_e**

Enumeration to define the timer 2 source.

Enumerator
>   ***CLK_Timer2Src_SysClk***   Denotes the CPU timer 2 clock source is SYSCLKOUT.
>   ***CLK_Timer2Src_ExtOsc***   Denotes the CPU timer 2 clock source is external oscillator.
>   ***CLK_Timer2Src_IntOsc1***   Denotes the CPU timer 2 clock source is internal oscillator 1.
>   ***CLK_Timer2Src_IntOsc2***   Denotes the CPU timer 2 clock source is internal oscillator 2.

5.1.2.9   enum **CLK_WdClkSrc_e**

Enumeration to define the watchdog clock source.

Enumerator
>   ***CLK_WdClkSrc_IntOsc1***   Denotes the watchdog clock source is internal oscillator 1.
>   ***CLK_WdClkSrc_ExtOscOrIntOsc2***   Denotes the watchdog clock source is external oscillator or internal oscillator 2.

5.1.3   Function Documentation

5.1.3.1   void CLK_disableAdcClock (

CLK_Handle clkHandle)

Disables the ADC clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.2   void CLK_disableClaClock (

CLK_Handle clkHandle)

Disables the CLA clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.3   void CLK_disableClkIn (

CLK_Handle clkHandle)

Disables the XCLKIN oscillator input.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.4   void CLK_disableCompClock (

CLK_Handle clkHandle,

const **CLK_CompNumber_e** compNumber)

Disables the comparator clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

---

in *compNumber* The comparator number

5.1.3.5   void CLK_disableCpuTimerClock (

CLK_Handle clkHandle,

const **CLK_CpuTimerNumber_e** cpuTimerNumber)

Disables the CPU timer clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

---

in *cpuTimerNumber* The CPU timer number

5.1.3.6   void CLK_disableCrystalOsc (

CLK_Handle clkHandle)

Disables the crystal oscillator.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.7   void CLK_disableEcanaClock (

CLK_Handle clkHandle)

Disables the ECANA clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.8   void CLK_disableEcap1Clock (

CLK_Handle clkHandle)

Disables the ECAP1 clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.9   void CLK_disableEqep1Clock (

CLK_Handle clkHandle)

Disables the EQEP1 clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.10   void CLK_disableGpioInputClock (

CLK_Handle clkHandle)

Disables the GPIO input clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.11   void CLK_disableHrPwmClock (

CLK_Handle clkHandle)

Disables the HRPWM clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.12   void CLK_disableI2cClock (

CLK_Handle clkHandle)

Disables the I2C clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.13   void CLK_disableLinAClock (

CLK_Handle clkHandle)

Disables the LIN-A clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.14   void CLK_disableOsc1 (

CLK_Handle clkHandle)

Disables internal oscillator 1.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.15   void CLK_disableOsc1HaltMode (

CLK_Handle clkHandle)

Disables internal oscillator 1 halt mode ignore.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.16   void CLK_disableOsc2 (

CLK_Handle clkHandle)

Disables internal oscillator 2.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.17   void CLK_disableOsc2HaltMode (

CLK_Handle clkHandle)

Disables internal oscillator 2 halt mode ignore.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.18   void CLK_disablePwmClock (

CLK_Handle clkHandle,

const **PWM_Number_e** pwmNumber)

Disables the pwm clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

---

in *pwmNumber* The PWM number

5.1.3.19   void CLK_disableSciaClock (

CLK_Handle clkHandle)

Disables the SCI-A clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.20   void CLK_disableSpiaClock (

CLK_Handle clkHandle)

Disables the SPI-A clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.21   void CLK_disableSpibClock (

CLK_Handle clkHandle)

Disables the SPI-B clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.22   void CLK_disableTbClockSync (

CLK_Handle clkHandle)

Disables the ePWM module time base clock sync signal.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.23 void CLK_disableWatchDogHaltMode (

CLK_Handle clkHandle)

Disables the watchdog halt mode ignore.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.24 void CLK_enableAdcClock (

CLK_Handle clkHandle)

Enables the ADC clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.25 void CLK_enableClaClock (

CLK_Handle clkHandle)

Enables the CLA clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.26 void CLK_enableClkIn (

CLK_Handle clkHandle)

Enables the XCLKIN oscillator input.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.27 void CLK_enableCompClock (

CLK_Handle clkHandle,

const **CLK_CompNumber_e** compNumber)

Enables the comparator clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

in *compNumber* The comparator number

5.1.3.28 void CLK_enableCpuTimerClock (

CLK_Handle clkHandle,

const **CLK_CpuTimerNumber_e** cpuTimerNumber)

Enables the CPU timer clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

in *cpuTimerNumber* The CPU timer number

5.1.3.29 void CLK_enableCrystalOsc (

CLK_Handle clkHandle)

Enables the crystal oscillator.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.30 void CLK_enableEcanaClock (

CLK_Handle clkHandle)

Enables the ECANA clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.31 void CLK_enableEcap1Clock (

CLK_Handle clkHandle)

Enables the ECAP1 clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.32 void CLK_enableEqep1Clock (

CLK_Handle clkHandle)

Enables the EQEP1 clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.33   void CLK_enableGpioInputClock (

CLK_Handle clkHandle)

Enables the GPIO input clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.34   void CLK_enableHrPwmClock (

CLK_Handle clkHandle)

Enables the HRPWM clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.35   void CLK_enableI2cClock (

CLK_Handle clkHandle)

Enables the I2C clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.36   void CLK_enableLinAClock (

CLK_Handle clkHandle)

Enables the LIN-A clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.37   void CLK_enableOsc1 (

CLK_Handle clkHandle)

Enables internal oscillator 1.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.38   void CLK_enableOsc1HaltMode (

CLK_Handle clkHandle)

Enables internal oscillator 1 halt mode ignore.

---

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.39   void CLK_enableOsc2 (

CLK_Handle clkHandle)

Enables internal oscillator 2.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.40   void CLK_enableOsc2HaltMode (

CLK_Handle clkHandle)

Enables internal oscillator 2 halt mode ignore.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.41   void CLK_enablePwmClock (

CLK_Handle clkHandle,

const **PWM_Number_e** pwmNumber)

Enables the pwm clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

in *pwmNumber* The PWM number

5.1.3.42   void CLK_enableSciaClock (

CLK_Handle clkHandle)

Enables the SCI-A clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

5.1.3.43   void CLK_enableSpiaClock (

CLK_Handle clkHandle)

Enables the SPI-A clock.

[1]Parameters in *clkHandle* The clock (CLK) object handle

722.7

> in *preScaler* The prescaler value

5.1.3.49   void CLK_setLowSpdPreScaler (

CLK_Handle clkHandle,

const **CLK_LowSpdPreScaler_e** preScaler)

> Sets the low speed peripheral clock prescaler.
>
> [1]Parameters in *clkHandle* The clock (CLK) object handle

> in *preScaler* The prescaler value

5.1.3.50   void CLK_setOsc2Src (

CLK_Handle clkHandle,

const **CLK_Osc2Src_e** src)

> Sets the oscillator 2 clock source.
>
> [1]Parameters in *clkHandle* The clock (CLK) object handle

> in *src* The oscillator 2 clock source

5.1.3.51   void CLK_setOscSrc (

CLK_Handle clkHandle,

const **CLK_OscSrc_e** src)

> Sets the oscillator clock source.
>
> [1]Parameters in *clkHandle* The clock (CLK) object handle

> in *src* The oscillator clock source

5.1.3.52   void CLK_setTimer2PreScaler (

CLK_Handle clkHandle,

const **CLK_Timer2PreScaler_e** preScaler)

> Sets the timer 2 clock prescaler.

[1]Parameters in *clkHandle* The clock (CLK) object handle

in *preScaler* The prescaler value

5.1.3.53 void CLK_setTimer2Src (

CLK_Handle clkHandle,

const **CLK_Timer2Src_e** src)

Sets the timer 2 clock source.

[1]Parameters in *clkHandle* The clock (CLK) object handle

in *src* The timer 2 clock source

5.1.3.54 void CLK_setWatchDogSrc (

CLK_Handle clkHandle,

const **CLK_WdClkSrc_e** src)

Sets the watchdog clock source.

[1]Parameters in *clkHandle* The clock (CLK) object handle

in *src* The watchdog clock source

6 Comparater (COMP)

The Comparator (COMP) API provides the set of functions to configure the analog comparators present on this device.

This driver is contained in `f2802x0/common/source/comp.c`, with `f2802x0/common/include/comp.h` containing the API definitions for use by applications.

6.1 COMP

Data Structures

struct _COMP_Obj_

Macros

#define COMP1_BASE_ADDR

#define COMP2_BASE_ADDR

#define COMP_COMPCTL_CMPINV_BITS

#define COMP_COMPCTL_COMPDACE_BITS

#define COMP_COMPCTL_COMPSOURCE_BITS

#define COMP_COMPCTL_QUALSEL_BITS

#define COMP_COMPCTL_SYNCSEL_BITS

#define COMP_COMPSTS_COMPSTS_BITS

#define COMP_DACCTL_DACSOURCE_BITS

#define COMP_DACCTL_FREESOFT_BITS

#define COMP_DACCTL_RAMPSOURCE_BITS

Typedefs

typedef struct _COMP_Obj_ ∗ COMP_Handle

typedef struct _COMP_Obj_ COMP_Obj

Enumerations

enum COMP_QualSel_e {
COMP_QualSel_Sync, COMP_QualSel_Qual_2, COMP_QualSel_Qual_3,
COMP_QualSel_Qual_4,
COMP_QualSel_Qual_5, COMP_QualSel_Qual_6, COMP_QualSel_Qual_7,
COMP_QualSel_Qual_8,
COMP_QualSel_Qual_9, COMP_QualSel_Qual_10, COMP_QualSel_Qual_11,
COMP_QualSel_Qual_12,
COMP_QualSel_Qual_13, COMP_QualSel_Qual_14, COMP_QualSel_Qual_15,
COMP_QualSel_Qual_16,
COMP_QualSel_Qual_17, COMP_QualSel_Qual_18, COMP_QualSel_Qual_19,
COMP_QualSel_Qual_20,
COMP_QualSel_Qual_21, COMP_QualSel_Qual_22, COMP_QualSel_Qual_23,
COMP_QualSel_Qual_24,
COMP_QualSel_Qual_25, COMP_QualSel_Qual_26, COMP_QualSel_Qual_27,
COMP_QualSel_Qual_28,
COMP_QualSel_Qual_29, COMP_QualSel_Qual_30, COMP_QualSel_Qual_31,
COMP_QualSel_Qual_32,
COMP_QualSel_Qual_33 }

enum COMP_RampSyncSrc_e { COMP_RampSyncSrc_PWMSYNC1,
COMP_RampSyncSrc_PWMSYNC2, COMP_RampSyncSrc_PWMSYNC3,
COMP_RampSyncSrc_PWMSYNC4 }

Functions

void COMP_disable (COMP_Handle compHandle)

void COMP_disableDac (COMP_Handle compHandle)

void COMP_enable (COMP_Handle compHandle)

void COMP_enableDac (COMP_Handle compHandle)

COMP_Handle COMP_init (void *pMemory, const size_t numBytes)

void COMP_setDacValue (COMP_Handle compHandle, uint16_t dacValue)

6.1.1 Detailed Description

6.1.2 Enumeration Type Documentation

6.1.2.1 enum **COMP_QualSel_e**

Enumeration to define the comparator (COMP) output qualification.

Enumerator
　　COMP_QualSel_Sync Syncronize comparator output.

COMP_QualSel_Qual_2 Qualify comparator output with 2 cycles.
COMP_QualSel_Qual_3 Qualify comparator output with 3 cycles.
COMP_QualSel_Qual_4 Qualify comparator output with 4 cycles.
COMP_QualSel_Qual_5 Qualify comparator output with 5 cycles.
COMP_QualSel_Qual_6 Qualify comparator output with 6 cycles.
COMP_QualSel_Qual_7 Qualify comparator output with 7 cycles.
COMP_QualSel_Qual_8 Qualify comparator output with 8 cycles.
COMP_QualSel_Qual_9 Qualify comparator output with 9 cycles.
COMP_QualSel_Qual_10 Qualify comparator output with 10 cycles.
COMP_QualSel_Qual_11 Qualify comparator output with 11 cycles.
COMP_QualSel_Qual_12 Qualify comparator output with 12 cycles.
COMP_QualSel_Qual_13 Qualify comparator output with 13 cycles.
COMP_QualSel_Qual_14 Qualify comparator output with 14 cycles.
COMP_QualSel_Qual_15 Qualify comparator output with 15 cycles.
COMP_QualSel_Qual_16 Qualify comparator output with 16 cycles.
COMP_QualSel_Qual_17 Qualify comparator output with 17 cycles.
COMP_QualSel_Qual_18 Qualify comparator output with 18 cycles.
COMP_QualSel_Qual_19 Qualify comparator output with 19 cycles.
COMP_QualSel_Qual_20 Qualify comparator output with 20 cycles.
COMP_QualSel_Qual_21 Qualify comparator output with 21 cycles.
COMP_QualSel_Qual_22 Qualify comparator output with 22 cycles.
COMP_QualSel_Qual_23 Qualify comparator output with 23 cycles.
COMP_QualSel_Qual_24 Qualify comparator output with 24 cycles.
COMP_QualSel_Qual_25 Qualify comparator output with 25 cycles.
COMP_QualSel_Qual_26 Qualify comparator output with 26 cycles.
COMP_QualSel_Qual_27 Qualify comparator output with 27 cycles.
COMP_QualSel_Qual_28 Qualify comparator output with 28 cycles.
COMP_QualSel_Qual_29 Qualify comparator output with 29 cycles.
COMP_QualSel_Qual_30 Qualify comparator output with 30 cycles.
COMP_QualSel_Qual_31 Qualify comparator output with 31 cycles.
COMP_QualSel_Qual_32 Qualify comparator output with 32 cycles.
COMP_QualSel_Qual_33 Qualify comparator output with 33 cycles.

6.1.2.2 enum **COMP_RampSyncSrc_e**

Enumeration to define the comparator (COMP) ramp generator sync source.

Enumerator

COMP_RampSyncSrc_PWMSYNC1 PWMSync1 used as Ramp Sync.
COMP_RampSyncSrc_PWMSYNC2 PWMSync2 used as Ramp Sync.
COMP_RampSyncSrc_PWMSYNC3 PWMSync3 used as Ramp Sync.
COMP_RampSyncSrc_PWMSYNC4 PWMSync4 used as Ramp Sync.

6.1.3   Function Documentation

6.1.3.1   void COMP_disable (

COMP_Handle compHandle)

Disables the comparator (COMP)

[1]Parameters in *compHandle* The comparator (COMP) object handle

---

6.1.3.2   void COMP_disableDac (

COMP_Handle compHandle)

Disables the DAC.

[1]Parameters in *compHandle* The comparator (COMP) object handle

---

6.1.3.3   void COMP_enable (

COMP_Handle compHandle)

Enables the comparator (COMP)

[1]Parameters in *compHandle* The comparator (COMP) object handle

---

6.1.3.4   void COMP_enableDac (

COMP_Handle compHandle)

Enables the DAC.

[1]Parameters in *compHandle* The comparator (COMP) object handle

---

6.1.3.5   **COMP_Handle** COMP_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the comparator (COMP) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the COMP registers

---

in *numBytes* The number of bytes allocated for the COMP object, bytes

---

Returns The comparator (COMP) object handle

6.1.3.6   void COMP_setDacValue (

COMP_Handle compHandle,

uint16_t dacValue)   `[inline]`

Sets the DAC's value.

[1]Parameters `in` *compHandle* The comparator (COMP) object handle

`in` *dacValue* The DAC's value

References _COMP_Obj_::DACVAL.

7   Central Processing Unit (CPU)

The CPU API provides a set of functions for controlling the central processing unit of this device. This driver is unique in that when initialized `NULL` should be passed as the peripheral base address.

This driver is contained in `f2802x0/common/source/cpu.c,` with `f2802x0/common/include/cpu.h` containing the API definitions for use by applications.

7.1   CPU

Data Structures

struct _CPU_Obj_

Macros

#define CPU_DBGIER_DLOGINT_BITS

#define CPU_DBGIER_INT10_BITS

#define CPU_DBGIER_INT11_BITS

#define CPU_DBGIER_INT12_BITS

#define CPU_DBGIER_INT13_BITS

#define CPU_DBGIER_INT14_BITS

#define CPU_DBGIER_INT1_BITS

#define CPU_DBGIER_INT2_BITS

#define CPU_DBGIER_INT3_BITS

#define CPU_DBGIER_INT4_BITS

#define CPU_DBGIER_INT5_BITS

#define CPU_DBGIER_INT6_BITS

#define CPU_DBGIER_INT7_BITS

#define CPU_DBGIER_INT8_BITS

#define CPU_DBGIER_INT9_BITS

#define CPU_DBGIER_RTOSINT_BITS

#define CPU_IER_DLOGINT_BITS

#define CPU_IER_INT10_BITS

#define CPU_IER_INT11_BITS

#define CPU_IER_INT12_BITS

#define CPU_IER_INT13_BITS

#define CPU_IER_INT14_BITS

#define CPU_IER_INT1_BITS

#define CPU_IER_INT2_BITS

#define CPU_IER_INT3_BITS

#define CPU_IER_INT4_BITS

#define CPU_IER_INT5_BITS

#define CPU_IER_INT6_BITS

#define CPU_IER_INT7_BITS

#define CPU_IER_INT8_BITS

#define CPU_IER_INT9_BITS

#define CPU_IER_RTOSINT_BITS

#define CPU_IFR_DLOGINT_BITS

#define CPU_IFR_INT10_BITS

#define CPU_IFR_INT11_BITS

#define CPU_IFR_INT12_BITS

#define CPU_IFR_INT13_BITS

#define CPU_IFR_INT14_BITS

#define CPU_IFR_INT1_BITS

#define CPU_IFR_INT2_BITS

#define CPU_IFR_INT3_BITS

#define CPU_IFR_INT4_BITS

#define CPU_IFR_INT5_BITS

#define CPU_IFR_INT6_BITS

#define CPU_IFR_INT7_BITS

#define CPU_IFR_INT8_BITS

#define CPU_IFR_INT9_BITS

#define CPU_IFR_RTOSINT_BITS

#define CPU_ST0_C_BITS

#define CPU_ST0_N_BITS

#define CPU_ST0_OVCOVCU_BITS

#define CPU_ST0_OVM_BITS

#define CPU_ST0_PW_BITS

#define CPU_ST0_SXM_BITS

#define CPU_ST0_TC_BITS

#define CPU_ST0_V_BITS

#define CPU_ST0_Z_BITS

#define CPU_ST1_AMODE_BITS

#define CPU_ST1_ARP_BITS

#define CPU_ST1_DBGM_BITS

#define CPU_ST1_EALLOW_BITS

#define CPU_ST1_IDLESTAT_BITS

#define CPU_ST1_INTM_BITS

#define CPU_ST1_LOOP_BITS

#define CPU_ST1_MOM1MAP_BITS

#define CPU_ST1_OBJMODE_BITS

#define CPU_ST1_PAGE0_BITS

#define CPU_ST1_SPA_BITS

#define CPU_ST1_VMAP_BITS

#define CPU_ST1_XF_BITS

#define DINT

#define DISABLE_INTERRUPTS

#define DISABLE_PROTECTED_REGISTER_WRITE_MODE

#define DRTM

#define EALLOW

#define EDIS

#define EINT

#define ENABLE_INTERRUPTS

#define ENABLE_PROTECTED_REGISTER_WRITE_MODE

#define ERTM

#define ESTOP0

#define IDLE

Typedefs

typedef struct _CPU_Obj_ ∗ CPU_Handle

typedef struct _CPU_Obj_ CPU_Obj

Enumerations

enum   CPU_ExtIntNumber_e   {   CPU_ExtIntNumber_1,   CPU_ExtIntNumber_2,
CPU_ExtIntNumber_3 }

enum CPU_IntNumber_e {
CPU_IntNumber_1, CPU_IntNumber_2, CPU_IntNumber_3, CPU_IntNumber_4,
CPU_IntNumber_5, CPU_IntNumber_6, CPU_IntNumber_7, CPU_IntNumber_8,
CPU_IntNumber_9, CPU_IntNumber_10, CPU_IntNumber_11, CPU_IntNumber_12,
CPU_IntNumber_13, CPU_IntNumber_14 }

Functions

void CPU_clearIntFlags (CPU_Handle cpuHandle)

void CPU_disableDebugInt (CPU_Handle cpuHandle)

void CPU_disableGlobalInts (CPU_Handle cpuHandle)

void CPU_disableInt (CPU_Handle cpuHandle, const CPU_IntNumber_e intNumber)

void CPU_disableInts (CPU_Handle cpuHandle)

void CPU_disableProtectedRegisterWrite (CPU_Handle cpuHandle)

void CPU_enableDebugInt (CPU_Handle cpuHandle)

void CPU_enableGlobalInts (CPU_Handle cpuHandle)

void CPU_enableInt (CPU_Handle cpuHandle, const CPU_IntNumber_e intNumber)

void CPU_enableProtectedRegisterWrite (CPU_Handle cpuHandle)

CPU_Handle CPU_init (void ∗pMemory, const size_t numBytes)

Variables

CPU_Obj cpu

cregister volatile unsigned int IER

cregister volatile unsigned int IFR

7.1.1 Detailed Description

7.1.2 Enumeration Type Documentation

7.1.2.1 enum **CPU_ExtIntNumber_e**

Enumeration to define the external interrupt numbers.

Enumerator
 CPU_ExtIntNumber_1 Denotes external interrupt number 1.
 CPU_ExtIntNumber_2 Denotes external interrupt number 2.
 CPU_ExtIntNumber_3 Denotes external interrupt number 3.

7.1.2.2 enum **CPU_IntNumber_e**

Enumeration to define the interrupt numbers.

Enumerator
 CPU_IntNumber_1 Denotes interrupt number 1.
 CPU_IntNumber_2 Denotes interrupt number 2.
 CPU_IntNumber_3 Denotes interrupt number 3.
 CPU_IntNumber_4 Denotes interrupt number 4.
 CPU_IntNumber_5 Denotes interrupt number 5.
 CPU_IntNumber_6 Denotes interrupt number 6.
 CPU_IntNumber_7 Denotes interrupt number 7.
 CPU_IntNumber_8 Denotes interrupt number 8.
 CPU_IntNumber_9 Denotes interrupt number 9.
 CPU_IntNumber_10 Denotes interrupt number 10.
 CPU_IntNumber_11 Denotes interrupt number 11.
 CPU_IntNumber_12 Denotes interrupt number 12.
 CPU_IntNumber_13 Denotes interrupt number 13.
 CPU_IntNumber_14 Denotes interrupt number 14.

7.1.3   Function Documentation

7.1.3.1   void CPU_clearIntFlags (

CPU_Handle cpuHandle)

Clears all interrupt flags.

[1]Parameters `in` *cpuHandle* The central processing unit (CPU) object handle

---

7.1.3.2   void CPU_disableDebugInt (

CPU_Handle cpuHandle)

Disables the debug interrupt.

[1]Parameters `in` *cpuHandle* The central processing unit (CPU) object handle

---

7.1.3.3   void CPU_disableGlobalInts (

CPU_Handle cpuHandle)

Disables global interrupts.

[1]Parameters `in` *cpuHandle* The CPU handle

7.1.3.4   void CPU_disableInt (

CPU_Handle cpuHandle,

const **CPU_IntNumber_e** intNumber)

Disables a specified interrupt number.

[1]Parameters `in` *cpuHandle* The central processing unit (CPU) object handle

---

`in` *intNumber* The interrupt number

7.1.3.5   void CPU_disableInts (

CPU_Handle cpuHandle)

Disables all interrupts.

[1]Parameters `in` *cpuHandle* The central processing unit (CPU) object handle

---

7.1.3.6 void CPU_disableProtectedRegisterWrite (

CPU_Handle cpuHandle)

Disables protected register writes.

[1]Parameters in *cpuHandle* The central processing unit (CPU) object handle

7.1.3.7 void CPU_enableDebugInt (

CPU_Handle cpuHandle)

Enables the debug interrupt.

[1]Parameters in *cpuHandle* The CPU handle

7.1.3.8 void CPU_enableGlobalInts (

CPU_Handle cpuHandle)

Enables global interrupts.

[1]Parameters in *cpuHandle* The CPU handle

7.1.3.9 void CPU_enableInt (

CPU_Handle cpuHandle,

const **CPU_IntNumber_e** intNumber)

Enables a specified interrupt number.

[1]Parameters in *cpuHandle* The central processing unit (CPU) object handle

in *intNumber* The interrupt number

7.1.3.10 void CPU_enableProtectedRegisterWrite (

CPU_Handle cpuHandle)

Enables protected register writes.

[1]Parameters in *cpuHandle* The central processing unit (CPU) object handle

7.1.3.11 **CPU_Handle** CPU_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the central processing unit (CPU) object handle.

[1]Parameters `in` *pMemory* A pointer to the memory for the CPU object

`in` *numBytes* The number of bytes allocated for the CPU object, bytes

Returns The central processing unit (CPU) object handle

8   Flash

The Flash API contains functions for configuring the wait states as well as run and sleep modes of flash in the device.

CAUTION: The flash function(s) should only be run from RAM. Please copy the function to RAM using the memcpy function found in the run time support library before calling any of them.

This driver is contained in `f2802x0/common/source/flash.c`, with `f2802x0/common/include/flash.h` containing the API definitions for use by applications.

8.1   FLASH

Data Structures

struct _FLASH_Obj_

Macros

#define FLASH_ACTIVE_WAIT_COUNT_DEFAULT

#define FLASH_BASE_ADDR

#define FLASH_FACTIVEWAIT_ACTIVEWAIT_BITS

#define FLASH_FBANKWAIT_PAGEWAIT_BITS

#define FLASH_FBANKWAIT_RANDWAIT_BITS

#define FLASH_FOPT_ENPIPE_BITS

#define FLASH_FOTPWAIT_OTPWAIT_BITS

#define FLASH_FPWR_PWR_BITS

#define FLASH_FSTATUS_3VSTAT_BITS

#define FLASH_FSTATUS_ACTIVEWAITS_BITS

#define FLASH_FSTATUS_PWRS_BITS

#define FLASH_FSTATUS_STDBYWAITS_BITS

#define FLASH_FSTDBYWAIT_STDBYWAIT_BITS

#define FLASH_STANDBY_WAIT_COUNT_DEFAULT

Typedefs

typedef struct _FLASH_Obj_ ∗ FLASH_Handle

typedef struct _FLASH_Obj_ FLASH_Obj

Enumerations

enum FLASH_3VStatus_e { FLASH_3VStatus_InRange, FLASH_3VStatus_OutOfRange }

enum FLASH_CounterStatus_e { FLASH_CounterStatus_NotCounting, FLASH_CounterStatus_Counting }

enum FLASH_NumOtpWaitStates_e {
FLASH_NumOtpWaitStates_1, FLASH_NumOtpWaitStates_2, FLASH_NumOtpWaitStates_3, FLASH_NumOtpWaitStates_4,
FLASH_NumOtpWaitStates_5, FLASH_NumOtpWaitStates_6, FLASH_NumOtpWaitStates_7, FLASH_NumOtpWaitStates_8,
FLASH_NumOtpWaitStates_9, FLASH_NumOtpWaitStates_10, FLASH_NumOtpWaitStates_11, FLASH_NumOtpWaitStates_12,
FLASH_NumOtpWaitStates_13, FLASH_NumOtpWaitStates_14, FLASH_NumOtpWaitStates_15
}

enum FLASH_NumPagedWaitStates_e {
FLASH_NumPagedWaitStates_0, FLASH_NumPagedWaitStates_1, FLASH_NumPagedWaitStates_2, FLASH_NumPagedWaitStates_3,
FLASH_NumPagedWaitStates_4, FLASH_NumPagedWaitStates_5, FLASH_NumPagedWaitStates_6, FLASH_NumPagedWaitStates_7,
FLASH_NumPagedWaitStates_8, FLASH_NumPagedWaitStates_9, FLASH_NumPagedWaitStates_10, FLASH_NumPagedWaitStates_11,
FLASH_NumPagedWaitStates_12, FLASH_NumPagedWaitStates_13, FLASH_NumPagedWaitStates_14, FLASH_NumPagedWaitStates_15 }

enum FLASH_NumRandomWaitStates_e {
FLASH_NumRandomWaitStates_1, FLASH_NumRandomWaitStates_2, FLASH_NumRandomWaitStates_3, FLASH_NumRandomWaitStates_4,
FLASH_NumRandomWaitStates_5, FLASH_NumRandomWaitStates_6, FLASH_NumRandomWaitStates_7, FLASH_NumRandomWaitStates_8,
FLASH_NumRandomWaitStates_9, FLASH_NumRandomWaitStates_10, FLASH_NumRandomWaitStates_11, FLASH_NumRandomWaitStates_12,
FLASH_NumRandomWaitStates_13, FLASH_NumRandomWaitStates_14, FLASH_NumRandomWaitStates_15 }

enum FLASH_PowerMode_e { FLASH_PowerMode_PumpAndBankSleep, FLASH_PowerMode_PumpAndBankStandby, FLASH_PowerMode_PumpAndBankActive }

Functions

void FLASH_clear3VStatus (FLASH_Handle flashHandle)

void FLASH_disablePipelineMode (FLASH_Handle flashHandle)

void FLASH_enablePipelineMode (FLASH_Handle flashHandle)

FLASH_3VStatus_e FLASH_get3VStatus (FLASH_Handle flashHandle)

uint16_t FLASH_getActiveWaitCount (FLASH_Handle flashHandle)

FLASH_CounterStatus_e FLASH_getActiveWaitStatus (FLASH_Handle flashHandle)

FLASH_PowerMode_e FLASH_getPowerMode (FLASH_Handle flashHandle)

uint16_t FLASH_getStandbyWaitCount (FLASH_Handle flashHandle)

FLASH_CounterStatus_e FLASH_getStandbyWaitStatus (FLASH_Handle flashHandle)

FLASH_Handle FLASH_init (void ∗pMemory, const size_t numBytes)

void FLASH_setActiveWaitCount (FLASH_Handle flashHandle, const uint16_t count)

void   FLASH_setNumPagedReadWaitStates   (FLASH_Handle   flashHandle,   const
FLASH_NumPagedWaitStates_e numStates)

void   FLASH_setNumRandomReadWaitStates   (FLASH_Handle   flashHandle,   const
FLASH_NumRandomWaitStates_e numStates)

void FLASH_setOtpWaitStates (FLASH_Handle flashHandle, const FLASH_NumOtpWaitStates_e
numStates)

void FLASH_setPowerMode (FLASH_Handle flashHandle, const FLASH_PowerMode_e mode)

void FLASH_setStandbyWaitCount (FLASH_Handle flashHandle, const uint16_t count)

void FLASH_setup (FLASH_Handle flashHandle)

8.1.1 Detailed Description

8.1.2 Enumeration Type Documentation

8.1.2.1 enum **FLASH_3VStatus_e**

Enumeration to define the 3V status.

Enumerator
  FLASH_3VStatus_InRange Denotes the 3V flash voltage is in range.
  FLASH_3VStatus_OutOfRange Denotes the 3V flash voltage went out of range.

8.1.2.2 enum **FLASH_CounterStatus_e**

Enumeration to define the counter status.

Enumerator
  FLASH_CounterStatus_NotCounting Denotes the flash counter is not counting.
  FLASH_CounterStatus_Counting Denotes the flash counter is counting.

8.1.2.3 enum **FLASH_NumOtpWaitStates_e**

Enumeration to define the number of one-time programmable wait states.

Enumerator

FLASH_NumOtpWaitStates_1 Denotes the number of one-time programmable (OTP) wait states is 1.

FLASH_NumOtpWaitStates_2 Denotes the number of one-time programmable (OTP) wait states is 2.

FLASH_NumOtpWaitStates_3 Denotes the number of one-time programmable (OTP) wait states is 3.

FLASH_NumOtpWaitStates_4 Denotes the number of one-time programmable (OTP) wait states is 4.

FLASH_NumOtpWaitStates_5 Denotes the number of one-time programmable (OTP) wait states is 5.

FLASH_NumOtpWaitStates_6 Denotes the number of one-time programmable (OTP) wait states is 6.

FLASH_NumOtpWaitStates_7 Denotes the number of one-time programmable (OTP) wait states is 7.

FLASH_NumOtpWaitStates_8 Denotes the number of one-time programmable (OTP) wait states is 8.

FLASH_NumOtpWaitStates_9 Denotes the number of one-time programmable (OTP) wait states is 9.

FLASH_NumOtpWaitStates_10 Denotes the number of one-time programmable (OTP) wait states is 10.

FLASH_NumOtpWaitStates_11 Denotes the number of one-time programmable (OTP) wait states is 11.

FLASH_NumOtpWaitStates_12 Denotes the number of one-time programmable (OTP) wait states is 12.

FLASH_NumOtpWaitStates_13 Denotes the number of one-time programmable (OTP) wait states is 13.

FLASH_NumOtpWaitStates_14 Denotes the number of one-time programmable (OTP) wait states is 14.

FLASH_NumOtpWaitStates_15 Denotes the number of one-time programmable (OTP) wait states is 15.

8.1.2.4 enum **FLASH_NumPagedWaitStates_e**

Enumeration to define the number of paged wait states.

Enumerator

FLASH_NumPagedWaitStates_0 Denotes the number of paged read wait states is 0.
FLASH_NumPagedWaitStates_1 Denotes the number of paged read wait states is 1.
FLASH_NumPagedWaitStates_2 Denotes the number of paged read wait states is 2.
FLASH_NumPagedWaitStates_3 Denotes the number of paged read wait states is 3.
FLASH_NumPagedWaitStates_4 Denotes the number of paged read wait states is 4.
FLASH_NumPagedWaitStates_5 Denotes the number of paged read wait states is 5.
FLASH_NumPagedWaitStates_6 Denotes the number of paged read wait states is 6.

FLASH_NumPagedWaitStates_7 Denotes the number of paged read wait states is 7.

FLASH_NumPagedWaitStates_8 Denotes the number of paged read wait states is 8.

FLASH_NumPagedWaitStates_9 Denotes the number of paged read wait states is 9.

FLASH_NumPagedWaitStates_10 Denotes the number of paged read wait states is 10.

FLASH_NumPagedWaitStates_11 Denotes the number of paged read wait states is 11.

FLASH_NumPagedWaitStates_12 Denotes the number of paged read wait states is 12.

FLASH_NumPagedWaitStates_13 Denotes the number of paged read wait states is 13.

FLASH_NumPagedWaitStates_14 Denotes the number of paged read wait states is 14.

FLASH_NumPagedWaitStates_15 Denotes the number of paged read wait states is 15.

8.1.2.5   enum **FLASH_NumRandomWaitStates_e**

Enumeration to define the number of random wait states.

Enumerator

FLASH_NumRandomWaitStates_1 Denotes the number of randowm read wait states is 1.

FLASH_NumRandomWaitStates_2 Denotes the number of randowm read wait states is 2.

FLASH_NumRandomWaitStates_3 Denotes the number of randowm read wait states is 3.

FLASH_NumRandomWaitStates_4 Denotes the number of randowm read wait states is 4.

FLASH_NumRandomWaitStates_5 Denotes the number of randowm read wait states is 5.

FLASH_NumRandomWaitStates_6 Denotes the number of randowm read wait states is 6.

FLASH_NumRandomWaitStates_7 Denotes the number of randowm read wait states is 7.

FLASH_NumRandomWaitStates_8 Denotes the number of randowm read wait states is 8.

FLASH_NumRandomWaitStates_9 Denotes the number of randowm read wait states is 9.

FLASH_NumRandomWaitStates_10 Denotes the number of randowm read wait states is 10.

FLASH_NumRandomWaitStates_11 Denotes the number of randowm read wait states is 11.

FLASH_NumRandomWaitStates_12 Denotes the number of randowm read wait states is 12.

FLASH_NumRandomWaitStates_13 Denotes the number of randowm read wait states is 13.

FLASH_NumRandomWaitStates_14 Denotes the number of randowm read wait states is 14.

FLASH_NumRandomWaitStates_15 Denotes the number of randowm read wait states is 15.

8.1.2.6   enum **FLASH_PowerMode_e**

Enumeration to define the power modes.

Enumerator

FLASH_PowerMode_PumpAndBankSleep Denotes a pump and bank sleep power mode.

FLASH_PowerMode_PumpAndBankStandby Denotes a pump and bank standby power mode.

FLASH_PowerMode_PumpAndBankActive Denotes a pump and bank active power mode.

8.1.3 Function Documentation

8.1.3.1 void FLASH_clear3VStatus (

FLASH_Handle flashHandle)

Clears the 3V status.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

---

8.1.3.2 void FLASH_disablePipelineMode (

FLASH_Handle flashHandle)

Disables the pipeline mode.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

---

8.1.3.3 void FLASH_enablePipelineMode (

FLASH_Handle flashHandle)

Enables the pipeline mode.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

---

8.1.3.4 **FLASH_3VStatus_e** FLASH_get3VStatus (

FLASH_Handle flashHandle)

Gets the 3V status.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

---

Returns The 3V status

8.1.3.5 uint16_t FLASH_getActiveWaitCount (

FLASH_Handle flashHandle)

Gets the active wait count.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

---

Returns The active wait count

722.7

in *numBytes* The number of bytes allocated for the FLASH object, bytes

Returns The flash (FLASH) object handle

8.1.3.11 void FLASH_setActiveWaitCount (

FLASH_Handle flashHandle,

const uint16_t count)

Sets the active wait count.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

in *count* The active wait count

8.1.3.12 void FLASH_setNumPagedReadWaitStates (

FLASH_Handle flashHandle,

const **FLASH_NumPagedWaitStates_e** numStates)

Sets the number of paged read wait states.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

in *numStates* The number of paged read wait states

8.1.3.13 void FLASH_setNumRandomReadWaitStates (

FLASH_Handle flashHandle,

const **FLASH_NumRandomWaitStates_e** numStates)

Sets the number of random read wait states.

[1]Parameters in *flashHandle* The flash (FLASH) object handle

in *numStates* The number of random read wait states

8.1.3.14 void FLASH_setOtpWaitStates (

FLASH_Handle flashHandle,

const **FLASH_NumOtpWaitStates_e** numStates)

> Sets the number of one-time programmable (OTP) wait states.
>
> [1]Parameters `in` *flashHandle* The flash (FLASH) object handle

---

> `in` *numStates* The number of one-time programmable (OTP) wait states

---

8.1.3.15 void FLASH_setPowerMode (

FLASH_Handle flashHandle,

const **FLASH_PowerMode_e** mode)

> Sets the power mode.
>
> [1]Parameters `in` *flashHandle* The flash (FLASH) object handle

---

> `in` *mode* The power mode

8.1.3.16 void FLASH_setStandbyWaitCount (

FLASH_Handle flashHandle,

const uint16_t count)

> Sets the standby wait count.
>
> [1]Parameters `in` *flashHandle* The flash (FLASH) object handle

---

> `in` *count* The standby wait count

8.1.3.17 void FLASH_setup (

FLASH_Handle flashHandle)

> Setup flash for optimal performance.
>
> [1]Parameters `in` *flashHandle* The flash (FLASH) object handle

---

9 General Purpose Input/Output (GPIO)

Introduction . . . . **??**
API Functions 69 The GPIO API provides functions to configure and control the GPIO of this device. Pins can be set as inputs, outputs, or a peripheral function and their value set or read via this API.

This driver is contained in `f2802x0/common/source/gpio.c`, with `f2802x0/common/include/gpio.h` containing the API definitions for use by applications.

9.1 GPIO

Data Structures

struct _GPIO_Obj_

Macros

#define GPIO_BASE_ADDR

#define GPIO_GPMUX_CONFIG_BITS

#define GPIO_GPMUX_NUMGPIOS_PER_REG

#define GPIO_GPxCTRL_QUALPRDx_BITS

#define GPIO_GPxCTRL_QUALPRDx_NUMBITS_PER_REG

#define GPIO_GPxQSELx_NUMGPIOS_PER_REG

#define GPIO_GPxQSELy_GPIOx_BITS

Typedefs

typedef struct _GPIO_Obj_ * GPIO_Handle

typedef struct _GPIO_Obj_ GPIO_Obj

Enumerations

enum GPIO_Direction_e { GPIO_Direction_Input, GPIO_Direction_Output }

enum GPIO_Mode_e {
GPIO_0_Mode_GeneralPurpose, GPIO_0_Mode_EPWM1A, GPIO_0_Mode_Rsvd_2, GPIO_0_Mode_Rsvd_3,
GPIO_1_Mode_GeneralPurpose, GPIO_1_Mode_EPWM1B, GPIO_1_Mode_Rsvd_2,

GPIO_1_Mode_COMP1OUT,
GPIO_2_Mode_GeneralPurpose,   GPIO_2_Mode_EPWM2A,   GPIO_2_Mode_Rsvd_2,
GPIO_2_Mode_Rsvd_3,
GPIO_3_Mode_GeneralPurpose,   GPIO_3_Mode_EPWM2B,   GPIO_3_Mode_Rsvd_2,
GPIO_3_Mode_COMP2OUT,
GPIO_4_Mode_GeneralPurpose,   GPIO_4_Mode_EPWM3A,   GPIO_4_Mode_Rsvd_2,
GPIO_4_Mode_Rsvd_3,
GPIO_5_Mode_GeneralPurpose,   GPIO_5_Mode_EPWM3B,   GPIO_5_Mode_Rsvd_2,
GPIO_5_Mode_ECAP1,
GPIO_6_Mode_GeneralPurpose,   GPIO_6_Mode_Rsvd_1,   GPIO_6_Mode_EPWMSYNCI,
GPIO_6_Mode_EPWMSYNCO,
GPIO_7_Mode_GeneralPurpose,   GPIO_7_Mode_Rsvd_1,   GPIO_7_Mode_SCIRXDA,
GPIO_7_Mode_Rsvd_3,
GPIO_12_Mode_GeneralPurpose,   GPIO_12_Mode_TZ1_NOT,   GPIO_12_Mode_SCITXDA,
GPIO_12_Mode_Rsvd_3,
GPIO_16_Mode_GeneralPurpose,   GPIO_16_Mode_SPISIMOA,   GPIO_16_Mode_Rsvd_2,
GPIO_16_Mode_TZ2_NOT,
GPIO_17_Mode_GeneralPurpose,   GPIO_17_Mode_SPISOMIA,   GPIO_17_Mode_Rsvd_2,
GPIO_17_Mode_TZ3_NOT,
GPIO_18_Mode_GeneralPurpose,   GPIO_18_Mode_SPICLKA,   GPIO_18_Mode_SCITXDA,
GPIO_18_Mode_XCLKOUT,
GPIO_19_Mode_GeneralPurpose, GPIO_19_Mode_SPISTEA_NOT, GPIO_19_Mode_SCIRXDA,
GPIO_19_Mode_ECAP1,
GPIO_28_Mode_GeneralPurpose,   GPIO_28_Mode_SCIRXDA,   GPIO_28_Mode_SDDA,
GPIO_28_Mode_TZ2_NOT,
GPIO_29_Mode_GeneralPurpose,   GPIO_29_Mode_SCITXDA,   GPIO_29_Mode_SCLA,
GPIO_29_Mode_TZ3_NOT,
GPIO_32_Mode_GeneralPurpose,   GPIO_32_Mode_SDAA,   GPIO_32_Mode_EPWMSYNCI,
GPIO_32_Mode_ADCSOCAO_NOT,
GPIO_33_Mode_GeneralPurpose,   GPIO_33_Mode_SCLA,   GPIO_33_Mode_EPWMSYNCO,
GPIO_33_Mode_ADCSOCBO_NOT,
GPIO_34_Mode_GeneralPurpose,   GPIO_34_Mode_COMP2OUT,   GPIO_34_Mode_Rsvd_2,
GPIO_34_Mode_Rsvd_3,
GPIO_35_Mode_JTAG_TDI,   GPIO_35_Mode_Rsvd_1,   GPIO_35_Mode_Rsvd_2,
GPIO_35_Mode_Rsvd_3,
GPIO_36_Mode_JTAG_TMS,   GPIO_36_Mode_Rsvd_1,   GPIO_36_Mode_Rsvd_2,
GPIO_36_Mode_Rsvd_3,
GPIO_37_Mode_JTAG_TDO,   GPIO_37_Mode_Rsvd_1,   GPIO_37_Mode_Rsvd_2,
GPIO_37_Mode_Rsvd_3,
GPIO_38_Mode_JTAG_TCK,   GPIO_38_Mode_Rsvd_1,   GPIO_38_Mode_Rsvd_2,
GPIO_38_Mode_Rsvd_3 }

enum GPIO_Number_e {
GPIO_Number_0, GPIO_Number_1, GPIO_Number_2, GPIO_Number_3,
GPIO_Number_4, GPIO_Number_5, GPIO_Number_6, GPIO_Number_7,
GPIO_Rsvd_8, GPIO_Rsvd_9, GPIO_Rsvd_10, GPIO_Rsvd_11,
GPIO_Number_12, GPIO_Rsvd_13, GPIO_Rsvd_14, GPIO_Rsvd_15,
GPIO_Number_16, GPIO_Number_17, GPIO_Number_18, GPIO_Number_19,
GPIO_Rsvd_20, GPIO_Rsvd_21, GPIO_Rsvd_22, GPIO_Rsvd_23,
GPIO_Rsvd_24, GPIO_Rsvd_25, GPIO_Rsvd_26, GPIO_Rsvd_27,
GPIO_Number_28, GPIO_Number_29, GPIO_Rsvd_30, GPIO_Rsvd_31,
GPIO_Number_32, GPIO_Number_33, GPIO_Number_34, GPIO_Number_35,
GPIO_Number_36, GPIO_Number_37, GPIO_Number_38 }

enum GPIO_Port_e { GPIO_Port_A, GPIO_Port_B }

enum GPIO_PullUp_e { GPIO_PullUp_Enable, GPIO_PullUp_Disable }

enum GPIO_Qual_e { GPIO_Qual_Sync, GPIO_Qual_Sample_3, GPIO_Qual_Sample_6, GPIO_Qual_ASync }

Functions

uint16_t GPIO_getData (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber)

uint32_t GPIO_getPortData (GPIO_Handle gpioHandle, const GPIO_Port_e gpioPort)

GPIO_Handle GPIO_init (void ∗pMemory, const size_t numBytes)

void GPIO_lpmSelect (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber)

void GPIO_setDirection (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber, const GPIO_Direction_e direction)

void GPIO_setExtInt (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber, const CPU_ExtIntNumber_e intNumber)

void GPIO_setHigh (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber)

void GPIO_setLow (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber)

void GPIO_setMode (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber, const GPIO_Mode_e mode)

void GPIO_setPortData (GPIO_Handle gpioHandle, const GPIO_Port_e gpioPort, const uint32_t data)

void GPIO_setPullUp (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber, const GPIO_PullUp_e pullUp)

void GPIO_setQualification (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber, const GPIO_Qual_e qualification)

void GPIO_setQualificationPeriod (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber, const uint8_t period)

void GPIO_toggle (GPIO_Handle gpioHandle, const GPIO_Number_e gpioNumber)

9.1.1   Detailed Description

9.1.2   Enumeration Type Documentation

9.1.2.1   enum **GPIO_Direction_e**

Enumeration to define the general purpose I/O (GPIO) directions.

Enumerator
    GPIO_Direction_Input Denotes an input direction.
    GPIO_Direction_Output Denotes an output direction.

9.1.2.2 enum **GPIO_Mode_e**

Enumeration to define the general purpose I/O (GPIO) modes for each pin.

Enumerator
    GPIO_0_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_0_Mode_EPWM1A Denotes a EPWM1A function.
    GPIO_0_Mode_Rsvd_2 Denotes a reserved function.
    GPIO_0_Mode_Rsvd_3 Denotes a reserved function.
    GPIO_1_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_1_Mode_EPWM1B Denotes a EPWM1B function.
    GPIO_1_Mode_Rsvd_2 Denotes a reserved function.
    GPIO_1_Mode_COMP1OUT Denotes a COMP1OUT function.
    GPIO_2_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_2_Mode_EPWM2A Denotes a EPWM2A function.
    GPIO_2_Mode_Rsvd_2 Denotes a reserved function.
    GPIO_2_Mode_Rsvd_3 Denotes a reserved function.
    GPIO_3_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_3_Mode_EPWM2B Denotes a EPWM2B function.
    GPIO_3_Mode_Rsvd_2 Denotes a reserved function.
    GPIO_3_Mode_COMP2OUT Denotes a COMP2OUT function.
    GPIO_4_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_4_Mode_EPWM3A Denotes a EPWM3A function.
    GPIO_4_Mode_Rsvd_2 Denotes a reserved function.
    GPIO_4_Mode_Rsvd_3 Denotes a reserved function.
    GPIO_5_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_5_Mode_EPWM3B Denotes a EPWM3B function.
    GPIO_5_Mode_Rsvd_2 Denotes a reserved function.
    GPIO_5_Mode_ECAP1 Denotes a ECAP1 function.
    GPIO_6_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_6_Mode_Rsvd_1 Denotes a reserved function.
    GPIO_6_Mode_EPWMSYNCI Denotes a EPWMSYNCI function.
    GPIO_6_Mode_EPWMSYNCO Denotes a EPWMSYNCO function.
    GPIO_7_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_7_Mode_Rsvd_1 Denotes a reserved function.
    GPIO_7_Mode_SCIRXDA Denotes a SCIRXDA function.
    GPIO_7_Mode_Rsvd_3 Denotes a reserved function.
    GPIO_12_Mode_GeneralPurpose Denotes a general purpose function.
    GPIO_12_Mode_TZ1_NOT Denotes a TZ1_NOT function.
    GPIO_12_Mode_SCITXDA Denotes a SCITXDA function.
    GPIO_12_Mode_Rsvd_3 Denotes a reserved function.

GPIO_16_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_16_Mode_SPISIMOA   Denotes a SPISIMOA function.

GPIO_16_Mode_Rsvd_2   Denotes a reserved function.

GPIO_16_Mode_TZ2_NOT   Denotes a TZ2_NOT function.

GPIO_17_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_17_Mode_SPISOMIA   Denotes a SPISOMIA function.

GPIO_17_Mode_Rsvd_2   Denotes a reserved function.

GPIO_17_Mode_TZ3_NOT   Denotes a TZ3_NOT function.

GPIO_18_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_18_Mode_SPICLKA   Denotes a SPICLKA function.

GPIO_18_Mode_SCITXDA   Denotes a SCITXDA function.

GPIO_18_Mode_XCLKOUT   Denotes a XCLKOUT function.

GPIO_19_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_19_Mode_SPISTEA_NOT   Denotes a SPISTEA_NOT function.

GPIO_19_Mode_SCIRXDA   Denotes a SCIRXDA function.

GPIO_19_Mode_ECAP1   Denotes a ECAP1 function.

GPIO_28_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_28_Mode_SCIRXDA   Denotes a SCIRXDA function.

GPIO_28_Mode_SDDA   Denotes a SDDA function.

GPIO_28_Mode_TZ2_NOT   Denotes a TZ2_NOT function.

GPIO_29_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_29_Mode_SCITXDA   Denotes a SCITXDA function.

GPIO_29_Mode_SCLA   Denotes a SCLA function.

GPIO_29_Mode_TZ3_NOT   Denotes a TZ2_NOT function.

GPIO_32_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_32_Mode_SDAA   Denotes a SDDA function.

GPIO_32_Mode_EPWMSYNCI   Denotes a EPWMSYNCI function.

GPIO_32_Mode_ADCSOCAO_NOT   Denotes a ADCSOCAO_NOT function.

GPIO_33_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_33_Mode_SCLA   Denotes a SCLA function.

GPIO_33_Mode_EPWMSYNCO   Denotes a EPWMSYNCO function.

GPIO_33_Mode_ADCSOCBO_NOT   Denotes a ADCSOCBO_NOT function.

GPIO_34_Mode_GeneralPurpose   Denotes a general purpose function.

GPIO_34_Mode_COMP2OUT   Denotes a COMP2OUT function.

GPIO_34_Mode_Rsvd_2   Denotes a reserved function.

GPIO_34_Mode_Rsvd_3   Denotes a reserved function.

GPIO_35_Mode_JTAG_TDI   Denotes a JTAG_TDI function.

GPIO_35_Mode_Rsvd_1   Denotes a reserved function.

GPIO_35_Mode_Rsvd_2   Denotes a reserved function.

GPIO_35_Mode_Rsvd_3   Denotes a reserved function.

GPIO_36_Mode_JTAG_TMS   Denotes a JTAG_TMS function.

GPIO_36_Mode_Rsvd_1   Denotes a reserved function.

GPIO_36_Mode_Rsvd_2   Denotes a reserved function.

GPIO_36_Mode_Rsvd_3   Denotes a reserved function.

GPIO_37_Mode_JTAG_TDO   Denotes a JTAG_TDO function.

GPIO_37_Mode_Rsvd_1   Denotes a reserved function.

GPIO_37_Mode_Rsvd_2 Denotes a reserved function.
GPIO_37_Mode_Rsvd_3 Denotes a reserved function.
GPIO_38_Mode_JTAG_TCK Denotes a JTAG_TCK function.
GPIO_38_Mode_Rsvd_1 Denotes a reserved function.
GPIO_38_Mode_Rsvd_2 Denotes a reserved function.
GPIO_38_Mode_Rsvd_3 Denotes a reserved function.

9.1.2.3 enum **GPIO_Number_e**

Enumeration to define the general purpose I/O (GPIO) numbers.

Enumerator

GPIO_Number_0 Denotes GPIO number 0.
GPIO_Number_1 Denotes GPIO number 1.
GPIO_Number_2 Denotes GPIO number 2.
GPIO_Number_3 Denotes GPIO number 3.
GPIO_Number_4 Denotes GPIO number 4.
GPIO_Number_5 Denotes GPIO number 5.
GPIO_Number_6 Denotes GPIO number 6.
GPIO_Number_7 Denotes GPIO number 7.
GPIO_Rsvd_8 This GPIO not present.
GPIO_Rsvd_9 This GPIO not present.
GPIO_Rsvd_10 This GPIO not present.
GPIO_Rsvd_11 This GPIO not present.
GPIO_Number_12 Denotes GPIO number 12.
GPIO_Rsvd_13 This GPIO not present.
GPIO_Rsvd_14 This GPIO not present.
GPIO_Rsvd_15 This GPIO not present.
GPIO_Number_16 Denotes GPIO number 16.
GPIO_Number_17 Denotes GPIO number 17.
GPIO_Number_18 Denotes GPIO number 18.
GPIO_Number_19 Denotes GPIO number 19.
GPIO_Rsvd_20 This GPIO not present.
GPIO_Rsvd_21 This GPIO not present.
GPIO_Rsvd_22 This GPIO not present.
GPIO_Rsvd_23 This GPIO not present.
GPIO_Rsvd_24 This GPIO not present.
GPIO_Rsvd_25 This GPIO not present.
GPIO_Rsvd_26 This GPIO not present.
GPIO_Rsvd_27 This GPIO not present.
GPIO_Number_28 Denotes GPIO number 28.
GPIO_Number_29 Denotes GPIO number 29.
GPIO_Rsvd_30 This GPIO not present.
GPIO_Rsvd_31 This GPIO not present.
GPIO_Number_32 Denotes GPIO number 32.

GPIO_Number_33 Denotes GPIO number 33.
GPIO_Number_34 Denotes GPIO number 34.
GPIO_Number_35 Denotes GPIO number 35.
GPIO_Number_36 Denotes GPIO number 36.
GPIO_Number_37 Denotes GPIO number 37.
GPIO_Number_38 Denotes GPIO number 38.

9.1.2.4   enum **GPIO_Port_e**

Enumeration to define the general purpose I/O (GPIO) ports.

Enumerator
GPIO_Port_A GPIO Port A.
GPIO_Port_B GPIO Port B.

9.1.2.5   enum **GPIO_PullUp_e**

Enumeration to define the general purpose I/O (GPIO) pull ups.

Enumerator
GPIO_PullUp_Enable Denotes pull up will be enabled.
GPIO_PullUp_Disable Denotes pull up will be disabled.

9.1.2.6   enum **GPIO_Qual_e**

Enumeration to define the general purpose I/O (GPIO) qualification.

Enumerator
GPIO_Qual_Sync Denotes input will be synchronized to SYSCLK.
GPIO_Qual_Sample_3 Denotes input is qualified with 3 samples.
GPIO_Qual_Sample_6 Denotes input is qualified with 6 samples.
GPIO_Qual_ASync Denotes input is asynchronous.

9.1.3   Function Documentation

9.1.3.1   uint16_t GPIO_getData (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber)

Returns the data value present on a pin (either input or output)

[1]Parameters `in` *gpioHandle* The general purpose I/O (GPIO) object handle

`in` *gpioNumber* The GPIO number

Returns The boolen state of a pin (high/low)

9.1.3.2   uint32_t GPIO_getPortData (

GPIO_Handle gpioHandle,

const **GPIO_Port_e** gpioPort)

Returns the data value present on a GPIO port.

[1]Parameters `in` *gpioHandle* The general purpose I/O (GPIO) object handle

`in` *gpioPort* The GPIO port

Returns The data values for the specified port

9.1.3.3   **GPIO_Handle** GPIO_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the general purpose I/O (GPIO) object handle.

[1]Parameters `in` *pMemory* A pointer to the base address of the GPIO registers

`in` *numBytes* The number of bytes allocated for the GPIO object, bytes

Returns The general purpose I/O (GPIO) object handle

9.1.3.4   void GPIO_lpmSelect (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber)

Selects a gpio pin to wake up device from STANDBY and HALT LPM.

[1]Parameters `in` *gpioHandle* The general purpose I/O (GPIO) object handle

`in` *gpioNumber* The GPIO number

9.1.3.5   void GPIO_setDirection (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber,

const **GPIO_Direction_e** direction)

Sets the general purpose I/O (GPIO) signal direction.

[1]Parameters `in` *gpioHandle* The general purpose I/O (GPIO) object handle

`in` *gpioNumber* The GPIO number

`in` *direction* The signal direction

9.1.3.6 void GPIO_setExtInt (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber,

const **CPU_ExtIntNumber_e** intNumber)

Sets the general purpose I/O (GPIO) external interrupt number.

[1]Parameters `in` *gpioHandle* The general purpose I/O (GPIO) object handle

`in` *gpioNumber* The GPIO number

`in` *intNumber* The interrupt number

9.1.3.7 void GPIO_setHigh (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber)

Sets the specified general purpose I/O (GPIO) signal high.

[1]Parameters `in` *gpioHandle* The general purpose I/O (GPIO) object handle

`in` *gpioNumber* The GPIO number

9.1.3.8 void GPIO_setLow (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber)

Sets the specified general purpose I/O (GPIO) signal low.

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioNumber* The GPIO number

9.1.3.9 void GPIO_setMode (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber,

const **GPIO_Mode_e** mode)

Sets the mode for the specified general purpose I/O (GPIO) signal.

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioNumber* The GPIO number

in *mode* The mode

9.1.3.10 void GPIO_setPortData (

GPIO_Handle gpioHandle,

const **GPIO_Port_e** gpioPort,

const uint32_t data)

Sets data output on a given GPIO port.

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioPort* The GPIO number

in *data* The data to write to the port

9.1.3.11 void GPIO_setPullUp (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber,

const **GPIO_PullUp_e** pullUp)

Sets the general purpose I/O (GPIO) signal pullups.

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioNumber* The GPIO number

in *pullUp* The pull up enable or disable

9.1.3.12 void GPIO_setQualification (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber,

const **GPIO_Qual_e** qualification)

Sets the qualification for the specified general purpose I/O (GPIO)

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioNumber* The GPIO number

in *qualification* The desired input qualification

9.1.3.13 void GPIO_setQualificationPeriod (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber,

const uint8_t period)

Sets the qualification period for the specified general purpose I/O block (8 I/O's per block)

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioNumber* The GPIO number

in *period* The desired input qualification period

9.1.3.14 void GPIO_toggle (

GPIO_Handle gpioHandle,

const **GPIO_Number_e** gpioNumber)

Toggles the specified general purpose I/O (GPIO) signal.

[1]Parameters in *gpioHandle* The general purpose I/O (GPIO) object handle

in *gpioNumber* The GPIO number

10 Oscillator (OSC)

The oscillator (OSC) API provides functions for configuring an external or internal oscillator as well as compensating the internal oscillator for temperature drift.

This driver is contained in `f2802x0/common/source/osc.c`, with `f2802x0/common/include/osc.h` containing the API definitions for use by applications.

10.1 OSC

Data Structures

struct _OSC_Obj_

Macros

#define OSC_BASE_ADDR

#define OSC_INTOSCnTRIM_COARSE_BITS

#define OSC_INTOSCnTRIM_FINE_BITS

#define OSC_OTP_COURSE_TRIM1

#define OSC_OTP_COURSE_TRIM2

#define OSC_OTP_FINE_TRIM_OFFSET1

#define OSC_OTP_FINE_TRIM_OFFSET2

#define OSC_OTP_FINE_TRIM_SLOPE1

#define OSC_OTP_FINE_TRIM_SLOPE2

#define OSC_OTP_REF_TEMP_OFFSET

Typedefs

typedef struct _OSC_Obj_ * OSC_Handle

typedef struct _OSC_Obj_ OSC_Obj

Enumerations

enum OSC_Number_e { OSC_Number_1, OSC_Number_2 }

enum OSC_Osc2Src_e { OSC_Osc2Src_Internal, OSC_Osc2Src_External }

enum OSC_Src_e { OSC_Src_Internal, OSC_Src_External }

Functions

int16_t OSC_getCourseTrim1 (OSC_Handle oscHandle)

int16_t OSC_getCourseTrim2 (OSC_Handle oscHandle)

int16_t OSC_getFineTrimOffset1 (OSC_Handle oscHandle)

int16_t OSC_getFineTrimOffset2 (OSC_Handle oscHandle)

int16_t OSC_getFineTrimSlope1 (OSC_Handle oscHandle)

int16_t OSC_getFineTrimSlope2 (OSC_Handle oscHandle)

int16_t OSC_getRefTempOffset (OSC_Handle oscHandle)

OSC_Handle OSC_init (void ∗pMemory, const size_t numBytes)

void OSC_setCoarseTrim (OSC_Handle oscHandle, const OSC_Number_e oscNumber, const uint8_t trimValue)

void OSC_setFineTrim (OSC_Handle oscHandle, const OSC_Number_e oscNumber, const uint8_t trimValue)

10.1.1 Detailed Description

10.1.2 Enumeration Type Documentation

10.1.2.1 enum **OSC_Number_e**

Enumeration to define the oscillator (OSC) number.

Enumerator
    OSC_Number_1 Denotes oscillator number 1.
    OSC_Number_2 Denotes oscillator number 2.

10.1.2.2 enum **OSC_Osc2Src_e**

Enumeration to define the oscillator (OSC) 2 source.

Enumerator

> ***OSC_Osc2Src_Internal***   Denotes an internal oscillator source for oscillator 2.
> ***OSC_Osc2Src_External***   Denotes an external oscillator source for oscillator 2.

10.1.2.3   enum **OSC_Src_e**

Enumeration to define the oscillator (OSC) source.

Enumerator

> ***OSC_Src_Internal***   Denotes an internal oscillator.
> ***OSC_Src_External***   Denotes an external oscillator.

10.1.3   Function Documentation

10.1.3.1   int16_t OSC_getCourseTrim1 (

OSC_Handle oscHandle)   `[inline]`

Gets the fine trim offset for oscillator 1.

[1]Parameters `in` *oscHandle*   The oscillator (OSC) object handle

Returns The fine trim offset for oscillator 1

References OSC_OTP_COURSE_TRIM1.

10.1.3.2   int16_t OSC_getCourseTrim2 (

OSC_Handle oscHandle)   `[inline]`

Gets the fine trim offset for oscillator 2.

[1]Parameters `in` *oscHandle*   The oscillator (OSC) object handle

Returns The fine trim offset for oscillator 2

References OSC_OTP_COURSE_TRIM2.

10.1.3.3   int16_t OSC_getFineTrimOffset1 (

OSC_Handle oscHandle)   `[inline]`

Gets the fine trim offset for oscillator 1.

[1]Parameters `in` *oscHandle*   The oscillator (OSC) object handle

Returns The fine trim offset for oscillator 1

References OSC_OTP_FINE_TRIM_OFFSET1.

10.1.3.4 int16_t OSC_getFineTrimOffset2 (

OSC_Handle oscHandle) `[inline]`

Gets the fine trim offset for oscillator 2.

[1]Parameters in *oscHandle* The oscillator (OSC) object handle

Returns The fine trim offset for oscillator 2

References OSC_OTP_FINE_TRIM_OFFSET2.

10.1.3.5 int16_t OSC_getFineTrimSlope1 (

OSC_Handle oscHandle) `[inline]`

Gets the fine trim offset for oscillator 1.

[1]Parameters in *oscHandle* The oscillator (OSC) object handle

Returns The fine trim offset for oscillator 1

References OSC_OTP_FINE_TRIM_SLOPE1.

10.1.3.6 int16_t OSC_getFineTrimSlope2 (

OSC_Handle oscHandle) `[inline]`

Gets the fine trim offset for oscillator 2.

[1]Parameters in *oscHandle* The oscillator (OSC) object handle

Returns The fine trim offset for oscillator 2

References OSC_OTP_FINE_TRIM_SLOPE2.

10.1.3.7 int16_t OSC_getRefTempOffset (

OSC_Handle oscHandle) `[inline]`

Gets the reference temperature offset.

[1]Parameters in *oscHandle* The oscillator (OSC) object handle

Returns The reference temperature offset

References OSC_OTP_REF_TEMP_OFFSET.

10.1.3.8 **OSC_Handle** OSC_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the oscillator (OSC) handle.

[1]Parameters in *pMemory* A pointer to the base address of the FLASH registers

in *numBytes* The number of bytes allocated for the FLASH object, bytes

Returns The flash (FLASH) object handle

10.1.3.9 void OSC_setCoarseTrim (

OSC_Handle oscHandle,

const **OSC_Number_e** oscNumber,

const uint8_t trimValue)

Sets the coarse trim value for a specified oscillator.

[1]Parameters in *oscHandle* The oscillator (OSC) object handle

in *oscNumber* The oscillator number

in *trimValue* The coarse trim value

10.1.3.10 void OSC_setFineTrim (

OSC_Handle oscHandle,

const **OSC_Number_e** oscNumber,

const uint8_t trimValue)

Sets the fine trim value for a specified oscillator.

[1]Parameters in *oscHandle* The oscillator (OSC) object handle

in *oscNumber* The oscillator number

in *trimValue* The fine trim value

11 Peripheral Interrupt Expansion Module (PIE)

The Peripheral Interrupt Expansion controller (PIE) API provides functions for configuring and using the PIE on Piccolo devices. This API provides functions for enabling and disabling individual interrupt sources as well as acknowledging interrupts that have occurred.

This driver is contained in `f2802x0/common/source/pie.c`, with `f2802x0/common/include/pie.h` containing the API definitions for use by applications.

11.1 PIE

Data Structures

struct _PIE_IERIFR_t

struct _PIE_Obj_

Macros

#define PIE_BASE_ADDR

#define PIE_DBGIER_DLOGINT_BITS

#define PIE_DBGIER_INT10_BITS

#define PIE_DBGIER_INT11_BITS

#define PIE_DBGIER_INT12_BITS

#define PIE_DBGIER_INT13_BITS

#define PIE_DBGIER_INT14_BITS

#define PIE_DBGIER_INT1_BITS

#define PIE_DBGIER_INT2_BITS

#define PIE_DBGIER_INT3_BITS

#define PIE_DBGIER_INT4_BITS

#define PIE_DBGIER_INT5_BITS

#define PIE_DBGIER_INT6_BITS

#define PIE_DBGIER_INT7_BITS

#define PIE_DBGIER_INT8_BITS

#define PIE_DBGIER_INT9_BITS

#define PIE_DBGIER_RTOSINT_BITS

#define PIE_IER_DLOGINT_BITS

#define PIE_IER_INT10_BITS

#define PIE_IER_INT11_BITS

#define PIE_IER_INT12_BITS

#define PIE_IER_INT13_BITS

#define PIE_IER_INT14_BITS

#define PIE_IER_INT1_BITS

#define PIE_IER_INT2_BITS

#define PIE_IER_INT3_BITS

#define PIE_IER_INT4_BITS

#define PIE_IER_INT5_BITS

#define PIE_IER_INT6_BITS

#define PIE_IER_INT7_BITS

#define PIE_IER_INT8_BITS

#define PIE_IER_INT9_BITS

#define PIE_IER_RTOSINT_BITS

#define PIE_IERx_INTx1_BITS

#define PIE_IERx_INTx2_BITS

#define PIE_IERx_INTx3_BITS

#define PIE_IERx_INTx4_BITS

#define PIE_IERx_INTx5_BITS

#define PIE_IERx_INTx6_BITS

#define PIE_IERx_INTx7_BITS

#define PIE_IERx_INTx8_BITS

#define PIE_IFR_DLOGINT_BITS

#define PIE_IFR_INT10_BITS

#define PIE_IFR_INT11_BITS

#define PIE_IFR_INT12_BITS

#define PIE_IFR_INT13_BITS

#define PIE_IFR_INT14_BITS

#define PIE_IFR_INT1_BITS

#define PIE_IFR_INT2_BITS

#define PIE_IFR_INT3_BITS

#define PIE_IFR_INT4_BITS

#define PIE_IFR_INT5_BITS

#define PIE_IFR_INT6_BITS

#define PIE_IFR_INT7_BITS

#define PIE_IFR_INT8_BITS

#define PIE_IFR_INT9_BITS

#define PIE_IFR_RTOSINT_BITS

#define PIE_IFRx_INTx1_BITS

#define PIE_IFRx_INTx2_BITS

#define PIE_IFRx_INTx3_BITS

#define PIE_IFRx_INTx4_BITS

#define PIE_IFRx_INTx5_BITS

#define PIE_IFRx_INTx6_BITS

#define PIE_IFRx_INTx7_BITS

#define PIE_IFRx_INTx8_BITS

#define PIE_PIEACK_GROUP10_BITS

#define PIE_PIEACK_GROUP11_BITS

#define PIE_PIEACK_GROUP12_BITS

#define PIE_PIEACK_GROUP1_BITS

#define PIE_PIEACK_GROUP2_BITS

#define PIE_PIEACK_GROUP3_BITS

#define PIE_PIEACK_GROUP4_BITS

#define PIE_PIEACK_GROUP5_BITS

#define PIE_PIEACK_GROUP6_BITS

#define PIE_PIEACK_GROUP7_BITS

#define PIE_PIEACK_GROUP8_BITS

#define PIE_PIEACK_GROUP9_BITS

#define PIE_PIECTRL_ENPIE_BITS

#define PIE_PIECTRL_PIEVECT_BITS

Typedefs

typedef interrupt void(∗ intVec_t)(void)

typedef struct _PIE_Obj_ ∗ PIE_Handle

typedef struct _PIE_IERIFR_t PIE_IERIFR_t

typedef struct _PIE_Obj_ PIE_Obj

Enumerations

enum PIE_ExtIntPolarity_e { PIE_ExtIntPolarity_FallingEdge, PIE_ExtIntPolarity_RisingEdge, PIE_ExtIntPolarity_RisingAndFallingEdge }

enum PIE_GroupNumber_e {
PIE_GroupNumber_1, PIE_GroupNumber_2, PIE_GroupNumber_3, PIE_GroupNumber_4,
PIE_GroupNumber_5, PIE_GroupNumber_6, PIE_GroupNumber_7, PIE_GroupNumber_8,
PIE_GroupNumber_9, PIE_GroupNumber_10, PIE_GroupNumber_11, PIE_GroupNumber_12 }

enum PIE_InterruptSource_e {
PIE_InterruptSource_ADCINT_1_1, PIE_InterruptSource_ADCINT_1_2,
PIE_InterruptSource_XINT_1, PIE_InterruptSource_XINT_2,
PIE_InterruptSource_ADCINT_9, PIE_InterruptSource_TIMER_0, PIE_InterruptSource_WAKE,
PIE_InterruptSource_TZ1,
PIE_InterruptSource_TZ2, PIE_InterruptSource_TZ3, PIE_InterruptSource_EPWM1,
PIE_InterruptSource_EPWM2,
PIE_InterruptSource_EPWM3, PIE_InterruptSource_ECAP1, PIE_InterruptSource_SPIARX,
PIE_InterruptSource_SPIATX,
PIE_InterruptSource_I2CA1, PIE_InterruptSource_I2CA2, PIE_InterruptSource_SCIARX,
PIE_InterruptSource_SCIATX,
PIE_InterruptSource_ADCINT_10_1, PIE_InterruptSource_ADCINT_10_2,
PIE_InterruptSource_ADCINT_3, PIE_InterruptSource_ADCINT_4,
PIE_InterruptSource_ADCINT_5, PIE_InterruptSource_ADCINT_6,
PIE_InterruptSource_ADCINT_7, PIE_InterruptSource_ADCINT_8,
PIE_InterruptSource_XINT_3 }

enum PIE_SubGroupNumber_e {
PIE_SubGroupNumber_1, PIE_SubGroupNumber_2, PIE_SubGroupNumber_3,

PIE_SubGroupNumber_4,
PIE_SubGroupNumber_5, PIE_SubGroupNumber_6, PIE_SubGroupNumber_7,
PIE_SubGroupNumber_8 }

enum PIE_SystemInterrupts_e {
PIE_SystemInterrupts_Reset, PIE_SystemInterrupts_INT1, PIE_SystemInterrupts_INT2,
PIE_SystemInterrupts_INT3,
PIE_SystemInterrupts_INT4, PIE_SystemInterrupts_INT5, PIE_SystemInterrupts_INT6,
PIE_SystemInterrupts_INT7,
PIE_SystemInterrupts_INT8, PIE_SystemInterrupts_INT9, PIE_SystemInterrupts_INT10,
PIE_SystemInterrupts_INT11,
PIE_SystemInterrupts_INT12, PIE_SystemInterrupts_TINT1, PIE_SystemInterrupts_TINT2,
PIE_SystemInterrupts_DATALOG,
PIE_SystemInterrupts_RTOSINT, PIE_SystemInterrupts_EMUINT, PIE_SystemInterrupts_NMI,
PIE_SystemInterrupts_ILLEGAL,
PIE_SystemInterrupts_USER1, PIE_SystemInterrupts_USER2, PIE_SystemInterrupts_USER3,
PIE_SystemInterrupts_USER4,
PIE_SystemInterrupts_USER5, PIE_SystemInterrupts_USER6, PIE_SystemInterrupts_USER7,
PIE_SystemInterrupts_USER8,
PIE_SystemInterrupts_USER9, PIE_SystemInterrupts_USER10, PIE_SystemInterrupts_USER11,
PIE_SystemInterrupts_USER12 }

Functions

void PIE_clearAllFlags (PIE_Handle pieHandle)

void PIE_clearAllInts (PIE_Handle pieHandle)

void PIE_clearInt (PIE_Handle pieHandle, const PIE_GroupNumber_e groupNumber)

void PIE_disable (PIE_Handle pieHandle)

void PIE_disableAllInts (PIE_Handle pieHandle)

void PIE_disableCaptureInt (PIE_Handle pieHandle)

void PIE_disableInt (PIE_Handle pieHandle, const PIE_GroupNumber_e group, const PIE_InterruptSource_e intSource)

void PIE_enable (PIE_Handle pieHandle)

void PIE_enableAdcInt (PIE_Handle pieHandle, const ADC_IntNumber_e intNumber)

void PIE_enableCaptureInt (PIE_Handle pieHandle)

void PIE_enableExtInt (PIE_Handle pieHandle, const CPU_ExtIntNumber_e intNumber)

void PIE_enableInt (PIE_Handle pieHandle, const PIE_GroupNumber_e group, const PIE_InterruptSource_e intSource)

void PIE_enablePwmInt (PIE_Handle pieHandle, const PWM_Number_e pwmNumber)

void PIE_enablePwmTzInt (PIE_Handle pieHandle, const PWM_Number_e pwmNumber)

void PIE_enableTimer0Int (PIE_Handle pieHandle)

void PIE_forceInt (PIE_Handle pieHandle, const PIE_GroupNumber_e group, const PIE_InterruptSource_e intSource)

uint16_t PIE_getExtIntCount (PIE_Handle pieHandle, const CPU_ExtIntNumber_e intNumber)

uint16_t PIE_getIntEnables (PIE_Handle pieHandle, const PIE_GroupNumber_e group)

uint16_t PIE_getIntFlags (PIE_Handle pieHandle, const PIE_GroupNumber_e group)

interrupt void PIE_illegalIsr (void)

PIE_Handle PIE_init (void ∗pMemory, const size_t numBytes)

void PIE_registerPieIntHandler (PIE_Handle pieHandle, const PIE_GroupNumber_e groupNumber, const PIE_SubGroupNumber_e subGroupNumber, const intVec_t vector)

void PIE_registerSystemIntHandler (PIE_Handle pieHandle, const PIE_SystemInterrupts_e systemInt, const intVec_t vector)

void PIE_setDefaultIntVectorTable (PIE_Handle pieHandle)

void PIE_setExtIntPolarity (PIE_Handle pieHandle, const CPU_ExtIntNumber_e intNumber, const PIE_ExtIntPolarity_e polarity)

void PIE_unregisterPieIntHandler (PIE_Handle pieHandle, const PIE_GroupNumber_e groupNumber, const PIE_SubGroupNumber_e subGroupNumber)

void PIE_unregisterSystemIntHandler (PIE_Handle pieHandle, const PIE_SystemInterrupts_e systemInt)

11.1.1 Detailed Description

11.1.2 Enumeration Type Documentation

11.1.2.1 enum **PIE_ExtIntPolarity_e**

Enumeration to define the external interrupt polarity.

Enumerator

PIE_ExtIntPolarity_FallingEdge Denotes an interrupt is generated on the falling edge.

PIE_ExtIntPolarity_RisingEdge Denotes an interrupt is generated on the rising edge.

PIE_ExtIntPolarity_RisingAndFallingEdge Denotes an interrupt is generated on the falling and rising edges.

11.1.2.2 enum **PIE_GroupNumber_e**

Enumeration to define the peripheral interrupt expansion (PIE) group numbers.

Enumerator

    PIE_GroupNumber_1 Denotes PIE group number 1.
    PIE_GroupNumber_2 Denotes PIE group number 2.
    PIE_GroupNumber_3 Denotes PIE group number 3.
    PIE_GroupNumber_4 Denotes PIE group number 4.
    PIE_GroupNumber_5 Denotes PIE group number 5.
    PIE_GroupNumber_6 Denotes PIE group number 6.
    PIE_GroupNumber_7 Denotes PIE group number 7.
    PIE_GroupNumber_8 Denotes PIE group number 8.
    PIE_GroupNumber_9 Denotes PIE group number 9.
    PIE_GroupNumber_10 Denotes PIE group number 10.
    PIE_GroupNumber_11 Denotes PIE group number 11.
    PIE_GroupNumber_12 Denotes PIE group number 12.

11.1.2.3 enum **PIE_InterruptSource_e**

Enumeration to define the peripheral interrupt expansion (PIE) individual interrupt sources.

Enumerator

    PIE_InterruptSource_ADCINT_1_1 Group 1 ADC Interrupt 1.
    PIE_InterruptSource_ADCINT_1_2 Group 1 ADC Interrupt 2.
    PIE_InterruptSource_XINT_1 External Interrupt 1.
    PIE_InterruptSource_XINT_2 External Interrupt 2.
    PIE_InterruptSource_ADCINT_9 ADC Interrupt 9.
    PIE_InterruptSource_TIMER_0 Timer Interrupt 0.
    PIE_InterruptSource_WAKE Wake Up Interrupt.
    PIE_InterruptSource_TZ1 EPWM TZ1 Interrupt.
    PIE_InterruptSource_TZ2 EPWM TZ2 Interrupt.
    PIE_InterruptSource_TZ3 EPWM TZ3 Interrupt.
    PIE_InterruptSource_EPWM1 EPWM 1 Interrupt.
    PIE_InterruptSource_EPWM2 EPWM 2 Interrupt.
    PIE_InterruptSource_EPWM3 EPWM 3 Interrupt.
    PIE_InterruptSource_ECAP1 ECAP 1 Interrupt.
    PIE_InterruptSource_SPIARX SPI A RX Interrupt.
    PIE_InterruptSource_SPIATX SPI A TX Interrupt.
    PIE_InterruptSource_I2CA1 I2C A Interrupt 1.
    PIE_InterruptSource_I2CA2 I2C A Interrupt 2.
    PIE_InterruptSource_SCIARX SCI A RX Interrupt.
    PIE_InterruptSource_SCIATX SCI A TX Interrupt.
    PIE_InterruptSource_ADCINT_10_1 Group 10 ADC Interrupt 1.
    PIE_InterruptSource_ADCINT_10_2 Group 10 ADC Interrupt 2.
    PIE_InterruptSource_ADCINT_3 ADC Interrupt 3.
    PIE_InterruptSource_ADCINT_4 ADC Interrupt 4.
    PIE_InterruptSource_ADCINT_5 ADC Interrupt 5.
    PIE_InterruptSource_ADCINT_6 ADC Interrupt 6.
    PIE_InterruptSource_ADCINT_7 ADC Interrupt 7.
    PIE_InterruptSource_ADCINT_8 ADC Interrupt 8.
    PIE_InterruptSource_XINT_3 External Interrupt 3.

11.1.2.4   enum **PIE_SubGroupNumber_e**

Enumeration to define the peripheral interrupt expansion (PIE) sub-group numbers.

Enumerator

PIE_SubGroupNumber_1 Denotes PIE group number 1.
PIE_SubGroupNumber_2 Denotes PIE group number 2.
PIE_SubGroupNumber_3 Denotes PIE group number 3.
PIE_SubGroupNumber_4 Denotes PIE group number 4.
PIE_SubGroupNumber_5 Denotes PIE group number 5.
PIE_SubGroupNumber_6 Denotes PIE group number 6.
PIE_SubGroupNumber_7 Denotes PIE group number 7.
PIE_SubGroupNumber_8 Denotes PIE group number 8.

11.1.2.5   enum **PIE_SystemInterrupts_e**

Enumeration to define the system interrupts.

Enumerator

PIE_SystemInterrupts_Reset Reset interrupt vector.
PIE_SystemInterrupts_INT1 INT1 interrupt vector.
PIE_SystemInterrupts_INT2 INT2 interrupt vector.
PIE_SystemInterrupts_INT3 INT3 interrupt vector.
PIE_SystemInterrupts_INT4 INT4 interrupt vector.
PIE_SystemInterrupts_INT5 INT5 interrupt vector.
PIE_SystemInterrupts_INT6 INT6 interrupt vector.
PIE_SystemInterrupts_INT7 INT7 interrupt vector.
PIE_SystemInterrupts_INT8 INT8 interrupt vector.
PIE_SystemInterrupts_INT9 INT9 interrupt vector.
PIE_SystemInterrupts_INT10 INT10 interrupt vector.
PIE_SystemInterrupts_INT11 INT11 interrupt vector.
PIE_SystemInterrupts_INT12 INT12 interrupt vector.
PIE_SystemInterrupts_TINT1 INT13 interrupt vector.
PIE_SystemInterrupts_TINT2 INT14 interrupt vector.
PIE_SystemInterrupts_DATALOG DATALOG interrupt vector.
PIE_SystemInterrupts_RTOSINT RTOSINT interrupt vector.
PIE_SystemInterrupts_EMUINT EMUINT interrupt vector.
PIE_SystemInterrupts_NMI NMI interrupt vector.
PIE_SystemInterrupts_ILLEGAL ILLEGAL interrupt vector.
PIE_SystemInterrupts_USER1 USER1 interrupt vector.
PIE_SystemInterrupts_USER2 USER2 interrupt vector.
PIE_SystemInterrupts_USER3 USER3 interrupt vector.
PIE_SystemInterrupts_USER4 USER4 interrupt vector.
PIE_SystemInterrupts_USER5 USER5 interrupt vector.
PIE_SystemInterrupts_USER6 USER6 interrupt vector.
PIE_SystemInterrupts_USER7 USER7 interrupt vector.

PIE_SystemInterrupts_USER8 USER8 interrupt vector.
PIE_SystemInterrupts_USER9 USER9 interrupt vector.
PIE_SystemInterrupts_USER10 USER10 interrupt vector.
PIE_SystemInterrupts_USER11 USER11 interrupt vector.
PIE_SystemInterrupts_USER12 USER12 interrupt vector.

11.1.3 Function Documentation

11.1.3.1 void PIE_clearAllFlags (

PIE_Handle pieHandle)

Clears all the interrupt flags.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

---

11.1.3.2 void PIE_clearAllInts (

PIE_Handle pieHandle)

Clears all the interrupts.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

---

11.1.3.3 void PIE_clearInt (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** groupNumber) `[inline]`

Clears an interrupt defined by group number.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

---

`in` *groupNumber* The group number

References _PIE_Obj_::PIEACK.

11.1.3.4 void PIE_disable (

PIE_Handle pieHandle)

Disables the peripheral interrupt expansion (PIE)

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

---

722.7

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

in *intNumber* The interrupt number

11.1.3.10 void PIE_enableCaptureInt (

PIE_Handle pieHandle)

Enables the capture interrupt.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

11.1.3.11 void PIE_enableExtInt (

PIE_Handle pieHandle,

const **CPU_ExtIntNumber_e** intNumber)

Enables the prescribed external interrupt.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) handle

in *intNumber* The interrupt number

11.1.3.12 void PIE_enableInt (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** group,

const **PIE_InterruptSource_e** intSource)

Enable a specific PIE interrupt.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

in *group* The PIE group an interrupt belongs to

in *intSource* The specific interrupt source to enable

11.1.3.13 void PIE_enablePwmInt (

PIE_Handle pieHandle,

const **PWM_Number_e** pwmNumber)

Enables the PWM interrupt.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) handle

`in` *pwmNumber* The PWM number

11.1.3.14 void PIE_enablePwmTzInt (

PIE_Handle pieHandle,

const **PWM_Number_e** pwmNumber)

Enables the PWM Trip Zone interrupt.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) handle

`in` *pwmNumber* The PWM number

11.1.3.15 void PIE_enableTimer0Int (

PIE_Handle pieHandle)

Enables the Cpu Timer 0 interrupt.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) handle

11.1.3.16 void PIE_forceInt (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** group,

const **PIE_InterruptSource_e** intSource)

Force a specific PIE interrupt.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

`in` *group* The PIE group an interrupt belongs to

`in` *intSource* The specific interrupt source to force

11.1.3.17 uint16_t PIE_getExtIntCount (

PIE_Handle pieHandle,

const **CPU_ExtIntNumber_e** intNumber)

Gets the external interrupt count value.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) handle

in *intNumber* The external interrupt number

Returns The count value

11.1.3.18 uint16_t PIE_getIntEnables (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** group)

Gets PIE interrupt enable values.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

in *group* The PIE group the flags belong to

11.1.3.19 uint16_t PIE_getIntFlags (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** group)

Gets PIE interrupt flag values.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

in *group* The PIE group the flags belong to

11.1.3.20 **PIE_Handle** PIE_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the peripheral interrupt expansion (PIE) object handle.

[1]Parameters in *pMemory* A pointer to the memory for the PIE object

in *numBytes* The number of bytes allocated for the PIE object, bytes

Returns The peripheral interrupt expansion (PIE) object handle

11.1.3.21 void PIE_registerPieIntHandler (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** groupNumber,

const **PIE_SubGroupNumber_e** subGroupNumber,

const **intVec_t** vector)

Registers a handler for a PIE interrupt.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

in *groupNumber* The PIE group an interrupt belongs to

in *subGroupNumber* The PIE subgroup an interrupt belongs to

in *vector* The specific interrupt handler

11.1.3.22 void PIE_registerSystemIntHandler (

PIE_Handle pieHandle,

const **PIE_SystemInterrupts_e** systemInt,

const **intVec_t** vector)

Registers a handler for a PIE interrupt.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

in *systemInt* The system interrupt to register this handler to

in *vector* The specific interrupt handler

11.1.3.23 void PIE_setDefaultIntVectorTable (

PIE_Handle pieHandle)

Initializes the vector table with illegal ISR handlers.

[1]Parameters in *pieHandle* The peripheral interrupt expansion (PIE) object handle

11.1.3.24 void PIE_setExtIntPolarity (

PIE_Handle pieHandle,

const **CPU_ExtIntNumber_e** intNumber,

const **PIE_ExtIntPolarity_e** polarity)

Sets the external interrupt polarity.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) handle

`in` *intNumber* The external interrupt number

`in` *polarity* The signal polarity

11.1.3.25 void PIE_unregisterPieIntHandler (

PIE_Handle pieHandle,

const **PIE_GroupNumber_e** groupNumber,

const **PIE_SubGroupNumber_e** subGroupNumber)

Unregisters a handler for a PIE interrupt.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

`in` *groupNumber* The PIE group an interrupt belongs to

`in` *subGroupNumber* The PIE subgroup an interrupt belongs to

11.1.3.26 void PIE_unregisterSystemIntHandler (

PIE_Handle pieHandle,

const **PIE_SystemInterrupts_e** systemInt)

Unregisters a handler for a PIE interrupt.

[1]Parameters `in` *pieHandle* The peripheral interrupt expansion (PIE) object handle

`in` *systemInt* The system interrupt to unregister

12 Phase Locked Loop (PLL)

The Phase Locked Loop (PLL) API provides functions for configuring the device's PLL as well as other miscellaneous clock functions.

This driver is contained in `f2802x0/common/source/pll.c`, with `f2802x0/common/include/pll.h` containing the API definitions for use by applications.

12.1 PLL

Data Structures

struct _PLL_Obj_

Macros

#define PLL_BASE_ADDR

#define PLL_PLLCR_DIV_BITS

#define PLL_PLLSTS_DIVSEL_BITS

#define PLL_PLLSTS_MCLKCLR_BITS

#define PLL_PLLSTS_MCLKOFF_BITS

#define PLL_PLLSTS_MCLKSTS_BITS

#define PLL_PLLSTS_NORMRDYE_BITS

#define PLL_PLLSTS_OSCOFF_BITS

#define PLL_PLLSTS_PLLLOCKS_BITS

#define PLL_PLLSTS_PLLOFF_BITS

Typedefs

typedef struct _PLL_Obj_ ∗ PLL_Handle

typedef struct _PLL_Obj_ PLL_Obj

Enumerations

enum PLL_ClkStatus_e { PLL_ClkStatus_Normal, PLL_ClkStatus_Missing }

enum PLL_DivideSelect_e { PLL_DivideSelect_ClkIn_by_4, PLL_DivideSelect_ClkIn_by_2, PLL_DivideSelect_ClkIn_by_1 }

enum PLL_LockStatus_e { PLL_LockStatus_Locking, PLL_LockStatus_Done }

enum PLL_Multiplier_e {
PLL_Multiplier_1, PLL_Multiplier_2, PLL_Multiplier_3, PLL_Multiplier_4,
PLL_Multiplier_5, PLL_Multiplier_6, PLL_Multiplier_7, PLL_Multiplier_8,
PLL_Multiplier_9, PLL_Multiplier_10, PLL_Multiplier_11, PLL_Multiplier_12 }

Functions

void PLL_disable (PLL_Handle pllHandle)

void PLL_disableClkDetect (PLL_Handle pllHandle)

void PLL_disableNormRdy (PLL_Handle pllHandle)

void PLL_disableOsc (PLL_Handle pllHandle)

void PLL_enable (PLL_Handle pllHandle)

void PLL_enableClkDetect (PLL_Handle pllHandle)

void PLL_enableNormRdy (PLL_Handle pllHandle)

void PLL_enableOsc (PLL_Handle pllHandle)

PLL_ClkStatus_e PLL_getClkStatus (PLL_Handle pllHandle)

PLL_DivideSelect_e PLL_getDivider (PLL_Handle pllHandle)

PLL_LockStatus_e PLL_getLockStatus (PLL_Handle pllHandle)

PLL_Multiplier_e PLL_getMultiplier (PLL_Handle pllHandle)

PLL_Handle PLL_init (void *pMemory, const size_t numBytes)

void PLL_resetClkDetect (PLL_Handle pllHandle)

void PLL_setDivider (PLL_Handle pllHandle, const PLL_DivideSelect_e divSelect)

void PLL_setLockPeriod (PLL_Handle pllHandle, const uint16_t lockPeriod)

void PLL_setMultiplier (PLL_Handle pllHandle, const PLL_Multiplier_e freq)

void PLL_setup (PLL_Handle pllHandle, const PLL_Multiplier_e clkMult, const PLL_DivideSelect_e divSelect)

12.1.1 Detailed Description

12.1.2 Enumeration Type Documentation

12.1.2.1 enum **PLL_ClkStatus_e**

Enumeration to define the phase lock loop (PLL) clock status.

Enumerator
>   ***PLL_ClkStatus_Normal***   Denotes a normal clock.
>   ***PLL_ClkStatus_Missing***   Denotes a missing clock.

12.1.2.2 enum **PLL_DivideSelect_e**

Enumeration to define the phase lock loop (PLL) divide select.

Enumerator
>   ***PLL_DivideSelect_ClkIn_by_4***   Denotes a divide select of CLKIN/4.
>   ***PLL_DivideSelect_ClkIn_by_2***   Denotes a divide select of CLKIN/2.
>   ***PLL_DivideSelect_ClkIn_by_1***   Denotes a divide select of CLKIN/1.

12.1.2.3 enum **PLL_LockStatus_e**

Enumeration to define the phase lock loop (PLL) clock lock status.

Enumerator
>   ***PLL_LockStatus_Locking***   Denotes that the system is locking to the clock.
>   ***PLL_LockStatus_Done***   Denotes that the system is locked to the clock.

12.1.2.4 enum **PLL_Multiplier_e**

Enumeration to define the phase lock loop (PLL) clock frequency.

Enumerator
>   ***PLL_Multiplier_1***   Denotes a multiplier of 1.
>   ***PLL_Multiplier_2***   Denotes a multiplier of 2.
>   ***PLL_Multiplier_3***   Denotes a multiplier of 3.
>   ***PLL_Multiplier_4***   Denotes a multiplier of 4.
>   ***PLL_Multiplier_5***   Denotes a multiplier of 5.
>   ***PLL_Multiplier_6***   Denotes a multiplier of 6.
>   ***PLL_Multiplier_7***   Denotes a multiplier of 7.
>   ***PLL_Multiplier_8***   Denotes a multiplier of 8.
>   ***PLL_Multiplier_9***   Denotes a multiplier of 9.
>   ***PLL_Multiplier_10***   Denotes a multiplier of 10.
>   ***PLL_Multiplier_11***   Denotes a multiplier of 11.
>   ***PLL_Multiplier_12***   Denotes a multiplier of 12.

12.1.3 Function Documentation

12.1.3.1 void PLL_disable (

PLL_Handle pllHandle)

Disables the phase lock loop (PLL)

[1]Parameters `in` *pllHandle* The phase lock loop (PLL) object handle

12.1.3.2 void PLL_disableClkDetect (

PLL_Handle pllHandle)

Disables the clock detect logic.

[1]Parameters `in` *pllHandle* The phase lock loop (PLL) object handle

12.1.3.3 void PLL_disableNormRdy (

PLL_Handle pllHandle)

Disables the NORMRDY signal.

[1]Parameters `in` *pllHandle* The phase lock loop (PLL) object handle

12.1.3.4 void PLL_disableOsc (

PLL_Handle pllHandle)

Disables the oscillator.

[1]Parameters `in` *pllHandle* The phase lock loop (PLL) object handle

12.1.3.5 void PLL_enable (

PLL_Handle pllHandle)

Enables the phase lock loop (PLL)

[1]Parameters `in` *pllHandle* The phase lock loop (PLL) object handle

12.1.3.6 void PLL_enableClkDetect (

722.7

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

Returns The lock status

12.1.3.12 **PLL_Multiplier_e** PLL_getMultiplier (

PLL_Handle pllHandle)

Gets the phase lock loop (PLL) clock frequency.

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

Returns The clock frequency

12.1.3.13 **PLL_Handle** PLL_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the phase lock loop (PLL) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the PLL registers

in *numBytes* The number of bytes allocated for the PLL object, bytes

Returns The phase lock loop (PLL) object handle

12.1.3.14 void PLL_resetClkDetect (

PLL_Handle pllHandle)

Resets the phase lock loop (PLL) clock detect logic.

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

12.1.3.15 void PLL_setDivider (

PLL_Handle pllHandle,

const **PLL_DivideSelect_e** divSelect)

Sets the phase lock loop (PLL) divide select value.

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

in *divSelect* The divide select value

12.1.3.16 void PLL_setLockPeriod (

PLL_Handle pllHandle,

const uint16_t lockPeriod)

Sets the phase lock loop (PLL) lock time.

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

in *lockPeriod* The lock period, cycles

12.1.3.17 void PLL_setMultiplier (

PLL_Handle pllHandle,

const **PLL_Multiplier_e** freq)

Sets the phase lock loop (PLL) clock frequency.

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

in *freq* The clock frequency

12.1.3.18 void PLL_setup (

PLL_Handle pllHandle,

const **PLL_Multiplier_e** clkMult,

const **PLL_DivideSelect_e** divSelect)

Sets the phase lock loop (PLL) divider and multiplier.

[1]Parameters in *pllHandle* The phase lock loop (PLL) object handle

in *clkMult* The clock multiplier value

in *divSelect* The divide select value

13 Pulse Width Modulator (PWM)

The pulse width modulation peripheral (PWM) APIs provide functions for configuring and updating the PWM peripherals on this device.

This driver is contained in `f2802x0/common/source/pwm.c`, with `f2802x0/common/include/pwm.h` containing the API definitions for use by applications.

13.1 PWM

Data Structures

struct _PWM_Obj_

Macros

#define PWM_AQCTL_CAD_BITS

#define PWM_AQCTL_CAU_BITS

#define PWM_AQCTL_CBD_BITS

#define PWM_AQCTL_CBU_BITS

#define PWM_AQCTL_PRD_BITS

#define PWM_AQCTL_ZRO_BITS

#define PWM_CMPCTL_LOADAMODE_BITS

#define PWM_CMPCTL_LOADBMODE_BITS

#define PWM_CMPCTL_SHDWAFULL_BITS

#define PWM_CMPCTL_SHDWAMODE_BITS

#define PWM_CMPCTL_SHDWBFULL_BITS

#define PWM_CMPCTL_SHDWBMODE_BITS

#define PWM_DBCTL_HALFCYCLE_BITS

#define PWM_DBCTL_INMODE_BITS

#define PWM_DBCTL_OUTMODE_BITS

#define PWM_DBCTL_POLSEL_BITS

#define PWM_DCFCTL_BLANKE_BITS

#define PWM_DCFCTL_BLANKINV_BITS

#define PWM_DCFCTL_PULSESEL_BITS

#define PWM_DCFCTL_SRCSEL_BITS

#define PWM_DCTRIPSEL_DCAHCOMPSEL_BITS

#define PWM_DCTRIPSEL_DCALCOMPSEL_BITS

#define PWM_DCTRIPSEL_DCBHCOMPSEL_BITS

#define PWM_DCTRIPSEL_DCBLCOMPSEL_BITS

#define PWM_ePWM1_BASE_ADDR

#define PWM_ePWM2_BASE_ADDR

#define PWM_ePWM3_BASE_ADDR

#define PWM_ETCLR_INT_BITS

#define PWM_ETCLR_SOCA_BITS

#define PWM_ETCLR_SOCB_BITS

#define PWM_ETPS_INTCNT_BITS

#define PWM_ETPS_INTPRD_BITS

#define PWM_ETPS_SOCACNT_BITS

#define PWM_ETPS_SOCAPRD_BITS

#define PWM_ETPS_SOCBCNT_BITS

#define PWM_ETPS_SOCBPRD_BITS

#define PWM_ETSEL_INTEN_BITS

#define PWM_ETSEL_INTSEL_BITS

#define PWM_ETSEL_SOCAEN_BITS

#define PWM_ETSEL_SOCASEL_BITS

#define PWM_ETSEL_SOCBEN_BITS

#define PWM_ETSEL_SOCBSEL_BITS

#define PWM_PCCTL_CHPDUTY_BITS

#define PWM_PCCTL_CHPEN_BITS

#define PWM_PCCTL_CHPFREQ_BITS

#define PWM_PCCTL_OSHTWTH_BITS

#define PWM_TBCTL_CLKDIV_BITS

#define PWM_TBCTL_CTRMODE_BITS

#define PWM_TBCTL_FREESOFT_BITS

#define PWM_TBCTL_HSPCLKDIV_BITS

#define PWM_TBCTL_PHSDIR_BITS

#define PWM_TBCTL_PHSEN_BITS

#define PWM_TBCTL_PRDLD_BITS

#define PWM_TBCTL_SWFSYNC_BITS

#define PWM_TBCTL_SYNCOSEL_BITS

#define PWM_TZCLR_CBC_BITS

#define PWM_TZCLR_DCAEVT1_BITS

#define PWM_TZCLR_DCAEVT2_BITS

#define PWM_TZCLR_DCBEVT1_BITS

#define PWM_TZCLR_DCBEVT2_BITS

#define PWM_TZCLR_INT_BITS

#define PWM_TZCLR_OST_BITS

#define PWM_TZCTL_DCAEVT1_BITS

#define PWM_TZCTL_DCAEVT2_BITS

#define PWM_TZCTL_DCBEVT1_BITS

#define PWM_TZCTL_DCBEVT2_BITS

#define PWM_TZCTL_TZA_BITS

#define PWM_TZCTL_TZB_BITS

#define PWM_TZDCSEL_DCAEVT1_BITS

#define PWM_TZDCSEL_DCAEVT2_BITS

#define PWM_TZDCSEL_DCBEVT1_BITS

#define PWM_TZDCSEL_DCBEVT2_BITS

#define PWM_TZFRC_CBC_BITS

#define PWM_TZFRC_DCAEVT1_BITS

#define PWM_TZFRC_DCAEVT2_BITS

#define PWM_TZFRC_DCBEVT1_BITS

#define PWM_TZFRC_DCBEVT2_BITS

#define PWM_TZFRC_OST_BITS

Typedefs

typedef struct _PWM_Obj_ ∗ PWM_Handle

typedef struct _PWM_Obj_ PWM_Obj

Enumerations

enum PWM_ActionQual_e

enum PWM_ChoppingClkFreq_e

enum PWM_ChoppingDutyCycle_e

enum PWM_ChoppingPulseWidth_e

enum PWM_ClkDiv_e

enum PWM_CounterMode_e

enum PWM_DeadBandInputMode_e

enum PWM_DeadBandOutputMode_e

enum PWM_DeadBandPolarity_e

enum PWM_DigitalCompare_FilterSrc_e

enum PWM_DigitalCompare_Input_e

enum PWM_DigitalCompare_InputSel_e

enum PWM_DigitalCompare_PulseSel_e

enum PWM_HspClkDiv_e

enum PWM_IntMode_e

enum PWM_IntPeriod_e

enum PWM_LoadMode_e

enum PWM_Number_e

enum PWM_PeriodLoad_e

enum PWM_PhaseDir_e

enum PWM_RunMode_e

enum PWM_ShadowMode_e

enum PWM_ShadowStatus_e

enum PWM_SocPeriod_e

enum PWM_SocPulseSrc_e

enum PWM_SyncMode_e

enum PWM_TripZoneDCEventSel_e {
PWM_TripZoneDCEventSel_Disabled, PWM_TripZoneDCEventSel_DCxHL_DCxLX,
PWM_TripZoneDCEventSel_DCxHH_DCxLX, PWM_TripZoneDCEventSel_DCxHx_DCxLL,
PWM_TripZoneDCEventSel_DCxHx_DCxLH, PWM_TripZoneDCEventSel_DCxHL_DCxLH }

enum PWM_TripZoneFlag_e {
PWM_TripZoneFlag_Global, PWM_TripZoneFlag_CBC, PWM_TripZoneFlag_OST,
PWM_TripZoneFlag_DCAEVT1,
PWM_TripZoneFlag_DCAEVT2, PWM_TripZoneFlag_DCBEVT1, PWM_TripZoneFlag_DCBEVT2
}

enum PWM_TripZoneSrc_e

enum PWM_TripZoneState_e

Functions

void PWM_clearIntFlag (PWM_Handle pwmHandle)

void PWM_clearOneShotTrip (PWM_Handle pwmHandle)

void PWM_clearSocAFlag (PWM_Handle pwmHandle)

void PWM_clearSocBFlag (PWM_Handle pwmHandle)

void PWM_clearTripZone (PWM_Handle pwmHandle, const PWM_TripZoneFlag_e tripZoneFlag)

void PWM_decrementDeadBandFallingEdgeDelay (PWM_Handle pwmHandle)

void PWM_decrementDeadBandRisingEdgeDelay (PWM_Handle pwmHandle)

void PWM_disableChopping (PWM_Handle pwmHandle)

void PWM_disableCounterLoad (PWM_Handle pwmHandle)

void PWM_disableDeadBand (PWM_Handle pwmHandle)

void PWM_disableDeadBandHalfCycle (PWM_Handle pwmHandle)

void PWM_disableDigitalCompareBlankingWindow (PWM_Handle pwmHandle)

void PWM_disableDigitalCompareBlankingWindowInversion (PWM_Handle pwmHandle)

void PWM_disableInt (PWM_Handle pwmHandle)

void PWM_disableSocAPulse (PWM_Handle pwmHandle)

void PWM_disableSocBPulse (PWM_Handle pwmHandle)

void PWM_disableTripZoneInt (PWM_Handle pwmHandle, const PWM_TripZoneFlag_e interrupt-Source)

void PWM_disableTripZones (PWM_Handle pwmHandle)

void PWM_disableTripZoneSrc (PWM_Handle pwmHandle, const PWM_TripZoneSrc_e src)

void PWM_enableChopping (PWM_Handle pwmHandle)

void PWM_enableCounterLoad (PWM_Handle pwmHandle)

void PWM_enableDeadBandHalfCycle (PWM_Handle pwmHandle)

void PWM_enableDigitalCompareBlankingWindow (PWM_Handle pwmHandle)

void PWM_enableDigitalCompareBlankingWindowInversion (PWM_Handle pwmHandle)

void PWM_enableInt (PWM_Handle pwmHandle)

void PWM_enableSocAPulse (PWM_Handle pwmHandle)

void PWM_enableSocBPulse (PWM_Handle pwmHandle)

void PWM_enableTripZoneInt (PWM_Handle pwmHandle, const PWM_TripZoneFlag_e interrupt-Source)

void PWM_enableTripZoneSrc (PWM_Handle pwmHandle, const PWM_TripZoneSrc_e src)

uint16_t PWM_getCmpA (PWM_Handle pwmHandle)

uint16_t PWM_getCmpB (PWM_Handle pwmHandle)

uint16_t PWM_getDeadBandFallingEdgeDelay (PWM_Handle pwmHandle)

uint16_t PWM_getDeadBandRisingEdgeDelay (PWM_Handle pwmHandle)

uint16_t PWM_getIntCount (PWM_Handle pwmHandle)

uint16_t PWM_getPeriod (PWM_Handle pwmHandle)

uint16_t PWM_getSocACount (PWM_Handle pwmHandle)

uint16_t PWM_getSocBCount (PWM_Handle pwmHandle)

void PWM_incrementDeadBandFallingEdgeDelay (PWM_Handle pwmHandle)

void PWM_incrementDeadBandRisingEdgeDelay (PWM_Handle pwmHandle)

PWM_Handle PWM_init (void ∗pMemory, const size_t numBytes)

void PWM_setActionQual_CntDown_CmpA_PwmA (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntDown_CmpA_PwmB (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntDown_CmpB_PwmA (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntDown_CmpB_PwmB (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntUp_CmpA_PwmA (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntUp_CmpA_PwmB (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntUp_CmpB_PwmA (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_CntUp_CmpB_PwmB (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_Period_PwmA (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_Period_PwmB (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_Zero_PwmA (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setActionQual_Zero_PwmB (PWM_Handle pwmHandle, const PWM_ActionQual_e actionQual)

void PWM_setChoppingClkFreq (PWM_Handle pwmHandle, const PWM_ChoppingClkFreq_e clkFreq)

void PWM_setChoppingDutyCycle (PWM_Handle pwmHandle, const PWM_ChoppingDutyCycle_e dutyCycle)

void PWM_setChoppingPulseWidth (PWM_Handle pwmHandle, const PWM_ChoppingPulseWidth_e pulseWidth)

void PWM_setClkDiv (PWM_Handle pwmHandle, const PWM_ClkDiv_e clkDiv)

void PWM_setCmpA (PWM_Handle pwmHandle, const uint16_t pwmData)

void PWM_setCmpB (PWM_Handle pwmHandle, const uint16_t pwmData)

void PWM_setCount (PWM_Handle pwmHandle, const uint16_t count)

void PWM_setCounterMode (PWM_Handle pwmHandle, const PWM_CounterMode_e counterMode)

void PWM_setDeadBandFallingEdgeDelay (PWM_Handle pwmHandle, const uint16_t delay)

void PWM_setDeadBandInputMode (PWM_Handle pwmHandle, const PWM_DeadBandInputMode_e inputMode)

void PWM_setDeadBandOutputMode (PWM_Handle pwmHandle, const PWM_DeadBandOutputMode_e outputMode)

void PWM_setDeadBandPolarity (PWM_Handle pwmHandle, const PWM_DeadBandPolarity_e polarity)

void PWM_setDeadBandRisingEdgeDelay (PWM_Handle pwmHandle, const uint16_t delay)

void PWM_setDigitalCompareAEvent1 (PWM_Handle pwmHandle, const bool_t selectFilter, const bool_t disableSync, const bool_t enableSoc, const bool_t generateSync)

void PWM_setDigitalCompareAEvent2 (PWM_Handle pwmHandle, const bool_t selectFilter, const bool_t disableSync)

void PWM_setDigitalCompareBEvent1 (PWM_Handle pwmHandle, const bool_t selectFilter, const bool_t disableSync, const bool_t enableSoc, const bool_t generateSync)

void PWM_setDigitalCompareBEvent2 (PWM_Handle pwmHandle, const bool_t selectFilter, const bool_t disableSync)

void PWM_setDigitalCompareBlankingPulse (PWM_Handle pwmHandle, const PWM_DigitalCompare_PulseSel_e pulseSelect)

void PWM_setDigitalCompareFilterOffset (PWM_Handle pwmHandle, const uint16_t offset)

void PWM_setDigitalCompareFilterSource (PWM_Handle pwmHandle, const PWM_DigitalCompare_FilterSrc_e input)

void PWM_setDigitalCompareFilterWindow (PWM_Handle pwmHandle, const uint16_t window)

void PWM_setDigitalCompareInput (PWM_Handle pwmHandle, const PWM_DigitalCompare_Input_e input, const PWM_DigitalCompare_InputSel_e inputSel)

void PWM_setHighSpeedClkDiv (PWM_Handle pwmHandle, const PWM_HspClkDiv_e clkDiv)

void PWM_setIntMode (PWM_Handle pwmHandle, const PWM_IntMode_e intMode)

void PWM_setIntPeriod (PWM_Handle pwmHandle, const PWM_IntPeriod_e intPeriod)

void PWM_setLoadMode_CmpA (PWM_Handle pwmHandle, const PWM_LoadMode_e loadMode)

void PWM_setLoadMode_CmpB (PWM_Handle pwmHandle, const PWM_LoadMode_e loadMode)

void PWM_setOneShotTrip (PWM_Handle pwmHandle)

void PWM_setPeriod (PWM_Handle pwmHandle, const uint16_t period)

void PWM_setPeriodLoad (PWM_Handle pwmHandle, const PWM_PeriodLoad_e periodLoad)

void PWM_setPhase (PWM_Handle pwmHandle, const uint16_t phase)

void PWM_setPhaseDir (PWM_Handle pwmHandle, const PWM_PhaseDir_e phaseDir)

void PWM_setRunMode (PWM_Handle pwmHandle, const PWM_RunMode_e runMode)

void PWM_setShadowMode_CmpA (PWM_Handle pwmHandle, const PWM_ShadowMode_e shadowMode)

void PWM_setShadowMode_CmpB (PWM_Handle pwmHandle, const PWM_ShadowMode_e shadowMode)

void PWM_setSocAPeriod (PWM_Handle pwmHandle, const PWM_SocPeriod_e intPeriod)

void PWM_setSocAPulseSrc (PWM_Handle pwmHandle, const PWM_SocPulseSrc_e pulseSrc)

void PWM_setSocBPeriod (PWM_Handle pwmHandle, const PWM_SocPeriod_e intPeriod)

void PWM_setSocBPulseSrc (PWM_Handle pwmHandle, const PWM_SocPulseSrc_e pulseSrc)

void PWM_setSwSync (PWM_Handle pwmHandle)

void PWM_setSyncMode (PWM_Handle pwmHandle, const PWM_SyncMode_e syncMode)

void PWM_setTripZoneDCEventSelect_DCAEVT1 (PWM_Handle pwmHandle, const PWM_TripZoneDCEventSel_e tripZoneEvent)

void PWM_setTripZoneDCEventSelect_DCAEVT2 (PWM_Handle pwmHandle, const PWM_TripZoneDCEventSel_e tripZoneEvent)

void PWM_setTripZoneDCEventSelect_DCBEVT1 (PWM_Handle pwmHandle, const PWM_TripZoneDCEventSel_e tripZoneEvent)

void PWM_setTripZoneDCEventSelect_DCBEVT2 (PWM_Handle pwmHandle, const PWM_TripZoneDCEventSel_e tripZoneEvent)

void PWM_setTripZoneState_DCAEVT1 (PWM_Handle pwmHandle, const PWM_TripZoneState_e tripZoneState)

void PWM_setTripZoneState_DCAEVT2 (PWM_Handle pwmHandle, const PWM_TripZoneState_e tripZoneState)

void PWM_setTripZoneState_DCBEVT1 (PWM_Handle pwmHandle, const PWM_TripZoneState_e tripZoneState)

void PWM_setTripZoneState_DCBEVT2 (PWM_Handle pwmHandle, const PWM_TripZoneState_e tripZoneState)

void PWM_setTripZoneState_TZA (PWM_Handle pwmHandle, const PWM_TripZoneState_e tripZoneState)

void PWM_setTripZoneState_TZB (PWM_Handle pwmHandle, const PWM_TripZoneState_e tripZoneState)

void PWM_write_CmpA (PWM_Handle pwmHandle, const int16_t pwmData)

void PWM_write_CmpB (PWM_Handle pwmHandle, const int16_t pwmData)

13.1.1 Detailed Description

13.1.2 Enumeration Type Documentation

13.1.2.1 enum **PWM_TripZoneDCEventSel_e**

Enumeration to define the pulse width modulation (PWM) trip zone event selections.

Enumerator

PWM_TripZoneDCEventSel_Disabled Event Disabled.
PWM_TripZoneDCEventSel_DCxHL_DCxLX Compare H = Low, Compare L = Don't Care.
PWM_TripZoneDCEventSel_DCxHH_DCxLX Compare H = High, Compare L = Don't Care.

PWM_TripZoneDCEventSel_DCxHx_DCxLL Compare H = Don't Care, Compare L = Low.
PWM_TripZoneDCEventSel_DCxHx_DCxLH Compare H = Don't Care, Compare L = High.

PWM_TripZoneDCEventSel_DCxHL_DCxLH Compare H = Low, Compare L = High.

13.1.2.2 enum **PWM_TripZoneFlag_e**

Enumeration to define the pulse width modulation (PWM) trip zone states.

Enumerator

PWM_TripZoneFlag_Global Global Trip Zone flag.
PWM_TripZoneFlag_CBC Cycle by cycle Trip Zone flag.
PWM_TripZoneFlag_OST One Shot Trip Zone flag.
PWM_TripZoneFlag_DCAEVT1 Digital Compare A Event 1 Trip Zone flag.
PWM_TripZoneFlag_DCAEVT2 Digital Compare A Event 2 Trip Zone flag.
PWM_TripZoneFlag_DCBEVT1 Digital Compare B Event 1 Trip Zone flag.
PWM_TripZoneFlag_DCBEVT2 Digital Compare B Event 2 Trip Zone flag.

13.1.3 Function Documentation

13.1.3.1 void PWM_clearIntFlag (

PWM_Handle pwmHandle) `[inline]`

Clears the pulse width modulation (PWM) interrupt flag.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

References _PWM_Obj_::ETCLR, and PWM_ETCLR_INT_BITS.

13.1.3.2 void PWM_clearOneShotTrip (

PWM_Handle pwmHandle) `[inline]`

Clears the pulse width modulation (PWM) one shot trip.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

---

References DISABLE_PROTECTED_REGISTER_WRITE_MODE, EN-ABLE_PROTECTED_REGISTER_WRITE_MODE, PWM_TZCLR_OST_BITS, and _PWM_Obj_::TZCLR.

13.1.3.3   void PWM_clearSocAFlag (

PWM_Handle pwmHandle) `[inline]`

Clears the pulse width modulation (PWM) start of conversion (SOC) A flag.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

---

References _PWM_Obj_::ETCLR, and PWM_ETCLR_SOCA_BITS.

13.1.3.4   void PWM_clearSocBFlag (

PWM_Handle pwmHandle) `[inline]`

Clears the pulse width modulation (PWM) start of conversion (SOC) B flag.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

---

References _PWM_Obj_::ETCLR, and PWM_ETCLR_SOCB_BITS.

13.1.3.5   void PWM_clearTripZone (

PWM_Handle pwmHandle,

const **PWM_TripZoneFlag_e** tripZoneFlag)

Clears the trip zone (TZ) flag specified.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

---

`in` *tripZoneFlag* The trip zone flag to clear

13.1.3.6   void PWM_decrementDeadBandFallingEdgeDelay (

PWM_Handle pwmHandle)

Decrement the dead band falling edge delay.

---

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.7   void PWM_decrementDeadBandRisingEdgeDelay (

PWM_Handle pwmHandle)

Decrement the dead band rising edge delay.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.8   void PWM_disableChopping (

PWM_Handle pwmHandle)

Disables the pulse width modulation (PWM) chopping.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.9   void PWM_disableCounterLoad (

PWM_Handle pwmHandle)

Disables the pulse width modulation (PWM) counter loading from the phase register.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.10 void PWM_disableDeadBand (

PWM_Handle pwmHandle)

Disables the pulse width modulation (PWM) deadband.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.11 void PWM_disableDeadBandHalfCycle (

PWM_Handle pwmHandle)

Disables the pulse width modulation (PWM) deadband half cycle clocking.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

722.7

const **PWM_TripZoneFlag_e** interruptSource)

Disables the pulse width modulation (PWM) trip zones interrupts.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *interruptSource* The interrupt source to disable

13.1.3.18 void PWM_disableTripZones (

PWM_Handle pwmHandle)

Disables the pulse width modulation (PWM) trip zones.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.19 void PWM_disableTripZoneSrc (

PWM_Handle pwmHandle,

const **PWM_TripZoneSrc_e** src)

Disable the pulse width modulation (PWM) trip zone source.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *src* The pulse width modulation (PWM) trip zone source

13.1.3.20 void PWM_enableChopping (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) chopping.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.21 void PWM_enableCounterLoad (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) counter loading from the phase register.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.22 void PWM_enableDeadBandHalfCycle (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) deadband half cycle clocking.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.23 void PWM_enableDigitalCompareBlankingWindow (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) digital compare blanking window.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.24 void PWM_enableDigitalCompareBlankingWindowInversion (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) digital compare blanking window inversion.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.25 void PWM_enableInt (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) interrupt.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.26 void PWM_enableSocAPulse (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) start of conversion (SOC) A pulse generation.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.27 void PWM_enableSocBPulse (

PWM_Handle pwmHandle)

Enables the pulse width modulation (PWM) start of conversion (SOC) B pulse generation.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.28 void PWM_enableTripZoneInt (

PWM_Handle pwmHandle,

const **PWM_TripZoneFlag_e** interruptSource)

Enables the pulse width modulation (PWM) trip zones interrupts.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *interruptSource* The interrupt source to enable

13.1.3.29 void PWM_enableTripZoneSrc (

PWM_Handle pwmHandle,

const **PWM_TripZoneSrc_e** src)

Enable the pulse width modulation (PWM) trip zone source.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *src* The pulse width modulation (PWM) trip zone source

13.1.3.30 uint16_t PWM_getCmpA (

PWM_Handle pwmHandle) `[inline]`

Gets the pulse width modulation (PWM) data value from the Counter Compare A hardware.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The PWM compare data value

References _PWM_Obj_::CMPA.

13.1.3.31 uint16_t PWM_getCmpB (

PWM_Handle pwmHandle) `[inline]`

Gets the pulse width modulation (PWM) data value from the Counter Compare B hardware.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The PWM compare data value

References _PWM_Obj_::CMPB.

13.1.3.32 uint16_t PWM_getDeadBandFallingEdgeDelay (

PWM_Handle pwmHandle)

Gets the pulse width modulation (PWM) deadband falling edge delay.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The delay

13.1.3.33 uint16_t PWM_getDeadBandRisingEdgeDelay (

PWM_Handle pwmHandle)

Gets the pulse width modulation (PWM) deadband rising edge delay.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The delay

13.1.3.34 uint16_t PWM_getIntCount (

PWM_Handle pwmHandle)

Gets the pulse width modulation (PWM) interrupt event count.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The interrupt event count

13.1.3.35 uint16_t PWM_getPeriod (

PWM_Handle pwmHandle) `[inline]`

Gets the pulse width modulation (PWM) period value.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The pwm period value

References _PWM_Obj_::TBPRD.

13.1.3.36 uint16_t PWM_getSocACount (

PWM_Handle pwmHandle)

Gets the pulse width modulation (PWM) start of conversion (SOC) A count.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The SOC A count

13.1.3.37 uint16_t PWM_getSocBCount (

PWM_Handle pwmHandle)

Gets the pulse width modulation (PWM) start of conversion (SOC) B count.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

Returns The SOC B count

13.1.3.38 void PWM_incrementDeadBandFallingEdgeDelay (

PWM_Handle pwmHandle)

Increment the dead band falling edge delay.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.39 void PWM_incrementDeadBandRisingEdgeDelay (

PWM_Handle pwmHandle)

Increment the dead band rising edge delay.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.40 **PWM_Handle** PWM_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the pulse width modulation (PWM) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the PWM registers

in *numBytes* The number of bytes allocated for the PWM object, bytes

Returns The pulse width modulation (PWM) object handle

13.1.3.41 void PWM_setActionQual_CntDown_CmpA_PwmA (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM A when the counter equals CMPA and the counter is decrementing.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *actionQual* The action qualifier

13.1.3.42 void PWM_setActionQual_CntDown_CmpA_PwmB (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM B when the counter equals CMPA and the counter is decrementing.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *actionQual* The action qualifier

13.1.3.43 void PWM_setActionQual_CntDown_CmpB_PwmA (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM A when the counter equals CMPB and the counter is decrementing.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *actionQual* The action qualifier

13.1.3.44 void PWM_setActionQual_CntDown_CmpB_PwmB (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM B when the counter equals CMPB and the counter is decrementing.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *actionQual* The action qualifier

13.1.3.45 void PWM_setActionQual_CntUp_CmpA_PwmA (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM A when the counter equals CMPA and the counter is incrementing.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.46 void PWM_setActionQual_CntUp_CmpA_PwmB (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM B when the counter equals CMPA and the counter is incrementing.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.47 void PWM_setActionQual_CntUp_CmpB_PwmA (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM A when the counter equals CMPB and the counter is incrementing.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.48 void PWM_setActionQual_CntUp_CmpB_PwmB (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM B when the counter equals CMPB and the counter is incrementing.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.49 void PWM_setActionQual_Period_PwmA (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM A when the counter equals the period.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.50 void PWM_setActionQual_Period_PwmB (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM B when the counter equals the period.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.51 void PWM_setActionQual_Zero_PwmA (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

Sets the pulse width modulation (PWM) object action for PWM A when the counter equals the zero.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *actionQual* The action qualifier

13.1.3.52 void PWM_setActionQual_Zero_PwmB (

PWM_Handle pwmHandle,

const **PWM_ActionQual_e** actionQual)

> Sets the pulse width modulation (PWM) object action for PWM B when the counter equals the zero.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> in *actionQual* The action qualifier

13.1.3.53 void PWM_setChoppingClkFreq (

PWM_Handle pwmHandle,

const **PWM_ChoppingClkFreq_e** clkFreq)

> Sets the pulse width modulation (PWM) chopping clock frequency.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> in *clkFreq* The clock frequency

13.1.3.54 void PWM_setChoppingDutyCycle (

PWM_Handle pwmHandle,

const **PWM_ChoppingDutyCycle_e** dutyCycle)

> Sets the pulse width modulation (PWM) chopping clock duty cycle.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> in *dutyCycle* The duty cycle

13.1.3.55 void PWM_setChoppingPulseWidth (

PWM_Handle pwmHandle,

const **PWM_ChoppingPulseWidth_e** pulseWidth)

> Sets the pulse width modulation (PWM) chopping clock pulse width.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> in *pulseWidth* The pulse width

13.1.3.56 void PWM_setClkDiv (

PWM_Handle pwmHandle,

const **PWM_ClkDiv_e** clkDiv)

Sets the pulse width modulation (PWM) clock divisor.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *clkDiv* The clock divisor

13.1.3.57 void PWM_setCmpA (

PWM_Handle pwmHandle,

const uint16_t pwmData) `[inline]`

Writes the pulse width modulation (PWM) data value to the Counter Compare A hardware.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *pwmData* The PWM data value

References _PWM_Obj_::CMPA.

13.1.3.58 void PWM_setCmpB (

PWM_Handle pwmHandle,

const uint16_t pwmData) `[inline]`

Writes the pulse width modulation (PWM) data value to the Counter Compare B hardware.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *pwmData* The PWM data value

References _PWM_Obj_::CMPB.

13.1.3.59 void PWM_setCount (

PWM_Handle pwmHandle,

const uint16_t count)

Sets the pulse width modulation (PWM) count.

[1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

`in` *count* The count

13.1.3.60 void PWM_setCounterMode (

PWM_Handle pwmHandle,

const **PWM_CounterMode_e** counterMode)

Sets the pulse width modulation (PWM) counter mode.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *counterMode* The count mode

13.1.3.61 void PWM_setDeadBandFallingEdgeDelay (

PWM_Handle pwmHandle,

const uint16_t delay)

Sets the pulse width modulation (PWM) deadband falling edge delay.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *delay* The delay

13.1.3.62 void PWM_setDeadBandInputMode (

PWM_Handle pwmHandle,

const **PWM_DeadBandInputMode_e** inputMode)

Sets the pulse width modulation (PWM) deadband input mode.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *inputMode* The input mode

13.1.3.63 void PWM_setDeadBandOutputMode (

PWM_Handle pwmHandle,

const **PWM_DeadBandOutputMode_e** outputMode)

Sets the pulse width modulation (PWM) deadband output mode.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *outputMode* The output mode

13.1.3.64 void PWM_setDeadBandPolarity (

PWM_Handle pwmHandle,

const **PWM_DeadBandPolarity_e** polarity)

Sets the pulse width modulation (PWM) deadband polarity.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *polarity* The polarity

13.1.3.65 void PWM_setDeadBandRisingEdgeDelay (

PWM_Handle pwmHandle,

const uint16_t delay)

Sets the pulse width modulation (PWM) deadband rising edge delay.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *delay* The delay

13.1.3.66 void PWM_setDigitalCompareAEvent1 (

PWM_Handle pwmHandle,

const bool_t selectFilter,

const bool_t disableSync,

const bool_t enableSoc,

const bool_t generateSync)

Sets the pulse width modulation (PWM) digital compare A event 1 source parameters.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *selectFilter* Select filter output if true

in *disableSync* Asynchronous if true

in *enableSoc* Enable SOC generation if true

in *generateSync* Generate SYNC if true

722.7

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *selectFilter* Select filter output if true

in *disableSync* Asynchronous if true

13.1.3.70 void PWM_setDigitalCompareBlankingPulse (

PWM_Handle pwmHandle,

const **PWM_DigitalCompare_PulseSel_e** pulseSelect)

Sets the pulse width modulation (PWM) digital compare blanking pulse.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *pulseSelect* The pulse selection

13.1.3.71 void PWM_setDigitalCompareFilterOffset (

PWM_Handle pwmHandle,

const uint16_t offset)

Sets the pulse width modulation (PWM) digital compare filter offset.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *offset* The offset

13.1.3.72 void PWM_setDigitalCompareFilterSource (

PWM_Handle pwmHandle,

const **PWM_DigitalCompare_FilterSrc_e** input)

Sets the pulse width modulation (PWM) digital compare filter source.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *input* The filter's source

13.1.3.73 void PWM_setDigitalCompareFilterWindow (

PWM_Handle pwmHandle,

const uint16_t window)

> Sets the pulse width modulation (PWM) digital compare filter offset.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> `in` *window* The window

13.1.3.74 void PWM_setDigitalCompareInput (

PWM_Handle pwmHandle,

const **PWM_DigitalCompare_Input_e** input,

const **PWM_DigitalCompare_InputSel_e** inputSel)

> Sets the pulse width modulation (PWM) digital compare input.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> `in` *input* Comparator input to change

> `in` *inputSel* Input selection for designated input

13.1.3.75 void PWM_setHighSpeedClkDiv (

PWM_Handle pwmHandle,

const **PWM_HspClkDiv_e** clkDiv)

> Sets the pulse width modulation (PWM) high speed clock divisor.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> `in` *clkDiv* The clock divisor

13.1.3.76 void PWM_setIntMode (

PWM_Handle pwmHandle,

const **PWM_IntMode_e** intMode)

> Sets the pulse width modulation (PWM) interrupt mode.
>
> [1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

> `in` *intMode* The interrupt mode

13.1.3.77 void PWM_setIntPeriod (

PWM_Handle pwmHandle,

const **PWM_IntPeriod_e** intPeriod)

Sets the pulse width modulation (PWM) interrupt period.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *intPeriod* The interrupt period

13.1.3.78 void PWM_setLoadMode_CmpA (

PWM_Handle pwmHandle,

const **PWM_LoadMode_e** loadMode)

Sets the pulse width modulation (PWM) load mode for CMPA.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *loadMode* The load mode

13.1.3.79 void PWM_setLoadMode_CmpB (

PWM_Handle pwmHandle,

const **PWM_LoadMode_e** loadMode)

Sets the pulse width modulation (PWM) load mode for CMPB.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *loadMode* The load mode

13.1.3.80 void PWM_setOneShotTrip (

PWM_Handle pwmHandle) `[inline]`

Sets the pulse width modulation (PWM) one shot trip.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

References DISABLE_PROTECTED_REGISTER_WRITE_MODE, EN-ABLE_PROTECTED_REGISTER_WRITE_MODE, PWM_TZFRC_OST_BITS, and _PWM_Obj_::TZFRC.

13.1.3.81 void PWM_setPeriod (

PWM_Handle pwmHandle,

const uint16_t period)

Sets the pulse width modulation (PWM) period.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *period* The period

13.1.3.82 void PWM_setPeriodLoad (

PWM_Handle pwmHandle,

const **PWM_PeriodLoad_e** periodLoad)

Sets the pulse width modulation (PWM) period load mode.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *periodLoad* The period load mode

13.1.3.83 void PWM_setPhase (

PWM_Handle pwmHandle,

const uint16_t phase)

Sets the pulse width modulation (PWM) phase.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *phase* The phase

13.1.3.84 void PWM_setPhaseDir (

PWM_Handle pwmHandle,

const **PWM_PhaseDir_e** phaseDir)

Sets the pulse width modulation (PWM) phase direction.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *phaseDir* The phase direction

13.1.3.85 void PWM_setRunMode (

PWM_Handle pwmHandle,

const **PWM_RunMode_e** runMode)

Sets the pulse width modulation (PWM) run mode.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *runMode* The run mode

13.1.3.86 void PWM_setShadowMode_CmpA (

PWM_Handle pwmHandle,

const **PWM_ShadowMode_e** shadowMode)

Sets the pulse width modulation (PWM) shadow mode for CMPA.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *shadowMode* The shadow mode

13.1.3.87 void PWM_setShadowMode_CmpB (

PWM_Handle pwmHandle,

const **PWM_ShadowMode_e** shadowMode)

Sets the pulse width modulation (PWM) shadow mode for CMPB.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *shadowMode* The shadow mode

13.1.3.88 void PWM_setSocAPeriod (

PWM_Handle pwmHandle,

const **PWM_SocPeriod_e** intPeriod)

Sets the pulse width modulation (PWM) start of conversion (SOC) A interrupt period.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *intPeriod* The interrupt period

13.1.3.89 void PWM_setSocAPulseSrc (

PWM_Handle pwmHandle,

const **PWM_SocPulseSrc_e** pulseSrc)

Sets the pulse width modulation (PWM) start of conversion (SOC) A interrupt pulse source.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *pulseSrc* The interrupt pulse source

13.1.3.90 void PWM_setSocBPeriod (

PWM_Handle pwmHandle,

const **PWM_SocPeriod_e** intPeriod)

Sets the pulse width modulation (PWM) start of conversion (SOC) B interrupt period.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *intPeriod* The interrupt period

13.1.3.91 void PWM_setSocBPulseSrc (

PWM_Handle pwmHandle,

const **PWM_SocPulseSrc_e** pulseSrc)

Sets the pulse width modulation (PWM) start of conversion (SOC) B interrupt pulse source.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *pulseSrc* The interrupt pulse source

13.1.3.92 void PWM_setSwSync (

PWM_Handle pwmHandle)

Sets the pulse width modulation (PWM) software sync.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

13.1.3.93 void PWM_setSyncMode (

PWM_Handle pwmHandle,

const **PWM_SyncMode_e** syncMode)

Sets the pulse width modulation (PWM) sync mode.

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *syncMode* The sync mode

13.1.3.94 void PWM_setTripZoneDCEventSelect_DCAEVT1 (

PWM_Handle pwmHandle,

const **PWM_TripZoneDCEventSel_e** tripZoneEvent)

Sets the pulse width modulation (PWM) trip zone digital compare event select for Digital Compare Output A Event 1 (DCAEVT1)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneEvent* The trip zone digital compare event

13.1.3.95 void PWM_setTripZoneDCEventSelect_DCAEVT2 (

PWM_Handle pwmHandle,

const **PWM_TripZoneDCEventSel_e** tripZoneEvent)

Sets the pulse width modulation (PWM) trip zone digital compare event select for Digital Compare Output A Event 2 (DCAEVT2)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneEvent* The trip zone digital compare event

13.1.3.96 void PWM_setTripZoneDCEventSelect_DCBEVT1 (

PWM_Handle pwmHandle,

const **PWM_TripZoneDCEventSel_e** tripZoneEvent)

Sets the pulse width modulation (PWM) trip zone digital compare event select for Digital Compare Output B Event 1 (DCBEVT1)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneEvent* The trip zone digital compare event

13.1.3.97 void PWM_setTripZoneDCEventSelect_DCBEVT2 (

PWM_Handle pwmHandle,

const **PWM_TripZoneDCEventSel_e** tripZoneEvent)

Sets the pulse width modulation (PWM) trip zone digital compare event select for Digital Compare Output B Event 2 (DCBEVT2)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneEvent* The trip zone digital compare event

13.1.3.98 void PWM_setTripZoneState_DCAEVT1 (

PWM_Handle pwmHandle,

const **PWM_TripZoneState_e** tripZoneState)

Sets the pulse width modulation (PWM) trip zone state for Digital Compare Output A Event 1 (DCAEVT1)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneState* The trip zone state

13.1.3.99 void PWM_setTripZoneState_DCAEVT2 (

PWM_Handle pwmHandle,

const **PWM_TripZoneState_e** tripZoneState)

Sets the pulse width modulation (PWM) trip zone state for Digital Compare Output A Event 2 (DCAEVT1)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneState* The trip zone state

13.1.3.100 void PWM_setTripZoneState_DCBEVT1 (

PWM_Handle pwmHandle,

const **PWM_TripZoneState_e** tripZoneState)

Sets the pulse width modulation (PWM) trip zone state for Digital Compare Output B Event 1 (DCBEVT1)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneState* The trip zone state

13.1.3.101 void PWM_setTripZoneState_DCBEVT2 (

PWM_Handle pwmHandle,

const **PWM_TripZoneState_e** tripZoneState)

Sets the pulse width modulation (PWM) trip zone state for Digital Compare Output B Event 2 (DCBEVT1)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneState* The trip zone state

13.1.3.102 void PWM_setTripZoneState_TZA (

PWM_Handle pwmHandle,

const **PWM_TripZoneState_e** tripZoneState)

Sets the pulse width modulation (PWM) trip zone state for Output A (TZA)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneState* The trip zone state

13.1.3.103 void PWM_setTripZoneState_TZB (

PWM_Handle pwmHandle,

const **PWM_TripZoneState_e** tripZoneState)

Sets the pulse width modulation (PWM) trip zone state for Output B (TZB)

[1]Parameters in *pwmHandle* The pulse width modulation (PWM) object handle

in *tripZoneState* The trip zone state

13.1.3.104 void PWM_write_CmpA (

PWM_Handle pwmHandle,

const int16_t pwmData) `[inline]`

> Writes the pulse width modulation (PWM) data value to the Counter Compare A hardware.
>
> [1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

> `in` *pwmData* The PWM data value

> References _PWM_Obj_::CMPA, and _PWM_Obj_::TBPRD.

13.1.3.105 void PWM_write_CmpB (

PWM_Handle pwmHandle,

const int16_t pwmData) `[inline]`

> Writes the pulse width modulation (PWM) data value to the Counter Compare B hardware.
>
> [1]Parameters `in` *pwmHandle* The pulse width modulation (PWM) object handle

> `in` *pwmData* The PWM data value

> References _PWM_Obj_::CMPB, and _PWM_Obj_::TBPRD.

14   Power Control (PWR)

The power API is a set of functions for configuring low power modes as well as other power related functions such as brown out.

This driver is contained in `f2802x0/common/source/pwr.c`, with `f2802x0/common/include/pwr.h` containing the API definitions for use by applications.

14.1   PWR

Data Structures

struct _PWR_Obj_

Macros

#define PWR_BASE_ADDR

#define PWR_BORCFG_BORENZ_BITS

#define PWR_LPMCR0_LPM_BITS

#define PWR_LPMCR0_QUALSTDBY_BITS

#define PWR_LPMCR0_WDINTE_BITS

Typedefs

typedef struct _PWR_Obj_ ∗ PWR_Handle

typedef struct _PWR_Obj_ PWR_Obj

Enumerations

enum PWR_LowPowerMode_e { PWR_LowPowerMode_Idle, PWR_LowPowerMode_Standby, PWR_LowPowerMode_Halt }

enum PWR_NumStandByClocks_e {
PWR_NumStandByClocks_2, PWR_NumStandByClocks_3, PWR_NumStandByClocks_4,
PWR_NumStandByClocks_5,
PWR_NumStandByClocks_6, PWR_NumStandByClocks_7, PWR_NumStandByClocks_8,
PWR_NumStandByClocks_9,
PWR_NumStandByClocks_10, PWR_NumStandByClocks_11, PWR_NumStandByClocks_12,

PWR_NumStandByClocks_13,
PWR_NumStandByClocks_14, PWR_NumStandByClocks_15, PWR_NumStandByClocks_16,
PWR_NumStandByClocks_17,
PWR_NumStandByClocks_18, PWR_NumStandByClocks_19, PWR_NumStandByClocks_20,
PWR_NumStandByClocks_21,
PWR_NumStandByClocks_22, PWR_NumStandByClocks_23, PWR_NumStandByClocks_24,
PWR_NumStandByClocks_25,
PWR_NumStandByClocks_26, PWR_NumStandByClocks_27, PWR_NumStandByClocks_28,
PWR_NumStandByClocks_29,
PWR_NumStandByClocks_30, PWR_NumStandByClocks_31, PWR_NumStandByClocks_32,
PWR_NumStandByClocks_33,
PWR_NumStandByClocks_34, PWR_NumStandByClocks_35, PWR_NumStandByClocks_36,
PWR_NumStandByClocks_37,
PWR_NumStandByClocks_38, PWR_NumStandByClocks_39, PWR_NumStandByClocks_40,
PWR_NumStandByClocks_41,
PWR_NumStandByClocks_42, PWR_NumStandByClocks_43, PWR_NumStandByClocks_44,
PWR_NumStandByClocks_45,
PWR_NumStandByClocks_46, PWR_NumStandByClocks_47, PWR_NumStandByClocks_48,
PWR_NumStandByClocks_49,
PWR_NumStandByClocks_50, PWR_NumStandByClocks_51, PWR_NumStandByClocks_52,
PWR_NumStandByClocks_53,
PWR_NumStandByClocks_54, PWR_NumStandByClocks_55, PWR_NumStandByClocks_56,
PWR_NumStandByClocks_57,
PWR_NumStandByClocks_58, PWR_NumStandByClocks_59, PWR_NumStandByClocks_60,
PWR_NumStandByClocks_61,
PWR_NumStandByClocks_62, PWR_NumStandByClocks_63, PWR_NumStandByClocks_64,
PWR_NumStandByClocks_65 }

Functions

void PWR_disableBrownOutReset (PWR_Handle pwrHandle)

void PWR_disableWatchDogInt (PWR_Handle pwrHandle)

void PWR_enableBrownOutReset (PWR_Handle pwrHandle)

void PWR_enableWatchDogInt (PWR_Handle pwrHandle)

PWR_Handle PWR_init (void ∗pMemory, const size_t numBytes)

void PWR_setLowPowerMode (PWR_Handle pwrHandle, const PWR_LowPowerMode_e lowPowerMode)

void PWR_setNumStandByClocks (PWR_Handle pwrHandle, const PWR_NumStandByClocks_e numClkCycles)

14.1.1   Detailed Description

14.1.2   Enumeration Type Documentation

14.1.2.1   enum **PWR_LowPowerMode_e**

Enumeration to define the power (PWR) low power modes.

Enumerator
    PWR_LowPowerMode_Idle   Denotes the idle mode.
    PWR_LowPowerMode_Standby   Denotes the standby mode.
    PWR_LowPowerMode_Halt   Denotes the halt mode.

14.1.2.2   enum **PWR_NumStandByClocks_e**

Enumeration to define the power (PWR) number of standby clock cycles.

Enumerator
    PWR_NumStandByClocks_2   Denotes 2 standby clock cycles.
    PWR_NumStandByClocks_3   Denotes 3 standby clock cycles.
    PWR_NumStandByClocks_4   Denotes 4 standby clock cycles.
    PWR_NumStandByClocks_5   Denotes 5 standby clock cycles.
    PWR_NumStandByClocks_6   Denotes 6 standby clock cycles.
    PWR_NumStandByClocks_7   Denotes 7 standby clock cycles.
    PWR_NumStandByClocks_8   Denotes 8 standby clock cycles.
    PWR_NumStandByClocks_9   Denotes 9 standby clock cycles.
    PWR_NumStandByClocks_10   Denotes 10 standby clock cycles.
    PWR_NumStandByClocks_11   Denotes 11 standby clock cycles.
    PWR_NumStandByClocks_12   Denotes 12 standby clock cycles.
    PWR_NumStandByClocks_13   Denotes 13 standby clock cycles.
    PWR_NumStandByClocks_14   Denotes 14 standby clock cycles.
    PWR_NumStandByClocks_15   Denotes 15 standby clock cycles.
    PWR_NumStandByClocks_16   Denotes 16 standby clock cycles.
    PWR_NumStandByClocks_17   Denotes 17 standby clock cycles.
    PWR_NumStandByClocks_18   Denotes 18 standby clock cycles.
    PWR_NumStandByClocks_19   Denotes 19 standby clock cycles.
    PWR_NumStandByClocks_20   Denotes 20 standby clock cycles.
    PWR_NumStandByClocks_21   Denotes 21 standby clock cycles.
    PWR_NumStandByClocks_22   Denotes 22 standby clock cycles.
    PWR_NumStandByClocks_23   Denotes 23 standby clock cycles.
    PWR_NumStandByClocks_24   Denotes 24 standby clock cycles.
    PWR_NumStandByClocks_25   Denotes 25 standby clock cycles.
    PWR_NumStandByClocks_26   Denotes 26 standby clock cycles.
    PWR_NumStandByClocks_27   Denotes 27 standby clock cycles.
    PWR_NumStandByClocks_28   Denotes 28 standby clock cycles.

PWR_NumStandByClocks_29	Denotes 29 standby clock cycles.
PWR_NumStandByClocks_30	Denotes 30 standby clock cycles.
PWR_NumStandByClocks_31	Denotes 31 standby clock cycles.
PWR_NumStandByClocks_32	Denotes 32 standby clock cycles.
PWR_NumStandByClocks_33	Denotes 33 standby clock cycles.
PWR_NumStandByClocks_34	Denotes 34 standby clock cycles.
PWR_NumStandByClocks_35	Denotes 35 standby clock cycles.
PWR_NumStandByClocks_36	Denotes 36 standby clock cycles.
PWR_NumStandByClocks_37	Denotes 37 standby clock cycles.
PWR_NumStandByClocks_38	Denotes 38 standby clock cycles.
PWR_NumStandByClocks_39	Denotes 39 standby clock cycles.
PWR_NumStandByClocks_40	Denotes 40 standby clock cycles.
PWR_NumStandByClocks_41	Denotes 41 standby clock cycles.
PWR_NumStandByClocks_42	Denotes 42 standby clock cycles.
PWR_NumStandByClocks_43	Denotes 43 standby clock cycles.
PWR_NumStandByClocks_44	Denotes 44 standby clock cycles.
PWR_NumStandByClocks_45	Denotes 45 standby clock cycles.
PWR_NumStandByClocks_46	Denotes 46 standby clock cycles.
PWR_NumStandByClocks_47	Denotes 47 standby clock cycles.
PWR_NumStandByClocks_48	Denotes 48 standby clock cycles.
PWR_NumStandByClocks_49	Denotes 49 standby clock cycles.
PWR_NumStandByClocks_50	Denotes 50 standby clock cycles.
PWR_NumStandByClocks_51	Denotes 51 standby clock cycles.
PWR_NumStandByClocks_52	Denotes 52 standby clock cycles.
PWR_NumStandByClocks_53	Denotes 53 standby clock cycles.
PWR_NumStandByClocks_54	Denotes 54 standby clock cycles.
PWR_NumStandByClocks_55	Denotes 55 standby clock cycles.
PWR_NumStandByClocks_56	Denotes 56 standby clock cycles.
PWR_NumStandByClocks_57	Denotes 57 standby clock cycles.
PWR_NumStandByClocks_58	Denotes 58 standby clock cycles.
PWR_NumStandByClocks_59	Denotes 59 standby clock cycles.
PWR_NumStandByClocks_60	Denotes 60 standby clock cycles.
PWR_NumStandByClocks_61	Denotes 61 standby clock cycles.
PWR_NumStandByClocks_62	Denotes 62 standby clock cycles.
PWR_NumStandByClocks_63	Denotes 63 standby clock cycles.
PWR_NumStandByClocks_64	Denotes 64 standby clock cycles.
PWR_NumStandByClocks_65	Denotes 65 standby clock cycles.

14.1.3   Function Documentation

14.1.3.1   void PWR_disableBrownOutReset (

PWR_Handle pwrHandle)

Disables the brownout reset functions.

[1]Parameters `in` *pwrHandle* The power (PWR) object handle

722.7

      `in` *lowPowerMode* The low power mode

14.1.3.7 void PWR_setNumStandByClocks (

PWR_Handle pwrHandle,

const **PWR_NumStandByClocks_e** numClkCycles)

Sets the number of standby clock cycles.

[1]Parameters `in` *pwrHandle* The power (PWR) object handle

      `in` *numClkCycles* The number of standby clock cycles

---

15   Serial Communications Interface (SCI)

The Serial Communication Interface (SCI) API provides a set of functions for configuring and using the SCI peripheral(s) on this device.

This driver is contained in `f2802x0/common/source/sci.c`, with `f2802x0/common/include/sci.h` containing the API definitions for use by applications.

15.1   SCI

Data Structures

struct _SCI_Obj_

Macros

#define SCI_SCICCR_CHAR_LENGTH_BITS

#define SCI_SCICCR_LB_ENA_BITS

#define SCI_SCICCR_MODE_BITS

#define SCI_SCICCR_PARITY_BITS

#define SCI_SCICCR_PARITY_ENA_BITS

#define SCI_SCICCR_STOP_BITS

#define SCI_SCICTL1_RESET_BITS

#define SCI_SCICTL1_RX_ERR_INT_ENA_BITS

#define SCI_SCICTL1_RXENA_BITS

#define SCI_SCICTL1_SLEEP_BITS

#define SCI_SCICTL1_TXENA_BITS

#define SCI_SCICTL1_TXWAKE_BITS

#define SCI_SCICTL2_RX_INT_ENA_BITS

#define SCI_SCICTL2_TX_INT_ENA_BITS

#define SCI_SCICTL2_TXEMPTY_BITS

#define SCI_SCICTL2_TXRDY_BITS

#define SCI_SCIFFCT_ABD_BITS

#define SCI_SCIFFCT_ABDCLR_BITS

#define SCI_SCIFFCT_CDC_BITS

#define SCI_SCIFFCT_DELAY_BITS

#define SCI_SCIFFRX_FIFO_OVF_BITS

#define SCI_SCIFFRX_FIFO_OVFCLR_BITS

#define SCI_SCIFFRX_FIFO_RESET_BITS

#define SCI_SCIFFRX_FIFO_ST_BITS

#define SCI_SCIFFRX_IENA_BITS

#define SCI_SCIFFRX_IL_BITS

#define SCI_SCIFFRX_INT_BITS

#define SCI_SCIFFRX_INTCLR_BITS

#define SCI_SCIFFTX_CHAN_RESET_BITS

#define SCI_SCIFFTX_FIFO_ENA_BITS

#define SCI_SCIFFTX_FIFO_RESET_BITS

#define SCI_SCIFFTX_FIFO_ST_BITS

#define SCI_SCIFFTX_IENA_BITS

#define SCI_SCIFFTX_IL_BITS

#define SCI_SCIFFTX_INT_BITS

#define SCI_SCIFFTX_INTCLR_BITS

#define SCI_SCIRXST_BRKDT_BITS

#define SCI_SCIRXST_FE_BITS

#define SCI_SCIRXST_OE_BITS

#define SCI_SCIRXST_PE_BITS

#define SCI_SCIRXST_RXERROR_BITS

#define SCI_SCIRXST_RXRDY_BITS

#define SCI_SCIRXST_RXWAKE_BITS

#define SCIA_BASE_ADDR

Typedefs

typedef struct _SCI_Obj_ ∗ SCI_Handle

typedef struct _SCI_Obj_ SCI_Obj

Enumerations

enum SCI_BaudRate_e { SCI_BaudRate_9_6_kBaud, SCI_BaudRate_19_2_kBaud, SCI_BaudRate_57_6_kBaud, SCI_BaudRate_115_2_kBaud }

enum SCI_CharLength_e {
SCI_CharLength_1_Bit, SCI_CharLength_2_Bits, SCI_CharLength_3_Bits, SCI_CharLength_4_Bits,
SCI_CharLength_5_Bits, SCI_CharLength_6_Bits, SCI_CharLength_7_Bits, SCI_CharLength_8_Bits }

enum SCI_FifoLevel_e {
SCI_FifoLevel_Empty, SCI_FifoLevel_1_Word, SCI_FifoLevel_2_Words, SCI_FifoLevel_3_Words, SCI_FifoLevel_4_Words }

enum SCI_FifoStatus_e {
SCI_FifoStatus_Empty, SCI_FifoStatus_1_Word, SCI_FifoStatus_2_Words, SCI_FifoStatus_3_Words, SCI_FifoStatus_4_Words }

enum SCI_Mode_e { SCI_Mode_IdleLine, SCI_Mode_AddressBit }

enum SCI_NumStopBits_e { SCI_NumStopBits_One, SCI_NumStopBits_Two }

enum SCI_Parity_e { SCI_Parity_Odd, SCI_Parity_Even }

enum SCI_Priority_e { SCI_Priority_Immediate, SCI_Priority_FreeRun, SCI_Priority_AfterRxRxSeq }

Functions

void SCI_clearAutoBaudDetect (SCI_Handle sciHandle)

void SCI_clearRxFifoInt (SCI_Handle sciHandle)

void SCI_clearRxFifoOvf (SCI_Handle sciHandle)

void SCI_clearTxFifoInt (SCI_Handle sciHandle)

void SCI_disable (SCI_Handle sciHandle)

void SCI_disableAutoBaudAlign (SCI_Handle sciHandle)

void SCI_disableFifoEnh (SCI_Handle sciHandle)

void SCI_disableLoopBack (SCI_Handle sciHandle)

void SCI_disableParity (SCI_Handle sciHandle)

void SCI_disableRx (SCI_Handle sciHandle)

void SCI_disableRxErrorInt (SCI_Handle sciHandle)

void SCI_disableRxFifoInt (SCI_Handle sciHandle)

void SCI_disableRxInt (SCI_Handle sciHandle)

void SCI_disableSleep (SCI_Handle sciHandle)

void SCI_disableTx (SCI_Handle sciHandle)

void SCI_disableTxFifoInt (SCI_Handle sciHandle)

void SCI_disableTxInt (SCI_Handle sciHandle)

void SCI_disableTxWake (SCI_Handle sciHandle)

void SCI_enable (SCI_Handle sciHandle)

void SCI_enableAutoBaudAlign (SCI_Handle sciHandle)

void SCI_enableFifoEnh (SCI_Handle sciHandle)

void SCI_enableLoopBack (SCI_Handle sciHandle)

void SCI_enableParity (SCI_Handle sciHandle)

void SCI_enableRx (SCI_Handle sciHandle)

void SCI_enableRxErrorInt (SCI_Handle sciHandle)

void SCI_enableRxFifoInt (SCI_Handle sciHandle)

void SCI_enableRxInt (SCI_Handle sciHandle)

void SCI_enableSleep (SCI_Handle sciHandle)

void SCI_enableTx (SCI_Handle sciHandle)

void SCI_enableTxFifoInt (SCI_Handle sciHandle)

void SCI_enableTxInt (SCI_Handle sciHandle)

void SCI_enableTxWake (SCI_Handle sciHandle)

uint16_t SCI_getData (SCI_Handle sciHandle)

uint16_t SCI_getDataBlocking (SCI_Handle sciHandle)

uint16_t SCI_getDataNonBlocking (SCI_Handle sciHandle, uint16_t ∗success)

SCI_FifoStatus_e SCI_getRxFifoStatus (SCI_Handle sciHandle)

SCI_FifoStatus_e SCI_getTxFifoStatus (SCI_Handle sciHandle)

SCI_Handle SCI_init (void ∗pMemory, const size_t numBytes)

bool_t SCI_isRxDataReady (SCI_Handle sciHandle)

bool_t SCI_isTxReady (SCI_Handle sciHandle)

void SCI_putData (SCI_Handle sciHandle, const uint16_t data)

void SCI_putDataBlocking (SCI_Handle sciHandle, uint16_t data)

uint16_t SCI_putDataNonBlocking (SCI_Handle sciHandle, uint16_t data)

void SCI_reset (SCI_Handle sciHandle)

void SCI_resetChannels (SCI_Handle sciHandle)

void SCI_resetRxFifo (SCI_Handle sciHandle)

void SCI_resetTxFifo (SCI_Handle sciHandle)

void SCI_setBaudRate (SCI_Handle sciHandle, const SCI_BaudRate_e baudRate)

void SCI_setCharLength (SCI_Handle sciHandle, const SCI_CharLength_e charLength)

void SCI_setMode (SCI_Handle sciHandle, const SCI_Mode_e mode)

void SCI_setNumStopBits (SCI_Handle sciHandle, const SCI_NumStopBits_e numBits)

void SCI_setParity (SCI_Handle sciHandle, const SCI_Parity_e parity)

void SCI_setPriority (SCI_Handle sciHandle, const SCI_Priority_e priority)

void SCI_setRxFifoIntLevel (SCI_Handle sciHandle, const SCI_FifoLevel_e fifoLevel)

void SCI_setTxDelay (SCI_Handle sciHandle, const uint8_t delay)

void SCI_setTxFifoIntLevel (SCI_Handle sciHandle, const SCI_FifoLevel_e fifoLevel)

15.1.1 Detailed Description

15.1.2 Enumeration Type Documentation

15.1.2.1 enum **SCI_BaudRate_e**

Enumeration to define the serial communications interface (SCI) baud rates. This enumeration assume a device clock of 50Mhz and a LSPCLK of 12.5 MHz.

Enumerator
   SCI_BaudRate_9_6_kBaud Denotes 9.6 kBaud.
   SCI_BaudRate_19_2_kBaud Denotes 19.2 kBaud.
   SCI_BaudRate_57_6_kBaud Denotes 57.6 kBaud.
   SCI_BaudRate_115_2_kBaud Denotes 115.2 kBaud.

15.1.2.2 enum **SCI_CharLength_e**

Enumeration to define the serial communications interface (SCI) character lengths.

Enumerator

    SCI_CharLength_1_Bit Denotes a character length of 1 bit.

    SCI_CharLength_2_Bits Denotes a character length of 2 bits.

    SCI_CharLength_3_Bits Denotes a character length of 3 bits.

    SCI_CharLength_4_Bits Denotes a character length of 4 bits.

    SCI_CharLength_5_Bits Denotes a character length of 5 bits.

    SCI_CharLength_6_Bits Denotes a character length of 6 bits.

    SCI_CharLength_7_Bits Denotes a character length of 7 bits.

    SCI_CharLength_8_Bits Denotes a character length of 8 bits.

15.1.2.3 enum **SCI_FifoLevel_e**

Enumeration to define the serial communications interface (SCI) FIFO level.

Enumerator

    SCI_FifoLevel_Empty Denotes the fifo is empty.

    SCI_FifoLevel_1_Word Denotes the fifo contains 1 word.

    SCI_FifoLevel_2_Words Denotes the fifo contains 2 words.

    SCI_FifoLevel_3_Words Denotes the fifo contains 3 words.

    SCI_FifoLevel_4_Words Denotes the fifo contains 4 words.

15.1.2.4 enum **SCI_FifoStatus_e**

Enumeration to define the serial communications interface (SCI) FIFO status.

Enumerator

    SCI_FifoStatus_Empty Denotes the fifo is empty.

    SCI_FifoStatus_1_Word Denotes the fifo contains 1 word.

    SCI_FifoStatus_2_Words Denotes the fifo contains 2 words.

    SCI_FifoStatus_3_Words Denotes the fifo contains 3 words.

    SCI_FifoStatus_4_Words Denotes the fifo contains 4 words.

15.1.2.5 enum **SCI_Mode_e**

Enumeration to define the serial communications interface (SCI) multiprocessor protocol mode.

Enumerator

    SCI_Mode_IdleLine Denotes idle-line mode protocol.

    SCI_Mode_AddressBit Denotes address-bit mode protocol.

15.1.2.6 enum **SCI_NumStopBits_e**

Enumeration to define the serial communications interface (SCI) number of stop bits.

Enumerator
> ***SCI_NumStopBits_One*** Denotes 1 stop bit.
> ***SCI_NumStopBits_Two*** Denotes 2 stop bits.

15.1.2.7 enum **SCI_Parity_e**

Enumeration to define the serial communications interface (SCI) parity.

Enumerator
> ***SCI_Parity_Odd*** Denotes odd parity.
> ***SCI_Parity_Even*** Denotes even parity.

15.1.2.8 enum **SCI_Priority_e**

Enumeration to define the serial communications interface (SCI) emulation suspend priority.

Enumerator
> ***SCI_Priority_Immediate*** Denotes an immediate stop.
> ***SCI_Priority_FreeRun*** Denotes free running.
> ***SCI_Priority_AfterRxRxSeq*** Denotes that a stop after the current receive/transmit sequence.

15.1.3 Function Documentation

15.1.3.1 void SCI_clearAutoBaudDetect (

SCI_Handle sciHandle)

Clears the auto baud detect mode.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.2 void SCI_clearRxFifoInt (

SCI_Handle sciHandle)

Clears the Rx FIFO interrupt flag.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.3 void SCI_clearRxFifoOvf (

SCI_Handle sciHandle)

Clears the Rx FIFO overflow flag.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.4 void SCI_clearTxFifoInt (

SCI_Handle sciHandle)

Clears the Tx FIFO interrupt flag.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.5 void SCI_disable (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.6 void SCI_disableAutoBaudAlign (

SCI_Handle sciHandle)

Disable the serial communications interface (SCI) auto baud alignment.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.7 void SCI_disableFifoEnh (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) FIFO enhancements.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.8 void SCI_disableLoopBack (

SCI_Handle sciHandle)

Disables the serial peripheral interface (SCI) loop back mode.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.9 void SCI_disableParity (

SCI_Handle sciHandle)

Disable the parity.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.10 void SCI_disableRx (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) master/slave receive mode.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.11 void SCI_disableRxErrorInt (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) receive error interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.12 void SCI_disableRxFifoInt (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) receive FIFO interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.13 void SCI_disableRxInt (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) receive interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.14 void SCI_disableSleep (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) sleep mode.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.15 void SCI_disableTx (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) master/slave transmit mode.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.16 void SCI_disableTxFifoInt (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) transmit FIFO interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.17 void SCI_disableTxInt (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) transmit interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.18 void SCI_disableTxWake (

SCI_Handle sciHandle)

Disables the serial communications interface (SCI) wakeup method.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.19 void SCI_enable (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI)

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.20 void SCI_enableAutoBaudAlign (

SCI_Handle sciHandle)

Enable the serial communications interface (SCI) auto baud alignment.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.21 void SCI_enableFifoEnh (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) FIFO enhancements.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.22 void SCI_enableLoopBack (

SCI_Handle sciHandle)

Enables the serial peripheral interface (SCI) loop back mode.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.23 void SCI_enableParity (

SCI_Handle sciHandle)

Enables the serial peripheral interface (SCI) parity.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.24 void SCI_enableRx (

SCI_Handle sciHandle)

Enables the serial peripheral interface (SCI) receiver.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

---

15.1.3.25 void SCI_enableRxErrorInt (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) receive error interrupt.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.26 void SCI_enableRxFifoInt (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) receive FIFO interrupt.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.27 void SCI_enableRxInt (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) receive interrupt.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.28 void SCI_enableSleep (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) sleep mode.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.29 void SCI_enableTx (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) masater/slave transmit mode.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

15.1.3.30 void SCI_enableTxFifoInt (

SCI_Handle sciHandle)

Enables the serial communications interface (SCI) transmit FIFO interrupt.

722.7

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

out *success* Pointer to a variable which will house whether the read was successful or not (true on success)

Returns Data if successful, or NULL if no characters

15.1.3.36 **SCI_FifoStatus_e** SCI_getRxFifoStatus (

SCI_Handle sciHandle)

Gets the serial communications interface (SCI) receive FIFO status.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

Returns The receive FIFO status

15.1.3.37 **SCI_FifoStatus_e** SCI_getTxFifoStatus (

SCI_Handle sciHandle)

Gets the serial communications interface (SCI) transmit FIFO status.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

Returns The transmit FIFO status

15.1.3.38 **SCI_Handle** SCI_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the serial communications interface (SCI) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the SCI registers

in *numBytes* The number of bytes allocated for the SCI object, bytes

Returns The serial communications interface (SCI) object handle

15.1.3.39 bool_t SCI_isRxDataReady (

SCI_Handle sciHandle) `[inline]`

Determines if the serial communications interface (SCI) has receive data ready.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

Returns The receive data status

References SCI_SCIRXST_RXRDY_BITS, and _SCI_Obj_::SCIRXST.

15.1.3.40 bool_t SCI_isTxReady (

SCI_Handle sciHandle) `[inline]`

Determines if the serial communications interface (SCI) is ready to transmit.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

Returns The transmit status

References SCI_SCICTL2_TXRDY_BITS, and _SCI_Obj_::SCICTL2.

15.1.3.41 void SCI_putData (

SCI_Handle sciHandle,

const uint16_t data) `[inline]`

Writes data to the serial communications interface (SCI)

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *data* The data value

References _SCI_Obj_::SCITXBUF.

15.1.3.42 void SCI_putDataBlocking (

SCI_Handle sciHandle,

uint16_t data)

Writes data to the serial communications interface (Blocking)

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *data* The data value

15.1.3.43 uint16_t SCI_putDataNonBlocking (

SCI_Handle sciHandle,

uint16_t data)

Writes data to the serial communications interface (Non-Blocking)

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *data* The data value

Returns True on successful write, false if no space is available in the transmit buffer

15.1.3.44 void SCI_reset (

SCI_Handle sciHandle)

Resets the serial communications interface (SCI)

[1]Parameters in *sciHandle* The serial communication interface (SCI) object handle

15.1.3.45 void SCI_resetChannels (

SCI_Handle sciHandle)

Resets the serial communications interface (SCI) transmit and receive channels.

[1]Parameters in *sciHandle* The serial communication interface (SCI) object handle

15.1.3.46 void SCI_resetRxFifo (

SCI_Handle sciHandle)

Resets the serial communications interface (SCI) receive FIFO.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.47 void SCI_resetTxFifo (

SCI_Handle sciHandle)

Resets the serial communications interface (SCI) transmit FIFO.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

15.1.3.48 void SCI_setBaudRate (

SCI_Handle sciHandle,

const **SCI_BaudRate_e** baudRate)

Sets the serial communications interface (SCI) baud rate.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *baudRate* The baud rate

15.1.3.49 void SCI_setCharLength (

SCI_Handle sciHandle,

const **SCI_CharLength_e** charLength)

Sets the serial communications interface (SCI) character length.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *charLength* The character length

15.1.3.50 void SCI_setMode (

SCI_Handle sciHandle,

const **SCI_Mode_e** mode)

Sets the serial communications interface (SCI) miltprocessor mode.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *mode* The multiprocessor mode

15.1.3.51 void SCI_setNumStopBits (

SCI_Handle sciHandle,

const **SCI_NumStopBits_e** numBits)

Sets the serial communications interface (SCI) number of stop bits.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *numBits* The number of bits

15.1.3.52 void SCI_setParity (

SCI_Handle sciHandle,

const **SCI_Parity_e** parity)

Sets the serial communications interface (SCI) parity.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *parity* The parity

15.1.3.53 void SCI_setPriority (

SCI_Handle sciHandle,

const **SCI_Priority_e** priority)

Sets the serial communications interface (SCI) priority.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *priority* The priority

15.1.3.54 void SCI_setRxFifoIntLevel (

SCI_Handle sciHandle,

const **SCI_FifoLevel_e** fifoLevel)

Sets the serial communications interface (SCI) receive FIFO level for generating an interrupt.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *fifoLevel* The FIFO level

15.1.3.55 void SCI_setTxDelay (

SCI_Handle sciHandle,

const uint8_t delay)

Sets the serial communications interface (SCI) transmit delay.

[1]Parameters in *sciHandle* The serial communications interface (SCI) object handle

in *delay* The transmit delay

15.1.3.56 void SCI_setTxFifoIntLevel (

SCI_Handle sciHandle,

const **SCI_FifoLevel_e** fifoLevel)

Sets the serial communications interface (SCI) transmit FIFO level for generating an interrupt.

[1]Parameters `in` *sciHandle* The serial communications interface (SCI) object handle

`in` *fifoLevel* The FIFO level

16 Serial Peripheral Interface (SPI)

The Serial Peripheral Interface (SPI) API provides a set of functions for configuring and using the device's SPI peripheral(s).

This driver is contained in `f2802x0/common/source/spi.c`, with `f2802x0/common/include/spi.h` containing the API definitions for use by applications.

16.1 SPI

Data Structures

struct _SPI_Obj_

Macros

#define SPI_SPICCR_CHAR_LENGTH_BITS

#define SPI_SPICCR_CLKPOL_BITS

#define SPI_SPICCR_RESET_BITS

#define SPI_SPICCR_SPILBK_BITS

#define SPI_SPICTL_CLK_PHASE_BITS

#define SPI_SPICTL_INT_ENA_BITS

#define SPI_SPICTL_MODE_BITS

#define SPI_SPICTL_OVRRUN_INT_ENA_BITS

#define SPI_SPICTL_TALK_BITS

#define SPI_SPIFFRX_FIFO_OVF_BITS

#define SPI_SPIFFRX_FIFO_OVFCLR_BITS

#define SPI_SPIFFRX_FIFO_RESET_BITS

#define SPI_SPIFFRX_FIFO_ST_BITS

#define SPI_SPIFFRX_IENA_BITS

#define SPI_SPIFFRX_IL_BITS

#define SPI_SPIFFRX_INT_BITS

#define SPI_SPIFFRX_INTCLR_BITS

#define SPI_SPIFFTX_CHAN_RESET_BITS

#define SPI_SPIFFTX_FIFO_ENA_BITS

#define SPI_SPIFFTX_FIFO_RESET_BITS

#define SPI_SPIFFTX_FIFO_ST_BITS

#define SPI_SPIFFTX_IENA_BITS

#define SPI_SPIFFTX_IL_BITS

#define SPI_SPIFFTX_INT_BITS

#define SPI_SPIFFTX_INTCLR_BITS

#define SPIA_BASE_ADDR

Typedefs

typedef struct _SPI_Obj_ ∗ SPI_Handle

typedef struct _SPI_Obj_ SPI_Obj

Enumerations

enum SPI_BaudRate_e { SPI_BaudRate_500_KBaud, SPI_BaudRate_1_MBaud }

enum SPI_CharLength_e {
SPI_CharLength_1_Bit, SPI_CharLength_2_Bits, SPI_CharLength_3_Bits,
SPI_CharLength_4_Bits,
SPI_CharLength_5_Bits, SPI_CharLength_6_Bits, SPI_CharLength_7_Bits,
SPI_CharLength_8_Bits,
SPI_CharLength_9_Bits, SPI_CharLength_10_Bits, SPI_CharLength_11_Bits,
SPI_CharLength_12_Bits,
SPI_CharLength_13_Bits, SPI_CharLength_14_Bits, SPI_CharLength_15_Bits,
SPI_CharLength_16_Bits }

enum SPI_ClkPhase_e { SPI_ClkPhase_Normal, SPI_ClkPhase_Delayed }

enum SPI_ClkPolarity_e { SPI_ClkPolarity_OutputRisingEdge_InputFallingEdge,
SPI_ClkPolarity_OutputFallingEdge_InputRisingEdge }

enum SPI_FifoLevel_e {
SPI_FifoLevel_Empty, SPI_FifoLevel_1_Word, SPI_FifoLevel_2_Words, SPI_FifoLevel_3_Words,
SPI_FifoLevel_4_Words }

enum SPI_FifoStatus_e {
SPI_FifoStatus_Empty, SPI_FifoStatus_1_Word, SPI_FifoStatus_2_Words,
SPI_FifoStatus_3_Words,
SPI_FifoStatus_4_Words }

enum SPI_Mode_e { SPI_Mode_Slave, SPI_Mode_Master }

enum SPI_Priority_e { SPI_Priority_Immediate, SPI_Priority_FreeRun, SPI_Priority_AfterRxRxSeq }

enum SPI_SteInv_e { SPI_SteInv_ActiveLow, SPI_SteInv_ActiveHigh }

enum SPI_TriWire_e { SPI_TriWire_NormalFourWire, SPI_TriWire_ThreeWire }

Functions

void SPI_clearRxFifoInt (SPI_Handle spiHandle)

void SPI_clearRxFifoOvf (SPI_Handle spiHandle)

void SPI_clearTxFifoInt (SPI_Handle spiHandle)

void SPI_disable (SPI_Handle spiHandle)

void SPI_disableChannels (SPI_Handle spiHandle)

void SPI_disableInt (SPI_Handle spiHandle)

void SPI_disableLoopBack (SPI_Handle spiHandle)

void SPI_disableOverRunInt (SPI_Handle spiHandle)

void SPI_disableRxFifo (SPI_Handle spiHandle)

void SPI_disableRxFifoInt (SPI_Handle spiHandle)

void SPI_disableTx (SPI_Handle spiHandle)

void SPI_disableTxFifo (SPI_Handle spiHandle)

void SPI_disableTxFifoEnh (SPI_Handle spiHandle)

void SPI_disableTxFifoInt (SPI_Handle spiHandle)

void SPI_enable (SPI_Handle spiHandle)

void SPI_enableChannels (SPI_Handle spiHandle)

void SPI_enableFifoEnh (SPI_Handle spiHandle)

void SPI_enableInt (SPI_Handle spiHandle)

void SPI_enableLoopBack (SPI_Handle spiHandle)

void SPI_enableOverRunInt (SPI_Handle spiHandle)

void SPI_enableRxFifo (SPI_Handle spiHandle)

void SPI_enableRxFifoInt (SPI_Handle spiHandle)

void SPI_enableTx (SPI_Handle spiHandle)

void SPI_enableTxFifo (SPI_Handle spiHandle)

void SPI_enableTxFifoInt (SPI_Handle spiHandle)

SPI_FifoStatus_e SPI_getRxFifoStatus (SPI_Handle spiHandle)

SPI_FifoStatus_e SPI_getTxFifoStatus (SPI_Handle spiHandle)

SPI_Handle SPI_init (void ∗pMemory, const size_t numBytes)

uint16_t SPI_read (SPI_Handle spiHandle)

void SPI_reset (SPI_Handle spiHandle)

void SPI_resetChannels (SPI_Handle spiHandle)

void SPI_resetRxFifo (SPI_Handle spiHandle)

void SPI_resetTxFifo (SPI_Handle spiHandle)

void SPI_setBaudRate (SPI_Handle spiHandle, const SPI_BaudRate_e baudRate)

void SPI_setCharLength (SPI_Handle spiHandle, const SPI_CharLength_e length)

void SPI_setClkPhase (SPI_Handle spiHandle, const SPI_ClkPhase_e clkPhase)

void SPI_setClkPolarity (SPI_Handle spiHandle, const SPI_ClkPolarity_e polarity)

void SPI_setMode (SPI_Handle spiHandle, const SPI_Mode_e mode)

void SPI_setPriority (SPI_Handle spiHandle, const SPI_Priority_e priority)

void SPI_setRxFifoIntLevel (SPI_Handle spiHandle, const SPI_FifoLevel_e fifoLevel)

void SPI_setSteInv (SPI_Handle spiHandle, const SPI_SteInv_e steinv)

void SPI_setTriWire (SPI_Handle spiHandle, const SPI_TriWire_e triwire)

void SPI_setTxDelay (SPI_Handle spiHandle, const uint8_t delay)

void SPI_setTxFifoIntLevel (SPI_Handle spiHandle, const SPI_FifoLevel_e fifoLevel)

void SPI_write (SPI_Handle spiHandle, const uint16_t data)

void SPI_write8 (SPI_Handle spiHandle, const uint16_t data)

16.1.1 Detailed Description

16.1.2 Enumeration Type Documentation

16.1.2.1 enum **SPI_BaudRate_e**

Enumeration to define the serial peripheral interface (SPI) baud rates. These assume a LSCLK of 12.5MHz.

Enumerator
> ***SPI_BaudRate_500_KBaud*** Denotes 500 KBaud.
> ***SPI_BaudRate_1_MBaud*** Denotes 1 MBaud.

16.1.2.2 enum **SPI_CharLength_e**

Enumeration to define the serial peripheral interface (SPI) character lengths.

Enumerator
> ***SPI_CharLength_1_Bit*** Denotes a character length of 1 bit.
> ***SPI_CharLength_2_Bits*** Denotes a character length of 2 bits.
> ***SPI_CharLength_3_Bits*** Denotes a character length of 3 bits.
> ***SPI_CharLength_4_Bits*** Denotes a character length of 4 bits.
> ***SPI_CharLength_5_Bits*** Denotes a character length of 5 bits.
> ***SPI_CharLength_6_Bits*** Denotes a character length of 6 bits.
> ***SPI_CharLength_7_Bits*** Denotes a character length of 7 bits.
> ***SPI_CharLength_8_Bits*** Denotes a character length of 8 bits.
> ***SPI_CharLength_9_Bits*** Denotes a character length of 9 bits.
> ***SPI_CharLength_10_Bits*** Denotes a character length of 10 bits.
> ***SPI_CharLength_11_Bits*** Denotes a character length of 11 bits.
> ***SPI_CharLength_12_Bits*** Denotes a character length of 12 bits.
> ***SPI_CharLength_13_Bits*** Denotes a character length of 13 bits.
> ***SPI_CharLength_14_Bits*** Denotes a character length of 14 bits.
> ***SPI_CharLength_15_Bits*** Denotes a character length of 15 bits.
> ***SPI_CharLength_16_Bits*** Denotes a character length of 16 bits.

16.1.2.3 enum **SPI_ClkPhase_e**

Enumeration to define the serial peripheral interface (SPI) clock phase.

Enumerator
> ***SPI_ClkPhase_Normal*** Denotes a normal clock scheme.
> ***SPI_ClkPhase_Delayed*** Denotes that the SPICLK signal is delayed by one half-cycle.

16.1.2.4 enum **SPI_ClkPolarity_e**

Enumeration to define the serial peripheral interface (SPI) clock polarity for the input and output data.

Enumerator
> ***SPI_ClkPolarity_OutputRisingEdge_InputFallingEdge*** Denotes that the tx data is output on the rising edge, the rx data is latched on the falling edge.
> ***SPI_ClkPolarity_OutputFallingEdge_InputRisingEdge*** Denotes that the tx data is output on the falling edge, the rx data is latched on the rising edge.

16.1.2.5 enum **SPI_FifoLevel_e**

Enumeration to define the serial peripheral interface (SPI) FIFO level.

Enumerator

    SPI_FifoLevel_Empty   Denotes the fifo is empty.

    SPI_FifoLevel_1_Word   Denotes the fifo contains 1 word.

    SPI_FifoLevel_2_Words   Denotes the fifo contains 2 words.

    SPI_FifoLevel_3_Words   Denotes the fifo contains 3 words.

    SPI_FifoLevel_4_Words   Denotes the fifo contains 4 words.

16.1.2.6 enum **SPI_FifoStatus_e**

Enumeration to define the serial peripheral interface (SPI) FIFO status.

Enumerator

    SPI_FifoStatus_Empty   Denotes the fifo is empty.

    SPI_FifoStatus_1_Word   Denotes the fifo contains 1 word.

    SPI_FifoStatus_2_Words   Denotes the fifo contains 2 words.

    SPI_FifoStatus_3_Words   Denotes the fifo contains 3 words.

    SPI_FifoStatus_4_Words   Denotes the fifo contains 4 words.

16.1.2.7 enum **SPI_Mode_e**

Enumeration to define the serial peripheral interface (SPI) network mode control.

Enumerator

    SPI_Mode_Slave   Denotes slave mode.

    SPI_Mode_Master   Denotes master mode.

16.1.2.8 enum **SPI_Priority_e**

Enumerator

    SPI_Priority_Immediate   Stops immediately after EMU halt.

    SPI_Priority_FreeRun   Doesn't stop after EMU halt.

    SPI_Priority_AfterRxRxSeq   Stops after EMU halt and next rx/rx sequence.

16.1.2.9 enum **SPI_SteInv_e**

Enumerator

    SPI_SteInv_ActiveLow   Denotes active low STE pin.

    SPI_SteInv_ActiveHigh   Denotes active high STE pin.

722.7

> [1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.6   void SPI_disableInt (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) interrupt.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.7   void SPI_disableLoopBack (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) loop back mode.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.8   void SPI_disableOverRunInt (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) over-run interrupt.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.9   void SPI_disableRxFifo (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) receive FIFO.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.10 void SPI_disableRxFifoInt (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) receive FIFO interrupt.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.11 void SPI_disableTx (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) master/slave transmit mode.

[1]Parameters `in` *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.12 void SPI_disableTxFifo (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) transmit FIFO.

[1]Parameters `in` *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.13 void SPI_disableTxFifoEnh (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) transmit FIFO enhancements.

[1]Parameters `in` *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.14 void SPI_disableTxFifoInt (

SPI_Handle spiHandle)

Disables the serial peripheral interface (SPI) transmit FIFO interrupt.

[1]Parameters `in` *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.15 void SPI_enable (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI)

[1]Parameters `in` *spiHandle* The serial peripheral interface (SPI) object handle

---

16.1.3.16 void SPI_enableChannels (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI) transmit and receive channels.

---

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

16.1.3.17 void SPI_enableFifoEnh (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI) transmit FIFO enhancements.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

16.1.3.18 void SPI_enableInt (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI) interrupt.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

16.1.3.19 void SPI_enableLoopBack (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI) loop back mode.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

16.1.3.20 void SPI_enableOverRunInt (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI) over-run interrupt.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

16.1.3.21 void SPI_enableRxFifo (

SPI_Handle spiHandle)

Enables the serial peripheral interface (SPI) receive FIFO.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

722.7

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

Returns The transmit FIFO status

16.1.3.28 **SPI_Handle** SPI_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the serial peripheral interface (SPI) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the SPI registers

in *numBytes* The number of bytes allocated for the SPI object, bytes

Returns The serial peripheral interface (SPI) object handle

16.1.3.29 uint16_t SPI_read (

SPI_Handle spiHandle) `[inline]`

Reads data from the serial peripheral interface (SPI)

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

Returns The received data value

References _SPI_Obj_::SPIRXBUF.

16.1.3.30 void SPI_reset (

SPI_Handle spiHandle)

Resets the serial peripheral interface (SPI)

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

16.1.3.31 void SPI_resetChannels (

SPI_Handle spiHandle)

Resets the serial peripheral interface (SPI) transmit and receive channels.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

722.7

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *clkPhase* The clock phase

16.1.3.37 void SPI_setClkPolarity (

SPI_Handle spiHandle,

const **SPI_ClkPolarity_e** polarity)

Sets the serial peripheral interface (SPI) clock polarity.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *polarity* The clock polarity

16.1.3.38 void SPI_setMode (

SPI_Handle spiHandle,

const **SPI_Mode_e** mode)

Sets the serial peripheral interface (SPI) network mode.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *mode* The network mode

16.1.3.39 void SPI_setPriority (

SPI_Handle spiHandle,

const **SPI_Priority_e** priority)

Sets the priority of the SPI port vis-a-vis the EMU.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *priority* The priority of the SPI port vis-a-vis the EMU

16.1.3.40 void SPI_setRxFifoIntLevel (

SPI_Handle spiHandle,

const **SPI_FifoLevel_e** fifoLevel)

> Sets the serial peripheral interface (SPI) receive FIFO level for generating an interrupt.
>
> [1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *fifoLevel* The FIFO level

16.1.3.41 void SPI_setSteInv (

SPI_Handle spiHandle,

const **SPI_SteInv_e** steinv)

> Controls pin inversion of STE pin.
>
> [1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *steinv* Polarity of STE pin

16.1.3.42 void SPI_setTriWire (

SPI_Handle spiHandle,

const **SPI_TriWire_e** triwire)

> Sets SPI port operating mode.
>
> [1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *triwire* 3 or 4 wire mode

16.1.3.43 void SPI_setTxDelay (

SPI_Handle spiHandle,

const uint8_t delay)

> Sets the serial peripheral interface (SPI) transmit delay.
>
> [1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *delay* The delay value

16.1.3.44 void SPI_setTxFifoIntLevel (

SPI_Handle spiHandle,

const **SPI_FifoLevel_e** fifoLevel)

Sets the serial peripheral interface (SPI) transmit FIFO level for generating an interrupt.

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *fifoLevel* The FIFO level

16.1.3.45 void SPI_write (

SPI_Handle spiHandle,

const uint16_t data) `[inline]`

Writes data to the serial peripheral interface (SPI)

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *data* The data value

References _SPI_Obj_::SPITXBUF.

16.1.3.46 void SPI_write8 (

SPI_Handle spiHandle,

const uint16_t data) `[inline]`

Writes a byte of data to the serial peripheral interface (SPI)

[1]Parameters in *spiHandle* The serial peripheral interface (SPI) object handle

in *data* The data value

References _SPI_Obj_::SPITXBUF.

17 Timer

The timer API provides a set of functions for configuring, starting, stopping, and reading the CPU timers.

This driver is contained in `f2802x0/common/source/timer.c`, with `f2802x0/common/include/timer.h` containing the API definitions for use by applications.

17.1 TIMER

Data Structures

struct _TIMER_Obj_

Macros

#define TIMER0_BASE_ADDR

#define TIMER1_BASE_ADDR

#define TIMER2_BASE_ADDR

#define TIMER_TCR_FREESOFT_BITS

#define TIMER_TCR_TIE_BITS

#define TIMER_TCR_TIF_BITS

#define TIMER_TCR_TRB_BITS

#define TIMER_TCR_TSS_BITS

Typedefs

typedef struct _TIMER_Obj_ ∗ TIMER_Handle

typedef struct _TIMER_Obj_ TIMER_Obj

Enumerations

enum   TIMER_EmulationMode_e   {   TIMER_EmulationMode_StopAfterNextDecrement, TIMER_EmulationMode_StopAtZero, TIMER_EmulationMode_RunFree }

enum TIMER_Status_e { TIMER_Status_CntIsNotZero, TIMER_Status_CntIsZero }

Functions

void TIMER_clearFlag (TIMER_Handle timerHandle)

void TIMER_disableInt (TIMER_Handle timerHandle)

void TIMER_enableInt (TIMER_Handle timerHandle)

uint32_t TIMER_getCount (TIMER_Handle timerHandle)

TIMER_Status_e TIMER_getStatus (TIMER_Handle timerHandle)

TIMER_Handle TIMER_init (void ∗pMemory, const size_t numBytes)

void TIMER_reload (TIMER_Handle timerHandle)

void TIMER_setDecimationFactor (TIMER_Handle timerHandle, const uint16_t decFactor)

void TIMER_setEmulationMode (TIMER_Handle timerHandle, const TIMER_EmulationMode_e mode)

void TIMER_setPeriod (TIMER_Handle timerHandle, const uint32_t period)

void TIMER_setPreScaler (TIMER_Handle timerHandle, const uint16_t preScaler)

void TIMER_start (TIMER_Handle timerHandle)

void TIMER_stop (TIMER_Handle timerHandle)

17.1.1 Detailed Description

17.1.2 Enumeration Type Documentation

17.1.2.1 enum **TIMER_EmulationMode_e**

Enumeration to define the timer (TIMER) emulation mode.

Enumerator
> ***TIMER_EmulationMode_StopAfterNextDecrement*** Denotes that the timer will stop after the next decrement.
> ***TIMER_EmulationMode_StopAtZero*** Denotes that the timer will stop when it reaches zero.
> ***TIMER_EmulationMode_RunFree*** Denotes that the timer will run free.

17.1.2.2 enum **TIMER_Status_e**

Enumeration to define the timer (TIMER) status.

Enumerator
> ***TIMER_Status_CntIsNotZero*** Denotes that the counter is non-zero.
> ***TIMER_Status_CntIsZero*** Denotes that the counter is zero.

17.1.3 Function Documentation

17.1.3.1 void TIMER_clearFlag (

TIMER_Handle timerHandle)

Clears the timer (TIMER) flag.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

---

17.1.3.2 void TIMER_disableInt (

TIMER_Handle timerHandle)

Disables the timer (TIMER) interrupt.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

---

17.1.3.3 void TIMER_enableInt (

TIMER_Handle timerHandle)

Enables the timer (TIMER) interrupt.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

---

17.1.3.4 uint32_t TIMER_getCount (

TIMER_Handle timerHandle) `[inline]`

Gets the timer (TIMER) count.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

---

Returns The timer (TIMER) count

References _TIMER_Obj_::TIM.

17.1.3.5 **TIMER_Status_e** TIMER_getStatus (

TIMER_Handle timerHandle)

Gets the timer (TIMER) status.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

---

Returns The timer (TIMER) status

17.1.3.6 **TIMER_Handle** TIMER_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the timer (TIMER) object handle.

[1]Parameters in *pMemory* A pointer to the base address of the TIMER registers

in *numBytes* The number of bytes allocated for the TIMER object, bytes

Returns The timer (CLK) object handle

17.1.3.7 void TIMER_reload (

TIMER_Handle timerHandle)

Reloads the timer (TIMER) value.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

17.1.3.8 void TIMER_setDecimationFactor (

TIMER_Handle timerHandle,

const uint16_t decFactor)

Sets the timer (TIMER) decimation factor.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

in *decFactor* The timer decimation factor

17.1.3.9 void TIMER_setEmulationMode (

TIMER_Handle timerHandle,

const **TIMER_EmulationMode_e** mode)

Sets the timer (TIMER) emulation mode.

[1]Parameters in *timerHandle* The timer (TIMER) object handle

in *mode* The emulation mode

17.1.3.10 void TIMER_setPeriod (

TIMER_Handle timerHandle,

const uint32_t period)

Sets the timer (TIMER) period.

[1]Parameters `in` *timerHandle* The timer (TIMER) object handle

`in` *period* The period

17.1.3.11 void TIMER_setPreScaler (

TIMER_Handle timerHandle,

const uint16_t preScaler)

Sets the timer (TIMER) prescaler.

[1]Parameters `in` *timerHandle* The timer (TIMER) object handle

`in` *preScaler* The preScaler value

17.1.3.12 void TIMER_start (

TIMER_Handle timerHandle)

Starts the timer (TIMER)

[1]Parameters `in` *timerHandle* The timer (TIMER) object handle

17.1.3.13 void TIMER_stop (

TIMER_Handle timerHandle)

Stops the timer (TIMER)

[1]Parameters `in` *timerHandle* The timer (TIMER) object handle

18 Watchdog Timer

The Watchdog Timer API provides a set of functions for using the watchdog module.

This driver is contained in `f2802x0/common/source/watchdog.c`, with `f2802x0/common/include/watchdog.h` containing the API definitions for use by applications.

18.1 WDOG

Data Structures

struct _WDOG_Obj_

Macros

#define WDOG_BASE_ADDR

#define WDOG_SCSR_WDENINT_BITS

#define WDOG_SCSR_WDINTS_BITS

#define WDOG_SCSR_WDOVERRIDE_BITS

#define WDOG_WDCNTR_BITS

#define WDOG_WDCR_WDCHK_BITS

#define WDOG_WDCR_WDDIS_BITS

#define WDOG_WDCR_WDFLAG_BITS

#define WDOG_WDCR_WDPS_BITS

#define WDOG_WDCR_WRITE_ENABLE

#define WDOG_WDKEY_BITS

Typedefs

typedef struct _WDOG_Obj_ ∗ WDOG_Handle

typedef struct _WDOG_Obj_ WDOG_Obj

Enumerations

enum WDOG_IntStatus_e { WDOG_IntStatus_Active, WDOG_IntStatus_InActive }

enum WDOG_PreScaler_e {
WDOG_PreScaler_OscClk_by_512_by_1, WDOG_PreScaler_OscClk_by_512_by_2,
WDOG_PreScaler_OscClk_by_512_by_4, WDOG_PreScaler_OscClk_by_512_by_8,
WDOG_PreScaler_OscClk_by_512_by_16, WDOG_PreScaler_OscClk_by_512_by_32,
WDOG_PreScaler_OscClk_by_512_by_64 }

Functions

void WDOG_clearCounter (WDOG_Handle wdogHandle)

void WDOG_disable (WDOG_Handle wdogHandle)

void WDOG_disableInt (WDOG_Handle wdogHandle)

void WDOG_enable (WDOG_Handle wdogHandle)

void WDOG_enableInt (WDOG_Handle wdogHandle)

void WDOG_enableOverRide (WDOG_Handle wdogHandle)

WDOG_IntStatus_e WDOG_getIntStatus (WDOG_Handle wdogHandle)

WDOG_Handle WDOG_init (void ∗pMemory, const size_t numBytes)

void WDOG_setCount (WDOG_Handle wdogHandle, const uint8_t count)

void WDOG_setPreScaler (WDOG_Handle wdogHandle, const WDOG_PreScaler_e preScaler)

18.1.1 Detailed Description

18.1.2 Enumeration Type Documentation

18.1.2.1 enum **WDOG_IntStatus_e**

Enumeration to define the watchdog (WDOG) interrupt status.

Enumerator
    WDOG_IntStatus_Active Denotes an active interrupt status.
    WDOG_IntStatus_InActive Denotes an in-active interrupt status.

18.1.2.2 enum **WDOG_PreScaler_e**

Enumeration to define the watchdog (WDOG) timer clock prescaler, which sets the clock frequency.

Enumerator

WDOG_PreScaler_OscClk_by_512_by_1 Denotes WDCLK = OSCCLK/512/1.
WDOG_PreScaler_OscClk_by_512_by_2 Denotes WDCLK = OSCCLK/512/2.
WDOG_PreScaler_OscClk_by_512_by_4 Denotes WDCLK = OSCCLK/512/4.
WDOG_PreScaler_OscClk_by_512_by_8 Denotes WDCLK = OSCCLK/512/8.
WDOG_PreScaler_OscClk_by_512_by_16 Denotes WDCLK = OSCCLK/512/16.
WDOG_PreScaler_OscClk_by_512_by_32 Denotes WDCLK = OSCCLK/512/32.
WDOG_PreScaler_OscClk_by_512_by_64 Denotes WDCLK = OSCCLK/512/64.

18.1.3 Function Documentation

18.1.3.1 void WDOG_clearCounter (

WDOG_Handle wdogHandle)

Clears the watchdog (WDOG) counter.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

18.1.3.2 void WDOG_disable (

WDOG_Handle wdogHandle)

Disables the watchdog (WDOG) timer.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

18.1.3.3 void WDOG_disableInt (

WDOG_Handle wdogHandle)

Disables the watchdog (WDOG) timer interrupt.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

18.1.3.4 void WDOG_enable (

WDOG_Handle wdogHandle)

Enables the watchdog (WDOG) timer.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

18.1.3.5 void WDOG_enableInt (

WDOG_Handle wdogHandle)

Enables the watchdog (WDOG) timer interrupt.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

18.1.3.6 void WDOG_enableOverRide (

WDOG_Handle wdogHandle)

Enables the watchdog (WDOG) timer override.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

18.1.3.7 **WDOG_IntStatus_e** WDOG_getIntStatus (

WDOG_Handle wdogHandle)

Gets the watchdog (WDOG) interrupt status.

[1]Parameters `in` *wdogHandle* The watchdog (WDOG) timer object handle

Returns The interrupt status

18.1.3.8 **WDOG_Handle** WDOG_init (

void ∗ pMemory,

const size_t numBytes)

Initializes the watchdog (WDOG) object handle.

[1]Parameters `in` *pMemory* A pointer to the base address of the WDOG registers

`in` *numBytes* The number of bytes allocated for the WDOG object, bytes

Returns The watchdog (WDOG) object handle

18.1.3.9 void WDOG_setCount (

WDOG_Handle wdogHandle,

const uint8_t count)

Sets the watchdog (WDOG) counter.

[1]Parameters in *wdogHandle* The watchdog (WDOG) timer object handle

in *count* The count

18.1.3.10 void WDOG_setPreScaler (

WDOG_Handle wdogHandle,

const **WDOG_PreScaler_e** preScaler)

Sets the watchdog (WDOG) timer clock prescaler.

[1]Parameters in *wdogHandle* The watchdog (WDOG) timer object handle

in *preScaler* The prescaler

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		**Applications**	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DLP® Products	www.dlp.com	Broadband	www.ti.com/broadband
DSP	dsp.ti.com	Digital Control	www.ti.com/digitalcontrol
Clocks and Timers	www.ti.com/clocks	Medical	www.ti.com/medical
Interface	interface.ti.com	Military	www.ti.com/military
Logic	logic.ti.com	Optical Networking	www.ti.com/opticalnetwork
Power Mgmt	power.ti.com	Security	www.ti.com/security
Microcontrollers	microcontroller.ti.com	Telephony	www.ti.com/telephony
RFID	www.ti-rfid.com	Video & Imaging	www.ti.com/video
RF/IF and ZigBee® Solutions	www.ti.com/lprf	Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2024, Texas Instruments Incorporated