
Image Analysis

An Open-Source Summary

Thomas Debelle



April 22, 2026

Contents

1	Introduction	2
1.1	The basics	2
1.1.1	Light	2
1.1.2	Perception	2
1.1.3	Interaction with matter	2
2	Acquisition of images	5
2.1	Image formation - Lens	6
2.2	Sensor array	8
2.2.1	CCD vs CMOS	8
2.2.2	Colour cameras	8
2.3	Perspective Projection - Image Plane	9
2.3.1	Projections limitations	11
3	Sampling and Quantisation	11
3.1	Sampling	12
3.1.1	Integrate brightness over the cell window	12
3.1.2	Read out values only at the pixel centers	13
4	License	14
4.1	Modification	14
4.2	Take down	14

1 Introduction

The key take away is that vision is subjective to the human being and themselves. It is the results of continuous evolution and survival of the fittest. We are more sensitive to light and certain colors, to motion, ... And this fact will be used for efficient image representation and analysis.

We can think of the classic illusion where our brain will interpret certain lengths of an arrow longer than others. Context also does matter, even in a blurry picture our brain will train to make up for what he sees.

1.1 The basics

We first need light to have vision. Light is influenced by object and create perception. ADD image slide 51. The light source bounce on the object and some scattered ray will get trough the 2D Image plane, which will be casted on the sensor array thanks to the lens system.

1.1.1 Light

We will look at it from a physical optic (not geometrical (constant speed and straight path) nor quantum). Light is an Electro-magnetic wave which we assume it to be planar. aka $\frac{|E|}{|H|} = \eta$ in simple term, light is perpendicular. This is a **self-sustaining process** that is characterized by:

1. λ : wavelength
2. Direction
3. E : Amplitude
4. φ : phase
5. Direction of polarisation

Violet: low frequency ($380nm$); Red: high frequency ($760nm$). Remember $\lambda = \frac{c}{f}$.

1.1.2 Perception

We don't perceive light equally. Humans have 3 cones that are not evenly spread apart. But the human vision is trained to compensate for it so everything feels similar in intensity to us. Some animals can have more cones.

1.1.3 Interaction with matter

Table 1: The four types of interaction

Phenomenon	Example
Absorption	Blue water, green leaf
Scattering	blue sky, red sunset
Reflection	colored in k
Refraction	dispersion by a prism

1.1.3.1 Absorption Dissipation of λ specific for the medium. Resonance in molecules.

1.1.3.2 Scattering When light (radiation/particles) deviates from a straight trajectory by local non-uniformities. Type depends on the relative size of particles and wavelengths:

1. **Rayleigh:** small (λ dependent)
2. **Mie:** comparable (weakly λ dependent)
3. **Non-selective:** large (λ independent)

We ignored transmission and diffraction.




Figure 1: Wavelength dependence for scattering

We need scatter to get the bluesky (Rayleigh with Tyndall effect) or it would be dark. Coloured cloud from volcanic eruption = Mie (particle all over the air). Grey cloud is due to non-selective. Less scatter for lower frequency light (infrared).




Figure 2: Mirror reflection

1.1.3.3 Reflection With reflection, the notion of polarization is important. The polarization effect creates the fact that a reflected wave on certain surfaces can be reflected with all but one direction of the electric field. This effect is more

prominent on **non-metallic** surfaces!




Figure 3: Non-metallic reflection - strong reflectors




Figure 4: Metallic reflection - Red dot: Brewster angle (polarizer) - Blue zone: Grazing angles

Rough surfaces will lead to **diffuse** reflection as the reflection angles will be all over the place. On the other hand, smooth surfaces give **specular** reflection. Both **diffuse** and **specular** can also happen all together.

Reflectance varies through λ and different side of vegetation can typically give various reflection¹

1.1.3.4 Refraction Typically, refraction which is the bending of the light and dispersion which is a frequency dependency.




Figure 5: Refraction - governed by Snell's law property of the medium **and** material

2 Acquisition of images




Figure 6: Image acquisition model

Controlling the lights is essential for acquisition as it is the main vector to acquire images. Several techniques exist

Type	Description	Examples
Back-lighting	Light source behind object (better with a diffuser plate)	High contrast silhouette. Binary vision , inspection

¹This fact can be used for spectral reflectance of vegetation since it forms a signature

Type	Description	Examples
Directional	Tilt lights to generate sharp shadow of specular reflection (rough surfaces)	Detection of cracks
Diffuse	Uniform lighting, all directions contribute to the diffusion reflection but specular spike due to spike	Detection of cracks
Polarized: Contrast diffuse and specular	diffuse makes light non-polarized while specular keeps polarized. Put polarizer/analyzer orthogonal, better for glare (high dynamic range) issue.	Detection of cracks
Polarized: Contrast dielectrics and metal	Dielectric at Brewster angle can be used as a polarizer which is not possible for metallic surface (see previous chapter).	So use a polarizer to suppress specular reflection from dielectric OR distinguish between specular and dielectric surfaces
Coloured	Highlight region of similar colour. Use laser (monochromatic light), differentiation between specular and diffuse. Comparing colours. Spectral sensitivity of a sensor.	
Structured	Spatially or temporally modulated light pattern. Projection on a 3D object will distort the projection pattern	3D reconstruction
Stroboscopic	High intensity light flash. Eliminate motion blur.	For high speed inspection

Note about the dark and bright field. Mostly relevant for the Directional/Diffuse lighting. *Dark field*, when the camera is placed outside the specular reflection area of the normal area, only specular reflection (different orientation from normal) will show up. On the other hand, *Bright field*, we place camera inside this specular reflection light area and the non-normal area will appear dark.

2.1 Image formation - Lens

We use the pinhole model in this class:




Figure 7: Pinhole model

From this we can use the thin-lens equation which assumes:

- Spherical lens surfaces
- Incoming light $\perp$ to axis
- Thickness $\ll$ radii
- Same refractive index on both sides





Figure 8: Thin-lens equation



$$\Delta Z_0^- = Z_0 - Z_0^- = \frac{Z_0(Z_0 - f)}{Z_0 + f \quad d/b - f}$$

Figure 9: Depth of field of the thin lens

There is one focal point. Strike a balance between incoming light (d) and large depth-of-field. Smaller depth-of-field is

present in microscopes for example.

2.2 Sensor array

2.2.1 CCD vs CMOS

We have 2 types of sensors:

- CCD: Charge-coupled device
 - Old school
 - Charges must hop from tile to tile
 - Cover the total pixel (high fill rate)
 - Expensive
 - Blooming (due to the charge hopping)
 - High power consumption
- CMOS: integrated
 - Cheap, Can put other component on the chip (integration)
 - Read line by line (like RAM = random access)
 - Smaller
 - Low power
 - Same sensor as CCD but each has their own amplifier = more noise + not covering the full space = lower fill rate / sensitivity

They both work in 2 steps:

1. Photon to electron (charge) conversion
2. Electron (charge) to voltage conversion




Figure 10: CCD vs CMOS

2.2.2 Colour cameras

2.2.2.1 1. Prism The idea is to split the light using *dichroic prism* to split it in 3 colors. This requires really good precision but allows for good color separation.

2.2.2.2 2. Filter mosaic Back to the *bayer pattern* introduced earlier. Good for tricking the human eyes. Each pixel will have a filter in front to follow the bayer pattern. This is good but can create some aliasing especially when an edge is right on a pixel array causing some extra inexistant colors (aliasing).




Figure 11: Aliasing with bayer pattern

We loose actual resolution since know we need 2x2 pixel array to get 1 colored pixel ! We have to stack even more density but need to capture more lights → Use microlenses.

2.2.2.3 3. Filter wheel Here instead of having 3 filters like in a filter mosaic, we have a full wheel with many filters. Behind the wheel, there is a static sensor (**only static scenes**).

2.2.2.4 Summary

Table 3: Summary of the 3 coloured camera

Type	Prism	Mosaic	Wheel
# Sensors	3	1	1
Resolution	High	Medium	Good
Cost	High	Low	Medium
Framerate	High	High	Low
Artefacts	Low	Aliasing	Aliasing (just motion of wheel)
Bands (color)	3	3	3 or +
Application	High-end cameras	Low-end cameras	Scientific applications

2.2.2.5 Improvements One issue is the Aliasing problem for object in motion. Since we read line by line in CMOS camera, for fast turning object (turning at $\geq f_s/2$) we have aliasing. To solve this, we need a global shutter instead of reading line by line.

2.3 Perspective Projection - Image Plane

Here, we revisit the pinhole model where now, we first project everything on an object plane and then this will get through the lens. The center of the lens is the center of the projection, we have an virtual image plane which is also called **perspective projection** (we flattened out everything from the outside on it):




Figure 12: Camera projection model




Figure 13: 3D view of the camera projection model

The origin is the center of the projection (X_c row-pixel, Y_c column-pixel space), the Z_c axis correspond with the optical axis.

If we look at the u, v space we have the following relationship, which comes from the “similar triangles property” where you look once from above (for X case) and one from the side (for Y case).

$$u = f \frac{X_c}{Z_c} \quad v = f \frac{Y_c}{Z_c}$$

We can then say that if Z is constant, we can write $x = kX_c$ and $y = kY_c$ where $k = f/Z$. Orthographic projection + a scaling. This forms a good approximation if objects are small compared to their distance from the camera.

2.3.1 Projections limitations



Figure 14: Pseudo-orthographic vs Perspective projection

The perspective projection model is incomplete. What about world coordinate ? What if we want our u,v coordinates as a row and column numbers (like in a matrix of pixels).

This part of the class that does not form exam material but helps with understanding where does those matrices come from.

2.3.1.1 The (u,v) projection to pixel We can see a matrix of pixel instead of the (u,v) projection. We just need 3 informations: 1. Center of matrix x_0 and y_0 , 2. Width of array k_x and 3. Height of array k_y giving us:

$$\begin{cases} x &= k_x u + x_0 + s v \\ y &= k_y v + y_0 \end{cases}$$

Note: the s is for skew, we have the aspect ratio k_y/k_x^2

2.3.1.2 The global world coordinate problem

3 Sampling and Quantisation

We live in an analog world but our computers and digital world is finite. So we have to sample (Discretize points) and quantize (attribute them a finite value).

From what we have seen and learned before, we can trick the human eye to see a higher quality image than it is actually. For example the display on a phone has a RGB pixel ratio as 2:1:1 because the human is less sensible to green. We call this grid the **bayer filter**. Other representation exist which can be more exotic, e.g.: hexagonal (more isotropic, similar structure as in the retina, no connectivity ambiguities).

We have quantization where we usually talk about levels. Typically a n bits representation has 2^n levels. We can also apply fancier quantization scheme instead of simple linear one. The most classic representation is the RGB888 (1 byte per pixel for each color).

²I thought it was the opposite...





Figure 15: Various quantization scheme

3.0.0.1 HDR High Dynamic Range (HDR) is a technology where we have various luminance on the screen giving really good contrast in dark and bright area. Usually, we combine multiple photos with various gains and then recombine it all together with the various exposure.

3.1 Sampling

3.1.1 Integrate brightness over the cell window



$$o(x', y') = \iint i(x, y) p(x - x', y - y') dx dy$$

This is *convolution*: $i(x, y) * p(-x, -y)$

Figure 16: Integrating over a pixel cell

This forms a convolution. Convolution are **linear**, $f_1 \rightarrow g_1 \quad f_2 \rightarrow g_2 \Rightarrow af_1 + bf_2 \rightarrow ag_1 + bg_2$, and **shift-invariant**, $f(x, y) \rightarrow g(x, y) \Rightarrow f(x - a, y - b) \rightarrow g(x - a, y - b)$.

3.1.2 Read out values only at the pixel centers

4 License

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License (CC BY-NC-SA 4.0) for KU Leuven students.

You are free to:

- **Share** — copy and redistribute the material in any medium or format with people inside of KU Leuven or being granted access to the source material.
- **Adapt** — remix, transform, and build upon the material if you are a KU Leuven student.

Under the following terms:

- **Attribution** — You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
- **NonCommercial** — You may not use the material for commercial purposes.
- **ShareAlike** — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

For the full legal text of the license, please visit: <https://creativecommons.org/licenses/by-nc-sa/4.0/legalcode>

4.1 Modification

To contribute to this work or any other one from this project please find more information at the Github repository.

4.2 Take down

If you are a professor or representing any official party and wish to take down this work, you can submit a takedown request at this url: https://github.com/Tfloow/ESATSummary/issues/new?template=takedown_notice.yml

Some Rights Reserved 2026 Authors of the Summary, Professors of the Course and possible book's authors. Some Rights Reserved.