Technical Reproducibility Validation Report

HipSTR

Version v0.7
Y-STR

Verification date	2026-11-01
Repository commit	b2033bfbb5cf55496b776463bdf2993fa763a4be
Result	**Not verified as documented**
Reached	Runs + Plausible output
Permalink	https://strhub.app/verified/hipstr-y
STRhub	https://strhub.app

SCOPE OF THIS REPORT

Independent automated verification of reproducible execution. It confirms the tool installs, runs end-to-end, and produces structurally valid output in a standardized environment.

This is **not** an analytical validation. Genotype accuracy, concordance, forensic suitability, and regulatory compliance are out of scope.

WHAT WAS VERIFIED

– Source available
– Installation successful
– End-to-end execution
– Output generated

NOT VERIFIED

– Genotype accuracy
– Concordance
– Forensic validity
– Regulatory compliance

1. Executive Summary

PURPOSE	Verify that the tool installs, runs end-to-end, and produces structurally valid output.
RESULT	**Not verified as documented**
REACHED	Runs + Plausible output, 5/5 gates passed
WHY	The tool installed and its run produced its documented output.
SCOPE	Installation, execution, and output structure verification.
NOT EVALUATED	Genotype accuracy · Concordance · Forensic validity · Regulatory compliance

2. What STRhub had to do to run this tool

STRhub wrote its own recipe for this tool, an environment and a command of its own rather than the repository's instructions, and ran that. Each item below is something a first-time user following the README would have to work out for themselves, and so a recommendation to the author. This run does not change the tool's label: the label is what happens as it is in the repository.

– Runs HipSTR with flags tuned to STRhub's reference slice (--min-reads 5 --use-unpaired --read-qual-trim ! --def-stutter-model --max-str-len 250). Instead of: The README's command, which has none of them. On a BAM slice around the panel loci most mates fall outside the slice and read quality trims most reads; without these flags nearly every locus is skipped.

– Supplies the Y-STR regions BED from STRhub's library. Instead of: A regions file the README leaves to the user.

With those changes, the run reached: **Runs + Plausible output**.

3. Verification Gates

Available	The pinned public source exists	PASS
Installs	The environment builds from source	PASS
Runs	Executes end-to-end without crashing	PASS
Expected IO	Produces a non-empty file in the declared format	PASS
Plausible Output	Output structure matches expected genotype-bearing format	PASS
Execution log	hipstr-y.log-external.txt	

4. Exact Run Command

This is the command that was executed, verbatim, in the CI environment.

```
# Environment: ubuntu-22.04 · HipSTR v0.7 · commit b2033bf
$ HipSTR \
--bams /data/in/input.bam \
--fasta /data/ref/hg38.fa \
--regions /data/in/regions.bed \
--str-vcf /data/out/result.vcf.gz \
--min-reads 5 \
--use-unpaired \
--read-qual-trim ! \
--def-stutter-model \
--max-str-len 250
```

5. Reproducibility Metadata

Tool	HipSTR
Version	v0.7
Repository	https://github.com/tfwillems/HipSTR
Commit (pinned)	b2033bfbb5cf55496b776463bdf2993fa763a4be
Container OS	ubuntu-22.04
Marker panel	Y-STR
Verified on	2026-11-01 12:49:32 UTC
CI run	https://github.com/Tfronta/strhub-verified/actions/runs/41307968157

Verified automatically, in a clean environment, on the tool's public source at the pinned commit. This certificate records what happened; it is not an endorsement by the tool's author.

6. Out of Scope

This report does not evaluate any of the following:

– Genotype correctness or accuracy
– Concordance against known truth sets
– Sensitivity, specificity, or stutter performance
– Allele calling accuracy or forensic casework suitability
– Regulatory compliance or ISO accreditation
– Multi-laboratory or multi-dataset reproducibility

7. Output Content Evidence

Output file	result.vcf.gz
Format	VCF
Sequence records	13
Distinct STR loci	13
Total reads	2,912
Max depth (single locus)	320

8. Verification Data

The repository ships example data (3 file(s)); this run did not use it. STRhub ran the verification using the public reference dataset listed below. That dataset is a slice around 14 forensic STR loci, not a whole genome: it carries reads only at the loci listed below. A small test file in the repository lets a new user run the tool on their first day and see it working before trusting it with their own data, and it lets a verification run against the author's own sample as well as this one. Publishing the output that file should produce helps just as much: it shows what the results are meant to look like, which is what a reader needs to tell a correct run from one that merely finished.

Dataset	Illumina BAM (hg38), HG002 (Y-STR, male)
Source	https://ftp-trace.ncbi.nlm.nih.gov/ReferenceSamples/giab/dat…
License	Open access (GIAB / NIST). Research and educational use. STRhub is not the data provider.
Ref. genome	GRCh38 / hg38
Loci tested	DYS385_2 · DYS389I · DYS389II.1 · DYS390 · DYS391 · DYS392 · DYS393 · DYS438 · DYS456 · DYS458 · DYS635 · Y-GATA-A10 · Y-GATA-H4
Regions BED	Provided by STRhub

9. Verification Matrix

PASS	Reference dataset	Illumina BAM (hg38), HG002 (Y-STR, male)
	README check (5/5)	Advisory: all items present
	Install / environment setup	Present
	Run command	Present
	Expected input format	Present
	Produced output format	Present
	Dependencies / versions	Present

10. What This Run Needed Beyond the Repository

The result above describes a run configured as follows. Anyone repeating it needs the same things.

– A container environment and a command written by STRhub, not taken from the repository's instructions; what they do differently is listed under "What STRhub had to do to run this tool".

11. Limitations

– Single reference dataset per input type
– Single containerized environment (Docker / ubuntu-22.04)
– No truth-set comparison or ground-truth genotypes
– No accuracy or concordance assessment
– No forensic validation of results
– Short-read limitations apply (very long STR alleles may not span reads)

12. Scope and Disclaimers

Executed end-to-end in the stated environment with output in the expected format. Concerns reproducible execution only; no claim of accuracy, casework fitness, or regulatory validation.

Each result is a dated snapshot, verified on the tool's public repository at a pinned commit. STRhub does not store tool source code.

13. Conclusion

◆ **Runs end-to-end**

HipSTR v0.7 installs and executes without error in a clean ubuntu-22.04 environment at the pinned commit.

◆ **Produces plausible output**

The tool generated a structurally valid VCF output file with genotype calls across 13 target forensic STR loci, with a maximum read depth of 320 at Y-GATA-H4.

◆ **Verdict: Runs**

The tool installed and its run produced its documented output.

◆ **Repository test data not used**

The repository ships example data (3 file(s)), which this run did not use: the gates above ran on STRhub's reference dataset. STRhub Verified supplied Illumina BAM (hg38), HG002 (Y-STR, male) as the reference input for this verification run. Users replicating this result should use the same or equivalent publicly available reference material.

◆ **Reproducibility statement**

The exact command reported in Section 3, executed at the pinned commit in the described environment, is sufficient to reproduce this verification result independently.

Appendix: Detected Markers with Read Depth

HipSTR v0.7 · verified 2026-11-01

LOCUS	READ DEPTH		LOCUS	READ DEPTH	
Y-GATA-H4	320		**DYS456**	196	
DYS389II.1	298		**DYS391**	195	
DYS389I	272		**Y-GATA-A10**	194	
DYS635	258		**DYS458**	193	
DYS385_2	219		**DYS392**	190	
DYS390	218		**DYS393**	161	
DYS438	198				